



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



CVG Control Valve Group

Proportional, Load Sensing



ENGINEERING YOUR SUCCESS.

Note

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.

The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors. To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

Contents

Description	Page
Introduction	4
General description, applications, benefits	4
Operation	5
Technical data	6
Ordering code	7
How to order CVG – CVG master code	7
Inlet section	8
Control section	9
Outlet section	10
Adapter section	11
Measuring data CVG	12
Pressure drop CVG compensator spools	12
Measuring data CVG30	13
Pressure drop CVG 30 spools	13
Compensator adjustment range CVG30	13
Measuring data CVG50	14
Pressure drop CVG 50 spools	14
Compensator adjustment range CVG50	14
Measuring data CVG60	15
Pressure drop CVG60 spools	15
Compensator adjustment range CVG60	15
Spool Selection Table	16
Standard spools	16
Meter out spools	16
Assembly Diagrams	17
CVG33 assembly example	17
Hydraulic diagram CVG33	17
CVG53 assembly example	18
Hydraulic diagram CVG53	18
CVG63 assembly example	19
Hydraulic diagram CVG63	19
Dimensions CVG30	20
Inlet section connections	20
Outlet section connections	20
Assembly, dimensions	21
Control section connections	21
Dimensions CVG50	22
Inlet section connections	22
Outlet section connections	22
Assembly, dimensions	23
Control section connections	23
Dimensions CVG60	24
Inlet section connections	24
Outlet section connections	24
Assembly, dimensions	25
Control section connections	25
Spare Parts	26
CVG30 control section	26
CVG50 control section	27
CVG60 control section	28
CVG30 inlet section with pressure relief	29
CVG50 inlet section with pressure relief	30
CVG60 inlet section with pressure relief	31
Adapters	32

Introduction

General description

The CVG (Control Valve Group) is a compact load-sensing valve assembly consisting of multiple directional valve sections. Each control section has its own compensator, so that speed control of multiple sections is achieved, regardless of changes in pressure. The compensator limits the maximum flow of control section and it can be adjusted. Each control section has pressure limiting valves in work ports. If load exceeds the setting, the control section starts to reduce flow. The control section keeps flow steady with different main spool opening if pressure changes.

The design of the CVG is modular. There are three nominal sizes of control sections available: CVG30, CVG50 and CVG60. Different sizes can be fitted together with adapters. The nominal size determines the port sizes and compensators flow range. Specific flow range is selected by a main spool in each control section. The inlet section has an option for a main pressure relief valve and a pilot oil reducing valve for electrically controlled CVG. The outlet section has also ports P and T to ensure full flow for control sections.

The main spool of control section can be operated proportionally with hydraulic remote or electrically in an open loop and also in a closed loop depending on option.

Applications

A CVG can be used to control wide range of machines like cranes, large mobile vehicles, lifting equipment, drilling equipment and stationary applications. High flows can be accurately controlled with low pressure drop and low hysteresis.

Benefits

Excellent machine controllability – individual pressure compensation in each work section delivers predictable metering with single and multi-function operation, regardless of changes in pressure or input flow. The maximum work pressure can be limited individually in each work port. This enhances machine control and improves productivity. The CVG has excellent linearity, repeatability and low hysteresis.

Flexible design – the modular CVG design enables the machine designer to add or remove content to achieve the machine requirements. Different nominal sizes, several spools and a wide range of spool control options provide wide range of possibilities where to build customized assembly to meet the requirements.

Wide flow range – the CVG single control sections can handle flow starting from 50LPM in nominal size CVG30 ending up to 2000 LPM in CVG60. Inlet and outlet can handle pump input up to 10 000LPM in CVG60.

Energy-efficient – high level controllability and efficiency can be achieved by choosing the right spool size from different nominal sizes. CVG can handle load pressure up to 420 bar. With right system design this gives possibility to reduce oil flow and still have same power supplied through the valve.

Factory tested – every CVG valve assemblies are tested and adjusted before sending to the customer. This reduces start up time and reduces risk of system failure. Customer individual features can be fully tested before start up.

Ease of service – the components of CVG are easily changed without removing CVG from the system. Compensator, pressure limiting valves and load-sensing check valve are located on the top of each controls section making it a service friendly design. Spare parts are available worldwide from Parker.

Introduction

Operation

Speed and direction movements of actuators are proportionally controlled by spring centered main spools. The pilot pressure moves the main spool against spring force. In the electric version pilot pressure is adjusted by electro-proportional 3-way pressure reduction valves. In the hydraulic version the pilot pressure is adjusted by an external control valve. The pilot oil flow to electro-proportional pilot valves is supplied either internally or externally. The internal signal is taken from port P through a pressure reducing valve in the inlet section.

The pressure difference over main spool is kept constant by a 2-way pressure compensator. Flow (and speed of actuator) with certain opening of the main spool is constant independent of load variations. Pressure compensators are equipped with adjustable springs. The spring force sets also a limit for maximum flow (speed of actuator). Maximum feeding pressures in work ports A and B are adjusted separately. When pressure exceeds setting of the pilot valve, the pressure compensator starts to act like a pressure reducing valve.

The CVG is a load sensing valve group. Every main spool is equipped with LS signal channels. The highest load pressure in the system is always connected to the LS port in the inlet section. This signal can be used to control a variable displacement pump. A CVG can be used with fixed displacement pumps when the inlet section is equipped with a 3-way pressure compensator. When the system pressure exceeds the setting of the pilot valve of the 3-way compensator, it starts to act like a pressure relief valve.

In the open loop version, the position of the main spool follows electric control signal coming from the amplifier card. The main spool can be equipped with a position sensor to read the movement of the main spool. In close loop control with electro-proportional control version, the position signal is sent to the amplifier card that compares position signal to command signal and corrects the control signal to solenoids accordingly. When having close loop control option in CVG, the electro proportional control end of spool is replaced with the close loop control valve end. It has onboard electronics to compare spool position to command signal and needs only power supply and command signal for the main spool position.

Technical Data


General			
Design		Control valve group with modular design	
Mounting positions		Optional	
Ambient temperature		[°C]	-30 ... +70
Hydraulic			
Operating pressure		[bar]	350, peak pressure 420
Fluid		Mineral oil in accordance with DIN51524 and DIN51525	
Fluid temperature		[°C]	-20 ... +90
Viscosity permitted		[cSt] / [mm²/s]	15 ... 380
Viscosity recommended		[cSt] / [mm²/s]	30 ... 80
Filtration		ISO4406 (1999); 18/16/13	
Leakage at 40 cSt		[l/min]	Up to 3 with 350 bar, depending on spool
Pilot pressure		[bar]	Internally 45, externally to port PP2 through pressure reducing valve 45-420 should be 45-350 supply to port PP2 for pressure reducing valve Max. pilot pressure 100
Hydraulic pilot		[bar]	External remote control for spool 0 - 35
Tank line		[bar]	Port T maximum pressure 30
Drain pressure		[bar]	Port DR maximum pressure 1
Nominal flow		Flow with 5 bar pressure drop over one control edge of main spool	
		CVG30	CVG50 CVG60
		500 / section	800 / section1200 / section
Maximum flow		[l/min]	750 / section1200 / section2000 / section
Main pressure relief		Maximum flow of single* pressure relief valve	
		CVG30 Inlet section	CVG50 inlet section CVG60 inlet section
		400	12001200
		Parker A06G2PZN	Parker Lokomec CEL40Parker Lokomec CEL40
Static / Dynamic			
Step response		[ms]	Open loop step response 0 to 100 %
		CVG30	CVG50 CVG60
		300	600600
		Closed loop control with onboard electronics <150 ms. Consult factory.	
Electrical characteristic			
Duty cycle		[%]	100
Amplifier		Parker IQAN control systems or Parker amplifiers for proportional valves	
Protection class		IP65	
Current		[mA]	For spool control 0-800 mA (spool movement 300 - 750 mA)
Solenoid connection		AMP Junior-Power-Timer (optional Deutsch DT04-2P connector)	
ATEX solenoids		Consult factory	
Surface treatment			
Painting		2-component epoxy primer RAL7004	

*Outlet section can be equipped with secondary pressure relief. Adjustment is 10 bar higher than inlet pressure relief valve.

Ordering Code

How to order CVG

CVG master code



Example: CVG-51-32

Inlet with pressure relief valve and pilot oil pressure reducing valve. One CVG50 control section with electro-proportional pilot cover. Adapter to fit two CVG30 control sections and outlet with ports P and T.

Adjustment values

Pressure and flow adjustment values of CVG assembly are added after each part item code. Pressure setting of main pressure relief is added after inlet section code. Flow and pressure settings of A and B port is added after control section code.


Qxx = maximum flow setting

Axx = maximum supply pressure of port A

Bxx = maximum supply pressure of port B

CVG-51-32 specific order code with pressure and flow settings ¹⁾.

1. P50-21-BN2 350
2. S50-81-08-C1-00-F0-BN2 Q800 A350 B280
3. A530-BN2
4. S30-81-05-C1-00-F0-BN2 Q600 A350 B280
5. S30-31-03-C1-00-F0-BN2 Q450 A280 B280
6. T30-12-BN





¹⁾ See specified coding for inlet, control and outlet section from ordering code pages.

Ordering Code

Mobile Directional Control Valve
CVG

Inlet section





1

Ordering Code

Control section

S		-		-		-		-		-	B		
Control section	Control section size	Spool option	Spool size	Pilot control cover	Adapter	Adapter	Spool cover	Design	Seals	Measuring connector			

Code	Control section size
30	CVG30
50	CVG50
60	CVG60

Code	Drawing	Spool option
31		Spool 03, symmetric
32		Spool 03, meter out
81		Spool 08, symmetric
82		Spool 08, meter out
XX		Specially designed spool ¹⁾

Code	Spool size
00	50 l/min (size 30)
01	150 l/min (size 30)
02	200 l/min (size 30)
05	500 l/min (size 30)
08	800 l/min (size 50)
10	1000 l/min (size 50/60)
12	1200 l/min (size 60)

Code	Pilot control cover (A side)
C1	Electro-proportional
C2	Electro-proportional and external hydraulic pilot
C3	External hydraulic pilot
C4	Electro-proportional high step response
C5	Electro-proportional high step response and external hydraulic pilot
C6	Closed loop with onboard electronics
E1	Electro-proportional ATEX
E2	Electro-proportional ATEX and external hydraulic pilot
E4	Electro-proportional high step response ATEX


Code	Measuring connector type
2	Carbon steel connectors
3	Stainless steel connectors

Code	Seals type
N	NBR
V	FPM

Code	Spool Cover (B side)
F0	No feedback
F1	Spool position feedback LVDT ²⁾

Code	Adapter in port B
0	No adapter
1	2x 1 1/2" SAE62 (CVG50, CVG60)
2	2x 2" SAE62 (CVG60)



Code	Adapter in port A
0	No adapter
1	2x 1 1/2" SAE62 (CVG50, CVG60)
2	2x 2" SAE62 (CVG60)


¹⁾ Please consult Parker.²⁾ Please consult Parker for different types of LVDT sensors.

Ordering Code

Mobile Directional Control Valve
CVG

Outlet section




Ordering Code**Mobile Directional Control Valve
CVG****Adapter section**

Code	Inlet section size
330	CVG30 to CVG30
530	CVG50 to CVG30
630	CVG60 to CVG30
650	CVG60 to CVG50
550	CVG50 to CVG50


Code	Extra ports
1	No ports
2	Extra ports P, T

Code	Seal type
N	NBR
V	FPM




Pressure drop CVG compensator spools

The pressure difference over compensator is measured when compensator spool is forced fully open. Pressure is measured from ports MP and M1. Total pressure loss over control section is sum of compensator spool pressure loss and main spool pressure loss.




Measured with HLP46 at 50 °C


CVG30 spool opening vs current




CVG30 step response



CVG50/60 spool opening vs current



CVG50/60 step response




HY11-3353 CVG UK.indd CM 07.10.13

Measuring Data CVG30**Pressure drop CVG30 spools**

The diagram below specifies the pressure loss over spool control edge.

Δp over main spool [bar]




spool	nominal size	Position b		Position a	
		P-B	A-T	P-A	B-T
00	50 l/min (size 30)	1	1	1	1
01	150 l/min (size 30)	2	2	2	2
02	200 l/min (size 30)	3	3	3	3
05	500 l/min (size 30)	4	4	4	4

Compensator adjustment range CVG30

The diagram specifies the control curves for spool "81-05"* with different compensator settings.

Flow [l/min]



All characteristic curves measured with HLP46 at 50 °C


* For adjustment range for other spools, please consult Parker.

HY11-3353 CVG UK.indd CM 07.10.13

Pressure drop CVG 50 spools

The diagram below specifies the pressure loss over spool control edge.


Δp over main spool [bar]




spool	nominal size	Position b		Position a	
		P-B	A-T	P-A	B-T
08	800 l/min (size 50)	1	1	1	1
10	1000 l/min (size 50)	2	2	2	2

Compensator adjustment range CVG50

The diagram shows the control curves for spool “81-08” with different compensator settings.



The diagram shows the control curves for spool “81-10” with different compensator settings.



All characteristic curves measured with HLP46 at 50 °C


* For adjustment range for other spools, please consult Parker.

HY11-3353 CVG UK.indd CM 07.10.13

Pressure drop CVG60 spools

The diagram below specifies the pressure loss over spool control edge.


Δp over main spool [bar]



spool	nominal size	Position b		Position a	
		P-B	A-T	P-A	B-T
10	1000 l/min (size 60)	1	1	1	1
12	1200 l/min (size 60)	2	2	2	2

Compensator adjustment range CVG60

The diagram shows the control curves for spool "81-12"* with different compensator settings.



All characteristic curves measured with HLP46 at 50 °C

* For adjustment range for other spools, please consult Parker.

Spool Selection Table**CVG-B spool table****Standard spools**

CVG size	Code	Nominal flow*	Recommended compensator adjustment range [l/min]	Function	Spool assembly part number	Spool part number
CVG30	81-00	60	70 - 110	open center, symmetric	31008702	31013300
CVG30	31-00	60	70 - 110	closed center, symmetric	31008705	31014400
CVG30	81-01	140	130 - 220	open center, symmetric	31008713	31131200
CVG30	31-01	140	130 - 220	closed center, symmetric	31008719	31172100
CVG30	81-02	220	220 - 370	open center, symmetric	31008701	31013200
CVG30	31-02	220	220 - 370	closed center, symmetric	31008704	31014500
CVG30	81-05	500	360 - 750	open center, symmetric	31008700	31011500
CVG30	31-05	500	360 - 750	closed center, symmetric	31008703	31014600
CVG50	81-08	820	600 - 1200	open center, symmetric	31012801	39721200
CVG50	31-08	820	600 - 1200	closed center, symmetric	31012804	31043800
CVG50	81-10	1000	700 - 1400	open center, symmetric	31012800	39721000
CVG50	31-10	1000	700 - 1400	closed center, symmetric	31012803	31036800
CVG60	81-10	950	800 - 1500	open center, symmetric	31012801	39721200
CVG60	31-10	950	800 - 1500	closed center, symmetric	31012804	31043800
CVG60	81-12	1150	1000 - 2000	open center, symmetric	31012800	39721000
CVG60	31-12	1150	1000 - 2000	closed center, symmetric	31012803	31036800

Meter out spools


CVG size	Code	Nominal flow*	Recommended compensator adjustment range [l/min]	Function	Spool assembly part number	Spool part number
CVG30	32-02	220	215 - 370	closed center, A-T meter-out 25 %	31008707	31068300
CVG30	32-05	500	360 - 750	closed center, A-T meter-out 25 %	31008706	31063500
CVG50	82-10	1000	700 - 1400	open center, A-T meter-out 25 %	31012808	31086000
CVG50	32-10	1000	700 - 1400	closed center, A-T meter-out 25 %	31012806	31049800
CVG60	82-12	1150	1000 - 2000	open center, A-T meter-out 25 %	31012808	31086000
CVG60	32-12	1150	1000 - 2000	closed center, A-T meter-out 25 %	31012806	31049800

* l/min at 5 bar over one control edge measured from M1 and MA. Accuracy ± 2 %.

CVG33 assembly example

The CVG33 assembly includes the inlet section, three control sections and the outlet section. Here is shown one variation of CVG33 assembly with three different types of control sections. The same assembly is shown in the dimensional section of this catalogue.



- 1 P30-21-BN2
Inlet section with pressure relief and pilot pressure valve
- 2 S30-81-05-C1-00-F0-BN2
Section 1 with electronic spool pilot
- 3 S30-81-05-C2-00-F0-BN2
Section 2 with electronic and hydraulic spool pilot
- 4 S30-31-05-C3-00-F1-BN2
Section 3 with hydraulic spool pilot and spool position sensor
- 5 T30-22-BN
Outlet section with pressure relief

**Hydraulic diagram CVG33**

CVG53 assembly example


The CVG53 assembly includes the inlet section, three control sections and the outlet section. Here is shown one variation of CVG53 assembly with three different types of control sections. The same assembly is shown in the dimensional section of this catalogue.

- 1 P50-21-BN2
Inlet section with pressure relief and pilot pressure valve
- 2 S50-81-08-C1-11-F0-BN2
Section 1 with electronic spool pilot
- 3 S50-81-08-C2-00-F0-BN2
Section 2 with electronic and hydraulic spool pilot
- 4 S50-31-08-C3-00-F1-BN2
Section 3 with hydraulic spool pilot and spool position sensor
- 5 T50-12-BN
Outlet section without pressure relief

**Hydraulic diagram CVG53**


CVG63 assembly example

The CVG63 assembly includes the inlet section, three control sections and the outlet section. Here is shown one variation of CVG63 assembly with three different types of control sections. The same assembly is shown in the dimensional section of this catalogue.



- 1 P60-21-BN
Inlet section with pressure relief and pilot pressure valve
- 2 S60-81-08-C1-22-F0-BN2
Section 1 with electronic spool pilot
- 3 S60-81-08-C2-11-F0-BN2
Section 2 with electronic and hydraulic spool pilot
- 4 S60-31-08-C3-00-F1-BN2
Section 3 with hydraulic spool pilot and spool position sensor
- 5 T60-22-BN
Outlet section with pressure relief

Hydraulic diagram CVG63



Dimensions CVG30




Mobile Directional Control Valve
CVG


Inlet section connections

P, T	G 1 1/2" BSPP
DR	G 3/8" BSPP
LS, PP, PP2	G 1/4" BSPP
MP, MT, MLS, MPP, MDR	G 1/4" BSPP


Outlet section connections

P, T	G 1 1/2" BSPP
------	---------------



	D1	D2	D3	L1
	G 1/8"	8.8	20	10
	G 1/4"	11.8	25	14
	G 3/8"	15.25	29	14
	G 1/2"	19	34	16
	G 3/4"	24.5	42	18
	G 1"	30.5	47	20
	G 1 1/4"	39.5	58	22
	G 1 1/2"	45	65	24
	G 2"	57	76	29

ISO 228 - G BSPP threads



Assembly




Pos.	Name	Code	Weight (kg)
1	Inlet section	P30-21-BN2	21
2	Control section	S30-81-05-C1-00-F0-BN2	38
3	Control section	S30-81-05-C2-00-F0-BN2	38
4	Control section	S30-31-05-C3-00-F1-BN2	38
5	Outlet section	T30-22-BN	22

Dimensions

No. of control sections	L (mm)	L2 (mm)	Weight (kg)
1	225	185	81
2	300	260	119
3	375	295	157
4	450	330	195
5	525	365	233

Control section connections

A, B	G 1 1/2" BSPP
MPA, MPB	G 1/4" BSPP
MLA, MLB, M1	G 1/4" BSPP
PA, PB (Cover C2 and C3)	G 1/4" BSPP



Dimensions CVG50




Mobile Directional Control Valve
CVG

Inlet section connections

P	2" SAE62
T	2 ½" SAE61
DR	G ½" BSPP
LS, PP, PP2	G ¾" BSPP
MP, MT, MLS, MPP, MDR	G ¼" BSPP



Outlet section connections

P	2" SAE62
T	2 ½" SAE61



	D1	D2	D3	L1
G 1/8"	8.8	20	10	
G 1/4"	11.8	25	14	
G 3/8"	15.25	29	14	
G 1/2"	19	34	16	
G 3/4"	24.5	42	18	
G 1"	30.5	47	20	
G 1 1/4"	39.5	58	22	
G 1 1/2"	45	65	24	
G 2"	57	76	29	

ISO 228 - G BSPP threads



Assembly



Pos.	Name	Code	Weight (kg)
1	Inlet section	P50-21-BN2	58
2	Control section	S50-81-08-C1-11-F0-BN2	81
3	Control section	S50-81-08-C2-00-F0-BN2	81
4	Control section	S50-31-08-C3-00-F1-BN2	81
5	Outlet section	T50-12-BN	54

Dimensions

No. of control sections	L (mm)	L2 (mm)	Weight (kg)
1	220	360	193
2	340	480	274
3	460	600	355
4	580	720	436
5	700	840	517

Control section connections

A, B	1 1/2" SAE62
MPA, MPB	G 1/4" BSPP
MLA, MLB, M1	G 1/4" BSPP
PA, PB (Cover C2 and C3)	G 1/4" BSPP



Dimensions CVG60




Mobile Directional Control Valve
CVG

Inlet section connections

P	2x 2" SAE62
T	3" SAE61
DR	G ½" BSPP
LS, PP, PP2	G ¾" BSPP
MP, MT, MLS, MPP, MDR	G ¼" BSPP


Outlet section connections

P	2x 2" SAE62
T	3" SAE61



	D1	D2	D3	L1
	G ⅛"	8.8	20	10
	G ¼"	11.8	25	14
	G ⅜"	15.25	29	14
	G ½"	19	34	16
	G ¾"	24.5	42	18
	G 1"	30.5	47	20
	G 1 ¼"	39.5	58	22
	G 1 ½"	45	65	24
	G 2"	57	76	29

ISO 228 - G BSPP threads



Dimensions CVG60**Mobile Directional Control Valve
CVG****Assembly**





Pos.	Name	Code	Weight
1	Inlet section	P60-21-BN2	79
2	Control section	S60-81-10-C1-22-F0-BN2	135
3	Control section	S60-81-10-C2-11-F0-BN2	131
4	Control section	S60-31-10-C3-00-F1-BN2	97
5	Outlet section	T60-22-BN	54

Dimensions

No. of control sections	L (mm)	L2 (mm)	Weight (kg)
1	280	420	250
2	420	560	347
3	560	700	444
4	700	840	541
5	840	980	638


Control section connections

A, B	2" SAE62
MPA, MPB	G 1/4" BSPP
MLA, MLB, M1	G 1/4" BSPP
PA, PB (Cover C2 and C3)	G 1/4" BSPP




CVG30 control section

Position	110829XX		Quantity
	Code	Type	
1	TS110829	SEAL KIT 110829	
2	31013500	CVG30 PILOT COVER ASSEMBLY C1	1
2	31013502	CVG30 PILOT COVER ASSEMBLY C2	1
2	31013502	CVG30 PILOT COVER ASSEMBLY C3	1
3	31013600	CVG30 COVER ASSEMBLY F0	1
4	310087XX	CVG30 SPOOL ASSEMBLY	1
5	31013400	CVG30 COMPENSATOR ASSEMBLY	1
6	PRPA1017	A04G2PZN + CAP 410312	2
7	K02A3N	K02A3N	1
8	VAHA0011	RK1 CHECK VALVE	1
9	KU005200	M5X5-2,0	2
10	PAMA0410	TM85201 24VDC32BAR FILT+OVER	2
11		LVDT ASSEMBLY	1
12	SF438064	SPRING FOR SPOOL	1
13	SF426127	SPRING FOR COMPENSATOR	1
14	41006800	COMPENSATOR SPOOL	1
15	KU006060	M6X6-0,6	1
16	MISTG142	SMK 20-G1/4-VC-V2A<1,4305>AI	8



CVG50 control section


Position	110842XX		Quantity
	Code	Type	
1	TS110842	SEAL KIT 110842	1
2	31013100	CVG PILOT COVER ASSEMBLY C1	1
2	31013101	CVG PILOT COVER ASSEMBLY C2	1
2	31013102	CVG PILOT COVER ASSEMBLY C3	1
3	31013000	CVG COVER ASSEMBLY F0	1
4	31012800	CVG SPOOL ASSEMBLY	1
5	31012900	CVG50 COMPENSATOR ASSEMBLY	1
6	PRPA1017	A04G2PZN + CAP 410312	2
7	K02A3N	K02A3N	1
8	VAHA0011	RK1 CHECK VALVE	1
9	KU005200	M5X5-2,0	2
10	PAMA0410	TM85201 24VDC32BAR FILT+OVER	2
11		LVDT ASSEMBLY	1
12	SF451001	SPRING FOR SPOOL	1
13	SF432000	SPRING FOR COMPENSATOR	1
14	44289400	COMPENSATOR SPOOL	1
15	KU006080	M6X6-0,8	1
16	EMA3/1/4EDBPCF	EMA3/1/4EDBPCF	8



HY11-3353 CVG UK.indd CM 07.10.13


CVG60 control section

Position	110734XX		Quantity
	Code	Type	
1	TS 110734	SEAL KIT 110734	
2	31013100	CVG PILOT COVER ASSEMBLY C1	1
2	31013101	CVG PILOT COVER ASSEMBLY C2	1
2	31013102	CVG PILOT COVER ASSEMBLY C3	1
3	31013000	CVG COVER ASSEMBLY F0	1
4	31012800	CVG SPOOL ASSEMBLY	1
5	31178700	CVG60 COMPENSATOR ASSEMBLY	1
6	PRPA1017	A04G2PZN + CAP 410312	2
7	K02A3N	K02A3N	1
8	VAHA0011	RK1 CHECK VALVE	1
9	KU005200	M5X5-2,0	2
10	PAMA0410	TM85201 24VDC32BAR FILT+OVER	2
11		LVDT ASSEMBLY	1
12	SF451001	SPRING FOR SPOOL	1
13	SF432000	SPRING FOR COMPENSATOR	1
14	44289400	COMPENSATOR SPOOL	1
15	KU006080	M6X6-0,8	1
16	EMA3/1/4EDBPCF	EMA3/1/4EDBPCF	8




CVG30 Inlet section with pressure relief

Position	211545XX		Quantity
	Code	Type	
1	TS211545	SEAL KIT 211545	1
2	PRPA2505	A06G2PZN + CAP 410312	1
3	PAPA1038	C04B3HZN + CAP 410312	1
4	KU006040	M6X6-0,4	
5	EMA3/1/4EDBPCF	EMA3/1/4EDBPCF	5




CVG50 Inlet section with pressure relief

Position	211080XX		Quantity
	Code	Type	
1	TS211080	SEAL KIT 211080	1
2	31156900	CRL40 R6S AN X12C10	1
3	41003802	CEL40 A40 AN 00	1
4	PAPA1038	C04B3HZN + CAP 410312	1
5	KU006040	M6X6-0,4	1
6	EMA3/1/4EDBPCF	EMA3/1/4EDBPCF	5




CVG60 Inlet section with pressure relief

Position	210938XX		Quantity
	Code	Type	
1	TS210938	SEAL KIT 210938	1
2	31156900	CRL40 R6S AN X12C10	1
3	41003802	CEL40 A40 AN 00	1
4	PAPA1038	C04B3HZN + CAP 410312	1
5	KU006040	M6X6-0,4	1
6	EMA3/1/4EDBPCF	EMA3/1/4EDBPCF	5




Adapters


	211350XX	Adapter A650	1
1	TS211350	SEAL KIT 211350	



	111198XX	Adapter A630	1
1	TS111198	SEAL KIT 111198	



	211351XX	Adapter A530	1
1	TS211351	SEAL KIT 211351	



This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.A full-page view of a blank sheet of graph paper. The grid consists of thin, light gray horizontal and vertical lines forming small squares across the entire page. There are no margins, text, or other markings present.

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.This image shows a full page of blank graph paper. The grid consists of small, uniform squares formed by thin, light gray lines. There are no margins, text, or other markings on the page.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.This image shows a full page of blank graph paper. The grid consists of small, equal-sized squares formed by thin gray lines. There are 20 columns and 20 rows of squares, creating a total area of 400 square units. The grid is perfectly aligned and covers the entire page without any margins or additional markings.

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates,
Dubai

Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, Wiener Neustadt

Tel: +43 (0)2622 23501-0
parker.austria@parker.com

AT – Eastern Europe, Wiener
Neustadt

Tel: +43 (0)2622 23501 900
parker.easteurope@parker.com

AZ – Azerbaijan, Baku

Tel: +994 50 22 33 458
parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles

Tel: +32 (0)67 280 900
parker.belgium@parker.com

BG – Bulgaria, Sofia

Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk

Tel: +375 17 209 9399
parker.belarus@parker.com

CH – Switzerland, Etoy

Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany

Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst

Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup

Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid

Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa

Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve

Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Athens

Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaoers

Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin

Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IT – Italy, Corsico (MI)

Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty

Tel: +7 7273 561 000
parker.easteurope@parker.com

NL – The Netherlands, Oldenzaal

Tel: +31 (0)541 585 000
parker.nl@parker.com

NO – Norway, Asker

Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw

Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal, Leca da Palmeira

Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest

Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow

Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga

Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SK – Slovakia, Banská Bystrica

Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto

Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul

Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev

Tel: +380 44 494 2731
parker.ukraine@parker.com

UK – United Kingdom, Warwick

Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park

Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario

Tel: +1 905 693 3000

US – USA, Cleveland

(industrial)
Tel: +1 216 896 3000

US – USA, Elk Grove Village

(mobile)
Tel: +1 847 258 6200

Asia Pacific

AU – Australia, Castle Hill

Tel: +61 (0)2-9634 7777

CN – China, Shanghai

Tel: +86 21 2899 5000

HK – Hong Kong

Tel: +852 2428 8008

ID – Indonesia, Tangerang

Tel: +62 21 7588 1906

IN – India, Mumbai

Tel: +91 22 6513 7081-85

JP – Japan, Fujisawa

Tel: +81 (0)4 6635 3050

KR – South Korea, Seoul

Tel: +82 2 559 0400

MY – Malaysia, Shah Alam

Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington

Tel: +64 9 574 1744

SG – Singapore

Tel: +65 6887 6300

TH – Thailand, Bangkok

Tel: +662 717 8140

TW – Taiwan, New Taipei City

Tel: +886 2 2298 8987

VN – Vietnam, Ho Chi Minh City

Tel: +84 8 3999 1600

South America

AR – Argentina, Buenos Aires

Tel: +54 3327 44 4129

BR – Brazil, Cachoeirinha RS

Tel: +55 51 3470 9144

CL – Chile, Santiago

Tel: +56 2 623 1216

MX – Mexico, Toluca

Tel: +52 72 2275 4200

EMEA Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL,
IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

US Product Information Centre

Toll-free number: 1-800-27 27 537

www.parker.com

Your local authorized Parker distributor

