

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	PARKER HANNIFIN MANUFACTURING SRL
Address	Via G.B. Pirelli 6, Veniano Como, 22070, Italy
Type	Flexible Hoses
Description	Flexible hydraulic hoses with synthetic rubber tube, reinforced by four or six high tensile steel wires and covered with a flame resistant compound.
Trade Name	FA35 - Firearmor 5000
Application	For hydraulic systems of Blowout Preventer control lines on drilling rigs.
Specified Standard	API Specification 16D, 3rd Edition, November 2018: Control Systems for Drilling Well Control Equipment and Control Systems for Diverter Equipment Lloyd's Register Fire Tests for Flexible Hoses on Offshore Installations (5 minutes fire test)
Ratings	Size: 6 (DN10) to 32 (DN51) Design pressure: 350 bar Temperature Range: -40°C to 100°C Exception: Air max 70°C Water max 85°C Fitting Series: VS size 6 and 8 (approved only with fire protection sleeve) V4 size 10 up to 20 (approved also with SS armor sleeve protection)

Johannes Wiegel

Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

V6 size 24 and 32 (approved also with SS armor sleeve protection)

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR21170871TA

The Design Appraisal Document HTS/ENS 42690-21 and its supplementary Type Approval Terms and Conditions form part of this Certificate.