GENERAL CATALOGUE

Solenoid Valves for Fluid Control

Parker

Who we are?

The Fluid Control Solutions Europe (FCSE) Business Unit is part of the Fluid and Climate Controls Division Europe (FCCE) of Parker Hannifin, the global leader in Motion and Control Technologies. FCSE core competences are the development and manufacturing of an extremely diverse range of fluid control products, including solenoid valves and pressure regulators.

Where we are?

Our European headquarters are located in Gessate (Milan-Italy) , this is also where our R&D, Marketing, Application Support and Product Management functions are located.
Our Products are mainly manufactured in Gessate (Milan - Italy). The Parker Sales Companies and comprehensive distribution network support you, wherever you are.

History

Parker FCSE has been a leading player in the manufacturing and development of solenoid valve technologies for over 60 years, with continuous research and development bringing innovative solutions to the marketplace, for example leading the way in the utilisation of synthetic ruby for critical water applications or the unsurpassed reliability and precision of our pressure regulators. The expertise accumulated and developed through the years is evident in the superior quality of FCSE solutions.

Markets

Our products and solutions are typically designed for markets including Industrial Equipment, Industrial Automation, Mobile, Transportation, Life Sciences, Beverage dispensing and for Fluid and Process Control.

Benefits

The modular concept of our products, having separate solenoid valves and electrical parts, provides the customer with increased flexibility by allowing numerous combinations. This additional flexibility can enable distributors to greater reduce valve inventory levels, whilst retaining the same number of capabilities. Parker also has unrivalled experience in developing customised product solutions complying with the highest technical, environmental, energy and service life requirements.

WARNING - USER RESPONSIBILITY

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

- **This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.**
- **The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.**
- **To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.**

FCSE HEADQUARTER - GESSATE (MI) - ITALY

GENERAL CATALOGUE FCSE

TABLE OF CONTENT

INTRODUCTION

A complete range of solenoid valves 06
A modular concept 08
ATEX Certification 10
World class standards 11
How to use this catalogue 12
How to select a valve 14
How to order 16
How to use coil groups 18

VALVES FOR INDUSTRIAL AND GENERAL PURPOSE

2 way valves for dry or lubricated air, neutral gases and liquids 21
3 way valves for dry or lubricated air, neutral gases and liquids 61
Valves for water and neutral liquids 95
Anti water hammer valves 123
Hot water and steam valves 135
2 way valves for hydraulic oil and neutral liquids 145
3 way valves for hydraulic oil and neutral liquids 161
2 way high corrosion resistant valves (303-316L Stainless Steel) 165
3 way high corrosion resistant valves (303-316L Stainless Steel) 183
Oil burner valves 191
Gas burner valves 205
Fast switching valves 209

VALVES FOR BEVERAGE DISPENSING

2 way Healthy Solenoid Valves 213
3 way Healthy Solenoid Valves 217
2 way valves & Liquipure® 221
3 way valves & Liquipure® 233
2 way Technopolymer valves 247
3 way Technopolymer valves 253

VALVES FOR TRANSPORTATION

2 way 261
3 way 267

DISTRIBUTORS FOR PNEUMATIC APPLICATIONS

5 way pneumatic distributors (Pipe mounting/Sub-base mounting) 271

PNEUMATIC DISTRIBUTORS FOR ACTUATION CONTROL

3 & 5 way pneumatic valves for actuator control (Pipe mounting) 297
3 & 5 way pneumatic valves for actuator control (NAMUR) 329
316L Stainless Steel 3 & 5 way valves for actuator control (Pipe mounting and NAMUR) 371

ELECTROPNEUMATIC PRESSURE REGULATORS

EPP4 Series - Basic, Comfort , Comfort ATEX Ranges 407

COILS, HOUSINGS & ELECTRICAL PARTS

Introduction 439
Coils 446
Explosion Proof Electrical Parts 472
Housings 502
Coil Accessories 506
Explosive Environments 508
Guidance Chart for IS-Barriers 518

TECHNICAL INFORMATION ABOUT SOLENOID VALVES

Technical information about solenoid valves 492

APPENDIX

Index by Coil Reference 540
Index by Coil Group 542
Index by Valve reference 544
Index for Valves 546

A COMPLETE RANGE OF SOLENOID VALVES FOR FLUID CONTROL

2 & 3 WAY VALVES FOR INDUSTRIAL AND GENERAL PURPOSE

- For dry or lubricated air, neutral gases and liquids
- For water and neutral liquids
- Anti water hammer
- Hot water and steam
- For hydraulic oil and neutral liquids (Max. 100 bar)
- High corrosion resistant
  (303 Stainless Steel)
  (316L Stainless Steel)
- Oil burner
- Gas burner
- Fast switching

2 & 3 WAYS VALVES FOR BEVERAGE DISPENSING:

- 2 & 3 way healthy solenoid valves
- 2 & 3 way valves & Liquipure®
- 2 & 3 way Technopolymer valves

2 & 3 WAY VALVES FOR TRANSPORTATION

- 2 way- direct and piloted
- 3 way- direct operated

3&5 WAY DISTRIBUTORS FOR PNEUMATIC APPLICATIONS

- Pipe mounted/ Sub-base mounting

3 & 5 WAY PNEUMATIC DISTRIBUTORS FOR ACTUATION CONTROL

- Pipe mounted
- NAMUR interface
- 316L Stainless Steel
  (Pipe mounted and with NAMUR interface)

COILS & ELECTRICAL PARTS

- Coils
- Housings
- Explosion-Proof Electrical Parts

EPP4 SERIES ELECTROPNEUMATIC PRESSURE REGULATORS

- Basic
- Comfort
- Comfort ATEX

A MODULAR CONCEPT FOR EVERY APPLICATION

CHOOSE BETWEEN:

Actuation Modes

- Direct Operated
- Magnalift
- Pilot Operated
- Manual Reset
- Externally Operated

Material Types

- Brass
- 303 Stainless St.
- 316L Stainless St.
- Anodized Aluminium
- Zinc Alloy
- POM

Mounting Solutions

- Pipe
- Sub-base
- NAMUR
- Banjo
- CETOP
- ISO

Control Functions

- Normally Closed
- Normally Open
- Universal
- Control by Electric Impulse
- Dual Solenoids
- PWM

Internal Design

- Piston
- Poppet
- Diaphragm
- Spool

Seals

- FKM
- NBR
- EPDM
- Ruby
- PUR
- PCTFE...



ELECTRICAL PART ATEX CERTIFICATION

A selection of electrical parts conform to the terms of the 2014/34/EU directive and are made for potentially explosive environments - zone 0/20, 1/21 and 2/22.

Within the coil section, the presence of the ATEX logo shows that the coil is ATEX approved.

PRESSURE VESSELS ATEX CERTIFICATION

A selection of pressure vessels conform to the terms of the 2014/34/EU directive specific to non electrical equipment for use within potentially explosive environments - zones 0/20, 1/21 and 2/22.

NAMUR & piped valve ranges now include a marking which indicates mechanical ATEX approval.

Within the valve section, the presence of the ATEX logo indicates that the valve family is covered by an ATEX Type Examination Certificate or is included in an ATEX Technical File.
Contact Technical Support for ATEX certification information on specific valve model.



SOLENOID VALVE CERTIFICATION

When both the electrical and mechanical part are ATEX approved, the solenoid valve can be used in explosive atmospheres.

The solenoid valve can be delivered assembled and tested.

Contact Technical Support for compatibility between ATEX mechanical part and ATEX coil.
Parker is not responsible for assembly operations between ATEX mechanical part and ATEX coils performed outside Parker plants.

FCSE IS MEETING WORLD CLASS STANDARDS

QUALITY STANDARDS:

- ISO 9001
- ISO 14001
- OHSAS 18001
- ISO 45001 : 2018

CERTIFICATIONS AND APPROVALS:

Our products have been approved and are compliant with the relevant market requirements including:

Regulatory compliance:

- CE
- UKCA
- RoHS
- REACH

Third party certifications:

- ATEX
- IECEx
- CCC
- KCs
- JPEx
- UL
- VDE
- IMQ
- DIN
- BSI
- AGA
- NSF

IMPORTANT NOTE:
Third party certifications apply to specific product families.
For detailed information about the product certifications available for a specific product family, please refer to the pertinent catalogue sections and to Parker technical support.

HOW TO USE THIS CATALOGUE

This catalogue is a comprehensive list of Parker Solenoid Valves program. It will help to identify appropriate valves and coils and enable the user to generate ordering numbers.

This catalogue is split product range. You will find a summary page at the beginning of each valve section. For ease of use, each valve section is divided by application.

On the first page of each Application section, you will find an overview of the products within and their technical characteristics, to guide you to the relevant page (example below):

SECTION SUMMARY PAGE



For further technical information regarding Actuation, Body and Function, please refer to the technical information section at the end of the catalogue.

Applicable Approvals within this page

Quick selection table with Min/Max values for all valves on the page

SECTION PRODUCT PAGE



Ordering information

ISO 1219 Symbol

A choice of Coil Groups compatible with the selected valve.

Dimensional 2D* and 3D drawings

* 2D drawing shown always corresponds to the standard coil.

HOW TO SELECT A VALVE

Once you are in the selected range 1 and application 2 The table is designed to help you navigate to the products matching your criteria.

First decide the actuation 3, then move accross the table selecting your body material 4, function 5 and technical requirements 6.

After you have found products fitting within your specification, please go to the corresponding page number in the final column 7, here you will find a selection of products that match your criteria.

1 SELECT PRODUCT FAMILY

2 SELECT APPLICATION

3 SELECT ACTUATION

4 SELECT BODY

5 SELECT FUNCTION

6 SELECT TECHNICAL DATA

7 SELECT CORRESPONDING PAGE

1

2 WAY VALVES

VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

2

Oil Water Air

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves	Page Parker LUCIFER® Valves
Direct Operated	Brass/Pipe mounting	Normally Closed	1/8''	1.2 to 3	4.5	70	140	28	32
			1/4''	1.2 to 5	13	100	140	30	32
			3/8''	4 to 6	12	10	120	-	36
			1/2''	8.5 to 11	36	4	120	-	36
		Normally Open	1/8''	2.5	3.5	30	140	-	40
			1/4''	1.5 to 3	4	40	140	38	40
		Control by Electric Impulse	1/4''	3 to 5	11	20	100	-	40
	Brass/Sub-base mounting	Normally Closed	5 mm	1.5 to 3	4.5	100	130	-	42
		Normally Open	5 mm	1.5	1.5	20	120	-	44
Magnalift	Brass/Pipe mounting	Normally Closed	3/8''	13 to 15	65	20	140	46	48
			1/2''	13 to 15	65	20	140	46	48
			3/4''	15 to 20	100	20	140	46	50
			1''	15 to 25	170	20	140	46	52
Pil	Brass/P ting	Normally	1/4''	8 to 12		40	120	-	
			3/8''	11 to 13		0	120	54	
			1/2''	11 to 15		0	120	54	
			3/4''	15 to 20		40	120	54	
			1''	18 to 28	270	16	120	54	64
			1 1/2''	40	425	16	120	-	66
			2''	40	540	16	120	-	66
		Normally Open	1/4''	8	36	40	140	-	70
			3/8''	11 to 13	50	40	140	68	70
			1/2''	13 to 15	60	40	140	68	70
			3/4''	15 to 20	135	40	120	68	72
			1''	25 to 40	420	16	120	68	72
			1 1/4''	28	270	16	120	-	72
			1 1/2''	40	420	12	100	-	72
			2''	40	540	12	120	-	72
		Control by Electric Impulse	1/4''	12	32	12	100	-	74
			3/8''	12	45	12	100	-	74
			1/2''	12	50	12	100	-	74
			3/4''	18	100	12	100	-	74
			1''	18	110	12	100	-	74
	Brass/Sub-base mounting	Normally Closed	14 mm	14	45	40	140	-	76
		Normally Open	14 mm	14	46	40	120	-	76

3 4 5 6 7

A SOLENOID VALVE IS COMPOSED OF 3 ELEMENTS:

The Valve (1) + Housing (2) + Coil (3)

1. Choose the valve reference
2. Choose the housing
3. Choose the coil

(1) Choose the Valve Reference

Valve Ref.
121K3206
121K3206
121K3206

(2) Select the housing depending on the protection level (IP 44 to IP 67 found in the coil section)

Housing Ref.
2995
4270
4270

2 WAY VALVES

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED

Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker LUCIFER® Valves			Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					W	W		
3/8"	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K3206	2995	481865	8	9	2.0	3551
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K3206	4270	481000	8	8	2.0	3551
		7.5	0.45	480	0	10	10	-10	120	FKM	121K3206	4270	486265	14	14	2.0	3551
	5	11	0.66	750	0	7	2	-10	100	FKM	121K3106	2995	481865	8	9	2.0	3551
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K3106	4270	481000	8	8	2.0	3551
	5	11	0.66	750	0	7	5	-10	120	FKM	121K3106	4270	486265	14	14	2.0	3551
	6	12	0.72	1100	0	5	1.1	-10	100	FKM	121K3306	2995	481865	8	9	2.0/14.2	3551
	6	12	0.72	1100	0	5	1.5	-10	120	FKM	121K3306	4270	481000	8	8	2.0/14.2	3551
	6	12	0.72	1100	0	5	3	-10	120	FKM	121K3306	4270	486265	14	14	2.0/14.2	3551
1/2"	8.5	25	1.5	1600	0	1.1	0.5	-10	100	FKM	E121K46	2995	481865	8	9	2.0	3427
	8.5	25	1.5	1600	0	2.2	0.5	-10	120	FKM	E121K46	4270	481000	8	8	2.0	3427
	8.5	25	1.5	1600	0	4	1.2	-10	120	FKM	E121K46	4270	486265	14	14	2.0	3427
	11	36	2.16	2500	0	0.7	0.3	-10	100	FKM	E121K45	2995	481865	8	9	2.0	3427
	11	36	2.16	2500	0	1.2	0.35	-10	120	FKM	E121K45	4270	481000	8	8	2.0	3427
	11	36	2.16	2500	0	2.5	0.7	-10	120	FKM	E121K45	4270	486265	14	14	2.0	3427

Notes:
1. Valve compatible with water only up to 40°C
2. With manual override

36

For a given valve, several coil types are being suggested.

For a wider choice, the selected valve is also compatible with every other coil from the same coil group.

Parker coils are available in many different voltages.
Choose the one you need by putting the voltage code at the end of your ordering number.

3 Choose the coil and voltage code

Coil Ref.

481865

Voltage Code

VAC/Hz	Code
12V 50-60Hz	1W
24V 50-60Hz	P0*
48V 50-60Hz	S4
110V 50Hz 115-120V 60Hz	T8*
100V 50Hz 100-120V 60Hz	T7
200V 50-60Hz	P6
220-240V 50Hz 240V 60Hz	S6*
380V 50Hz	A9

Valve and coil order example:

1	2	3
121K3206	2995	481865A2
Valve Reference	Housing	Coil and Voltage Code

2.0/2.1 COILS FOR DIN PLUG CONNECTION

COILS 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See coil on "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Reference (Without DIN Plug)			481865	
Coil Group			2.0 / 2.1	
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			H 180°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	-	10 W
		P (cold) 20°C	-	14 W
	AC	Pn (holding)	8 to 11 W	-
		Attraction cold	13 W	-
Weight			130 g (without plug)	

Voltages "Un"	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un	12V 50-60Hz 24V 50-60Hz 48V 50-60Hz 110V 50Hz 115-120V 60Hz 100V 50Hz 100-120V 60Hz 200V 50-60Hz 220-240V 50Hz 240V 60Hz 380V 50Hz	1W P0* S4 T8* T7 P6 S6* A9	12V 24V 48V 72V 96V 110V	C1* C2* C4* ON* 1T* C5*

To Order a Coil choose Coil Ref + Voltage Code, example: 481865 for 24 VDC = 481865C2
* = UL Approved

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type,

a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



Parker

EMEA Product Information Centre
Free phone: 00 800 27 27 5374
US Product Information Centre
Toll-free number: 1-800-27 27 537
www.parker.com

Your authorized Distributor

www.parker.com

© 2023 Parker Hannifin Corporation. All rights reserved.

Brochure xxxxx

IMPORTANT: Valve, Housing or Coil shall be ordered separately. In case you would require configured products, please consult your Parker contact or the PH Connect to determine available configurations.

HOW TO USE COIL GROUPS

WITHIN A VALVE PAGE

One of Parker's strengths is the modularity, adaptability and flexibility of our products.
When you select a solenoid valve, the coils displayed in the table have been chosen as they will fulfill the majority of application requirements.

Valve Ref.	Housing Ref.	Coil Ref.
121K3206	2995	481865
121K3206	4270	481000
121K3206	4270	486265

However, in some specific cases, you will need special features that will lead you to choose another coil.

Groups have been created in order to facilitate the selection of a compatible coil with the chosen valve.

Coil Group
2.0
2.0
2.0

Example:
The valve 121K3206 is proposed with the coil 481865 but you can also choose any coil from the group 2.0.



2 WAY VALVES

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED

Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker LUCIFER® Valves			Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
BSP	mm	Kv	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					W	W		
3/8"	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K3206	2995	481865	8	9	2.0	3551
	4	7.5	0.45	480	0	10	6	-10	120	FKM	121K3206	4270	481000	8	8	2.0	3551
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K3206	4270	486265	14	14	2.0	3551
	5	11	0.66	750	0	7	2	-10	100	FKM	121K3106	2995	481865	8	9	2.0	3551
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K3106	4270	481000	8	8	2.0	3551
	5	11	0.66	750	0	7	5	-10	120	FKM	121K3106	4270	486265	14	14	2.0	3551
	6	12	0.72	1100	0	5	1.1	-10	100	FKM	121K3306	2995	481865	8	9	2.0/14.2	3551
	6	12	0.72	1100	0	5	1.5	-10	120	FKM	121K3306	4270	481000	8	8	2.0/14.2	3551
	6	12	0.72	1100	0	5	3	-10	120	FKM	121K3306	4270	486265	14	14	2.0/14.2	3551
1/2"	8.5	25	1.5	1600	0	1.1	0.5	-10	100	FKM	E121K46	2995	481865	8	9	2.0	3427
	8.5	25	1.5	1600	0	2.2	0.5	-10	120	FKM	E121K46	4270	481000	8	8	2.0	3427
	8.5	25	1.5	1600	0	4	1.2	-10	120	FKM	E121K46	4270	486265	14	14	2.0	3427
	11	36	2.16	2500	0	0.7	0.3	-10	100	FKM	E121K45	2995	481865	8	9	2.0	3427
	11	36	2.16	2500	0	1.2	0.35	-10	120	FKM	E121K45	4270	481000	8	8	2.0	3427
	11	36	2.16	2500	0	2.5	0.7	-10	120	FKM	E121K45	4270	486265	14	14	2.0	3427

Notes:
1. Valve compatible with ... up to 40°C
2. With manual over...

36

It is also possible to choose the coil first and then select the valve using coil groups.

HOW TO USE COIL GROUPS

WITHIN A COIL PAGE

The coil section is at the end of the catalogue and displays the specifications of each coil, along with the reference number, class of insulation, ambient temperature, electrical power and weight.

2.0 / 2.1

Example: the valve 121K3206 is proposed with coil 481865 but is also compatible with the 2.0 coil group. This means the coil 482725 is also compatible with the chosen valve as it is within this group.

When refering to the coil section you will find the coil group for each coil. This allows you to discover which other coils are compatible with the valve you have chosen.



COIL GROUP

2.0/2.1 COILS FOR DIN PLUG CONNECTION

COILS 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined spaces, offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Reference (Without DIN Plug)			481865		
Coil Group			2.0 / 2.1		
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).		
Class of insulation			H 180°C		
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A		
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.		
Elect. Power	DC	Pn (hot)	-	10 W	
		P (cold) 20°C	-	14 W	
	AC	Pn (holding)	8 to 11 W	-	
		Attraction cold	13 W	-	
Weight			130 g (without plug)		
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			12V 50-60Hz 24V 50-60Hz 48V 50-60Hz 110V 50Hz 115-120V 60Hz 100V 50Hz 100-120V 60Hz 200V 50-60Hz 220-240V 50Hz 240V 60Hz 380V 50Hz	1W P0* S4 T8* T7 P6 S6* A9	12V 24V 48V 72V 96V 110V	C1* C2* C4* 0N* 1T* C5*

To Order a Coil choose Coil Ref + Voltage Code, example: 481865 for 24 VDC = 481865C2
* = UL Approved

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type,

a round washer and a nut to ensure the fixing between 32 mm coil and the valve.

EMEA Product Information Centre
Free phone: 00 800 27 27 5374
US Product Information Centre
Toll-free number: 1-800-27 27 537
www.parker.com

Your authorized Distributor

www.parker.com

© 2023 Parker Hannifin Corporation. All rights reserved.

Brochure xxxxx

NOTES

VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/8"	1.5 to 3	4.5	70	130	22
			1/4"	1.2 to 5	11	100	130	22 and 24
			3/8"	4 to 6	12	10	120	26
			1/2"	8.5 to 11	36	4	120	26
		Normally Open	1/8"	2.5	3.5	30	140	28
			1/4"	1.5 to 4.5	7.8	40	140	28
		Control by Electric Impulse	1/4"	3 to 5	11	20	100	28
	Brass/Sub-base Mounting	Normally Closed	5 mm	1.5 to 3	4.5	100	130	30
		Normally Open	5 mm	1.5	1.5	20	120	32
Magnalift	Brass/Pipe Mounting	Normally Closed	3/8"	15	65	20	140	34
			1/2"	15	65	20	140	34
			3/4"	15	80	20	140	36
			1"	15 to 25	170	20	120	38
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/4"	8 to 12	36	40	120	40
			3/8"	11 to 12	50	40	120	42
			1/2"	11 to 15	60	40	120	44
			3/4"	15 to 20	135	40	120	46
			1"	18 to 25	185	16	120	48
			1 1/4"	28	270	16	120	48
			1 1/2"	40	425	16	120	50
			2"	40	540	16	120	50
		Normally Open	1/4"	8	36	40	140	52
			3/8"	11	50	40	140	52
			1/2"	15	60	40	140	52
			3/4"	15 to 20	135	40	120	54
			1"	25	180	16	120	54
			1 1/4"	28	270	16	120	54
			1 1/2"	40	420	12	100	54
			2"	40	540	12	120	54
		Control by Electric Impulse	1/4"	12	32	12	100	56
			3/8"	12	45	12	100	56
			1/2"	12	50	12	100	56
			3/4"	18	100	12	100	56
			1"	18	110	12	100	56
	Brass/Sub-base Mounting	Normally Closed	14 mm	14	45	40	140	58
		Normally Open	14 mm	14	46	40	120	58

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/8"	1.5	0.9	0.05	70	0	20	12	-10	75	FKM	121M14	8993	481180	4	5	1.1	3382
	1.5	0.9	0.05	70	0	20	4	-10	75	FKM	121M14	8993	488980	2	2.5	1.1	3382
	1.5	1.5	0.09	80	0	60	25	-30	75	PCTFE	E121K14	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	70	30	-30	75	PCTFE	E121K14	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	70	55	-30	75	PCTFE	E121K14	4270	486265	14	14	2.0	3510
	2	2	0.12	125	0	10	7	-10	75	FKM	121M13	8993	481180	4	5	1.1	3382
	2	2	0.12	125	0	10	2.5	-10	75	FKM	121M13	8993	488980	2	2.5	1.1	3382
	2.5	2.8	0.17	-	0	10	10	-10	75	FKM	121Z03	2995	481865	9	10	2.0	7863
	2.5	3.5	0.21	220	0	28	10	-30	100	Ruby	E121K23	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	34	12	-30	130	Ruby	E121K23	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	50	22	-30	120	Ruby	E121K23	4270	486265	14	14	2.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	121K1302	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	10	8	-10	120	FKM	121K1302	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	10	10	-10	120	FKM	121K1302	4270	486265	14	14	2.0	3510
1/4"	1.2	0.85	0.05	50	0	80	36	-30	100	Ruby	E121K65	2995	481865	9	10	2.0	3510
	1.2	0.85	0.05	50	0	100	43	-30	130	Ruby	E121K65	4270	481000	8	8	2.0	3510
	1.2	0.85	0.05	50	0	100	75	-30	120	Ruby	E121K65	4270	486265	14	14	2.0	3510
	1.5	1.5	0.09	80	0	-	8	-20	75	PUR	121K0497 [1]	2995	482740	-	1.6	6.0/8.0	8274
	1.5	1.5	0.09	80	0	-	8	-20	65	PUR	121K0497 [1]	2995	496125	-	1.6	6.0/8.0	8274
	1.5	1.5	0.09	80	0	10	10	-20	75	PUR	121K0497 [1]	-	495900	2.5	2	6.0/8.0	8274
	1.5	1.5	0.09	80	0	-	10	-20	75	PUR	121K0497 [1]	-	495910	-	0.3-1.2	6.0/8.0	8274
	1.5	1.5	0.09	80	0	60	25	-30	75	PCTFE	E121K04	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	70	30	-30	75	PCTFE	E121K04	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	70	55	-30	75	PCTFE	E121K04	4270	486265	14	14	2.0	3510
	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	E121K0402	2995	481865	9	10	2.0/3.0	3510
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	E121K0402	4270	481000	8	8	2.0/3.0	3510
	1.5	1.5	0.09	80	0	60	25	-30	100	Ruby	E121K67	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	75	30	-30	130	Ruby	E121K67	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	100	55	-30	120	Ruby	E121K67	4270	486265	14	14	2.0	3510
	2.5	3.5	0.21	220	0	14	7	-10	100	FKM	121K0706	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	14	9	-10	120	FKM	121K0706	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	14	14	-10	120	FKM	121K0706	4270	486265	14	14	2.0	3510
	2.5	3.5	0.21	220	0	28	10	-30	75	PCTFE	E121K07	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	34	12	-30	75	PCTFE	E121K07	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	50	22	-30	75	PCTFE	E121K07	4270	486265	14	14	2.0	3510

Notes:
1.If fluid is water, media temperature shall not exceed 40°C

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.2	0.9	2.5	-30
To	1/4"	3	4.5	100	130



Drawing 3382



Drawing 3510



Drawing 7863

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
	2.5	3.5	0.21	220	0	28	10	-30	100	Ruby	E121K63	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	34	12	-30	130	Ruby	E121K63	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	50	22	-30	120	Ruby	E121K63	4270	486265	14	14	2.0	3510
	3	3.5	0.21	250	0	-	2	-20	75	PUR	121K0397 [1]	2995	482740	-	1.6	6.0/8.0	8274
	3	3.5	0.21	250	0	-	2	-20	65	PUR	121K0397 [1]	2995	496125	-	1.6	6.0/8.0	8274
	3	3.5	0.21	250	0	4.5	4	-20	75	PUR	121K0397 [1]	-	495900	2.5	2	6.0/8.0	8274
	3	3.5	0.21	250	0	-	4.5	-20	75	PUR	121K0397 [1]	-	495910	-	0.3-1.2	6.0/8.0	8274
	3	4.5	0.27	320	0	20	7	-30	75	PCTFE	E121K03	2995	481865	9	10	2.0/3.0	3510
	3	4.5	0.27	320	0	25	8.5	-30	75	PCTFE	E121K03	4270	481000	8	8	2.0/3.0	3510
	3	4.5	0.27	320	0	36	15	-30	75	PCTFE	E121K03	4270	486265	14	14	2.0/3.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121K0302	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	10	8.5	-10	120	FKM	E121K0302	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121K0302	4270	486265	14	14	2.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121K0352 [2]	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	10	8.5	-10	120	FKM	E121K0352 [2]	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	10	10	-10	120	FKM	E121K0352 [2]	4270	486265	14	14	2.0	3510
1/4"	3	4.5	0.27	320	0	20	7	-30	100	Ruby	E121K64	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	25	8.5	-30	130	Ruby	E121K64	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	36	15	-30	120	Ruby	E121K64	4270	486265	14	14	2.0	3510
	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K02	2995	481865	9	10	2.0	3510
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K02	4270	481000	8	8	2.0	3510
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K02	4270	486265	14	14	2.0	3510
	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K0250 [2]	2995	481865	9	10	2.0	3510
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K0250 [2]	4270	481000	8	8	2.0	3510
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K0250 [2]	4270	486265	14	14	2.0	3510
	5	11	0.66	750	0	7	2	-10	100	FKM	121K01	2995	481865	9	10	2.0/14.2	3510
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K01	4270	481000	8	8	2.0/14.2	3510
	5	11	0.66	750	0	7	5	-10	120	FKM	121K01	4270	486265	14	14	2.0/14.2	3510
	5	11	0.66	750	0	7	2	-10	100	FKM	121K0150 [2]	2995	481865	9	10	2.0	3510
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K0150 [2]	4270	481000	8	8	2.0	3510
	5	11	0.66	750	0	7	5	-10	120	FKM	121K0150 [2]	4270	486265	14	14	2.0	3510
	6.5	-	-	1400	0	0.5	0.5	-10	100	FKM	121K0601	2995	481865	9	10	2.0	3510
	6.5	-	-	1400	0	0.5	0.5	-10	120	FKM	121K0601	4270	481000	8	8	2.0	3510

Notes:
1.If fluid is water, media temperature shall not exceed 40°C
2.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	2.5	3.5	2	-30
To	1/4"	5	11	50	130



Drawing 3510



Drawing 8274

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
3/8"	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K3206	2995	481865	9	10	2.0	3551
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K3206	4270	481000	8	8	2.0	3551
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K3206	4270	486265	14	14	2.0	3551
	5	11	0.66	750	0	7	2	-10	100	FKM	121K3106	2995	481865	9	10	2.0	3551
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K3106	4270	481000	8	8	2.0	3551
	5	11	0.66	750	0	7	5	-10	120	FKM	121K3106	4270	486265	14	14	2.0	3551
	6	12	0.72	1100	0	5	1.1	-10	100	FKM	121K3306	2995	481865	9	10	2.0/14.2	3551
	6	12	0.72	1100	0	5	1.5	-10	120	FKM	121K3306	4270	481000	8	8	2.0/14.2	3551
	6	12	0.72	1100	0	5	3	-10	120	FKM	121K3306	4270	486265	14	14	2.0/14.2	3551
1/2"	5	11	0.66	750	0	7	2	-10	120	FKM	121K8206[1]	2995	481865	9	10	2.0	3352
	8.5	25	1.5	1600	0	1.1	0.5	-10	100	FKM	E121K46	2995	481865	9	10	2.0	3427
	8.5	25	1.5	1600	0	2.2	0.5	-10	120	FKM	E121K46	4270	481000	8	8	2.0	3427
	8.5	25	1.5	1600	0	4	1.2	-10	120	FKM	E121K46	4270	486265	14	14	2.0	3427
	11	36	2.16	2500	0	0.7	0.3	-10	100	FKM	E121K45	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0	1.2	0.35	-10	120	FKM	E121K45	4270	481000	8	8	2.0	3427
	11	36	2.16	2500	0	2.5	0.7	-10	120	FKM	E121K45	4270	486265	14	14	2.0	3427

Notes:

1. Available also with 1/2" NPT ports, code U121K8206

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	4	7.5	0.3	-10
To	1/2"	11	36	10	120



Drawing 3551



Drawing 3427



Drawing 3352

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8"	2.5	3.5	0.21	-	0	30	-	-30	140	Ruby	122K9363	4270	481044	14	-	2.2	3510
	2.5	3.5	0.21	-	0	30	30	-30	140	Ruby	122K9363	4270	486265	14	14	2.2	3510
1/4"	1.5	1.5	0.09	80	0	30	30	-10	100	PCTFE	122K84	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	30	30	-10	100	PCTFE	122K84	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	30	30	-10	120	PCTFE	122K84	4270	486265	14	14	2.0	3510
	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	122K8406	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	122K8406	4270	481000	8	8	2.1	3510
	1.5	1.5	0.09	80	0	40	40	-30	100	Ruby	122K8408	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	40	40	-30	130	Ruby	122K8408	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	40	40	-30	130	Ruby	122K8408	4270	486265	14	14	2.0	3510
	2.5	3	0.18	180	0	12	12	-30	75	PCTFE	122K83	2995	481865	9	10	2.0	3510
	2.5	3	0.18	180	0	12	12	-30	75	PCTFE	122K83	4270	481000	8	8	2.0	3510
	2.5	3	0.18	180	0	12	12	-30	75	PCTFE	122K83	4270	486265	14	14	2.0	3510
	2.5	3	0.18	180	0	12	12	-10	100	FKM	122K8306	2995	481865	9	10	2.0	3510
	2.5	3	0.18	180	0	12	12	-10	120	FKM	122K8306	4270	481000	8	8	2.0	3510
	2.5	3	0.18	180	0	12	12	-10	120	FKM	122K8306	4270	486265	14	14	2.0	3510
	2.5	3.5	0.21	-	0	30	-	-30	140	Ruby	122K8363	4270	481044	14	-	2.2	3510
	2.5	3.5	0.21	-	0	30	30	-30	140	Ruby	122K8363	4270	486265	14	14	2.2	3510
	4.5	7.8	0.47	-	0	4	4	-10	120	FKM	122K8606 [1]	2995	492425	14	14	-	3510

Notes: 1. Valve compatible only with 492425 or 491514 coils

BRASS
PIPE MOUNTING
CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	3	4.5	0.27	320	0	20	-	-30	75	PCTFE	125K03	4269	484990	11	-	4.0	8296
	3	4.5	0.27	320	0	-	7	-30	75	PCTFE	125K03	4269	485400	-	13	4.0	8296
	5	11	0.66	750	0	5	-	-10	100	FKM	125K01	4269	484990	11	-	4.0	8296
	5	11	0.66	750	0	-	1.5	-10	100	FKM	125K01	4269	485400	-	13	4.0	8296

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	1.5	1.5	-30
To	1/4"	5	11	40	140



Drawing 3510



Drawing 8296

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	1.5	1.5	0.09	80	0	20	-	-10	100	FKM	121F4417	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	60	25	-30	100	Ruby	121F67	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	75	30	-30	130	Ruby	121F67	4270	481000	8	8	2.0	3509
	1.5	1.5	0.09	80	0	100	55	-30	120	Ruby	121F67	4270	486265	14	14	2.0	3509
	1.5	1.5	0.09	80	0	60	25	-30	75	PCTFE	E121F44	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	70	30	-30	75	PCTFE	E121F44	4270	481000	8	8	2.0	3509
	1.5	1.5	0.09	80	0	70	55	-30	75	PCTFE	E121F44	4270	486265	14	14	2.0	3509
	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	E121F4406	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	E121F4406	4270	481000	8	8	2.0	3509
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	E121F4406	4270	486265	14	14	2.0	3509
	2.5	3.5	0.21	220	0	28	10	-30	75	PCTFE	121F47	2995	481865	9	10	2.0	3509
	2.5	3.5	0.21	220	0	34	12	-30	75	PCTFE	121F47	4270	481000	8	8	2.0	3509
	2.5	3.5	0.21	220	0	50	22	-30	75	PCTFE	121F47	4270	486265	14	14	2.0	3509
	2.5	3.5	0.21	220	0	14	7	-10	100	FKM	121F4706	2995	481865	9	10	2.0	3509
	2.5	3.5	0.21	220	0	14	9	-10	120	FKM	121F4706	4270	481000	8	8	2.0	3509
	2.5	3.5	0.21	220	0	14	14	-10	120	FKM	121F4706	4270	486265	14	14	2.0	3509
	2.5	3.5	0.21	220	0	28	10	-30	100	Ruby	121F63	2995	481865	9	10	2.0	3509
	2.5	3.5	0.21	220	0	34	12	-30	130	Ruby	121F63	4270	481000	8	8	2.0	3509
	2.5	3.5	0.21	220	0	50	22	-30	120	Ruby	121F63	4270	486265	14	14	2.0	3509
	3	4.5	0.27	320	0	20	7	-30	100	Ruby	121F64	2995	481865	9	10	2.0	3509
	3	4.5	0.27	320	0	25	8.5	-30	130	Ruby	121F64	4270	481000	8	8	2.0	3509
	3	4.5	0.27	320	0	36	15	-30	120	Ruby	121F64	4270	486265	14	14	2.0	3509
	3	4.5	0.27	320	0	20	7	-30	75	PCTFE	E121F43	2995	481865	9	10	2.0	3509
	3	4.5	0.27	320	0	25	8.5	-30	75	PCTFE	E121F43	4270	481000	8	8	2.0	3509
	3	4.5	0.27	320	0	36	15	-30	75	PCTFE	E121F43	4270	486265	14	14	2.0	3509
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121F4302	2995	481865	9	10	2.0/3.0	3509
	3	4.5	0.27	320	0	10	8.5	-10	120	FKM	E121F4302	4270	481000	8	8	2.0/3.0	3509
	3	4.5	0.27	320	0	10	10	-10	120	FKM	E121F4302	4270	486265	14	14	2.0/3.0	3509

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.5	7	-30
To	SB	3	4.5	100	130



Drawing 3509

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

DIRECT OPERATED

BRASS

SUB-BASE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	122F44	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	122F44	4270	481000	8	8	2.1	3509

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.5	20	-10
To	SB	1.5	1.5	20	120



Drawing 3509

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

MAGNALIFT

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/8"	15	65	3.9	4500	0	16	-	-10	100	NBR	221G13	2995	481865	9	-	2.0	3732
	15	65	3.9	4500	0	16	-	-10	100	NBR	221G13	4270	481000	8	-	2.0	3732
	15	65	3.9	4500	0	16	16	-10	100	NBR	221G13	4270	486265	14	14	2.0	3732
	15	65	3.9	4500	0	16	-	0	100	FKM	221G23 [1]	2995	481865	9	-	2.0	3732
	15	65	3.9	4500	0	16	-	0	120	FKM	221G23 [1]	4270	481000	8	-	2.0	3732
	15	65	3.9	4500	0	20	7	0	140	FKM	221G23 [1]	4270	486265	14	14	2.0	3732
	15	65	3.9	4500	0	-	10	-10	100	FKM	221G2330 [12]	2995	481865	-	10	2.0	3732
	15	65	3.9	4500	0	10	10	-10	65	FKM	221G2330 [12]	-	492070	9	8	2.1	3732
	15	65	3.9	4500	0	10	10	-10	75	FKM	221G2330 [12]	-	492190	11	9	2.1	3732
1/2"	15	65	3.9	4500	0	16	-	-10	100	NBR	221G15	2995	481865	9	-	2.0	3732
	15	65	3.9	4500	0	16	-	-10	100	NBR	221G15	4270	481000	8	-	2.0	3732
	15	65	3.9	4500	0	16	7	-10	100	NBR	221G15	4270	486265	14	14	2.0	3732
	15	65	3.9	4500	0	-	10	-10	100	NBR	221G1530 [2]	2995	481865	-	10	2.0	3732
	15	65	3.9	4500	0	10	10	-10	65	NBR	221G1530 [2]	-	492070	9	8	2.1	3732
	15	65	3.9	4500	0	10	10	-10	75	NBR	221G1530 [2]	-	492190	11	9	2.1	3732
	15	65	3.9	4500	0	16	-	0	100	FKM	221G25 [1]	2995	481865	9	-	2.0	3732
	15	65	3.9	4500	0	16	-	0	120	FKM	221G25 [1]	4270	481000	8	-	2.0	3732
	15	65	3.9	4500	0	20	7	0	140	FKM	221G25 [1]	4270	486265	14	14	2.0	3732
	15	65	3.9	4500	0	-	10	-10	100	FKM	221G2530 [12]	2995	481865	-	10	2.0	3732
	15	65	3.9	4500	0	10	10	-10	65	FKM	221G2530 [12]	-	492070	9	8	2.1	3732
	15	65	3.9	4500	0	10	10	-10	75	FKM	221G2530 [12]	-	492190	11	9	2.1	3732

Notes:
1.Valve only compatible with hydraulic oil and air/neutral gases
2.Valves with model number ending in 30 or 31 are mainly equipped with electrical parts for explosion proof applications or with standard DC coils.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	15	65	7	-10
To	1/2"	15	65	20	140



Drawing 3732

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

MAGNALIFT

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G16	2995	481865	9	-	2.0	3444
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G16	4270	481000	8	-	2.0	3444
	15	80	4.8	6000	0	7	7	-10	100	NBR	221G16	4270	486265	14	14	2.0	3444
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G1610 [3]	2995	481865	9	-	2.0	3444
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G1610 [3]	4270	481000	8	-	2.0	3444
	15	80	4.8	6000	0	16	7	-10	100	NBR	221G1610 [3]	4270	486265	14	14	2.0	3444
	15	80	4.8	6000	0	10	10	-10	100	NBR	221G1630 [2]	2995	481865	9	10	2.0	3444
	15	80	4.8	6000	0	10	10	-25	40	NBR	221G1630 [2]	-	492070	9	8	2.1	3444
3/4"	15	80	4.8	6000	0	10	10	-25	40	NBR	221G1630 [2]	-	492190	11	9	2.1	3444
	15	80	4.8	6000	0	10	10	-10	100	NBR	221G1631 [23]	2995	481865	9	10	2.0	3444
	15	80	4.8	6000	0	10	10	-25	40	NBR	221G1631 [23]	-	492070	9	8	2.1	3444
	15	80	4.8	6000	0	10	10	-25	40	NBR	221G1631 [23]	-	492190	11	9	2.1	3444
	15	80	4.8	6000	0	16	-	0	100	FKM	221G26 [1]	2995	481865	9	-	2.0	3444
	15	80	4.8	6000	0	16	-	0	120	FKM	221G26 [1]	4270	481000	8	-	2.0	3444
	15	80	4.8	6000	0	20	7	0	140	FKM	221G26 [1]	4270	486265	14	14	2.0	3444
	15	80	4.8	6000	0	-	10	-10	100	FKM	221G2630 [12]	2995	481865	-	10	2.0	3444
	15	80	4.8	6000	0	10	10	-25	40	FKM	221G2630 [12]	-	492070	9	8	2.1	3444
	15	80	4.8	6000	0	10	10	-25	40	FKM	221G2630 [12]	-	492190	11	9	2.1	3444

Notes:
1.Valve only compatible with hydraulic oil and air/neutral gases
2.Valves with model number ending in 30 or 31 are mainly equipped with electrical parts for explosion proof applications or with standard DC coils.
3. With 4 position selector for controlled closure rate.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	15	80	7	-25
To	3/4"	15	80	20	140



Drawing 3444

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

MAGNALIFT

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1"	15	80	4.8	6000	0	16	-	-10	100	NBR	221G17	2995	481865	9	-	2.0	3445
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G17	4270	481000	8	-	2.0	3445
	15	80	4.8	6000	0	16	7	-10	100	NBR	221G17	4270	486265	14	14	2.0	3445
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G1710 [3]	2995	481865	9	-	2.0	3445
	15	80	4.8	6000	0	16	-	-10	100	NBR	221G1710 [3]	4270	481000	8	-	2.0	3445
	15	80	4.8	6000	0	16	7	-10	100	NBR	221G1710 [3]	4270	486265	14	14	2.0	3445
	15	80	4.8	6000	0	-	10	-10	100	NBR	221G1730 [2]	2995	481865	-	10	2.0	3445
	15	80	4.8	6000	0	10	10	-10	65	NBR	221G1730 [2]	-	492070	9	8	2.1	3445
	15	80	4.8	6000	0	10	10	-10	75	NBR	221G1730 [2]	-	492190	11	9	2.1	3445
	15	80	4.8	6000	0	16	-	0	100	FKM	221G27 [1]	2995	481865	9	-	2.0	3445
	15	80	4.8	6000	0	16	-	0	120	FKM	221G27 [1]	4270	481000	8	-	2.0	3445
	15	80	4.8	6000	0	20	7	0	120	FKM	221G27 [1]	4270	486265	14	14	2.0	3445
	15	80	4.8	6000	0	-	10	0	100	FKM	221G2730 [12]	2995	481865	-	10	2.0	3445
	15	80	4.8	6000	0	10	10	-10	65	FKM	221G2730 [12]	-	492070	9	8	2.1	3445
	15	80	4.8	6000	0	10	10	-10	75	FKM	221G2730 [12]	-	492190	11	9	2.1	3445
	25	170	10.2	14000	0	16	-	-10	100	NBR	221G21	2995	481865	9	-	2.0	3448
	25	170	10.2	14000	0	16	-	-10	100	NBR	221G21	4270	481000	8	-	2.0	3448
	25	170	10.2	14000	0	16	6	-10	100	NBR	221G21	4270	486265	14	14	2.0	3448
	25	160	9.6	14000	0	16	-	0	100	FKM	221G2106 [1]	2995	481865	9	-	2.0	3448
	25	160	9.6	14000	0	16	-	0	120	FKM	221G2106 [1]	4270	481000	8	-	2.0	3448
	25	160	9.6	14000	0	16	6	0	120	FKM	221G2106 [1]	4270	486265	14	14	2.0	3448
	25	160	9.6	14000	0	16	-	-10	100	NBR	221G2110 [3]	2995	481865	9	-	2.0	3448
	25	160	9.6	14000	0	16	-	-10	100	NBR	221G2110 [3]	4270	481000	8	-	2.0	3448
	25	160	9.6	14000	0	16	6	-10	100	NBR	221G2110 [3]	4270	486265	14	14	2.0	3448
	25	170	10.2	14000	0	-	10	-10	40	NBR	221G2130 [12]	2995	481865	-	10	2.0	3448
	25	170	10.2	14000	0	10	10	-10	40	NBR	221G2130 [12]	-	492070	9	8	2.1	3448
	25	170	10.2	14000	0	10	10	-10	40	NBR	221G2130 [12]	-	492190	11	9	2.1	3448
	25	170	10.2	14000	0	-	10	0	100	FKM	221G2136 [12]	2995	481865	-	10	2.0	3448
	25	170	10.2	14000	0	-	10	0	100	FKM	221G2136 [12]	4270	481000	-	8	2.0	3448

Notes:
1.Valve only compatible with hydraulic oil and air/neutral gases
2.Valves with model number ending in 30 or 31 are mainly equipped with electrical parts for explosion proof applications or with standard DC coils.
3. With 4 position selector for controlled closure rate.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1"	15	80	6	-10
To	1"	25	170	20	120



Drawing 3445



Drawing 3448

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
PILOT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/4"	8	36	2.16	1600	0.3	40	25	-10	100	NBR	E321H11 [12]	2995	481865	9	10	2.0	3523
	8	36	2.16	1600	0.3	40	30	-10	100	NBR	E321H11 [12]	4270	481000	8	8	2.0	3523
	8	36	2.16	1600	0.3	40	40	-10	100	NBR	E321H11 [12]	4270	486265	14	14	2.0	3523
	11	28	1.68	1800	0.2	10	3	-10	100	NBR	E321K10	2995	481865	9	10	2.0	3429
	11	28	1.68	1800	0.2	10	4	-10	100	NBR	E321K10	4270	481000	8	8	2.0	3429
	12	30	1.8	2150	0.3	10	10	-10	100	NBR	321K31	8993	481180	4	5	1.1	7093
	12	30	1.8	2150	0.3	10	7	-10	75	NBR	321K31	8993	488980	2	2.5	1.1	7093
	12	30	1.8	2150	0.3	10	10	-10	100	FKM	321K3106	8993	481180	4	5	1.1	7093
	12	30	1.8	2150	0.3	10	7	-10	75	FKM	321K3106	8993	488980	2	2.5	1.1	7093
	12	32	1.92	2150	0.3	12	12	-10	100	FKM	321K4156 [3]	2995	481865	9	10	2.0/3.0	7094
	12	32	1.92	2150	0.3	12	12	-10	120	FKM	321K4156 [3]	4270	481000	8	8	2.1/3.0	7094

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby
3.Valve with manual override



Drawing 7094

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	28	3	-10
To	1/4"	12	36	40	120



Drawing 3523



Drawing 3429



Drawing 7093

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
3/8"	11	50	3	2800	0.3	40	25	-10	100	NBR	E321H13 [2]	2995	481865	9	10	2.0	3521
	11	50	3	2800	0.3	40	30	-10	100	NBR	E321H13 [2]	4270	481000	8	8	2.0	3521
	11	50	3	2800	0.3	40	40	-10	100	NBR	E321H13 [2]	4270	486265	14	14	2.0	3521
	11	36	2.16	2500	0.2	10	4	-10	100	NBR	E321K13	4270	481000	8	8	2.0	3429
	11	36	2.16	2500	0.2	10	10	-10	100	NBR	E321K13	4270	486265	14	14	2.0	3429
	12	45	2.7	3050	0.3	10	10	-10	100	NBR	321K33	8993	481180	4	5	1.1	7093
	12	45	2.7	3050	0.3	10	7	-10	75	NBR	321K33	8993	488980	2	2.5	1.1	7093
	12	45	2.7	3050	0.3	10	10	-10	100	FKM	321K3306	8993	481180	4	5	1.1	7093
	12	45	2.7	3050	0.3	10	7	-10	75	FKM	321K3306	8993	488980	2	2.5	1.1	7093
	12	45	2.7	3050	0.3	12	12	-10	100	FKM	321K4356 [1]	2995	481865	9	10	2.0/3.0	7094
	12	45	2.7	3050	0.3	12	12	-10	120	FKM	321K4356 [1]	4270	481000	8	8	2.1/3.0	7094

Notes:
1.Valve with manual override
2.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing



Drawing 7094

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	11	36	4	-10
To	3/8"	12	50	40	120



Drawing 3521



Valve	A
E321K13/63	G 3/8"
E321K10	G 1/4"

Drawing 3429



	A	B	C
321 K 31	G 1/4"	25	50
321 K 33	G 3/8"	25	50
321 K 35	G 1/2"	27,5	55

Drawing 7093

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/2"	11	36	2.16	2500	0.2	10	3	-10	100	NBR	E321K15	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0.2	10	10	-10	120	NBR	E321K15	4270	486265	14	14	2.0	3427
	11	36	2.16	2500	0.2	10	3	-10	100	FKM	E321K25	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0.2	4	4	-10	65	FKM	E321K25	-	492070	9	8	2.0	3427
	12	50	3	3400	0.3	12	12	-10	100	NBR	321K35	8993	481180	4	5	1.1	7093
	12	50	3	3400	0.3	10	7	-10	75	NBR	321K35	8993	488980	2	2.5	1.1	7093
	12	50	3	3400	0.3	12	12	-10	100	FKM	321K3506	8993	481180	4	5	1.1	7093
	12	50	3	3400	0.3	10	7	-10	75	FKM	321K3506	8993	488980	2	2.5	1.1	7093
	15	60	3.6	3150	0.3	-	10	-10	55	NBR	321H1590	2995	48358001	-	0.5-3	7.0/8.0	3978
	15	60	3.6	3150	0.3	-	10	-10	80	NBR	321H1590	-	495910	-	0.3-1.2	7.0/8.0	3978
	15	60	3.6	3150	1.5	40	40	-10	50	PUR	321H35	2995	481865	9	10	2.0	3522
	15	60	3.6	3150	1.5	40	40	-10	50	PUR	321H35	4270	481000	8	8	2.1	3522
	15	60	3.6	3150	0.3	40	25	-10	100	NBR	E321H15[1]	2995	481865	9	10	2.0	3522
	15	60	3.6	3150	0.3	40	30	-10	100	NBR	E321H15[1]	4270	481000	8	8	2.0	3522
	15	60	3.6	3150	0.3	40	40	-10	100	NBR	E321H15[1]	4270	486265	14	14	2.0	3522

Notes:
1. Minimum pressure differential = 0.3 bar for opening and 0 bar for closing





Drawing 3522

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	11	36	3	-10
To	1/2"	15	60	40	120



Drawing 3427



	A	B	C
321 K 31	G 1/4"	25	50
321 K 33	G 3/8"	25	50
321 K 35	G 1/2"	27,5	55

Drawing 7093



Drawing 3978

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
3/4"	15	60	3.6	3550	1.5	40	40	-10	50	PUR	**321H36**	**2995**	**481865**	9	10	2.0	3696
	15	60	3.6	3550	1.5	40	40	-10	50	PUR	**321H36**	**4270**	**481000**	8	8	2.1	3696
	18	100	6	9400	0.3	10	10	-10	100	NBR	**321K36**	**8993**	**481180**	4	5	1.1	7097
	18	100	6	9400	0.3	10	7	-10	75	NBR	**321K36**	**8993**	**488980**	2	2.5	1.1	7097
	18	100	6	9400	0.3	10	10	-10	100	FKM	**321K3606**	**8993**	**481180**	4	5	1.1	7097
	18	100	6	9400	0.3	10	7	-10	75	FKM	**321K3606**	**8993**	**488980**	2	2.5	1.1	7097
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	**E321G36**	**2995**	**481865**	9	10	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	**E321G36**	**4270**	**481000**	8	8	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	100	FKM	**E321G3606**	**2995**	**481865**	9	10	2.0/14.1	3442
	20	135	8.1	9500	0.3	16	16	-10	120	FKM	**E321G3606**	**4270**	**481000**	8	8	2.0/14.1	3442
	20	135	8.1	9500	0.3	16	16	-10	120	FKM	**E321G3606**	**4270**	**486265**	14	14	2.0/14.1	3442

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	15	60	7	-10
To	3/4"	20	135	40	120



Drawing 3696



Drawing 7097



	RACCORD	A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"		121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"		121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"		137.5	55	33	60.5	60	110	70
321/322/E321G39..	BSP 1 1/2"		144	75	33	67	60	140	99
321G3956/G3967	UNF 1 7/8"		144	75	33	67	60	140	99
U321/U322G40..	BSP 2"		158.5	80	41.5	73	75	150	99



Drawing 3442

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max									
	mm	Kv l/min	KV m³/h	Qn m³/h	bar	AC bar	DC bar	°C	°C						AC W	DC W		
1"	18	110	6.6	10150	0.3	10	10	-10	100	NBR	321K37	8993	481180		4	5	1.1	7098
	18	110	6.6	10150	0.3	10	7	-10	75	NBR	321K37	8993	488980		2	2.5	1.1	7098
	18	110	6.6	10150	0.3	10	10	-10	100	FKM	321K3706	8993	481180		4	5	1.1	7098
	18	110	6.6	10150	0.3	10	7	-10	75	FKM	321K3706	8993	488980		2	2.5	1.1	7098
	25	185	11.1	14100	0.3	-	10	-10	55	NBR	321G3790	2995	48358001	*	-	0.5-3	7.0/8.0	3442
	25	185	11.1	14100	0.3	-	10	-10	75	NBR	321G3790	-	495910	*	-	0.3-1.2	7.0/8.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	E321G37	2995	481865		9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	E321G37	4270	481000		8	8	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	FKM	E321G3706	2995	481865		9	10	2.0/14.1	3442
	25	180	10.8	14000	0.3	16	16	-10	120	FKM	E321G3706	4270	481000		8	8	2.0/14.1	3442
	25	180	10.8	14000	0.3	16	16	-10	120	FKM	E321G3706	4270	486265		14	14	2.0/14.1	3442
1 1/4"	28	270	16.2	18000	0.3	16	16	-10	100	NBR	E321G38	2995	481865		9	10	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	100	NBR	E321G38	4270	481000		8	8	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	100	FKM	E321G3806	2995	481865		9	10	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	120	FKM	E321G3806	4270	481000		8	8	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	100	FKM	E321G3806	4270	486265		14	14	2.0	3442

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1"	18	110	7	-10
To	1 1/4"	28	270	16	120



Drawing 7098



	RACCORD	A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"		121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"		121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"		137.5	55	33	60.5	50	110	70
321/322/E321G39..	BSP 1 1/2"		144	75	33	67	50	140	99
321G3966/G3967	UNF 1 7/8"		144	75	33	67	50	140	99
U321/U322G40..	BSP 2"		158.5	80	41.5	73	75	150	99

Drawing 3442

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
PILOT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	DC W	Coil Group	Dwg. No.
1 1/2"	40	425	25.5	31500	0.5	-	10	-10	55	NBR	321G3990	2995	48358001	*	-	0.5-3	7.0/8.0	8113
	40	425	25.5	31500	0.5	-	10	-10	75	NBR	321G3990	-	495910	*	-	0.3-1.2	7.0/8.0	8113
	40	420	25.2	31500	0.3	16	7	-10	100	NBR	E321G39	2995	481865		9	10	2.0	3442
	40	420	25.2	31500	0.3	16	8	-10	100	NBR	E321G39	4270	481000		8	8	2.0	3442
	40	420	25,2	31500	0,3	16	16	-10	100	NBR	E321G39	4270	486265		14	14	2.0	3442
	40	420	25.2	31500	0.3	16	7	-10	100	FKM	E321G3906	2995	481865		9	10	2.0	3442
	40	420	25.2	31500	0.3	16	8	-10	120	FKM	E321G3906	4270	481000		8	8	2.0	3442
	40	420	25.2	31500	0.3	16	16	-10	100	FKM	E321G3906	4270	486265		14	14	2.0	3442
2"	40	540	32.4	38100	0.5	-	10	-10	55	FKM	321G4090	2995	48358001	*	-	0.5-3	7.0/8.0	8113
	40	540	32.4	38100	0.5	-	10	-10	75	FKM	321G4090	-	495910	*	-	0.3-1.2	7.0/8.0	8113
	40	540	32.4	40000	0.3	16	7	-10	100	NBR	E321G40	2995	481865		9	10	2.0	3442
	40	540	32.4	40000	0.3	16	8	-10	100	NBR	E321G40	4270	481000		8	8	2.0	3442
	40	540	32,4	40000	0,3	16	16	-10	100	NBR	E321G40	4270	486265		14	14	2.0	3442
	40	540	32.4	40000	0.3	16	7	-10	100	FKM	E321G4006	2995	481865		9	10	2.0	3442
	40	540	32.4	40000	0.3	16	8	-10	120	FKM	E321G4006	4270	481000		8	8	2.0	3442
	40	540	32.4	40000	0.3	16	16	-10	120	FKM	E321G4006	4270	486265		14	14	2.0	3442

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1 1/2"	40	420	7	-10
To	2"	40	540	16	120



	RACCORD A	B	C	D	E	F	G	H
U321G3690	BSP 3/4"	135	50	23	54	41	100	70
321G3790	BSP 1"	135	50	23	54	41	100	70
321/U321G3990	BSP 1 1/2"	158	75	33	67	60	140	99
321/U321G4090	BSP 2"	172.5	80	41.5	73	75	150	99

Drawing 8113



	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	50	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	50	140	99
321G3966/G3967	UNF 1 7/8"	144	75	33	67	60	140	99
U321/U322G40..	BSP 2"	158.5	80	41.5	73	75	150	99

Drawing 3442

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/4"	8	36	2.16	1600	0.3	40	25	-10	100	NBR	322H71 [2]	2995	481865	9	10	2.0	3523
	8	36	2.16	1600	0.3	40	30	-10	100	NBR	322H71 [2]	4270	481000	8	8	2.0	3523
	8	36	2.16	1600	0.3	40	40	-10	100	NBR	322H71 [2]	4270	486265	14	14	2.0	3523
	8	36	2.16	1600	0.3	40	40	-10	100	FKM	322H7106 [2]	2995	481865	9	10	2.0/14.1	3523
	8	36	2.16	1600	0.3	40	40	-10	120	FKM	322H7106 [2]	4270	481000	8	8	2.0/14.1	3523
	8	36	2.16	1600	0.3	40	40	-10	140	FKM	322H7106 [2]	4270	486265	14	14	2.0/14.1	3523
3/8"	11	50	3	3240	0.3	40	40	-10	75	NBR	322H73 [2]	2995	481865	9	10	2.0	3523
	11	50	3	3240	0.3	40	40	-10	75	NBR	322H73 [2]	4270	481000	8	8	2.0	3523
	11	50	3	3240	0.3	40	40	-10	75	NBR	322H73 [2]	4270	486265	14	14	2.0	3523
	11	50	3	3240	0.3	40	40	-10	100	FKM	322H7306 [2]	2995	481865	9	10	2.0/14.1	3523
	11	50	3	3240	0.3	40	40	-10	100	FKM	322H7306 [2]	4270	481000	8	8	2.0/14.1	3523
	11	50	3	3240	0.3	40	40	-10	140	FKM	322H7306 [2]	4270	486265	14	14	2.0/14.1	3523
1/2"	15	60	3.6	3890	0.3	15	15	-10	100	NBR	322G75	2995	481865	9	10	2.0	3522
	15	60	3.6	3890	0.3	15	15	-10	100	NBR	322G75	4270	481000	8	8	2.1	3522
	15	60	3.6	3890	0.3	20	20	-10	100	FKM	322G7506 [2]	2995	481865	9	10	2.0	3522
	15	60	3.6	3890	0.3	20	20	-10	100	FKM	322G7506 [2]	4270	481000	8	8	2.0	3522
	15	60	3.6	3890	0.3	20	20	-10	100	FKM	322G7506 [2]	4270	486265	14	14	2.0	3522
	15	60	3.6	3150	1.5	40	40	-10	50	PUR	322H35 [1]	2995	481865	9	10	2.0	7569
	15	60	3.6	3150	1.5	40	40	-10	50	PUR	322H35 [1]	4270	481000	8	8	2.1	7569
	15	60	3.6	3890	0.3	40	40	-10	100	NBR	322H75 [2]	2995	481865	9	10	2.0	3522
	15	60	3.6	3890	0.3	40	40	-10	100	NBR	322H75 [2]	4270	481000	8	8	2.0	3522
	15	60	3.6	3890	0.3	40	40	-10	100	NBR	322H75 [2]	4270	486265	14	14	2.0	3522
	15	60	3.6	3890	0.3	40	40	-10	100	FKM	322H7506 [2]	2995	481865	9	10	2.0/14.1	3522
	15	60	3.6	3890	0.3	40	40	-10	120	FKM	322H7506 [2]	4270	481000	8	8	2.0/14.1	3522
	15	60	3.6	3890	0.3	40	40	-10	140	FKM	322H7506 [2]	4270	486265	14	14	2.0/14.1	3522

Notes:
1. Valve only compatible with air and neutral gases
2. Minimum pressure differential = 0.3 bar for opening and 0 bar for closing

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	36	15	-10
To	1/2"	15	60	40	140



Drawing 3523



Drawing 3522





Drawing 7569

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
3/4"	15	53.3	3.2	3550	1.5	40	40	-10	50	PUR	322H36 $_{12}$	2995	481865	9	10	2.0	7570
	15	53.3	3.2	3550	1.5	40	40	-10	50	PUR	322H36 $_{12}$	4270	481000	8	8	2.1	7570
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	322G36	2995	481865	9	10	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	322G36	4270	481000	8	8	2.1	3442
	20	135	8.1	9500	0.3	16	16	-10	100	FKM	322G3606	2995	481865	9	10	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	120	FKM	322G3606	4270	481000	8	8	2.1	3442
1"	25	180	10.8	14000	0.3	16	16	-10	100	NBR	322G37	2995	481865	9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	322G37	4270	481000	8	8	2.1	3442
	25	180	10.8	14000	0.3	16	16	-10	100	FKM	322G3706	2995	481865	9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	120	FKM	322G3706	4270	481000	8	8	2.1	3442
1 1/4"	28	270	16.2	18000	0.3	16	16	-10	100	NBR	322G38	2995	481865	9	10	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	100	NBR	322G38	4270	481000	8	8	2.1	3442
	28	270	16.2	18000	0.3	16	16	-10	100	FKM	322G3806	2995	481865	9	10	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	120	FKM	322G3806	4270	481000	8	8	2.1	3442
1 1/2"	40	420	25.2	31500	0.3	12	12	-10	100	NBR	322G39	2995	481865	9	10	2.0	3442
	40	420	25.2	31500	0.3	12	12	-10	100	NBR	322G39	4270	481000	8	8	2.1	3442
	40	420	25.2	31500	0.3	12	12	-10	100	FKM	322G3906	2995	481865	9	10	2.0	3442
	40	420	25.2	31500	0.3	12	12	-10	100	FKM	322G3906	4270	481000	8	8	2.1	3442
2"	40	540	32.4	40000	0.3	12	12	-10	100	NBR	322G40	2995	481865	9	10	2.0	3442
	40	540	32.4	40000	0.3	12	12	-10	100	NBR	322G40	4270	481000	8	8	2.1	3442
	40	540	32.4	40000	0.3	12	12	-10	100	FKM	322G4006	2995	481865	9	10	2.0	3442
	40	540	32.4	40000	0.3	12	12	-10	120	FKM	322G4006	4270	481000	8	8	2.1	3442

Notes:
1.Minimum pressure differential = 1.5 bar for opening and 0.3 bar for closing
2.Valve only compatible with air and neutral gases

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	15	53.3	12	-10
To	2"	40	540	40	120







Drawing 7570



	RACCORD	A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"		121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"		121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"		137.5	55	33	60.5	50	110	70
321/322/E321G39..	BSP 1 1/2"		144	75	33	67	50	140	99
3212996/E2967	UNF 1 7/8"		144	75	33	67	50	140	99
U321/U322G40..	BSP 2"		158.5	80	41.5	73	75	150	99



Drawing 3442

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	12	32	1.92	2150	0.3	12	-	-10	100	FKM	325K4106	4269	484990	11	-	4.0	7094
	12	32	1.92	2150	0.3	-	12	-10	100	FKM	325K4106	4269	485400	-	13	4.0	7094
3/8"	12	45	2.7	3050	0.3	12	-	-10	100	FKM	325K4306	4269	484990	11	-	4.0	7094
	12	45	2.7	3050	0.3	-	12	-10	100	FKM	325K4306	4269	485400	-	13	4.0	7094
1/2"	12	50	3	3400	0.3	12	-	-10	100	FKM	325K4506	4269	484990	11	-	4.0	7094
	12	50	3	3400	0.3	-	12	-10	100	FKM	325K4506	4269	485400	-	13	4.0	7094
3/4"	18	100	6	9400	0.3	12	-	-10	100	FKM	325K4606	4269	484990	11	-	4.0	7099
	18	100	6	9400	0.3	-	12	-10	100	FKM	325K4606	4269	485400	-	13	4.0	7099
1"	18	110	6.6	10150	0.3	12	-	-10	100	FKM	325K4706	4269	484990	11	-	4.0	7100
	18	110	6.6	10150	0.3	-	12	-10	100	FKM	325K4706	4269	485400	-	13	4.0	7100

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	12	32	12	-10
To	1"	18	110	12	100



Drawing 7094



Drawing 7099



Drawing 7100

2/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
PILOT OPERATED

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	-	-	2100	1.5	40	40	-10	50	PUR	321F35	2995	481865	9	10	2.0	3520
	14	-	-	2100	1.5	40	40	-10	50	PUR	321F35	2995	492425	14	14	2.0	3520
	14	-	-	2100	0	13	13	-10	50	PUR	421F35	2995	481865	9	10	2.0	3520
	14	45	2.7	2100	0.3	40	25	-10	100	NBR	E321F32 [2]	2995	481865	9	10	2.0	3520
	14	45	2.7	2100	0.3	40	30	-10	100	NBR	E321F32 [2]	4270	481000	8	8	2.0	3520
	14	45	2.7	2100	0.3	40	40	-10	100	NBR	E321F32 [2]	4270	486265	14	14	2.0	3520
	14	45	2.7	-	0.3	40	25	-10	100	FKM	E321F3202 [123]	2995	481865	9	10	2.0	3520
	14	45	2.7	-	0.3	40	30	-10	120	FKM	E321F3202 [123]	4270	481000	8	8	2.0	3520
	14	45	2.7	-	0.3	40	40	-10	140	FKM	E321F3202 [123]	4270	486265	14	14	2.0	3520

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby
3.Valve only compatible with hydraulic oil and neutral liquids

BRASS
SUB-BASE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	-	-	2100	1.5	40	40	-10	50	PUR	322F35	2995	481865	9	10	2.0	7527
	14	46	2.76	-	0.3	40	40	-10	75	NBR	322F72 [12]	2995	481865	9	10	2.0	3520
	14	46	2.76	-	0.3	40	40	-10	75	NBR	322F72 [12]	4270	481000	8	8	2.1	3520
	14	45	2.7	-	0.3	40	40	0	100	FKM	322F7206 [123]	2995	481865	9	10	2.0/14.1	3520
	14	45	2.7	-	0.3	40	40	0	120	FKM	322F7206 [123]	4270	481000	8	8	2.1/14.1	3520

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby
3.Valve only compatible with hydraulic oil and neutral liquids

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	14	-	13	-10
To	SB	14	46	40	140



Drawing 3520



Drawing 7527

NOTES

VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/8"	1.2 to 2.5	3.5	15	120	62
			1/4"	1 to 4.5	7	15	120	62 to 68
		Normally Open	1/4"	1.5 to 3	4.5	16	120	70
		Universal	1/8"	1.5 to 2.5	3.5	10	140	72
			1/4"	0.8 to 3	4.5	30	140	72 and 74
		Control by Electric Impulse	1/4"	1.5	1.5	16	100	74
	Brass/Sub-base Mounting	Normally Closed	SB	1 to 2.5	3.5	15	140	76 and 78
		Normally Open	SB	1.5 to 2.5	2.2	15	120	78
		Universal	SB	1.5 to 2.5	2.5	10	120	80
	Anodized Aluminium/ Banjo	Normally Closed	1/8"	1.2	-	10	50	82
			1/4"	1.2	-	10	50	82
	316L Stainless St./Sub-base Mounting	Normally Closed	SB	1.5	1.5	15	100	84
	POM/Sub-base Mounting	Normally Closed	SB	2	2	10	50	86
Pilot Operated	Anodized Aluminium/ Pipe Mounting	Normally Closed	1/4"	6.5 to 8	20	15	75	88
			1/2"	14	-	15	75	90
		Normally Open	1/4"	8	20	40	75	90
			1/2"	14	-	15	75	92
	Anodized Aluminium/ Sub-base Mounting/ Poppet	Normally Closed	SB	15	-	10	75	92

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C						W	W		
1/8"	1.2	1.5	0.7	0.9	0.04	0.05	0	10	10	-10	75	FKM	131M15	8993	488980		2	2.5	1.1	3382
	1.2	1.5	0.7	0.9	0.04	0.05	0	10	10	-10	75	FKM	131M1550$_1$	8993	488980		2	2.5	1.1	3382
	1.5	1.5	0.9	0.9	0.05	0.05	0	7	7	-10	75	FKM	131M14	8993	488980		2	2.5	1.1	3382
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	120	FKM	E131K14	4270	481000		8	8	2.1	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	E131K14	2995	481865		9	10	2.0	3510
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	131K16	4270	481000		8	8	2.1	3510
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	100	FKM	131K16	2995	481865		9	10	2.0	3510
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	131K1650$_1$	4270	481000		8	8	2.1	3510
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	100	FKM	131K1650$_1$	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	120	FKM	E131K13	4270	481000		8	8	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131K13	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131K13	4270	486265		14	14	2.0	3510
1/8"-1/4"	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	75	PUR	131K0397	2995	482740		-	1.6	6.0/8.0	8023
	2.5	2.5	3	3	0.18	0.18	0	2	2	-20	75	PUR	131K0397	-	495900		2.5	2	6.0/8.0	8023
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	75	PUR	131K0397	-	495910	*	-	0.3 to 3	6.0/8.0	8023
1/4"	1	1	0.6	0.6	0.03	0.03	0	-	10	-10	55	FKM	131K0490	2995	483580.01	*	-	0.5 to 3	7.0/8.0	7058
	1	1	0.6	0.6	0.03	0.03	0	-	10	-10	75	FKM	131K0490	-	48860.01	*	-	0.3 to 3	7.0/8.0	7058
	1	1	0.6	-	0.03	-	0	-	10	-10	75	FKM	131K0490	-	495910	*	-	0.3 to 3	7.0/8.0	7058

Notes:
1.With manual override



Drawing 7058

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1	0.6	2	-10
To	1/4"	2.5	3.5	15	120



Drawing 3382



Drawing 3510



Drawing 8023

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C						W	W		
	0.8	0.8	0.3	0.3	0.021	0.021	0	75	-	-30	130	Ruby	131K65	2995	481000		8	-	2.0	3510
	0.8	0.8	0.3	0.3	0.021	0.021	0	-	75	-30	140	Ruby	131K65	2995	486265		-	14	2.0	3510
	1.2	1.5	0.8	1.5	0.05	0.09	0	30	-	-30	130	Ruby	E131K64	4270	481000		8	-	2.0	3510
	1.2	1.5	0.8	1.5	0.05	0.09	0	30	30	-30	140	Ruby	E131K64	4270	486265		14	14	2.0	3510
	1.2	1.5	0.8	1.5	0.05	0.09	0	30	-	-30	130	Ruby	E131K6450 [1]	4270	481000		8	-	2.0	3510
	1.2	1.5	0.8	1.5	0.05	0.09	0	30	30	-30	140	Ruby	E131K6450 [1]	4270	486265		14	14	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	75	PUR	131K0497	2995	482740		-	1.6	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	7	7	-20	75	PUR	131K0497	-	495900		2.5	2	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	75	PUR	131K0497	-	495910	*	-	0.3-1.2	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	65	PUR	131K0497	2995	496125		-	1.6	6.0/8.0	8023
1/4"	1.5	1.5	1.5	1.5	0.09	0.09	0	16	16	-10	120	FKM	E131K04	4270	481000		8	8	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	16	16	-10	100	FKM	E131K04	2995	481865		9	10	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	16	16	-10	120	FKM	E131K04	4270	486265		14	14	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	120	FKM	E131K0450 [1]	4270	481000		8	8	2.1	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	E131K0450 [1]	2995	481865		9	10	2.0	3510
	2	3	2.5	4.5	0.15	0.27	0	10	10	-10	75	FKM	131T23	4270	481000		8	8	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	10	-10	75	FKM	131T23	2995	481865		9	10	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	10	-10	75	FKM	131T23	4270	486265		14	14	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	10	-10	75	FKM	131T2301 [1]	4270	481000		8	8	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	10	-10	75	FKM	131T2301 [1]	2995	481865		9	10	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	10	-10	75	FKM	131T2301 [1]	4270	486265		14	14	2.0	3223

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	0.8	0.3	7	-30
To	1/4"	2	2.5	30	140



Drawing 3510



Drawing 8023



Drawing 3223

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C						W	W		
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	E131K06	4270	481000		8	8	2.0	8119
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	100	FKM	E131K06	2995	481865		9	10	2.0	8119
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	E131K06	4270	486265		14	14	2.0	8119
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	E131K0650 [1]	4270	481000		8	8	2.1	3510
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	100	FKM	E131K0650 [1]	2995	481865		9	10	2.0	3510
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	75	PUR	131K0397	2995	482740		-	1.6	6.0/8.0	8023
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	65	PUR	131K0397	2995	496125		-	1.6	6.0/8.0	8023
1/4"	2.5	2.5	3	3	0.18	0.18	0	2	2	-20	75	PUR	131K0397	-	495900		2.5	2	6.0/8.0	8023
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	75	PUR	131K0397	-	495910	*	-	0.3-1.2	6.0/8.0	8023
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-40	75	PUR	E131K0358 [1]	4270	481000		8	8	2.1	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-40	75	PUR	E131K0358 [1]	2995	481865		9	10	2.0	3510
	2.5	3.5	3.5	5.5	0.21	0.33	0	7	7	-10	75	FKM	131T29	4270	481000		8	8	2.1	3223
	2.5	3.5	3.5	5.5	0.21	0.33	0	7	7	-10	75	FKM	131T29	2995	481865		9	10	2.0	3223
	2.5	3.5	3.5	5.5	0.21	0.33	0	7	7	-10	75	FKM	131T2901 [1]	4270	481000		8	8	2.1	3223
	2.5	3.5	3.5	5.5	0.21	0.33	0	7	7	-10	75	FKM	131T2901 [1]	2995	481865		9	10	2.0	3223

Notes:
1.With manual override



Drawing 3223

IECEx certified

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	2	2.5	2	-40
To	1/4"	2.5	3.5	10	120



Drawing 8119



Drawing 3510



Drawing 8023

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C						W	W		
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131K03	4270	481000		8	8	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131K03	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-40	75	PUR	E131K0308	4270	481000		8	8	2.1	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-40	75	PUR	E131K0308	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	120	FKM	E131K0350[1]	4270	481000		8	8	2.1	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131K0350[1]	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	130	Ruby	E131K63	4270	481000		8	8	2.0	3510
1/4"	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	100	Ruby	E131K63	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	130	Ruby	E131K6350[1]	4270	481000		8	8	2.1	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	100	Ruby	E131K6350[1]	2995	481865		9	10	2.0	3510
	3	4	4.5	6	0.27	0.36	0	10	-	-10	75	FKM	131T22	4270	481044		14	-	2.2	3223
	3	4	4.5	6	0.27	0.36	0	10	-	-10	75	FKM	131T22	2995	492425		14	-	2.2	3223
	4.5	6	7	9	0.42	0.54	0	2	2	-10	75	FKM	131T21	4270	481000		8	8	2.0	3223
	4.5	6	7	9	0.42	0.54	0	2	2	-10	75	FKM	131T21	2995	481865		9	10	2.0	3223
	4.5	6	7	9	0.42	0.54	0	2	2	-10	75	FKM	131T21	4270	486265		14	14	2.0	3223

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	2.5	2.7	2	-40
To	1/4"	4.5	7	10	130



Drawing 3525



Drawing 3510



Drawing 3223

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max								
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	1.5	1.5	1.4	1.4	0.08	0.08	0	16	16	-10	120	FKM	132K04	4270	481000	8	8	2.1	3510
	1.5	1.5	1.4	1.4	0.08	0.08	0	16	16	-10	100	FKM	132K04	2995	481865	9	10	2.0	3510
	2	2	1.8	1.8	0.11	0.11	0	10	10	-10	120	FKM	132K06	4270	481000	8	8	2.1	3510
	2	2	1.8	1.8	0.11	0.11	0	10	10	-10	100	FKM	132K06	2995	481865	9	10	2.0	3510
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T23	4270	481000	8	8	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T23	2995	481865	9	10	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	-	10	-10	75	FKM	132T23	4270	486265	-	14	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T2301 [1]	4270	481000	8	8	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	10	5	-10	75	FKM	132T2301 [1]	2995	481865	9	10	2.0	3223
	2	3	2.5	4.5	0.15	0.27	0	-	10	-10	75	FKM	132T2301 [1]	4270	486265	-	14	2.0	3223
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	120	FKM	132K03	4270	481000	8	8	2.1	3510
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	100	FKM	132K03	2995	481865	9	10	2.0	3510
	3	4	4.5	6	0.27	0.36	0	10	-	-10	75	FKM	132T22	4270	481044	14	-	2.2	3223
	3	4	4.5	6	0.27	0.36	0	7	-	-10	75	FKM	132T22	2995	492425	14	-	2.2	3223

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.4	5	-10
To	1/4"	3	4.5	16	120



Drawing 3510



Drawing 3223

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
UNIVERSAL



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C						W	W		
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	E133K14	2995	481865		9	10	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	E133K14	4270	481000		8	8	2.1	3510
1/8"	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	100	FKM	E133K16	2995	481865		9	10	2.0	3510
	2	2	2.5	-	0.15	-	0	7	7	-10	120	FKM	E133K16	4270	481000		8	8	2.1	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	100	FKM	E133K13	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	120	FKM	E133K13	4270	481000		8	8	2.1	3510
	0.8	0.8	0.3	0.3	0.02	0.02	0	30	30	-10	100	FKM	E133K05	2995	481865		9	10	2.0	3510
	0.8	0.8	0.3	0.3	0.02	0.02	0	30	30	-10	120	FKM	E133K05	4270	481000		8	8	2.1	3510
	0.8	0.8	0.3	0.3	0.02	0.02	0	30	30	-10	120	FKM	E133K05	4270	486265		14	14	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	3	-20	75	PUR	133K0497	2995	482740		-	1.6	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	3	3	-20	75	PUR	133K0497	-	495900		2.5	2	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	3	-20	75	PUR	133K0497	-	495910	*	-	0.3-1.2	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	3	-20	65	PUR	133K0497	2995	496125		-	1.6	6.0/8.0	8023
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	E133K04	2995	481865		9	10	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	E133K04	4270	481000		8	8	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	E133K04	4270	486265		14	14	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	E133K0450 [1]	2995	481865		9	10	2.0	3510
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	E133K0450 [1]	4270	481000		8	8	2.1	3510
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	75	FKM	133T23	2995	481865		9	10	2.0	3223
1/4"	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	75	FKM	133T23	4270	481000		8	8	2.1	3223
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	75	FKM	133T2301 [1]	2995	481865		9	10	2.0	3223
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	75	FKM	133T2301 [1]	4270	481000		8	8	2.1	3223
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	100	FKM	E133K06	2995	481865		9	10	2.0/3.0	3510
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	120	FKM	E133K06	4270	481000		8	8	2.0/3.0	3510
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	120	FKM	E133K06	4270	486265		14	14	2.0/3.0	3510
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	100	FKM	E133K0650 [1]	2995	481865		9	10	2.0	3510
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	120	FKM	E133K0650 [1]	4270	481000		8	8	2.1	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	100	FKM	E133K03	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	120	FKM	E133K03	4270	481000		8	8	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	120	FKM	E133K03	4270	486265		14	14	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	100	FKM	E133K0350 [1]	2995	481865		9	10	2.0	3510
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	120	FKM	E133K0350 [1]	4270	481000		8	8	2.1	3510
	3	3	4.5	4.5	0.27	0.27	0	2	2	-10	75	FKM	133T21	2995	481865		9	10	2.0	3223
	3	3	4.5	4.5	0.27	0.27	0	2	2	-10	75	FKM	133T21	4270	481000		8	8	2.1	3223

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	0.8	0.3	2	-20
To	1/4"	3	4.5	30	120



Drawing 3510



Drawing 8023



Drawing 3223

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
UNIVERSAL



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C						W	W		
1/4"	3	3	4.5	4.5	0.27	0.27	0	2	2	-10	75	FKM	133T2101 [1]	2995	481865		9	10	2.0	3223
	3	3	4.5	4.5	0.27	0.27	0	2	2	-10	75	FKM	133T2101 [1]	4270	481000		8	8	2.1	3223

Notes:
1.With manual override

BRASS
PIPE MOUNTING
CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max					AC	DC		
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C					W	W		
1/4"	1.5	1.5	1.5	1.5	0.09	0.09	0	-	16	-10	100	FKM	135K04	4269	485400	-	13	4.0	8104

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.5	2	-10
To	1/4"	3	4.5	16	100



Drawing 3223



Drawing 8104

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø 1	Orifice Ø (2)	Flow factors Kv 1 l/min	Flow factors Kv (2) l/min	Flow factors KV 1 m³/h	Flow factors KV (2) m³/h	Operating Pressure Differential Min bar	Operating Pressure Differential Max (MOPD) AC bar	Operating Pressure Differential Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	Power DC W	Coil Group	Dwg. No.
	mm						bar	AC bar	DC bar	°C	°C									
SB	1.2	1.5	0.7	0.9	0.04	0.05	0	10	10	-10	75	FKM	131M75	8993	488980		2	2.5	1.1	3383
	1.2	1.5	0.7	0.9	0.04	0.05	0	10	10	-10	75	FKM	131M7550 [1]	8993	488980		2	2.5	1.1	3383
	1.5	1.5	0.9	0.9	0.05	0.05	0	7	7	-10	75	FKM	131M74	8993	488980		2	2.5	1.1	3383
	1.5	1.5	0.9	0.9	0.05	0.05	0	7	7	-10	75	FKM	131M7450 [1]	8993	488980		2	2.5	1.1	3383
SB	1	1	0.6	0.6	0.04	0.036	0	-	10	-10	55	FKM	131F4490	2995	48358001	*	-	0.5-3	7.0	7057
	1	1	0.6	0.6	0.04	0.036	0	-	10	-10	75	FKM	131F4490	-	495910	*	-	0.3-1.2	7.0	7057
	1.5	2	1.5	2.2	0.09	0.13	0	-	16	-10	100	FKM	131F4410	2995	481865		-	10	2.0	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	75	PUR	131F4497	2995	482740		-	1.6	6.0/8.0	8022
	1.5	1.5	1.5	1.5	0.09	0.09	0	7	7	-20	75	PUR	131F4497	-	495900		2.5	2	6.0/8.0	8022
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	75	PUR	131F4497	-	495910	*	-	0.3-1.2	6.0/8.0	8022
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	65	PUR	131F4497	2995	496125		-	1.6	6.0/8.0	8022

Notes:
1.With manual override





Drawing 8022

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1	0.6	7	-20
To	SB	1.5	1.5	16	100



Drawing 3383



Drawing 7057



Drawing 3509

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Orifice Ø (2) mm	Flow factors 1 Kv l/min	Flow factors (2) Kv l/min	Flow factors 1 KV m³/h	Flow factors (2) KV m³/h	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	E131F44	2995	481865		9	10	2.0	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	120	FKM	E131F44	4270	481000		8	8	2.1	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	E131F4450 [1]	2995	481865		9	10	2.0	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	E131F4450 [1]	4270	481000		8	8	2.1	3509
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	100	FKM	131F46	2995	481865		9	10	2.0	3509
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	131F46	4270	481000		8	8	2.1	3509
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	100	FKM	131F4650 [1]	2995	481865		9	10	2.0	3509
	2	2.5	2.5	3.5	0.15	0.21	0	10	10	-10	120	FKM	131F4650 [1]	4270	481000		8	8	2.1	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131F43	2995	481865		9	10	2.0	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	120	FKM	E131F43	4270	481000		8	8	2.1	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131F4350 [1]	2995	481865		9	10	2.0	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	120	FKM	E131F4350 [1]	4270	481000		8	8	2.0	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	E131F4350 [1]	4270	486265		14	14	2.0	3509

Notes:
1.With manual override

BRASS
SUB-BASE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø 1 mm	Orifice Ø (2) mm	Flow factors 1 Kv l/min	Flow factors (2) Kv l/min	Flow factors 1 KV m³/h	Flow factors (2) KV m³/h	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	1.5	1.5	1.4	1.4	0.08	0.08	0	15	15	-10	75	FKM	132F44	4270	481000	8	8	2.1	3509
	1.5	1.5	1.4	1.4	0.08	0.08	0	15	15	-10	75	FKM	132F44	2995	481865	9	10	2.0	3509
	2	2	1.8	1.8	0.11	0.11	0	10	10	-10	120	FKM	132F46	4270	481000	8	8	2.1	3509
	2	2	1.8	1.8	0.11	0.11	0	10	10	-10	100	FKM	132F46	2995	481865	9	10	2.0	3509
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	75	FKM	132F43	4270	481000	8	8	2.0	3509
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	75	FKM	132F43	2995	481865	9	10	2.0	3509
	2.5	2.5	2.2	2.2	0.13	0.13	0	7	7	-10	75	FKM	132F43	4270	486265	14	14	2.0	3509

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.4	7	-10
To	SB	2.5	3.5	15	120



Drawing 3509

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS

DIRECT OPERATED

BRASS

SUB-BASE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1	Orifice Ø (2)	Flow factors 1 Kv l/min	Flow factors (2) Kv l/min	Flow factors 1 KV m³/h	Flow factors (2) KV m³/h	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
	mm						bar			°C									
SB	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	E133F4450 [1]	4270	481000	8	8	2.1	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	E133F4450 [1]	2995	481865	9	10	2.0	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	E133F44	4270	481000	8	8	2.1	3509
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	E133F44	2995	481865	9	10	2.0	3509
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	120	FKM	133F46	4270	481000	8	8	2.1	3509
	2	2	2.5	2.5	0.15	0.15	0	7	7	-10	100	FKM	133F46	2995	481865	9	10	2.0	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	120	FKM	E133F43	4270	481000	8	8	2.1	3509
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	100	FKM	E133F43	2995	481865	9	10	2.0	3509

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.5	4	-10
To	SB	2.5	3.5	10	120



Drawing 3509

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

ANODIZED ALUMINIUM
BANJO
NORMALLY CLOSED



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
	1.2	50	0	10	10	-10	50	NBR	131B14$_{12}$	-	496131	3	3	1.2	8227
1/8"	1.2	50	0	10	10	-10	50	NBR	131B14$_{12}$	-	496482	3	3	1.2	8227
	1.2	50	0	10	10	-10	50	NBR	131B14$_{12}$	-	496637	3	3	1.2	8227

Notes:
1.Valve only compatible with air and neutral gases
2.With manual override

ANODIZED ALUMINIUM
BANJO
NORMALLY CLOSED



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
	1.2	50	0	10	10	-10	50	NBR	131B04$_{12}$	-	496131	3	3	1.2	8226
1/4"	1.2	50	0	10	10	-10	50	NBR	131B04$_{12}$	-	496482	3	3	1.2	8226
	1.2	50	0	10	10	-10	50	NBR	131B04$_{12}$	-	496637	3	3	1.2	8226

Notes:
1.Valve only compatible with air and neutral gases
2.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.2	50	10	-10
To	1/4"	1.2	50	10	50



Drawing 8227



Drawing 8226

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

316L STAINLESS ST.
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max					AC	DC		
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C					W	W		
SB	1.5	1.5	1.5	2.2	0.09	0.13	0	15	15	-10	100	FKM	131F5406	2995	481865	9	10	2.0	3509

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.5	15	-10
To	SB	1.5	1.5	15	100



Drawing 3509

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

POM
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø 1	Orifice Ø (2)	Flow factors 1 Kv l/min	Flow factors (2) Kv l/min	Flow factors 1 KV m³/h	Flow factors (2) KV m³/h	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
	mm						bar			°C									
SB	2	2	2	2	0.12	0.12	0	10	10	-10	50	FKM	E131F26 [12]	2995	481865	9	10	2.0/3.0	3601
	2	2	2	2	0.12	0.12	0	10	10	-10	50	FKM	E131F26 [2]	2995	482730	6	7	2.1/3.0	3601

Notes:
1.20% Switch-on - max. 2 min
2.With manual override

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	2	2	10	-10
To	SB	2	2	10	50



Drawing 3601

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

ANODIZED ALUMINIUM
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		Q l/min		bar	AC bar	DC bar	°C	°C						W	W		
1/4"	6.5	6.5	10	-	645	-	1	-	10	-10	55	NBR	331B7490 [1]	2995	48358001	*	-	0.5-3	7.0/8.0	8270
	6.5	6.5	10	-	645	-	1	-	10	-10	75	NBR	331B7490 [1]	-	495910	*	-	0.3-1.2	7.0/8.0	8270
	6.5	6.5	10	-	750	-	1	10	10	-10	75	NBR	E331B74 [13]	2995	481865		9	10	2.0	3240
	6.5	6.5	10	-	750	-	1	10	10	-10	75	NBR	E331B74 [13]	4270	485100		8	8	2.1	3240
	8	8	20	20	1100	1100	1	15	15	-10	75	NBR	E331B01 [2]	4270	481000		8	8	2.1	3234
	8	8	20	20	1100	1100	1	15	15	-10	75	NBR	E331B01 [2]	2995	481865		9	10	2.0	3234
	8	8	20	20	1100	1100	1	15	15	-10	65	NBR	E331B01 [2]	-	483371		8	8	2.1	3234

Notes:
1.Valve only compatible with air and neutral gases
2.Valve only compatible with hydraulic oil and air/neutral gases
3.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	6.5	10	10	-10
To	1/4"	8	20	15	75



Drawing 8270



Weight: 0,51 kg

Drawing 3240



Weight: 0,88 kg

Drawing 3234

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

ANODIZED ALUMINIUM
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		Q l/min		bar	AC bar	DC bar	°C	°C						W	W		
1/2"	14	14	-	-	2500	2500	1	15	-	-10	75	NBR	E331B21 [1]	2995	481865		-	-	2.0	3238
	14	14	-	-	2500	2500	1	15	15	-10	65	NBR	E331B21 [1]	-	483371		8	8	2.1	3238

Notes:
1.Valve only compatible with air and neutral gases

ANODIZED ALUMINIUM
PIPE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max					AC	DC		
BSP	mm		Kv l/min		Q l/min		bar	AC bar	DC bar	°C	°C					W	W		
1/4"	8	8	10	10	750	750	1	40	40	-10	75	NBR	332B02 [12]	2995	481865	9	10	2.0	8114
	8	8	10	10	750	750	1	40	40	-10	75	NBR	332B02 [12]	4270	481000	8	8	2.1	8114
	8	8	20	20	1100	1100	1	15	15	-10	75	NBR	E332B01 [2]	2995	481865	9	10	2.0	3234
	8	8	20	20	1100	1100	1	15	15	-10	75	NBR	E332B01 [2]	4270	481000	8	8	2.1	3234
	8	8	20	20	1100	1100	1	15	15	-10	65	NBR	E332B01 [2]	-	483371	8	8	2.1	3234

Notes:
1.Pilot seat discs in Kel-F (PCTFE); valve with pilot return pipe
2.Valve only compatible with hydraulic oil and air/neutral gases

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	10	15	-10
To	1/2"	14	20	40	75





Drawing 3238





Drawing 8114





Drawing 3234

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 VALVES FOR DRY OR LUBRICATED AIR, NEUTRAL GASES AND LIQUIDS
DIRECT OPERATED

ANODIZED ALUMINIUM
PIPE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max					AC	DC		
BSP	mm		Kv l/min		Q l/min		bar	AC bar	DC bar	°C	°C					W	W		
1/2"	14	14	37.5	-	2500	2500	1	15	15	-10	75	NBR	E332B21 [1]	2995	481865	9	10	2.0	3238
	14	14	37.5	-	2500	2500	1	15	15	-10	75	NBR	E332B21 [1]	4270	481000	8	8	2.1	3238

Notes:
1.Valve only compatible with air and neutral gases

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max					AC	DC		
	mm	Qn l'min	bar	AC bar	DC bar	°C	°C					W	W		
SB	15	5000	0.5	10	10	-10	75	NBR	E331L21 [12]	2995	481865	9	10	2.0/3.0	3130
	15	5000	0.5	10	10	-10	65	NBR	E331L21 [12]	-	483371	8	8	2.1/3.0	3130

Notes:
1.Valve only compatible with air and neutral gases
2.With manual override

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	14	2500	15	-10
To	SB	15	5000	10	75



Drawing 3238



Drawing 3130

NOTES

VALVES FOR WATER AND NEUTRAL LIQUIDS

Water

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/8"	1.5 to 2	2	20	75	96
			1/4"	1.5 to 5	11	20	120	96
			3/8"	4 to 6	12	10	120	98
			1/2"	8.5 to 11	36	4	120	98
		Normally Open	1/4"	2.5	3	12	120	98
		Control by Electric Impulse	1/4"	5	11	5	100	100
	Brass/Sub-base Mounting	Normally Closed	5 mm	1.5 to 3	4.5	20	120	102
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/4"	11 to 12	32	12	120	108
			3/8"	11 to 13	50	20	140	104 and 108
			1/2"	11 to 13	50	20	140	104 and 110
			3/4"	18 to 20	140	20	140	104 and 112
			1"	18 to 25	180	20	140	104 and 114
			1 1/4"	28 to 35	420	16	140	106 and 112
			1 1/2"	40	500	16	140	106 and 114
			2"	40 to 50	620	16	140	106 and 114
		Normally Open	1/4"	12	32	12	120	118
			3/8"	12 to 13	50	20	140	116 and 118
			1/2"	12 to 15	60	20	140	116 and 118
			3/4"	18 to 20	140	20	140	116 and 118
			1"	18 to 25	180	20	140	114 and 120
			1 1/4"	35	420	10	140	116
			1 1/2"	40	500	10	140	116 and 120
			2"	50	620	10	140	116
			2 1/2"	65	1100	10	90	116
			3"	75	1334	10	90	116
	Brass/Sub-base Mounting	Normally Closed	14 mm	14	45	40	100	120

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8"	1.5	0.9	0.05	70	0	20	12	-10	75	FKM	121M14	8993	481180	4	5	1.1	3382
	1.5	0.9	0.05	70	0	20	4	-10	75	FKM	121M14	8993	488980	2	2.5	1.1	3382
	2	2	0.12	125	0	10	7	-10	75	FKM	121M13	8993	481180	4	5	1.1	3382
	2	2	0.12	125	0	10	2.5	-10	75	FKM	121M13	8993	488980	2	2.5	1.1	3382
1/4"	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	E121K0402	2995	481865	9	10	2.0/3.0	3510
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	E121K0402	4270	481000	8	8	2.0/3.0	3510
	2.5	3.5	0.21	220	0	14	7	-10	100	FKM	121K0706	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	14	9	-10	120	FKM	121K0706	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	14	14	-10	120	FKM	121K0706	4270	486265	14	14	2.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121K0302	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	10	8.5	-10	120	FKM	E121K0302	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121K0302	4270	486265	14	14	2.0	3510
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121K0352 [1]	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	10	8.5	-10	120	FKM	E121K0352 [1]	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	10	10	-10	120	FKM	E121K0352 [1]	4270	486265	14	14	2.0	3510
	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K02	2995	481865	9	10	2.0	3510
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K02	4270	481000	8	8	2.0	3510
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K02	4270	486265	14	14	2.0	3510
	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K0250 [1]	2995	481865	9	10	2.0	3510
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K0250 [1]	4270	481000	8	8	2.0	3510
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K0250 [1]	4270	486265	14	14	2.0	3510
	5	11	0.66	750	0	7	2	-10	100	FKM	121K01	2995	481865	9	10	2.0/14.2	3510
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K01	4270	481000	8	8	2.0/14.2	3510
	5	11	0.66	750	0	7	5	-10	120	FKM	121K01	4270	486265	14	14	2.0/14.2	3510
	5	11	0.66	750	0	7	2	-10	100	FKM	121K0150 [1]	2995	481865	9	10	2.0	3510
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K0150 [1]	4270	481000	8	8	2.0	3510
	5	11	0.66	750	0	7	5	-10	120	FKM	121K0150 [1]	4270	486265	14	14	2.0	3510

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	0.9	2	-10
To	1/4"	5	11	20	120



Drawing 3382



Drawing 3510

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/8"	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K3206	2995	481865	9	10	2.0	3551
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K3206	4270	481000	8	8	2.0	3551
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K3206	4270	486265	14	14	2.0	3551
	5	11	0.66	750	0	7	2	-10	100	FKM	121K3106	2995	481865	9	10	2.0	3551
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K3106	4270	481000	8	8	2.0	3551
	5	11	0.66	750	0	7	5	-10	120	FKM	121K3106	4270	486265	14	14	2.0	3551
	6	12	0.72	1100	0	5	1.1	-10	100	FKM	121K3306	2995	481865	9	10	2.0/14.2	3551
	6	12	0.72	1100	0	5	1.5	-10	120	FKM	121K3306	4270	481000	8	8	2.0/14.2	3551
	6	12	0.72	1100	0	5	3	-10	120	FKM	121K3306	4270	486265	14	14	2.0/14.2	3551
1/2"	8.5	25	1.5	1600	0	1.1	0.5	-10	100	FKM	E121K46	2995	481865	9	10	2.0	3427
	8.5	25	1.5	1600	0	2.2	0.5	-10	120	FKM	E121K46	4270	481000	8	8	2.0	3427
	8.5	25	1.5	1600	0	4	1.2	-10	120	FKM	E121K46	4270	486265	14	14	2.0	3427
	11	36	2.16	2500	0	0.7	0.3	-10	100	FKM	E121K45	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0	1.2	0.35	-10	120	FKM	E121K45	4270	481000	8	8	2.0	3427
	11	36	2.16	2500	0	2.5	0.7	-10	120	FKM	E121K45	4270	486265	14	14	2.0	3427

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	2.5	3	0.18	180	0	12	12	-10	100	FKM	122K8306	2995	481865	9	10	2.0	3510
	2.5	3	0.18	180	0	12	12	-10	120	FKM	122K8306	4270	481000	8	8	2.0	3510
	2.5	3	0.18	180	0	12	12	-10	120	FKM	122K8306	4270	486265	14	14	2.0	3510

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	2.5	3	0.3	-10
To	1/2"	11	36	12	120



WEIGHT : 215 gr

Drawing 3551



Drawing 3427



Drawing 3510

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

DIRECT OPERATED

BRASS

PIPE MOUNTING

CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	5	11	0.66	750	0	5	-	-10	100	FKM	125K01	4269	484990	11	-	4.0	8296
	5	11	0.66	750	0	-	1.5	-10	100	FKM	125K01	4269	485400	-	13	4.0	8296

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	5	11	1.5	-10
To	1/4"	5	11	5	100



Drawing 8296

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

DIRECT OPERATED

BRASS

SUB-BASE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	E121F4406	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	E121F4406	4270	481000	8	8	2.0	3509
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	E121F4406	4270	486265	14	14	2.0	3509
	3	4.5	0.27	320	0	10	7	-10	100	FKM	E121F4302	2995	481865	9	10	2.0/3.0	3509
	3	4.5	0.27	320	0	10	8.5	-10	120	FKM	E121F4302	4270	481000	8	8	2.0/3.0	3509
	3	4.5	0.27	320	0	10	10	-10	120	FKM	E121F4302	4270	486265	14	14	2.0/3.0	3509

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.5	7	-10
To	SB	3	4.5	20	120



Drawing 3509

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Order Number	Valve Type	Coil Type	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn m^3/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/8"	13	50	3	-	0.1	10	10	-10	140	EPDM	443778W$_1$	7321BIH00	481865	9	10	2.0	028
	13	50	3	-	0.1	20	20	-10	90	NBR	443776W	7321BIN00	481865	9	10	2.0	028
	13	50	3	-	0.1	20	20	-10	90	NBR	443777W$_2$	7321BIN01	481865	9	10	2.0	028
	13	50	3	-	0.1	20	20	-10	140	FKM	444492W	7321BIV00	481865	9	10	2.0	028
1/2"	13	50	3	-	0.1	10	10	-10	140	EPDM	443781W$_1$	7321BAH00	481865	9	10	2.0	028
	13	50	3	-	0.1	20	20	-10	90	NBR	443779W	7321BAN00	481865	9	10	2.0	028
	13	50	3	-	0.1	20	20	-10	90	NBR	443780W$_2$	7321BAN01	481865	9	10	2.0	028
	13	50	3	-	0.1	20	20	-10	140	FKM	444494W	7321BAV00	481865	9	10	2.0	028
3/4"	20	140	8.4	-	0.1	10	10	-10	140	EPDM	443785W$_1$	7321BCH00	481865	9	10	2.0	057
	20	140	8.4	-	0.1	20	20	-10	90	NBR	443782W	7321BCN00	481865	9	10	2.0	057
	20	140	8.4	-	0.1	10	10	-10	90	NBR	443783W$_2$	7321BCN01	481865	9	10	2.0	057
	20	140	8.4	-	0.1	20	20	-10	140	FKM	444497W	7321BCV00	481865	9	10	2.0	057
1"	25	160	9.6	-	0.1	10	10	-10	140	EPDM	443789W$_1$	7321BDH00	481865	9	10	2.0	057
	25	160	9.6	-	0.1	20	20	-10	90	NBR	443786W	7321BDN00	481865	9	10	2.0	057
	25	160	9.6	-	0.1	10	10	-10	90	NBR	443787W$_2$	7321BDN01	481865	9	10	2.0	057
	25	160	9.6	-	0.1	20	20	-10	140	FKM	443804W	7321BDV00	481865	9	10	2.0	057

Notes:
1.Maximum pressure for steam: 4 Bar (140°C)
2.With manual override
Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	13	50	10	-10
To	1"	25	160	20	140







Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	3/8"'		69	2.71	99.5	3.91	40	1.57
	1/2"		72	2.83	101.5	3.99	40	1.57
Normally Open	3/8"		69	2.71	110	4.33	40	1.57
	1/2"		72	2.83	112	4.41	40	1.57

Drawing 028







Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	3/4"		100	3.83	107	4.21	65	2.55
	1"		104	4.09	112.5	4.42	65	2.55
Normally Open	3/4"		100	3.83	117.5	4.62	65	2.55
	1"		104	4.09	123	4.84	65	2.55

Drawing 057

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Order Number	Valve Type	Coil Type	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn m^3/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1 1/4"	35	420	25.2	-	0.1	10	10	-10	140	EPDM	443793W[1]	7321BEH00	481865	9	10	2.0	058
	35	420	25.2	-	0.1	10	10	-10	90	NBR	443790W	7321BEN00	481865	9	10	2.0	058
	35	420	25.2	-	0.1	5	5	-10	90	NBR	443791W[2]	7321BEN01	481865	9	10	2.0	058
1 1/2"	40	500	30	-	0.1	10	10	-10	140	EPDM	443797W[1]	7321BFH00	481865	9	10	2.0	058
	40	500	30	-	0.1	10	10	-10	90	NBR	443794W	7321BFN00	481865	9	10	2.0	058
	40	500	30	-	0.1	5	5	-10	90	NBR	443795W[2]	7321BFN01	481865	9	10	2.0	058
2"	50	620	37.2	-	0.1	10	10	-10	140	EPDM	443801W[1]	7321BGH00	481865	9	10	2.0	058
	50	620	37.2	-	0.1	10	10	-10	90	NBR	443798W	7321BGN00	481865	9	10	2.0	058
	50	620	37.2	-	0.1	5	5	-10	90	NBR	443799W[2]	7321BGN01	481865	9	10	2.0	058

Notes:
1.Maximum pressure for steam: 4 Bar (140°C)
2.With manual override
Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1 1/4"	35	420	5	-10
To	2"	50	620	10	140





Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	1 1/4"'		145	5.70	134	5.27	102	4.01
	1 1/2"		145	5.70	134	5.27	102	4.01
	2"		173	6.81	148	5.82	118	4.64
Normal Open	1 1/4"		145	5.70	144.5	5.68	102	4.01
	1 1/2"		145	5.70	134	5.27	102	4.01
	2"		173	6.81	148	5.82	118	4.64

Drawing 058

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/4"	11	28	1.68	1800	0.2	10	3	-10	100	NBR	E321K10	2995	481865	9	10	2.0	3429
	11	28	1.68	1800	0.2	10	4	-10	100	NBR	E321K10	4270	481000	8	8	2.0	3429
	12	30	1.8	2150	0.3	10	10	-10	100	NBR	321K31	8993	481180	4	5	1.1	7093
	12	30	1.8	2150	0.3	10	7	-10	75	NBR	321K31	8993	488980	2	2.5	1.1	7093
	12	32	1.92	2150	0.3	12	12	-10	100	FKM	321K4106	2995	481865	9	10	2.0/3.0	7094
	12	32	1.92	2150	0.3	12	12	-10	120	FKM	321K4106	4270	481000	8	8	2.1/3.0	7094
3/8"	11	36	2.16	2500	0.2	10	4	-10	100	NBR	E321K13	4270	481000	8	8	2.0	3429
	11	36	2.16	2500	0.2	10	10	-10	100	NBR	E321K13	4270	486265	14	14	2.0	3429
	12	45	2.7	3050	0.3	10	10	-10	100	NBR	321K33	8993	481180	4	5	1.1	7093
	12	45	2.7	3050	0.3	10	7	-10	75	NBR	321K33	8993	488980	2	2.5	1.1	7093
	12	45	2.7	3050	0.3	12	12	-10	100	FKM	321K4306	2995	481865	9	10	2.0/3.0	7094
	12	45	2.7	3050	0.3	12	12	-10	120	FKM	321K4306	4270	481000	8	8	2.1/3.0	7094

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	11	28	3	-10
To	3/8"	12	45	12	120



Valve	A
E321K13/63	G 3/8"
E321K10	G 1/4"

Drawing 3429



	A	B	C
321 K 31	G 1/4"	25	50
321 K 33	G 3/8"	25	50
321 K 35	G 1/2"	27,5	55

Drawing 7093



	A	B	C
321 K 41	G 1/4"	25	50
321 K 43	G 3/8"	25	50
321 K 45	G 1/2"	27,5	55

Drawing 7094

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/2"	11	36	2.16	2500	0.2	10	3	-10	100	NBR	E321K15	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0.2	10	10	-10	120	NBR	E321K15	4270	486265	14	14	2.0	3427
	11	36	2.16	2500	0.2	10	3	-10	100	FKM	E321K25	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0.2	4	4	-10	65	FKM	E321K25	-	492070	9	8	2.0	3427
	12	50	3	3400	0.3	10	10	-10	100	NBR	321K35	8993	481180	4	5	1.1	7093
	12	50	3	3400	0.3	10	7	-10	75	NBR	321K35	8993	488980	2	2.5	1.1	7093
	12	50	3	3400	0.3	12	12	-10	100	FKM	321K4506	2995	481865	9	10	2.0/3.0	7094
	12	50	3	3400	0.3	12	12	-10	120	FKM	321K4506	4270	481000	8	8	2.1/3.0	7094
	12	50	3	3400	0.3	12	12	-10	100	FKM	321K4556 [1]	2995	481865	9	10	2.0/3.0	7094
	12	50	3	3400	0.3	12	12	-10	120	FKM	321K4556 [1]	4270	481000	8	8	2.1/3.0	7094

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	11	36	3	-10
To	1/2"	12	50	12	120



Drawing 3427



	A	B	C
321 K 31	G 1/4"	25	50
321 K 33	G 3/8"	25	50
321 K 35	G 1/2"	27,5	55

Drawing 7093



	A	B	C
321 K 41	G 1/4"	25	50
321 K 43	G 3/8"	25	50
321 K 45	G 1/2"	27,5	55

Drawing 7094

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
3/4"	18	100	6	9400	0.3	10	10	-10	100	NBR	321K36	8993	481180	4	5	1.1	7097
	18	100	6	9400	0.3	10	7	-10	75	NBR	321K36	8993	488980	2	2.5	1.1	7097
	18	100	6	9400	0.3	12	12	-10	100	FKM	321K4606	2995	481865	9	10	2.0/3.0	7099
	18	100	6	9400	0.3	12	12	-10	120	FKM	321K4606	4270	481000	8	8	2.1/3.0	7099
	18	100	6	9400	0.3	12	12	-10	100	FKM	321K4656 [1]	2995	481865	9	10	2.0/3.0	7099
	18	100	6	9400	0.3	12	12	-10	120	FKM	321K4656 [1]	4270	481000	8	8	2.1/3.0	7099
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	E321G36	2995	481865	9	10	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	E321G36	4270	481000	8	8	2.0	3442

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	18	100	7	-10
To	3/4"	20	135	16	120



Drawing 7097



Drawing 7099



	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	60	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	60	140	99
321G3956/G3967	UNF 1 7/8"	144	75	33	67	60	140	99
U321/U322G40..	BSP 2"	158.5	80	41.5	73	75	150	99

Drawing 3442

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1"	18	110	6.6	10150	0.3	10	10	-10	100	NBR	321K37	8993	481180	4	5	1.1	7098
	18	110	6.6	10150	0.3	10	7	-10	75	NBR	321K37	8993	488980	2	2.5	1.1	7098
	18	110	6.6	10150	0.3	12	12	-10	100	FKM	321K4706	2995	481865	9	10	2.0/3.0	7100
	18	110	6.6	10150	0.3	12	12	-10	120	FKM	321K4706	4270	481000	8	8	2.1/3.0	7100
	18	110	6.6	10150	0.3	12	12	-10	100	FKM	321K4756 [1]	2995	481865	9	10	2.0/3.0	7100
	18	110	6.6	10150	0.3	12	12	-10	120	FKM	321K4756 [1]	4270	481000	8	8	2.1/3.0	7100
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	E321G37	2995	481865	9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	E321G37	4270	481000	8	8	2.0	3442
1 1/4"	28	270	16.2	18000	0.3	16	16	-10	100	NBR	E321G38	2995	481865	9	10	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	100	NBR	E321G38	4270	481000	8	8	2.0	3442
1 1/2"	40	420	25.2	31500	0.3	16	7	-10	100	NBR	E321G39	2995	481865	9	10	2.0	3442
	40	420	25.2	31500	0.3	16	8.5	-10	100	NBR	E321G39	4270	481000	8	8	2.0	3442
	40	420	25,2	31500	0,3	16	16	-10	100	NBR	E321G39	4270	486265	14	14	2.0	3442
2"	40	540	32.4	40000	0.3	16	7	-10	100	NBR	E321G40	2995	481865	9	10	2.0	3442
	40	540	32.4	40000	0.3	16	8.5	-10	100	NBR	E321G40	4270	481000	8	8	2.0	3442
	40	540	32,4	40000	0,3	16	16	-10	100	NBR	E321G40	4270	486265	14	14	2.0	3442

Notes:
1.With manual override

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1"	18	110	7	-10
To	2"	40	540	16	120



Drawing 7098



Drawing 7100



	RACCORD	A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"		121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"		121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"		137.5	55	33	60.5	60	110	70
321/322/E321G39..	BSP 1 1/2"		144	75	33	67	60	140	99
321G3956/G3967	UNF 1 7/8"		144	75	33	67	60	140	99
U321/U322G40..	BSP 2"		158.5	80	41.5	73	75	150	99

Drawing 3442

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Order Number	Valve Type	Coil Type	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn m³/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/8"	13	50	3	-	0.1	10	10	-10	140	EPDM	444600W	7322BIH00	481865	9	10	2.0	060
	13	50	3	-	0.1	20	20	-10	90	NBR	443805W	7322BIN00	481865	9	10	2.0	060
	13	50	3	-	0.1	20	20	-10	140	FKM	444499W	7322BIV00	481865	9	10	2.0	060
1/2"	13	50	3	-	0.1	10	10	-10	140	EPDM	444601W	7322BAH00	481865	9	10	2.0	060
	13	50	3	-	0.1	20	20	-10	90	NBR	443806W	7322BAN00	481865	9	10	2.0	060
	13	50	3	-	0.1	20	20	-10	140	FKM	444500W	7322BAV00	481865	9	10	2.0	060
3/4"	20	140	8.4	-	0.1	10	10	-10	140	EPDM	444602W	7322BCH00	481865	9	10	2.0	061
	20	140	8.4	-	0.1	20	20	-10	90	NBR	443807W	7322BCN00	481865	9	10	2.0	061
	20	140	8.4	-	0.1	20	20	-10	140	FKM	444501W	7322BCV00	481865	9	10	2.0	061
1"	25	160	9.6	-	0.1	10	10	-10	140	EPDM	444603W	7322BDH00	481865	9	10	2.0	061
	25	160	9.6	-	0.1	20	20	-10	90	NBR	443808W	7322BDN00	481865	9	10	2.0	061
	25	160	9.6	-	0.1	20	20	-10	140	FKM	444502W	7322BDV00	481865	9	10	2.0	061
1 1/4"	35	420	25.2	-	0.1	10	10	-10	140	EPDM	444576W	7322BEH00	481865	9	10	2.0	062
	35	420	25.2	-	0.1	10	10	-10	90	NBR	443809W	7322BEN00	481865	9	10	2.0	062
1 1/2"	40	500	30	-	0.1	10	10	-10	140	EPDM	444604W	7322BFH00	481865	9	10	2.0	062
	40	500	30	-	0.1	10	10	-10	90	NBR	443810W	7322BFN00	481865	9	10	2.0	062
2"	50	620	37.2	-	0.1	10	10	-10	140	EPDM	444605W	7322BGH00	481865	9	10	2.0	062
	50	620	37.2	-	0.1	10	10	-10	90	NBR	443811W	7322BGN00	481865	9	10	2.0	062
2 1/2"	65	1100	66	-	0.2	10	10	-10	90	NBR	444513W	7322BLN06	481865	9	10	2.0	063
3"	75	1334	80	-	0.2	10	10	-10	90	NBR	444503W	7322BMN06	481865	9	10	2.0	063

Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.





Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	3/8"'		69	2.71	99.5	3.91	40	1.57
	1/2"		72	2.83	101.5	3.99	40	1.57
Normally Open	3/8"		69	2.71	110	4.33	40	1.57
	1/2"		72	2.83	112	4.41	40	1.57

Drawing 060

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	13	50	10	-10
To	3"	75	1334	20	140



Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	3/4"		100	3.83	107	4.21	65	2.55
	1"		104	4.09	112.5	4.42	65	2.55
Normally Open	3/4"		100	3.83	117.5	4.62	65	2.55
	1"		104	4.09	123	4.84	65	2.55

Drawing 061



Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	1 1/4"'		145	5.70	134	5.27	102	4.01
	1 1/2"		145	5.70	134	5.27	102	4.01
	2"		173	6.81	148	5.82	118	4.64
Normal Open	1 1/4"		145	5.70	144.5	5.68	102	4.01
	1 1/2"		145	5.70	134	5.27	102	4.01
	2"		173	6.81	148	5.82	118	4.64

Drawing 062



Function	Connections	A		B		C	
	BSP	mm	inch	mm	inch	mm	inch
Normally Closed	2 1/2"	245	9.64	195	7.67	184	7.24
	3"	250	9.84	195	7.67	184	7.24
Normally Open	2 1/2"	245	9.64	205	8.07	184	7.24
	3"	245	9.64	205	8.07	184	7.24

Drawing 063

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	12	32	1.92	2150	0.3	12	12	-10	100	FKM	322K4106	2995	481865	9	10	2.0	7094
	12	32	1.92	2150	0.3	12	12	-10	120	FKM	322K4106	4270	481000	8	8	2.1	7094
3/8"	12	45	2.7	3050	0.3	12	12	-10	100	FKM	322K4306	2995	481865	9	10	2.0	7094
	12	45	2.7	3050	0.3	12	12	-10	120	FKM	322K4306	4270	481000	8	8	2.1	7094
1/2"	12	50	3	3400	0.3	12	12	-10	100	FKM	322K4506	2995	481865	9	10	2.0	7094
	12	50	3	3400	0.3	12	12	-10	120	FKM	322K4506	4270	481000	8	8	2.1	7094
	15	60	3.6	3890	0.3	15	15	-10	100	NBR	322G75	2995	481865	9	10	2.0	3522
	15	60	3.6	3890	0.3	15	15	-10	100	NBR	322G75	4270	481000	8	8	2.1	3522
3/4"	18	100	6	9400	0.3	12	12	-10	100	FKM	322K4606	2995	481865	9	10	2.0	7099
	18	100	6	9400	0.3	12	12	-10	120	FKM	322K4606	4270	481000	8	8	2.1	7099
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	322G36	2995	481865	9	10	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	322G36	4270	481000	8	8	2.1	3442



	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	60	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	60	140	99
321G3956/G3967	UNF 1 7/8"	144	75	33	67	60	140	99
U321/U322G40..	BSP 2"	158.5	80	41.5	73	75	150	99



Drawing 3442

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	12	32	12	-10
To	3/4"	20	135	16	120



Drawing 7094



Drawing 3522



Drawing 7099

2/2 VALVES FOR WATER AND NEUTRAL LIQUIDS

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1"	18	110	6.6	10150	0.3	12	12	-10	100	FKM	322K4706	2995	481865	9	10	2.0	7100
	18	110	6.6	10150	0.3	12	12	-10	120	FKM	322K4706	4270	481000	8	8	2.0	7100
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	322G37	2995	481865	9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	322G37	4270	481000	8	8	2.1	3442
1 1/2"	40	420	25.2	31500	0.3	12	12	-10	100	NBR	322G39	2995	481865	9	10	2.0	3442
	40	420	25.2	31500	0.3	12	12	-10	100	NBR	322G39	4270	481000	8	8	2.1	3442

BRASS

SUB-BASE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	45	2.7	2100	0.3	40	25	-10	100	NBR	E321F32 [1]	2995	481865	9	10	2.0	3520
	14	45	2.7	2100	0.3	40	30	-10	100	NBR	E321F32 [1]	4270	481000	8	8	2.0	3520
	14	45	2.7	2100	0.3	40	40	-10	100	NBR	E321F32 [1]	4270	486265	14	14	2.0	3520

Notes:
1.Pilot seat disc in synthetic Ruby

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	14 mm	14	45	12	-10
To	1 1/2"	40	420	40	120



Drawing 7100



	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	50	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	50	140	99
3212966/E2967	UNF 1 7/8"	144	75	33	67	50	140	99
U321/U322G40..	BSP 2"	158.5	80	41.5	73	75	150	99

Drawing 3442



Drawing 3520

NOTES

ANTI WATER HAMMER VALVES

Water

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Magnalift	Brass/Pipe Mounting	Normally Closed	1"	15 to 25	170	10	140	124
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/4"	12	32	12	120	128
			3/8"	12	45	12	120	128
			1/2"	12	50	12	120	128
			3/4"	18 to 20	135	16	120	128
			1"	18 to 25	180	16	120	126 and 130
			1 1/4"	28 to 35	420	16	100	126 and 130
			1 1/2"	40	500	16	100	126 and 130
			2"	40 to 50	620	16	100	126 and 130
			2 1/2"	65	1100	10	90	126
			3"	75	1334	10	90	126
		Normally Open	3/4"	20	135	16	100	132
			1"	25	180	16	100	132
			1 1/4"	28	270	16	100	132
			1 1/2"	40	425	12	100	132
			2"	40	540	12	100	132

2/2 ANTI WATER HAMMER VALVES

MAGNALIFT

Commercial Equipment

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1"	15	80	4.8	6000	0	-	10	-10	100	NBR	221G1731 12	2995	481865	-	10	2.0	3445
	15	80	4.8	6000	0	10	10	-10	65	NBR	221G1731 12	-	492070	9	8	2.1	3445
	15	80	4.8	6000	0	10	10	-10	75	NBR	221G1731 12	-	492190	11	9	2.1	3445
	25	160	9.6	-	0	10	-	0	100	EPDM	221G2103	2995	481865	9	-	2.0	3448
	25	160	9.6	-	0	10	-	0	120	EPDM	221G2103	4270	481000	8	-	2.0	3448
	25	160	9.6	-	0	10	10	0	120	EPDM	221G2103	4270	486265	14	14	2.0	3448
	25	160	9.6	-	0	4	4	0	140	EPDM	221G2103	2995	492425	14	14	2.0	3448
	25	170	10.2	14000	0	-	10	-25	100	NBR	221G2131 12	2995	481865	-	10	2.0	3448
	25	170	10.2	14000	0	10	10	-25	40	NBR	221G2131 12	-	492070	9	8	2.1	3448
	25	170	10.2	14000	0	10	10	-25	40	NBR	221G2131 12	-	492190	11	9	2.1	3448

Notes:
1.Valves with model number ending in 30 or 31 are only compatible with explosion proof electrical parts shown, or with group 2.1 coils only in DC voltage.
2.With 4 position selector for controlled closure rate

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1"	15	80	4	-25
To	1"	25	170	10	140



Drawing 3445



Drawing 3448

2/2 ANTI WATER HAMMER VALVES

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Order Number	Valve Type	Coil Type	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn m^3/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/4"	20	140	8.4	-	0.1	10	10	-10	90	NBR	443784W$_{12}$	7321BCN02	481865	9	10	2.0	057
1"	25	160	9.6	-	0.1	10	10	-10	90	NBR	443788W$_{12}$	7321BDN02	481865	9	10	2.0	057
1 1/4"	35	420	25.2	-	0.1	5	5	-10	90	NBR	443792W$_{12}$	7321BEN02	481865	9	10	2.0	058
1 1/2"	40	500	30	-	0.1	5	5	-10	90	NBR	443796W$_{12}$	7321BFN02	481865	9	10	2.0	058
2"	50	620	37.2	-	0.1	5	5	-10	90	NBR	443800W$_{12}$	7321BGN02	481865	9	10	2.0	058
2 1/2"	65	1100	66	-	0.2	10	10	-10	90	NBR	443802W$_{12}$	7321BLN02	481865	9	10	2.0	059
3"	75	1334	80	-	0.2	10	10	-10	90	NBR	443803W$_{12}$	7321BMN02	481865	9	10	2.0	059

Notes:
1.With manual override
2. Valve with opening speed control regulation

Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	20	140	5	-10
To	3"	75	1334	10	90



Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	3/4"		100	3.83	107	4.21	65	2.55
	1"		104	4.09	112.5	4.42	65	2.55
Normally Open	3/4"		100	3.83	117.5	4.62	65	2.55
	1"		104	4.09	123	4.84	65	2.55

Drawing 057



Function	Connections		A		B		C	
	BSP	NPT	mm	inch	mm	inch	mm	inch
Normally Closed	1 1/4"'		145	5.70	134	5.27	102	4.01
	1 1/2"		145	5.70	134	5.27	102	4.01
	2"		173	6.81	148	5.82	118	4.64
Normal Open	1 1/4"		145	5.70	144.5	5.68	102	4.01
	1 1/2"		145	5.70	134	5.27	102	4.01
	2"		173	6.81	148	5.82	118	4.64

Drawing 058



Function	Connections	A		B		C	
	BSP	mm	inch	mm	inch	mm	inch
Normally Closed	2 1/2"	245	9.64	195	7.67	184	7.24
	3"	250	9.84	195	7.67	184	7.24
Normally Open	2 1/2"	245	9.64	205	8.07	184	7.24
	3"	245	9.64	205	8.07	184	7.24

Drawing 059

2/2 ANTI WATER HAMMER VALVES

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	12	32	1.92	2150	0.3	12	12	-10	100	FKM	321K4106	2995	481865	9	10	2.0/3.0	7094
	12	32	1.92	2150	0.3	12	12	-10	120	FKM	321K4106	4270	481000	8	8	2.1/3.0	7094
3/8"	12	45	2.7	3050	0.3	12	12	-10	100	FKM	321K4306	2995	481865	9	10	2.0/3.0	7094
	12	45	2.7	3050	0.3	12	12	-10	120	FKM	321K4306	4270	481000	8	8	2.1/3.0	7094
1/2"	12	50	3	3400	0.3	12	12	-10	100	FKM	321K4506	2995	481865	9	10	2.0/3.0	7094
	12	50	3	3400	0.3	12	12	-10	120	FKM	321K4506	4270	481000	8	8	2.1/3.0	7094
	12	50	3	3400	0.3	12	12	-10	100	FKM	321K4556 [1]	2995	481865	9	10	2.0/3.0	7094
	12	50	3	3400	0.3	12	12	-10	120	FKM	321K4556 [1]	4270	481000	8	8	2.1/3.0	7094
3/4"	18	100	6	9400	0.3	12	12	-10	100	FKM	321K4606	2995	481865	9	10	2.0/3.0	7099
	18	100	6	9400	0.3	12	12	-10	120	FKM	321K4606	4270	481000	8	8	2.1/3.0	7099
	18	100	6	9400	0.3	12	12	-10	100	FKM	321K4656 [1]	2995	481865	9	10	2.0/3.0	7099
	18	100	6	9400	0.3	12	12	-10	120	FKM	321K4656 [1]	4270	481000	8	8	2.1/3.0	7099
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	E321G3610 [2]	2995	481865	9	10	2.0	3442
	20	135	8.1	9500	0.3	16	16	-10	100	NBR	E321G3610 [2]	4270	481000	8	8	2.0	3442

Notes:
1.With manual override
2.With manual override and 4 position selector for controlled closure rate

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	12	32	12	-10
To	3/4"	20	135	16	120



	A	B	C
321 K 41	G 1/4"	25	50
321 K 43	G 3/8"	25	50
321 K 45	G 1/2"	27,5	55

Drawing 7094



Drawing 7099



	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	60	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	60	140	99
321G3956/G3967	UNF 1 7/8"	144	75	33	67	60	140	99
U321/U322G40..	BSP 2"	158.5	80	41.5	73	75	150	99

Drawing 3442

2/2 ANTI WATER HAMMER VALVES

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1"	18	110	6.6	10150	0.3	12	12	-10	100	FKM	321K4706	2995	481865	9	10	2.0/3.0	7100
	18	110	6.6	10150	0.3	12	12	-10	120	FKM	321K4706	4270	481000	8	8	2.1/3.0	7100
	18	110	6.6	10150	0.3	12	12	-10	100	FKM	321K4756 [1]	2995	481865	9	10	2.0/3.0	7100
	18	110	6.6	10150	0.3	12	12	-10	120	FKM	321K4756 [1]	4270	481000	8	8	2.1/3.0	7100
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	E321G3710 [2]	2995	481865	9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	E321G3710 [2]	4270	481000	8	8	2.0	3442
1 1/4"	28	280	16.8	18000	0.3	16	16	-10	100	NBR	E321G3810 [2]	2995	481865	9	10	2.0	3442
	28	280	16.8	18000	0.3	16	16	-10	100	NBR	E321G3810 [2]	4270	481000	8	8	2.0	3442
1 1/2"	40	420	25.2	31500	0.3	16	7	-10	100	FKM	E321G3910 [2]	2995	481865	9	10	2.0	3442
	40	420	25.2	31500	0.3	16	8.5	-10	100	FKM	E321G3910 [2]	4270	481000	8	8	2.0	3442
2"	40	540	32.4	40000	0.3	16	7	-10	100	FKM	E321G4010 [2]	2995	481865	9	10	2.0	3442
	40	540	32.4	40000	0.3	16	8.5	-10	100	FKM	E321G4010 [2]	4270	481000	8	8	2.0	3442

Notes:
1.With manual override
2.With manual override and 4 position selector for controlled closure rate

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1"	18	110	7	-10
To	2"	40	540	16	120



Drawing 7100



	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	50	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	50	140	99
3212356/E3256?	UNF 1 7/8"	144	75	33	67	50	140	99
U321/U322G40..	BSP 2"	158.5	80	41.5	73	75	150	99

Drawing 3442

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 ANTI WATER HAMMER VALVES

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/4"	20	135	8.1	9300	0.3	16	16	-10	100	NBR	322G3610 [1]	2995	481865	9	10	2.0	3442
	20	135	8.1	9300	0.3	16	16	-10	100	NBR	322G3610 [1]	4270	481000	8	8	2.1	3442
1"	25	180	10.8	14000	0.3	16	16	-10	100	NBR	322G3710 [1]	2995	481865	9	10	2.0	3442
	25	180	10.8	14000	0.3	16	16	-10	100	NBR	322G3710 [1]	4270	481000	8	8	2.1	3442
1 1/4"	28	270	16.2	18000	0.3	16	16	-10	100	NBR	322G3810 [1]	2995	481865	9	10	2.0	3442
	28	270	16.2	18000	0.3	16	16	-10	100	NBR	322G3810 [1]	4270	481000	8	8	2.1	3442
1 1/2"	40	425	25.5	31000	0.3	12	12	-10	100	NBR	322G3910 [1]	2995	481865	9	10	2.0	3442
	40	425	25.5	31000	0.3	12	12	-10	100	NBR	322G3910 [1]	4270	481000	8	8	2.1	3442
2"	40	540	32.4	40000	0.3	12	12	-10	100	NBR	322G4010 [1]	2995	481865	9	10	2.0	3442
	40	540	32.4	40000	0.3	12	12	-10	100	NBR	322G4010 [1]	4270	481000	8	8	2.1	3442

Notes:
1.With 4 position selector for controlled closure rate

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	20	135	12	-10
To	2"	40	540	16	100





	RACCORD A	B	C	D	E	F	G	H
321/322/E321G36..	BSP 3/4"	121	50	23	54	41	100	70
321/322/E321G37..	BSP 1"	121	50	23	54	41	100	70
321/322/E321G38..	BSP 1 1/4"	137.5	55	33	60.5	60	110	70
321/322/E321G39..	BSP 1 1/2"	144	75	33	67	60	140	99
321G396E/G396T	UNF 1 7/8"	144	75	33	67	60	140	99
L321/L322G40..	BSP 2"	158.5	80	41.5	73	75	150	99

Drawing 3442

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

NOTES

HOT WATER AND STEAM VALVES

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valvess
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/4"	3 to 5	11	10	120	136
			3/8"	6	12	5	140	136
			1/2"	8.5 to 11	36	4	120	136
	303 Stainless St./Pipe Mounting	Normally Closed	1/4"	1.5 to 5	10	100	180	138
Magnalift	Brass/Pipe Mounting	Normally Closed	3/8"	15	65	10	140	140
			1/2"	15	65	10	140	140
			3/4"	15	80	10	140	140
			1"	15	80	10	140	140
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/2"	11 to 16	36	10	140	142

2/2 HOT WATER AND STEAM VALVES

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	3	4.5	0.27	-	0	10	7	0	100	EPDM	121K0323	2995	481865	9	10	2.0	3510
	3	4.5	0.27	-	0	10	8.5	0	120	EPDM	121K0323	4270	481000	8	8	2.0	3510
	3	4.5	0.27	-	0	10	10	0	120	EPDM	121K0323	4270	486265	14	14	2.0	3510
	3	4.5	0.27	-	0	10	10	0	120	EPDM	121K0323	2995	492425	14	14	2.0	3510
	5	11	0.66	750	0	7	2	0	100	EPDM	121K0103	2995	481865	9	10	2.0	3510
	5	11	0.66	750	0	7	2.8	0	120	EPDM	121K0103	4270	481000	8	8	2.0	3510
	5	11	0.66	750	0	7	5	0	120	EPDM	121K0103	4270	486265	14	14	2.0	3510
	5	11	0.66	750	0	4	3.5	0	120	EPDM	121K0103	2995	492425	14	14	2.0	3510
3/8"	6	12	0.72	1100	0	5	1.1	0	100	EPDM	121K3303	2995	481865	9	10	2.0	3551
	6	12	0.72	1100	0	5	1.5	0	120	EPDM	121K3303	4270	481000	8	8	2.0	3551
	6	12	0.72	1100	0	4	4	0	120	EPDM	121K3303	4270	486265	14	14	2.0	3551
	6	12	0.72	1100	0	4	4	0	140	EPDM	121K3303	2995	492425	14	14	2.0	3551
1/2"	8.5	25	1.5	-	0	2.2	0.5	0	120	EPDM	E121K4603	4270	481000	8	8	2.0	3427
	8.5	25	1.5	-	0	4	1.2	0	120	EPDM	E121K4603	4270	486265	14	14	2.0	3427
	8.5	25	1.5	-	0	2.5	1	0	120	EPDM	E121K4603	2995	492425	14	14	2.0	3427
	11	36	2.16	-	0	1.2	0.35	0	120	EPDM	E121K4503	4270	481000	8	8	2.0	3427
	11	36	2.16	-	0	2.5	0.7	0	120	EPDM	E121K4503	4270	486265	14	14	2.0	3427
	11	36	2.16	-	0	1.5	0.5	0	120	EPDM	E121K4503	2995	492425	14	14	2.0	3427

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	3	4.5	0.35	0
To	1/2"	11	36	10	140



Drawing 3510



Drawing 3551



Drawing 3427

2/2 HOT WATER AND STEAM VALVES

DIRECT OPERATED

303 STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/4"	1.5	1.5	0.09	80	0	60	25	0	100	Ruby	121V5463	2995	481865	9	10	2.0	8116
	1.5	1.5	0.09	80	0	75	30	0	130	Ruby	121V5463	4270	481000	8	8	2.0	8116
	1.5	1.5	0.09	80	0	100	55	0	140	Ruby	121V5463	4270	486265	14	14	2.0	8116
	2.5	3.5	0.21	220	0	28	10	0	100	Ruby	121V5763	2995	481865	9	10	2.0	8116
	2.5	3.5	0.21	220	0	34	12	0	130	Ruby	121V5763	4270	481000	8	8	2.0	8116
	2.5	3.5	0.21	220	0	50	22	0	140	Ruby	121V5763	4270	486265	14	14	2.0	8116
	3	4.5	0.27	315	0	20	7	0	100	Ruby	121V5363	2995	481865	9	10	2.0	8116
	3	4.5	0.27	315	0	25	8.5	0	130	Ruby	121V5363	4270	481000	8	8	2.0	8116
	3	4.5	0.27	315	0	36	15	0	140	Ruby	121V5363	4270	486265	14	14	2.0	8116
	4	7	0.42	450	0	12	4	0	100	Ruby	121V5263	2995	481865	9	10	2.0	8116
	4	7	0.42	450	0	15	5	0	130	Ruby	121V5263	4270	481000	8	8	2.0	8116
	4	7	0.42	450	0	22	10	0	180	Ruby	121V5263	4270	486265	14	14	2.0	8116
	5	10	0.6	750	0	8.5	2	0	100	Ruby	121V5163	2995	481865	9	10	2.0	8116
	5	10	0.6	750	0	10	3.5	0	130	Ruby	121V5163	4270	481000	8	8	2.0	8116
	5	10	0.6	750	0	14	6.5	0	140	Ruby	121V5163	4270	486265	14	14	2.0	8116
1/4" NPT	3	4.5	0.27	315	0	20	7	0	100	Ruby	U121V5363	2995	481865	9	10	2.0	8116

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.5	2	0
To	1/4"	5	10	100	180



A	G 1/8"
	G 1/4"

Drawing 8116

2/2 HOT WATER AND STEAM VALVES

MAGNALIFT

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/8"	15	65	3.9	-	0	10	-	0	100	EPDM	221G1303	2995	481865	9	-	2.0	3732
	15	65	3.9	-	0	10	-	0	120	EPDM	221G1303	4270	481000	8	-	2.0	3732
	15	65	3.9	-	0	4	4	0	140	EPDM	221G1303	4270	486265	14	14	2.0	3732
	15	65	3.9	4500	0	10	10	-10	100	NBR	221G1330 [1]	2995	481865	9	10	2.0	3732
	15	65	3.9	4500	0	10	10	-10	65	NBR	221G1330 [1]	-	492070	9	8	2.1	3732
1/2"	15	65	3.9	-	0	10	-	0	100	EPDM	221G1503	2995	481865	9	-	2.0	3732
	15	65	3.9	-	0	10	-	0	120	EPDM	221G1503	4270	481000	8	-	2.0	3732
	15	65	3.9	-	0	10	7	0	140	EPDM	221G1503	4270	486265	14	14	2.0	3732
3/4"	15	80	4.8	-	0	10	-	0	100	EPDM	221G1603	2995	481865	9	-	2.0	3444
	15	80	4.8	-	0	10	-	0	120	EPDM	221G1603	4270	481000	8	-	2.0	3444
	15	80	4.8	-	0	4	4	0	140	EPDM	221G1603	4270	486265	14	14	2.0	3444
1"	15	80	4.8	6000	0	10	-	0	100	EPDM	221G1703	2995	481865	9	-	2.0	3445
	15	80	4.8	6000	0	10	-	0	120	EPDM	221G1703	2995	481000	8	-	2.0	3445
	15	80	4.8	6000	0	10	10	0	140	EPDM	221G1703	2995	486265	14	14	2.0	3445

Notes:
1.Valves with model number ending in 30 or 31 are mainly equipped with electrical parts for explosion proof applications or with standard DC coils.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	15	65	4	-10
To	1"	15	80	10	140



Drawing 3732



Drawing 3444



Drawing 3445

2/2 HOT WATER AND STEAM VALVES

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size (BSP)	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn m³/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/2"	11	36	2.16	2500	0.2	10	3	0	100	EPDM	E321K1503	2995	481865	9	10	2.0	3427
	11	36	2.16	2500	0.2	10	4	0	120	EPDM	E321K1503	4270	481000	8	8	2.0	3427
	11	36	2.16	2500	0.2	10	10	0	140	EPDM	E321K1503 [1]	4270	486265	14	14	2.0	3427

Notes:
1.Maximum pressure for steam: 4Bar (140°C)

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	11	36	3	0
To	1/2"	11	36	10	140



Drawing 3427

NOTES

VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS

Oil Water

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/8"	1.5 to 2.5	3.5	70	130	146
			1/4"	1.2 to 3	4.5	100	130	146
			3/8"	4 to 6	12	10	120	148
		Normally Open	1/8"	2.5	3.5	30	140	148
			1/4"	1.5 to 2.5	3.5	40	140	148
	Brass/Sub-base Mounting	Normally Closed	5 mm	1.5 to 3	4.5	100	130	150
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/4"	8	36	40	140	152
			3/8"	11	50	40	140	152
			1/2"	15	60	40	140	154
		Normally Open	1/4"	8	36	40	140	156
			3/8"	11	50	40	140	156
			1/2"	15	60	40	140	156
	Brass/Sub-base Mounting	Normally Closed	14 mm	14	45	40	140	158
		Normally Open	14 mm	14	45	40	120	158

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/8"	1.5	1.5	0.09	80	0	60	25	-30	75	PCTFE	E121K14	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	70	30	-30	75	PCTFE	E121K14	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	70	55	-30	75	PCTFE	E121K14	4270	486265	14	14	2.0	3510
	2.5	3.5	0.21	220	0	28	10	-30	100	Ruby	E121K23	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	34	12	-30	130	Ruby	E121K23	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	50	22	-30	120	Ruby	E121K23	4270	486265	14	14	2.0	3510
1/4"	1.2	0.85	0.05	50	0	80	36	-30	100	Ruby	E121K65	2995	481865	9	10	2.0	3510
	1.2	0.85	0.05	50	0	100	43	-30	130	Ruby	E121K65	4270	481000	8	8	2.0	3510
	1.2	0.85	0.05	50	0	100	75	-30	120	Ruby	E121K65	4270	486265	14	14	2.0	3510
	1.5	1.5	0.09	80	0	60	25	-30	75	PCTFE	E121K04	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	70	30	-30	75	PCTFE	E121K04	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	70	55	-30	75	PCTFE	E121K04	4270	486265	14	14	2.0	3510
	1.5	1.5	0.09	80	0	60	25	-30	100	Ruby	E121K67	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	75	30	-30	130	Ruby	E121K67	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	100	55	-30	120	Ruby	E121K67	4270	486265	14	14	2.0	3510
	2.5	3.5	0.21	220	0	28	10	-30	100	Ruby	E121K63	2995	481865	9	10	2.0	3510
	2.5	3.5	0.21	220	0	34	12	-30	130	Ruby	E121K63	4270	481000	8	8	2.0	3510
	2.5	3.5	0.21	220	0	50	22	-30	120	Ruby	E121K63	4270	486265	14	14	2.0	3510
	3	4.5	0.27	320	0	20	7	-30	75	PCTFE	E121K03	2995	481865	9	10	2.0/3.0	3510
	3	4.5	0.27	320	0	25	8.5	-30	75	PCTFE	E121K03	4270	481000	8	8	2.0/3.0	3510
	3	4.5	0.27	320	0	36	15	-30	75	PCTFE	E121K03	4270	486265	14	14	2.0/3.0	3510
	3	4.5	0.27	320	0	20	7	-30	100	Ruby	E121K64	2995	481865	9	10	2.0	3510
	3	4.5	0.27	320	0	25	8.5	-30	130	Ruby	E121K64	4270	481000	8	8	2.0	3510
	3	4.5	0.27	320	0	36	15	-30	120	Ruby	E121K64	4270	486265	14	14	2.0	3510

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.2	0.85	7	-30
To	1/4"	3	4.5	100	130



Drawing 3510

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
DIRECT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size (BSP)	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn m³/h	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
3/8"	4	7.5	0.45	480	0	10	4	-10	100	FKM	121K3206	2995	481865	9	10	2.0	3551
	4	7.5	0.45	480	0	10	5	-10	120	FKM	121K3206	4270	481000	8	8	2.0	3551
	4	7.5	0.45	480	0	10	10	-10	120	FKM	121K3206	4270	486265	14	14	2.0	3551
	5	11	0.66	750	0	7	2	-10	100	FKM	121K3106	2995	481865	9	10	2.0	3551
	5	11	0.66	750	0	7	2.8	-10	120	FKM	121K3106	4270	481000	8	8	2.0	3551
	5	11	0.66	750	0	7	5	-10	120	FKM	121K3106	4270	486265	14	14	2.0	3551
	6	12	0.72	1100	0	5	1.1	-10	100	FKM	121K3306	2995	481865	9	10	2.0/14.2	3551
	6	12	0.72	1100	0	5	1.5	-10	120	FKM	121K3306	4270	481000	8	8	2.0/14.2	3551
	6	12	0.72	1100	0	5	3	-10	120	FKM	121K3306	4270	486265	14	14	2.0/14.2	3551

BRASS
PIPE MOUNTING
NORMALLY OPEN



Port size BSP	Orifice Ø mm	Flow factors Kv l/min	KV m³/h	Qn l/min	Operating Pressure Differential Min bar	Max(MOPD) AC bar	DC bar	Fluid Temp. Min °C	Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	DC W	Coil Group	Dwg. No.
1/8"	2.5	3.5	0.21	-	0	30	-	-30	140	Ruby	122K9363	4270	481044	14	-	2.2	3510
	2.5	3.5	0.21	-	0	30	30	-30	140	Ruby	122K9363	4270	486265	14	14	2.2	3510
1/4"	1.5	1.5	0.09	80	0	30	30	-10	100	PCTFE	122K84	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	30	30	-10	100	PCTFE	122K84	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	30	30	-10	120	PCTFE	122K84	4270	486265	14	14	2.0	3510
	1.5	1.5	0.09	80	0	40	40	-30	100	Ruby	122K8408	2995	481865	9	10	2.0	3510
	1.5	1.5	0.09	80	0	40	40	-30	130	Ruby	122K8408	4270	481000	8	8	2.0	3510
	1.5	1.5	0.09	80	0	40	40	-30	130	Ruby	122K8408	4270	486265	14	14	2.0	3510
	2.5	3.5	0.21	-	0	30	-	-30	140	Ruby	122K8363	4270	481044	14	-	2.2	3510
	2.5	3.5	0.21	-	0	30	30	-30	140	Ruby	122K8363	4270	486265	14	14	2.2	3510

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	1.5	1.1	-30
To	3/8"	6	12	40	140



Drawing 3510



WEIGHT : 215 gr

Drawing 3551

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
DIRECT OPERATED

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	1.5	1.5	0.09	80	0	60	25	-30	100	Ruby	121F67	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	75	30	-30	130	Ruby	121F67	4270	481000	8	8	2.0	3509
	1.5	1.5	0.09	80	0	100	55	-30	120	Ruby	121F67	4270	486265	14	14	2.0	3509
	1.5	1.5	0.09	80	0	60	25	-30	75	PCTFE	E121F44	2995	481865	9	10	2.0	3509
	1.5	1.5	0.09	80	0	70	30	-30	75	PCTFE	E121F44	4270	481000	8	8	2.0	3509
	1.5	1.5	0.09	80	0	70	55	-30	75	PCTFE	E121F44	4270	486265	14	14	2.0	3509
	2.5	3.5	0.21	220	0	14	7	-10	100	FKM	121F4706	2995	481865	9	10	2.0	3509
	2.5	3.5	0.21	220	0	14	9	-10	120	FKM	121F4706	4270	481000	8	8	2.0	3509
	2.5	3.5	0.21	220	0	14	14	-10	120	FKM	121F4706	4270	486265	14	14	2.0	3509
	2.5	3.5	0.21	220	0	28	10	-30	100	Ruby	121F63	2995	481865	9	10	2.0	3509
	2.5	3.5	0.21	220	0	34	12	-30	130	Ruby	121F63	4270	481000	8	8	2.0	3509
	2.5	3.5	0.21	220	0	50	22	-30	120	Ruby	121F63	4270	486265	14	14	2.0	3509
	3	4.5	0.27	320	0	20	7	-30	100	Ruby	121F64	2995	481865	9	10	2.0	3509
	3	4.5	0.27	320	0	25	8.5	-30	130	Ruby	121F64	4270	481000	8	8	2.0	3509
	3	4.5	0.27	320	0	36	15	-30	120	Ruby	121F64	4270	486265	14	14	2.0	3509
	3	4.5	0.27	320	0	20	7	-30	75	PCTFE	E121F43	2995	481865	9	10	2.0	3509
	3	4.5	0.27	320	0	25	8.5	-30	75	PCTFE	E121F43	4270	481000	8	8	2.0	3509
	3	4.5	0.27	320	0	36	15	-30	75	PCTFE	E121F43	4270	486265	14	14	2.0	3509

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.5	7	-30
To	SB	3	4.5	100	130





Drawing 3509

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
PILOT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	8	36	2.16	1600	0.3	40	25	-10	100	NBR	E321H11 $_{12}$	2995	481865	9	10	2.0	3523
	8	36	2.16	1600	0.3	40	30	-10	100	NBR	E321H11 $_{12}$	4270	481000	8	8	2.0	3523
	8	36	2.16	1600	0.3	40	40	-10	100	NBR	E321H11 $_{12}$	4270	486265	14	14	2.0	3523
	8	36	2.16	-	0.3	40	25	-10	100	FKM	E321H21 $_{12}$	2995	481865	9	10	2.0	3523
	8	36	2.16	-	0.3	40	30	-10	120	FKM	E321H21 $_{12}$	4270	481000	8	8	2.0	3523
	8	36	2.16	-	0.3	40	40	-10	140	FKM	E321H21 $_{12}$	4270	486265	14	14	2.0	3523
3/8"	11	50	3	2800	0.3	40	25	-10	100	NBR	E321H13 $_{12}$	2995	481865	9	10	2.0	3521
	11	50	3	2800	0.3	40	30	-10	100	NBR	E321H13 $_{12}$	4270	481000	8	8	2.0	3521
	11	50	3	2800	0.3	40	40	-10	100	NBR	E321H13 $_{12}$	4270	486265	14	14	2.0	3521
	11	50	3	-	0.3	40	25	-10	100	FKM	E321H23 $_{12}$	2995	481865	9	10	2.0	3521
	11	50	3	-	0.3	40	30	-10	120	FKM	E321H23 $_{12}$	4270	481000	8	8	2.0	3521
	11	50	3	-	0.3	40	40	-10	140	FKM	E321H23 $_{12}$	4270	486265	14	14	2.0	3521
	11	36	2.16	-	0.2	20	3	-10	100	Ruby	E321K63	2995	481865	9	-	2.0	3429
	11	36	2.16	-	0.2	30	4	-10	140	Ruby	E321K63	4270	488553	9	-	2.0	3429
	11	36	2.16	-	0.2	4	4	-10	75	Ruby	E321K63	-	492190	11	9	2.0	3429

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	36	3	-10
To	3/8"	11	50	40	140



Drawing 3523



Drawing 3521



Drawing 3429

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
PILOT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/2"	15	60	3.6	3150	0.3	40	25	-10	100	NBR	E321H15 $_{12}$	2995	481865	9	10	2.0	3522
	15	60	3.6	3150	0.3	40	30	-10	100	NBR	E321H15 $_{12}$	4270	481000	8	8	2.0	3522
	15	60	3.6	3150	0.3	40	40	-10	100	NBR	E321H15 $_{12}$	4270	486265	14	14	2.0	3522
	15	60	3.6	-	0.3	40	25	-10	100	FKM	E321H25 $_{12}$	2995	481865	9	10	2.0/14.2	3522
	15	60	3.6	-	0.3	40	30	-10	65	FKM	E321H25 $_{12}$	-	483371	8	8	2.0/14.2	3522
	15	60	3.6	-	0.3	40	40	-10	140	FKM	E321H25 $_{12}$	4270	486265	14	14	2.0/14.2	3522

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	15	60	25	-10
To	1/2"	15	60	40	140



Drawing 3522

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
PILOT OPERATED

BRASS
PIPE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
	8	36	2.16	1600	0.3	40	40	-10	100	FKM	322H7106 12	2995	481865	9	10	2.0/14.1	3523
1/4"	8	36	2.16	1600	0.3	40	40	-10	120	FKM	322H7106 12	4270	481000	8	8	2.0/14.1	3523
	8	36	2.16	1600	0.3	40	40	-10	140	FKM	322H7106 12	4270	486265	14	14	2.0/14.1	3523
	11	50	3	3240	0.3	40	40	-10	75	NBR	322H73 12	2995	481865	9	10	2.0	3523
	11	50	3	3240	0.3	40	40	-10	75	NBR	322H73 12	4270	481000	8	8	2.0	3523
3/8"	11	50	3	3240	0.3	40	40	-10	75	NBR	322H73 12	4270	486265	14	14	2.0	3523
	11	50	3	3240	0.3	40	40	-10	100	FKM	322H7306 12	2995	481865	9	10	2.0/14.1	3523
	11	50	3	3240	0.3	40	40	-10	100	FKM	322H7306 12	4270	481000	8	8	2.0/14.1	3523
	11	50	3	3240	0.3	40	40	-10	140	FKM	322H7306 12	4270	486265	14	14	2.0/14.1	3523
	15	60	3.6	3890	0.3	20	20	-10	100	FKM	322G7506 1	2995	481865	9	10	2.0	3522
	15	60	3.6	3890	0.3	20	20	-10	100	FKM	322G7506 1	4270	481000	8	8	2.0	3522
	15	60	3.6	3890	0.3	20	20	-10	100	FKM	322G7506 1	4270	486265	14	14	2.0	3522
	15	60	3.6	3890	0.3	40	40	-10	100	NBR	322H75 12	2995	481865	9	10	2.0	3522
1/2"	15	60	3.6	3890	0.3	40	40	-10	100	NBR	322H75 12	4270	481000	8	8	2.0	3522
	15	60	3.6	3890	0.3	40	40	-10	100	NBR	322H75 12	4270	486265	14	14	2.0	3522
	15	60	3.6	3890	0.3	40	40	-10	100	FKM	322H7506 12	2995	481865	9	10	2.0/14.1	3522
	15	60	3.6	3890	0.3	40	40	-10	120	FKM	322H7506 12	4270	481000	8	8	2.0/14.1	3522
	15	60	3.6	3890	0.3	40	40	-10	140	FKM	322H7506 12	4270	486265	14	14	2.0/14.1	3522

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	36	20	-10
To	1/2"	15	60	40	140



Drawing 3523



Drawing 3522

2/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS
PILOT OPERATED

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	45	2.7	-	0.3	40	25	-10	100	FKM	E321F3202 12	2995	481865	9	10	2.0	3520
	14	45	2.7	-	0.3	40	30	-10	120	FKM	E321F3202 12	4270	481000	8	8	2.0	3520
	14	45	2.7	-	0.3	40	40	-10	140	FKM	E321F3202 12	4270	486265	14	14	2.0	3520

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby

BRASS
SUB-BASE MOUNTING
NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	45	2.7	-	0.3	40	40	0	100	FKM	322F7206 12	2995	481865	9	10	2.0/14.1	3520
	14	45	2.7	-	0.3	40	40	0	120	FKM	322F7206 12	4270	481000	8	8	2.1/14.1	3520

Notes:
1.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
2.Pilot seat disc in synthetic Ruby

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	14	45	25	-10
To	SB	14	45	40	140



Drawing 3520

NOTES

VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS

Oil Water

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valve
Pilot Operated	Anodized Aluminium/ Pipe Mounting	Normally Closed	1/4"	8	10	40	75	162

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 VALVES FOR HYDRAULIC OIL AND NEUTRAL LIQUIDS

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max					AC	DC		
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C					W	W		
1/4"	8	8	10	10	0.6	0.6	1	40	40	-10	75	NBR	331B02 12	2995	481865	9	10	2.0	8114
	8	8	10	10	0.6	0.6	1	40	40	-10	75	NBR	331B02 12	4270	481000	8	8	2.1	8114
	8	8	10	10	0.6	0.6	1	40	40	-10	75	NBR	331B0216 13	2995	481865	9	10	2.0	8114
	8	8	10	10	0.6	0.6	1	40	40	-10	75	NBR	331B0216 13	4270	481000	8	8	2.1	8114

Notes:
1.Pilot seat discs in Kel-F (PCTFE); valve with pilot return pipe
2.Valve only compatible with hydraulic oil
3 Pilot seat disk in PUR; valve only compatible with air/neutral gases

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	10	40	-10
To	1/4"	8	10	40	75



Drawing 8114

NOTES

HIGH CORROSION RESISTANT VALVES (303 STAINLESS STEEL)

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	303 Stainless St./Pipe Mounting	Normally Closed	1/4"	1.5 to 5	10	100	180	166 and 168
		Normally Open	1/4"	2.5	3	12	120	170

HIGH CORROSION RESISTANT VALVES (316 STAINLESS STEEL)



2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	316L Stainless St./Pipe Mounting	Normally Closed	1/8"	1.5 to 2.5	2.3	20	140	172
			1/4"	1.5 to 3	6	20	140	172
			1/2"	3	10	4	140	172
			3/8"	5 to 6.2	10	4	140	172
			1/4"	1	0.6	98	75	176
Direct Operated	316L Stainless St./Pipe Mounting	Normally Open	1/4"	3.0 to 5	8	6	140	174
			1/2"	5.0 to 6.2	10	3	140	174
Magnalift	316L Stainless St./Pipe Mounting	Normally Closed	3/8"	15	65	20	140	178
			1/2"	15	80	20	140	178
			3/4"	15	80	20	140	180
			1"	25	160	16	120	180

2/2 HIGH CORROSION RESISTANT VALVES (303 STAINLESS ST.) DIRECT OPERATED

Process

303 STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max									
BSP	mm	Kv l/min	KV m^3/h	Qn m^3/h	bar	AC bar	DC bar	°C	°C						AC W	DC W		
	1.5	1.5	0.09	80	0	20	20	-10	100	FKM	121V5406	2995	481865		9	10	2.0	8116
	1.5	1.5	0.09	80	0	20	20	-10	120	FKM	121V5406	4270	481000		8	8	2.0	8116
	1.5	1.5	0.09	80	0	60	25	0	100	Ruby	121V5463 [1]	2995	481865		9	10	2.0	8116
	1.5	1.5	0.09	80	0	75	30	0	130	Ruby	121V5463 [1]	4270	481000		8	8	2.0	8116
	1.5	1.5	0.09	80	0	100	55	0	140	Ruby	121V5463 [1]	4270	486265		14	14	2.0	8116
	1.5	1.5	0.09	80	0	-	8	-20	75	PUR	121V5497 [2]	2995	482740		-	1.6	6.0/8.0	8116
	1.5	1.5	0.09	80	0	10	10	-20	75	PUR	121V5497 [2]	-	495900		2.5	2	6.0/8.0	8024
	1.5	1.5	0.09	80	0	-	10	-20	75	PUR	121V5497 [2]	-	495910	*	-	0.3-1.2	6.0/8.0	8024
	1.5	1.5	0.09	80	0	-	8	-20	65	PUR	121V5497 [2]	2995	496125		-	1.6	6.0/8.0	8116
	2.5	3.5	0.21	220	0	14	7	-10	100	FKM	121V5706	2995	481865		9	10	2.0	8116
1/4"	2.5	3.5	0.21	220	0	14	9	-10	120	FKM	121V5706	4270	481000		8	8	2.0	8116
	2.5	3.5	0.21	220	0	14	14	-10	120	FKM	121V5706	4270	486265		14	14	2.0	8116
	2.5	3.5	0.21	220	0	28	10	0	100	Ruby	121V5763 [1]	2995	481865		9	10	2.0	8116
	2.5	3.5	0.21	220	0	34	12	0	130	Ruby	121V5763 [1]	4270	481000		8	8	2.0	8116
	2.5	3.5	0.21	220	0	50	22	0	140	Ruby	121V5763 [1]	4270	486265		14	14	2.0	8116
	3	4.5	0.27	315	0	10	7	-10	100	FKM	121V5306	2995	481865		9	10	2.0	8116
	3	4.5	0.27	315	0	10	8.5	-10	120	FKM	121V5306	4270	481000		8	8	2.0	8116
	3	4.5	0.27	315	0	10	10	-10	120	FKM	121V5306	4270	486265		14	14	2.0	8116
	3	4.5	0.27	315	0	20	7	0	100	Ruby	121V5363 [1]	2995	481865		9	10	2.0	8116
	3	4.5	0.27	315	0	25	8.5	0	130	Ruby	121V5363 [1]	4270	481000		8	8	2.0	8116
	3	4.5	0.27	315	0	36	15	0	140	Ruby	121V5363 [1]	4270	486265		14	14	2.0	8116

Notes:
1.Valve only compatible with hydraulic oil and neutral liquids
2.If media is water, the fluid temperature shall not exceed 40°C.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.5	7	-20
To	1/4"	3	4.5	100	140



Drawing 8116



Drawing 8024

2/2 HIGH CORROSION RESISTANT VALVES (303 STAINLESS ST.) DIRECT OPERATED

303 STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max									
BSP	mm	Kv l/min	KV m³/h	Qn m³/h	bar	AC bar	DC bar	°C	°C						AC W	DC W		
1/4"	3	3.5	0.21	220	0	-	2	-20	75	PUR	121V5397	2995	482740		-	1.6	6.0/8.0	8116
	3	3.5	0.21	220	0	4.5	4	-20	75	PUR	121V5397	-	495900		2.5	2	6.0/8.0	8024
	3	3.5	0.21	220	0	-	4.5	-20	75	PUR	121V5397	-	495910	*	-	0.3-1.2	6.0/8.0	8024
	3	3.5	0.21	220	0	-	2	-20	65	PUR	121V5397	2995	496125		-	1.6	6.0/8.0	8116
	4	7	0.42	450	0	10	4	-10	100	FKM	121V5206	2995	481865		9	10	2.0	8116
	4	7	0.42	450	0	10	5	-10	120	FKM	121V5206	4270	481000		8	8	2.0	8116
	4	7	0.42	450	0	10	10	-10	120	FKM	121V5206	4270	486265		14	14	2.0	8116
	4	7	0.42	450	0	3.5	3.5	0	100	PTFE	121V5212 [1]	2995	481865		9	10	2.0	8116
	4	7	0.42	450	0	3.5	3.5	0	130	PTFE	121V5212 [1]	4270	481000		8	8	2.0	8116
	4	7	0.42	450	0	3.5	3.5	0	130	PTFE	121V5212 [1]	4270	486265		14	14	2.0	8116
	4	7	0.42	450	0	12	4	0	100	Ruby	121V5263 [1]	2995	481865		9	10	2.0	8116
	4	7	0.42	450	0	15	5	0	130	Ruby	121V5263 [1]	4270	481000		8	8	2.0	8116
	4	7	0.42	450	0	22	10	0	180	Ruby	121V5263 [1]	4270	486265		14	14	2.0	8116
	5	10	0.6	750	0	7	2	-10	100	FKM	121V5106	2995	481865		9	10	2.0	8116
	5	10	0.6	750	0	7	2.8	-10	120	FKM	121V5106	4270	481000		8	8	2.0	8116
	5	10	0.6	750	0	7	5	-10	120	FKM	121V5106	4270	486265		14	14	2.0	8116
	5	10	0.6	-	0	2.8	2	0	100	PTFE	121V5112 [1]	2995	481865		9	10	2.0	8116
	5	10	0.6	-	0	2.8	2.8	0	130	PTFE	121V5112 [1]	4270	481000		8	8	2.0	8116
	5	10	0.6	-	0	2.8	2.8	0	130	PTFE	121V5112 [1]	4270	486265		14	14	2.0	8116
	5	10	0.6	750	0	8.5	2	0	100	Ruby	121V5163 [1]	2995	481865		9	10	2.0	8116
	5	10	0.6	750	0	10	3.5	0	130	Ruby	121V5163 [1]	4270	481000		8	8	2.0	8116
	5	10	0.6	750	0	14	6.5	0	140	Ruby	121V5163 [1]	4270	486265		14	14	2.0	8116
1/4" NPT	3	4.5	0.27	315	0	10	7	-10	100	FKM	U121V5306	2995	481865		9	10	2.0	8116
	3	4.5	0.27	315	0	20	7	0	100	Ruby	U121V5363	2995	481865		9	10	2.0	8116

Notes:
1.Valve only compatible with hydraulic oil and neutral liquids

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	3	3.5	2	-20
To	1/4"	5	10	22	180



Drawing 8024



Drawing 8116

2/2 HIGH CORROSION RESISTANT VALVES (303 STAINLESS ST.)

DIRECT OPERATED

303 STAINLESS ST.

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	2.5	3	0.18	180	0	12	12	-30	100	FKM	122V8306	2995	481865	9	10	2.0	8116
	2.5	3	0.18	180	0	12	12	-30	120	FKM	122V8306	4270	481000	8	8	2.1	8116

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	2.5	3	12	-30
To	1/4"	2.5	3	12	120



Drawing 8116

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 HIGH CORROSION RESISTANT VALVES 201LG SERIES DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8"	1.5	1	0.06	-	0	20	15	-10	140	FKM	201LG1GVG2	-	481180	4	5	1.1/1.3	074
	2.5	2.3	0.14	-	0	10	6	-10	140	FKM	201LG1LVG2	-	481180	4	5	1.1/1.3	074
1/4"	1.5	1	0.06	-	0	20	15	-10	140	FKM	201LG2GVG2	-	481180	4	5	1.1/1.3	075
	2.5	2.3	0.14	-	0	10	6	-10	140	FKM	201LG2LVG2	-	481180	4	5	1.1/1.3	075
	3	4.5	0.27	-	0	8	5	-10	140	FKM	201LG2NVG7	-	481865	9	10	2.0	076
3/8"	5	8	0.48	-	0	3	2	-10	140	FKM	201LG3SVG7	-	481865	9	10	2.0	077
	6.2	10	0.6	-	0	1.5	0.5	-10	140	FKM	201LG3UVG7	-	481865	9	10	2.0	077
1/2"	5	8	0.48	-	0	3	2	-10	140	FKM	201LG4SVG7	-	481865	9	10	2.0	078
	6.2	10	0.6	-	0	1.5	0.5	-10	140	FKM	201LG4UVG7	-	481865	9	10	2.0	078

Notes:
Available version A, shiding ring in silver material included

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	1	5	-10
To	1/2"	6.2	10	20	140



Drawing 074



Drawing 075



Drawing 076

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 HIGH CORROSION RESISTANT VALVES 202LG SERIES DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors		Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
				Min	Max(MOPD)		Min	Max							
BSP	mm	Kv l/min	KV m³/h	bar	AC bar	DC bar	°C	°C				AC W	DC W		
1/4"	3.0	4.5	0.27	0	6	6	-10	140	FKM	202LG2NVG7	481865	9	10	24/2.0	3
	5.0	8.0	0.48	0	3	3	-10	140	FKM	202LG2SVG7	481865	9	10	24/2.0	3
1/2"	5.0	8.0	0.48	0	3	3	-10	140	FKM	202LG4SVG7	481865	9	10	24/2.0	3
	6.2	10.0	0.60	0	1	1	-10	140	FKM	202LG4UVG7	481865	9	10	24/2.0	3

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	3	4.5	1	-10
To	1/2"	6.2	10	6	140



Drawing 3



Drawing 3

2/2 HIGH CORROSION RESISTANT VALVES V SERIES DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
					Min			Min	Max										
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4" NPT	0.8	-	-	20	0	-	200	-25	65	PUR	U121VS3750A [1]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2	8165
	0.8	-	-	20	0	-	200	-25	75	PUR	U121VS3750A [1]	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1 to 1.8	9.0/10.1/10.2	6713
	0.8	-	-	20	0	200	200	-25	75	PUR	U121VS3750A [1]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1/10.2	6713
	0.8	-	-	20	0	200	200	-25	65	PUR	U121VS3750A [1]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	0.8	-	-	20	0	200	200	-25	65	PUR	U121VS3750A [1]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	-	98	-40	75	PUR	U121V5595 [23]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	-	98	-40	75	PUR	U121V5595 [23]	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1 to 1.8	9.0/10.1/10.2	6713
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V5595 [23]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	98	98	-40	75	PUR	U121V5595 [23]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1/10.2	6713
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V5595 [23]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	98	98	-40	50	PUR	U121V5595 [23]	-	496895	-	-	8	8	9.0/10.1/10.2	8165
	1	0.6	0.04	40	0	-	98	-40	65	PUR	U121V7595 [3]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2/10.3	8165
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V7595 [3]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2/10.3	8165
	1	0.6	0.04	40	0	98	98	-40	65	PUR	U121V7595 [3]	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.2/10.3	8299
	1	0.6	0.04	40	0	98	98	-40	50	PUR	U121V7595 [3]	-	496895	-	-	8	8	9.0/10.1/10.2/10.3	8165

Notes:
1. Valve only compatible with neutral gases
2. Valve delivered with an individual material traceability certificate (2.2 following EN10204)
3. Valve compatible with water only up to 40°C

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	0.8	0.6	98	-40
To	1/4"	1	0.6	200	75



Drawing 8165



Drawing 8299



Drawing 6713

2/2 HIGH CORROSION RESISTANT VALVES 221G SERIES MAGNALIFT

316L STAINLESS ST. - SILVER SHADIN RING

PIPE MOUNTING

NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			IS	ATEX Zone	Protection Mode	Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.								AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C		Valve Ref.	Housing Ref.	Coil Ref.				W	W		
3/8"	15	65	3.90	0	16	-	-10	100	FKM	221G6306	2995	481865	-	-	-	9	-	2.0	3732
	15	65	3.90	0	20	5	-10	100	FKM	221G6306	2995	492425	-	-	-	14	14	2.0	3732
	15	65	3.90	0	16	-	-10	65	FKM	221G6306	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	3732
	15	65	3.90	0	16	-	-10	120	FKM	221G6306	4270	481000	-	-	-	8	-	2.0	3732
	15	65	3.90	0	20	7	-10	140	FKM	221G6306	4270	486265	-	-	-	14	14	2.0	3732
	15	65	3.90	0	16	-	-10	80	FKM	221G6306	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	3732
	15	65	3.90	0	-	10	-10	100	FKM	221G6336[1]	2995	481865	-	-	-	-	10	2.0	3732
	15	65	3.90	0	-	10	-10	65	FKM	221G6336[1]	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	-	9	2.1	3732
	15	65	3.90	0	10	10	-10	65	FKM	221G6336[1]	-	492070	-	1-21	Ex mb IIC T4/T5	9	8	2.1	3732
	15	65	3.90	0	10	10	-10	75	FKM	221G6336[1]	-	492190	-	1-21	Ex eb mb IIC T3/T4	11	9	2.1	3732
	15	65	3.90	0	-	10	-10	80	FKM	221G6336[1]	-	495905	-	1-21	Ex db mb IIC T4	-	8	2.1	3732
	15	65	3.90	0	10	-	-10	100	EPDM	221G6307	2995	481865	-	-	-	9	-	2.0	3732
	15	65	3.90	0	10	-	-10	65	EPDM	221G6307	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	3732
	15	65	3.90	0	10	-	-10	120	EPDM	221G6307	4270	481000	-	-	-	8	-	2.0	3732
	15	65	3.90	0	10	7	-10	140	EPDM	221G6307[2]	4270	486265	-	-	-	14	14	2.0	3732
	15	65	3.90	0	10	-	-10	80	EPDM	221G6307	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	3732
1/2"	15	80	4.80	0	16	-	-10	100	FKM	221G6506	2995	481865	-	-	-	9	-	2.0	3732
	15	80	4.80	0	20	5	-10	100	FKM	221G6506	2995	492425	-	-	-	14	14	2.0	3732
	15	80	4.80	0	16	-	-10	65	FKM	221G6506	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	3732
	15	80	4.80	0	16	-	-10	120	FKM	221G6506	4270	481000	-	-	-	8	-	2.0	3732
	15	80	4.80	0	20	7	-10	140	FKM	221G6506	4270	486265	-	-	-	14	14	2.0	3732
	15	80	4.80	0	16	-	-10	80	FKM	221G6506	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	3732
	15	80	4.80	0	-	10	-10	100	FKM	221G6536[1]	2995	481865	-	-	-	-	10	2.0	3732
	15	80	4.80	0	-	10	-10	65	FKM	221G6536[1]	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	-	9	2.1	3732
	15	80	4.80	0	10	10	-10	65	FKM	221G6536[1]	-	492070	-	1-21	Ex mb IIC T4/T5	9	8	2.1	3732
	15	80	4.80	0	10	10	-10	75	FKM	221G6536[1]	-	492190	-	1-21	Ex eb mb IIC T3/T4	11	9	2.1	3732
	15	80	4.80	0	-	10	-10	80	FKM	221G6536[1]	-	495905	-	1-21	Ex db mb IIC T4	-	8	2.1	3732
	15	80	4.80	0	10	-	-10	100	EPDM	221G6507	2995	481865	-	-	-	9	-	2.0	3732
	15	80	4.80	0	10	-	-10	65	EPDM	221G6507	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	3732
	15	80	4.80	0	10	-	-10	120	EPDM	221G6507	4270	481000	-	-	-	8	-	2.0	3732
	15	80	4.80	0	10	7	-10	140	EPDM	221G6507[2]	4270	486265	-	-	-	14	14	2.0	3732
	15	80	4.80	0	10	-	-10	80	EPDM	221G6507	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	3732

Notes:
1. Without shading ring
2. Maximum pressure for steam: 4 bar (140°C)

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	15	65	6	-10
To	1/2"	15	80	20	140



Drawing 3732

2/2 HIGH CORROSION RESISTANT VALVES 221G SERIES MAGNALIFT

316L STAINLESS ST. - SILVER SHADIN RING

PIPE MOUNTING



NORMALLY CLOSED

Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			IS	ATEX Zone	Protection Mode	Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.								AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C		Valve Ref.	Housing Ref.	Coil Ref.				W	W		
3/4"	15	80	4.80	0	16	-	-10	100	FKM	221G6606	2995	481865	-	-	-	9	-	2.0	8451
	15	80	4.80	0	20	5	-10	60	FKM	221G6606	2995	492425	-	-	-	14	14	2.0	8451
	15	80	4.80	0	16	-	-10	65	FKM	221G6606	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	8451
	15	80	4.80	0	16	-	-10	120	FKM	221G6606	4270	481000	-	-	-	8	-	2.0	8451
	15	80	4.80	0	20	7	-10	140	FKM	221G6606	4270	486265	-	-	-	14	14	2.0	8451
	15	80	4.80	0	16	-	-10	80	FKM	221G6606	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	8451
	15	80	4.80	0	-	10	-10	100	FKM	221G6636[1]	2995	481865	-	-	-	-	10	2.0	8451
	15	80	4.80	0	-	10	-10	65	FKM	221G6636[1]	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	-	9	2.1	8451
	15	80	4.80	0	10	10	-10	65	FKM	221G6636[1]	-	492070	-	1-21	Ex mb IIC T4/T5	9	8	2.1	8451
	15	80	4.80	0	10	10	-10	75	FKM	221G6636[1]	-	492190	-	1-21	Ex eb mb IIC T3/T4	11	9	2.1	8451
	15	80	4.80	0	-	10	-10	80	FKM	221G6636[1]	-	495905	-	1-21	Ex db mb IIC T4	-	8	2.1	8451
	15	80	4.80	0	10	-	-10	100	EPDM	221G6607	2995	481865	-	-	-	9	-	2.0	8451
	15	80	4.80	0	10	-	-10	65	EPDM	221G6607	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	8451
	15	80	4.80	0	10	-	-10	120	EPDM	221G6607	4270	481000	-	-	-	8	-	2.0	8451
	15	80	4.80	0	10	7	-10	140	EPDM	221G6607[2]	4270	486265	-	-	-	14	14	2.0	8451
	15	80	4.80	0	10	-	-10	80	EPDM	221G6607	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	8451
1"	25	160	9.60	0	16	-	-10	100	FKM	221G6106	2995	481865	-	-	-	9	-	2.0	3448
	25	160	9.60	0	20	5	-10	60	FKM	221G6106	2995	492425	-	-	-	14	14	2.0	3448
	25	160	9.60	0	16	-	-10	65	FKM	221G6106	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	3448
	25	160	9.60	0	16	6	-10	120	FKM	221G6106	4270	486265	-	-	-	14	14	2.0	3448
	25	160	9.60	0	16	-	-10	80	FKM	221G6106	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	3448
	25	160	9.60	0	-	10	-10	100	FKM	221G6136[1]	2995	481865	-	-	-	-	10	2.0	3448
	25	160	9.60	0	-	10	-10	65	FKM	221G6136[1]	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	-	9	2.0	3448
	25	160	9.60	0	-	10	-10	100	FKM	221G6136[1]	4270	481000	-	-	-	-	8	2.0	3448
	25	160	9.60	0	-	10	-10	80	FKM	221G6136[1]	-	495905	-	1-21	Ex db mb IIC T4	-	8	2.0	3448
	25	160	9.60	0	10	-	-10	100	EPDM	221G6107	2995	481865	-			9	---	2.0	8448
	25	160	9.60	0	10	-	-10	65	EPDM	221G6107	2995	495870	-	2-22	Ex nAc nCc IIC T3/T4	8	-	2.0	8448
	25	160	9.60	0	10	-	-10	120	EPDM	221G6107	4270	481000	-			8	---	2.0	8448
	25	160	9.60	0	10	10	-10	140	EPDM	221G6107[2]	4270	486265	-			14	14	2.0	8448
	25	160	9.60	0	10	-	-10	80	EPDM	221G6107	-	495905	-	1-21	Ex db mb IIC T4	8	-	2.0	8448

Notes:
1. Without shading ring
2. Maximum pressure for steam: 4 bar (140°C)

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/4"	15	80	5	-10
To	1"	25	160	20	140



Drawing 8451



Drawing 8448

NOTES

HIGH CORROSION RESISTANT VALVES (303-316L STAINLESS ST.)

Oil Water Air

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valve
Direct Operated	303 Stainless St./Pipe Mounting	Normally Closed	1/4"	1 to 2.5	3	15	180	184
		Universal	1/4"	1.5 to 2.5	3.5	10	180	186
Direct Operated	316 Stainless St./Pipe Mounting	Normally Closed	1/8"	1.5 to 2.5	1 to 2.3	3	140	188
			1/4"	1.5 to 3	1 to 4.5	12	140	188

3/2 HIGH CORROSION RESISTANT VALVES (303 STAINLESS ST.) DIRECT OPERATED

303 STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max						AC	DC		
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C						W	W		
1/4"	1	1	0.6	0.6	0.04	0.04	0	-	10	-10	55	FKM	131V5490	2995	48358001	*	-	0.5-3	7.0/8.0	6740
	1	1	0.6	0.6	0.04	0.04	0	-	10	-10	75	FKM	131V5490	-	495910	*	-	0.3-1.2	7.0/8.0	6740
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	120	FKM	131V5406	4270	481000		8	8	2.1	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	131V5406	2995	481865		9	10	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	0	130	Ruby	131V5463$_1$	4270	481000		8	8	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	0	100	Ruby	131V5463$_1$	2995	481865		9	10	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	0	180	Ruby	131V5463$_1$	4270	486265		14	14	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	75	PUR	131V5497	2995	482740		-	1.6	6.0/8.0	8024
	1.5	1.5	1.5	1.5	0.09	0.09	0	7	7	-20	75	PUR	131V5497	-	495900		2.5	2	6.0/8.0	8024
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	75	PUR	131V5497	-	495910	*	-	0.3-1.2	6.0/8.0	8024
	1.5	1.5	1.5	1.5	0.09	0.09	0	-	7	-20	65	PUR	131V5497	2995	496125		-	1.6	6.0/8.0	8024
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	120	FKM	131V5306	4270	481000		8	8	2.1	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	131V5306	2995	481865		9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	130	Ruby	131V5363$_1$	4270	481000		8	8	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	100	Ruby	131V5363$_1$	2995	481865		9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	180	Ruby	131V5363$_1$	4270	486265		14	14	2.0	8116
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	75	PUR	131V5397	2995	482740		-	1.6	6.0/8.0	8024
	2.5	2.5	3	3	0.18	0.18	0	2	2	-20	75	PUR	131V5397	-	495900		2.5	2	6.0/8.0	8024
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	75	PUR	131V5397	-	495910	*	-	0.3-1.2	6.0/8.0	8024
	2.5	2.5	3	3	0.18	0.18	0	-	2	-20	65	PUR	131V5397	2995	496125		-	1.6	6.0/8.0	8024
1/4" NPT	1	1	0.6	0.6	0.04	0.04	0	-	10	-10	55	FKM	U131V5490	2995	483580.01	*	-	0.5-3	7.0/8.0	6740
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	-10	100	FKM	U131V5406	2995	481865		9	10	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	15	15	0	100	Ruby	U131V5463$_1$	2995	481865		9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-10	100	FKM	U131V5306	2995	481865		9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	7	7	-30	100	Ruby	U131V5363$_1$	2995	481865		9	10	2.0	8116

Notes:
1.Valve only compatible with hydraulic oil and neutral liquids

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1	0.6	2	-30
To	1/4"	2.5	3.5	15	180



Drawing 6740



Drawing 8116



Drawing 8024

3/2 HIGH CORROSION RESISTANT VALVES (303 STAINLESS ST.) DIRECT OPERATED

303 STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max								
BSP	mm		Kv l/min		KV m^3/h		bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	120	FKM	133V5406	4270	481000	8	8	2.1	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	133V5406	2995	481865	9	10	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	0	130	Ruby	133V5463[1]	4270	481000	8	8	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	0	100	Ruby	133V5463[1]	2995	481865	9	10	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	0	180	Ruby	133V5463[1]	4270	486265	14	14	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	120	FKM	133V5306	4270	481000	8	8	2.1	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	100	FKM	133V5306	2995	481865	9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	0	130	Ruby	133V5363[1]	4270	481000	8	8	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	0	100	Ruby	133V5363[1]	2995	481865	9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	0	180	Ruby	133V5363[1]	4270	486265	14	14	2.0	8116
1/4" NPT	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	-10	100	FKM	U133V5406	2995	481865	9	10	2.0	8116
	1.5	1.5	1.5	1.5	0.09	0.09	0	10	10	0	100	Ruby	U133V5463[1]	2995	481865	9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	-10	100	FKM	U133V5306	2995	481865	9	10	2.0	8116
	2.5	2.5	3.5	3.5	0.21	0.21	0	4	4	0	100	Ruby	U133V5363[1]	2995	481865	9	10	2.0	8116

Notes:
1.Valve only compatible with hydraulic oil and neutral liquids

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.5	4	-10
To	1/4"	2.5	3.5	10	180



Drawing 8116

3/2 HIGH CORROSION RESISTANT VALVES (316L STAINLESS ST.)

DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port Size	Orifice	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves		Power		Coil Group	Fluid Compatibility	
BSP	mm	kv l/min	Kv m³/h	Min. Bar	Max. (MOPD) AC bar	Max. (MOPD) DC bar	Min. °C	Max. °C		Valve Ref.	Coil Ref.	AC W	DC W		Class Columm	
1/8"	1.5	1	0.06	0	8	8	-10	140	FKM	301LG1GVG2	481180	4	5	1.1/1.3	A	4
	2.5	2.3	0.14	0	3	3	-10	140	FKM	301LG1LVG2	481180	4	5	1.1/1.3	A	4
1/4"	1.5	1	0.06	0	8	8	-10	140	FKM	301LG2GVG2	481180	4	5	1.1/1.3	A	4
	2.5	2.3	0.14	0	3	3	-10	140	FKM	301LG2LVG2	481180	4	5	1.1/1.3	A	4
	1.5	1	0.06	0	12	12	-10	140	FKM	301LG2GVG7	481865	9	10	24/2.0	A	5
	3.0	4.5	0.27	0	4	4	-10	140	FKM	301LG2NVG7	481865	9	10	24/2.0	A	5

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	1	3	-10
To	1/4"	3	4.5	12	140



Drawing 4

All dimensions are in mm



All dimensions are in mm

Drawing 5

NOTES

OIL BURNER VALVES

Oil Burner

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/8"	3	4	30	160	192
			1/4"	3	4	30	160	192
			3/8"	6 to 11	22	30	160	192
			1/2"	14	25	30	160	192
	Brass/Pipe Mounting	Normally Open	1/8"	2.5	3.5	30	160	194
			1/4"	2.5	3.5	30	160	194
	Brass/Sub-base Mounting	Normally Closed	SB	2.5	3.5	30	160	194
Magnalift	Brass/Pipe Mounting	Normally Closed	1/2"	15	50	5	140	196
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/4"	8	36	40	140	198
			3/8"	11	50	40	160	198
			1/2"	15	60	40	160	200
Pilot Operated	Brass/Sub-base Mounting	Normally Closed	14 mm	14	45	30	160	200
Pilot Operated	Brass/Pipe Mounting	Normally Closed	1/8"	1.7	1.4	16	90	202

2/2 OIL BURNER VALVES

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8"	2.2	2.8	0.17	-	0	25	-	-10	120	Ruby	121Z2323 [1]	299522	481865	9	-	2.0	7863
	3	4	0.24	-	0	30	-	-30	160	Ruby	121K2423 [1]	852023	483824	19	-	14.1	3292
1/4"	3	4.5	0.27	-	0	30	-	-30	160	Ruby	121K6423 [1]	852023	483824	19	-	14.1	3292
	4	6.5	0.39	-	0	30	-	0	160	Ruby	121K6220 [1]	852023	483541	20	-	14.3	3510
3/8"	6	12	0.72	-	0	5	-	0	120	FKM	121K3321 [1]	299525	492425	14	-	14.1	3551
	11	22	1.32	-	0	30	-	0	160	FKM	121G2320 [12]	852023	483541	20	-	14.3	3646
1/2"	14	25	1.5	-	0	30	-	0	160	FKM	121G2520 [12]	852023	483541	20	-	14.3	3646
	14	25	1.5	-	0	30	-	0	160	FKM	121G2523 [12]	852023	483824	19	-	14.1	3646

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners
2.Max. Static pressure = 30 bar; max pressure differential = 0.2 bar



Drawing 7863

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	2.2	4	5	-30
To	1/2"	14	25	30	160



Drawing 3292



Drawing 3646



Drawing 3551



WEIGHT : 215 gr





Drawing 3510

2/2 OIL BURNER VALVES

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8"	2.5	3.5	0.21	-	0	30	-	-30	160	Ruby	122K9321 [1]	852023	483824	19	-	14.1	6766
1/4"	2.5	3.5	0.21	-	0	30	-	-30	160	Ruby	122K8321 [1]	852023	483824	19	-	14.1	6766

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners

BRASS

SUB-BASE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	25	1.5	-	0	30	-	0	160	FKM	121F2523 [1]	852023	483824	19	-	14.1	7638

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	2.5	3.5	30	-30
To	SB	14	25	30	160



Drawing 6766



Drawing 7638

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 OIL BURNER VALVES

MAGNALIFT

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/2"	15	50	3	-	0	5	-	0	140	FKM	221G2523 [1]	852023	483824	19	-	14.1	8298

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	15	50	5	0
To	1/2"	15	50	5	140



Drawing 8298

2/2 OIL BURNER VALVES

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	8	36	2.16	-	0.3	40	25	-10	100	FKM	E321H21 $_{23}$	2995	481865	9	10	2.0	3523
	8	36	2.16	-	0.3	40	30	-10	120	FKM	E321H21 $_{23}$	4270	481000	8	8	2.0	3523
	8	36	2.16	-	0.3	40	40	-10	140	FKM	E321H21 $_{23}$	4270	486265	14	14	2.0	3523
3/8"	11	40	2.4	-	0.3	30	-	0	160	fkm	321H2322 $_{123}$	852023	483541	20	-	14.1	3633
	11	50	3	-	0.3	40	25	-10	100	FKM	E321H23 $_{23}$	2995	481865	9	10	2.0	3521
	11	50	3	-	0.3	40	30	-10	120	FKM	E321H23 $_{23}$	4270	481000	8	8	2.0	3521
	11	50	3	-	0.3	40	40	-10	140	FKM	E321H23 $_{23}$	4270	486265	14	14	2.0	3521

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners
2.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
3.Pilot seat disc in synthetic Ruby

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	36	25	-10
To	3/8"	11	50	40	160



Drawing 3523



Drawing 3633



Drawing 3521

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 OIL BURNER VALVES

PILOT OPERATED

BRASS
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/2"	15	60	3.6	-	0.3	30	-	0	160	FKM	**321H2522** 13	**852023**	**483541**	20	-	14.1	3633
	15	60	3.6	-	0.3	30	-	0	160	FKM	**321H2523** 13	**852023**	**483824**	19	-	14.1	3633
	15	60	3.6	-	0.3	40	25	-10	100	FKM	**E321H25** 23	**2995**	**481865**	9	10	2.0/14.2	3522
	15	60	3.6	-	0.3	40	30	-10	65	FKM	**E321H25** 23	**-**	**483371**	8	8	2.0/14.2	3522
	15	60	3.6	-	0.3	40	40	-10	140	FKM	**E321H25** 23	**4270**	**486265**	14	14	2.0/14.2	3522

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners
2.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing
3.Pilot seat disc in synthetic Ruby

BRASS
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	14	45	2.7	-	0	30	-	0	160	FKM	321F2523 12	852023	483824	19	-	14.1	7639

Notes:
1.DIN-EN-ISO 23553-1:2014-09 approved for oil burners
2.Minimum pressure differential = 0.3 bar for opening and 0 bar for closing

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	14	45	25	-10
To	SB	15	60	40	160



Drawing 3633



Drawing 3522



Drawing 7639

2/2 OIL BURNER VALVES

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max		Valve Order Number	Valve Type	Coil Type				
BSP	mm	Kv l/min	KV m³/h	Qn m³/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
	1.7	1.4	0.086	-	0	16	-	-10	90	NBR	390300	131IN	XT09 230/50	9	-	22.0	015
1/8''	1.7	1.4	0.086	-	0	12	-	-10	90	FKM	390086	131IV	KT09 208-230/60	9	-	22.0	015
	1.7	1.4	0.086	-	0	16	-	-10	90	FKM	390088	131IV	KT09 230/50	9	-	22.0	015

Notes:

Valves above are certificate ISO 23553-1
Max admitted overpressure = 25bar

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)	Amb Temp (°C)
From	1/8''	1.7	1.4	12	-10	-10
To	1/8''	1.7	1.4	16	90	60



Drawing 015

NOTES



GAS BURNER VALVES

Gas Burner

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe Mounting	Normally Closed	1/8"	4	5.3	2	90	206
			1/4"	4	5.3	2	90	206

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 GAS BURNER VALVES

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max		Valve Order Number	Valve Type	Coil Type				
RP	mm	Kv l/min	KV m³/h	Qn m³/h	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8''	4	5.3	0.318	-	0	2	-	-10	90	FKM	390878 [1]	131.4CG	KT09 230/50	9	-	22.0	013
	4	5.3	0.318	-	0	2	-	-10	90	FKM	390875 [1]	131.4CG	KT09 240/50	9	-	22.0	013
1/4''	4	5.3	0.318	-	0	2	-	-10	90	FKM	390945 [1]	131.4GG	KT09 230/50	9	-	22.0	013
	4	5.3	0.318	-	0	2	-	-10	90	FKM	390975 [1]	131.4GG	KT09 240/50	9	-	22.0	013

Notes:

1. Ordering number is for an assembled valve and coil, with the voltage shown.
- Valves are EN161 (BSI) certified

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)	Amb Temp (°C)
From	1/8''	4	5.3	0	-10	-10
To	1/4''	4	5.3	2	90	60



Drawing 013

NOTES

FAST SWITCHING VALVES

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Magnalift	Brass/Pipe Mounting	Normally Closed	3/8"	8	0	7	40	210

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 FAST SWITCHING VALVES

MAGNALIFT

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max								
BSP	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
3/8"	8			-	0	-	7	0	40	PUR	221J3301E [1]	29956	483816	-	14		8020

Notes:
1.For more details, please consult catalogue 8674UK



For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8"	8	-	7	0
To	3/8"	8	-	7	40



Drawing 8020

NOTES

VALVES FOR BEVERAGE DISPENSING
HEALTHY SOLENOID

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	LLB Brass/Pipe Mounting	Normally Closed	1/8"	1.0 to 2.5	0.5 to 2.3	20	140	214

Food Compliance: NSF 169 certified, 1935/2004/CE

2/2 VALVES FOR BEVERAGE DISPENSING - HEALTHY SOLENOID VALVES
DIRECT OPERATED

CW510L BRASS BODY
PIPE MOUNTING
NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C					W	W		
G1/8"	1.0	0.5	0.03	0	20	20	-10	140	FKM FDA	121WH1010	8993	481180	4	5	1.1, 1.3	12
	1.2	0.7	0.04	0	20	12	-10	140	FKM FDA	121WH1012	8993	481180	4	5	1.1, 1.3	
	1.5	1	0.06	0	20	10	-10	140	FKM FDA	121WH1015	8993	481180	4	5	1.1, 1.3	
	1.8	0.9	0.05	0	19	7.5	-10	140	FKM FDA	121WH1018	8993	481180	4	5	1.1, 1.3	
	2.0	1.8	0.11	0	15	7	-10	140	FKM FDA	121WH1020	8993	481180	4	5	1.1, 1.3	
	2.5	2.3	0.14	0	10	4	-10	140	FKM FDA	121WH1025	8993	481180	4	5	1.1, 1.3	



Drawing 12

NOTES

VALVES FOR BEVERAGE DISPENSING HEALTHY SOLENOID

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	LLB Brass/Pipe Mounting	Normally Closed	1/8"	1.0 to 2.5	0.5 to 2.3	15	140	218

Food Compliance: NSF 169 certified, 1935/2004/CE

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 VALVES FOR BEVERAGE DISPENSING - HEALTHY SOLENOID VALVES
DIRECT OPERATED

CW510L BRASS BODY
PIPE MOUNTING
NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C					W	W		
G1/8''	1.0	0.5	0.03	0	15	15	-10	140	FKM FDA	131WH1410	8993	481180	4	5	1.1, 1.3*	13
	1.2	0.7	0.04	0	14	14	-10	140	FKM FDA	131WH1412	8993	481180	4	5	1.1, 1.3*	
	1.5	1.0	0.06	0	8	8	-10	140	FKM FDA	131WH1415	8993	481180	4	5	1.1, 1.3*	
	1.8	1.2	0.07	0	6	6	-10	140	FKM FDA	131WH1418	8993	481180	4	5	1.1, 1.3*	
	2.0	1.5	0.09	0	5	5	-10	140	FKM FDA	131WH1420	8993	481180	4	5	1.1, 1.3*	
	2.5	2.3	0.14	0	3	-	-10	140	FKM FDA	131WH1425	8993	481180	4	5	1.1, 1.3*	
G1/8''	1.0	0.5	0.03	0	15	15	-10	140	FKM FDA	131WH1510	8993	481180	4	5	1.1, 1.3*	14
	1.2	0.7	0.04	0	14	14	-10	140	FKM FDA	131WH1512	8993	481180	4	5	1.1, 1.3*	
	1.5	1.0	0.06	0	8	8	-10	140	FKM FDA	131WH1515	8993	481180	4	5	1.1, 1.3*	
	1.8	1.2	0.07	0	6	6	-10	140	FKM FDA	131WH1518	8993	481180	4	5	1.1, 1.3*	
	2.0	1.5	0.09	0	5	5	-10	140	FKM FDA	131WH1520	8993	481180	4	5	1.1, 1.3*	
	2.5	2.3	0.14	0	3	-	-10	140	FKM FDA	131WH1525	8993	481180	4	-	1.1, 1.3*	

* 1.3 Coil group solution applicable in AC voltages only



Drawing 13





Drawing 14

NOTES

VALVES FOR BEVERAGE DISPENSING AND LIQUIPURE®

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	LLB Brass/Pipe Mounting	Normally Closed	1/8"	1.0 to 3	0.5 a 4.5	20	140	222
			1/4"	1.5 to 5	1.5 a 9.5	20	140	224
	LLB Brass/Sub-base Mounting	Normally Closed	SB	1.5 to 3	1.4 a 3.4	20	140	224
	Stainless St./Sub-base Mounting	Normally Closed	SB	1.5 to 3	4.2	20	140	226

Food Compliance: NSF 169 certified, 1935/2004/CE

2/2 VALVES FOR BEVERAGE DISPENSING

DIRECT OPERATED

CW510L BRASS BODY

PIPE MOUNTING

NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.					AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C		Valve Ref.	Housing Ref.	Coil Ref.	W	W		
G1/8"	1.0	0.7	0.04	0	20	18	-10	140	FKM FDA	121ZH1010	2995	481865	9	10	2.0	1
	1.5	1.5	0.09	0	20	18	-10	140	FKM FDA	121ZH1015	2995	481865	9	10	2.0	
	2.0	2.6	0.16	0	20	15	-10	140	FKM FDA	121ZH1020	2995	481865	9	10	2.0	
	2.5	3.5	0.21	0	19	14.5	-10	140	FKM FDA	121ZH1025	2995	481865	9	10	2.0	
	3.0	4.5	0.27	0	13	8.5	-10	140	FKM FDA	121ZH1030	2995	481865	9	10	2.0	
	1.0	0.7	0.04	0	20	18	-10	140	Ruby	121ZH0010	2995	481865	9	10	2.0	
	1.5	1.5	0.09	0	20	18	-10	140	Ruby	121ZH0015	2995	481865	9	10	2.0	
	2.0	2.6	0.16	0	20	15	-10	140	Ruby	121ZH0020	2995	481865	9	10	2.0	
	2.5	3.5	0.21	0	19	14.5	-10	140	Ruby	121ZH0025	2995	481865	9	10	2.0	
	3.0	4.5	0.27	0	13	8.5	-10	140	Ruby	121ZH0030	2995	481865	9	10	2.0	
NPT 1/8"	1.0	0.7	0.04	0	20	18	- 10	140	FKM FDA	U121ZH1010	2995	481865	9	10	2.0	
	1.5	1.5	0.09	0	20	18	-10	140	FKM FDA	U121ZH1015	2995	481865	9	10	2.0	
	2.0	2.6	0.16	0	20	15	-10	140	FKM FDA	U121ZH1020	2995	481865	9	10	2.0	
	2.5	3.5	0.21	0	19	14.5	-10	140	FKM FDA	U121ZH1025	2995	481865	9	10	2.0	
	3.0	4.5	0.27	0	13	8.5	-10	140	FKM FDA	U121ZH1030	2995	481865	9	10	2.0	
	1.0	0.7	0.04	0	20	18	-10	140	Ruby	U121ZH0010	2995	481865	9	10	2.0	
	1.5	1.5	0.09	0	20	18	-10	140	Ruby	U121ZH0015	2995	481865	9	10	2.0	
	2.0	2.6	0.16	0	20	15	-10	140	Ruby	U121ZH0020	2995	481865	9	10	2.0	
	2.5	3.5	0.21	0	19	14.5	-10	140	Ruby	U121ZH0025	2995	481865	9	10	2.0	
	3.0	4.5	0.27	0	13	8.5	-10	140	Ruby	U121ZH0030	2995	481865	9	10	2.0	

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1	0.7	8.5	-10
To	1/8"	3	4.5	20	140



Drawing 1

2/2 VALVES FOR BEVERAGE DISPENSING

DIRECT OPERATED

CW510L BRASS BODY

PIPE MOUNTING / FLANGED (SB)



NORMALLY CLOSED

Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.					AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C		Valve Ref.	Housing Ref.	Coil Ref.	W	W		
G1/4"	1.5	1.5	0.09	0	20	18	-10	140	FKM FDA	121KH1015	2995	481865	9	10	2.0	1
	2.0	2.6	0.16	0	20	15	-10	140	FKM FDA	121KH1020	2995	481865	9	10	2.0	
	2.5	3.5	0.21	0	19	14.5	-10	140	FKM FDA	121KH1025	2995	481865	9	10	2.0	
	3.0	4.5	0.27	0	13	8.5	-10	140	FKM FDA	121KH1030	2995	481865	9	10	2.0	
	4.0	5.5	0.33	0	9	6	-10	140	FKM FDA	121KH1040	2995	481865	9	10	2.0	2
	5.0	9.5	0.57	0	2.5	2	-10	140	FKM FDA	121KH1050	2995	481865	9	10	2.0	
	1.5	1.5	0.09	0	20	18	-10	140	Ruby	121KH0015	2995	481865	9	10	2.0	1
	2.0	2.6	0.16	0	20	15	-10	140	Ruby	121KH0020	2995	481865	9	10	2.0	
	2.5	3.5	0.21	0	19	14.5	-10	140	Ruby	121KH0025	2995	481865	9	10	2.0	
	3.0	4.5	0.27	0	13	8.5	-10	140	Ruby	121KH0030	2995	481865	9	10	2.0	
SB	1.5	1.4	0.08	0	20	20	-10	140	FKM FDA	121FH1015	2995	481865	9	10	2.0	3
	2.0	2.3	0.14	0	20	20	-10	140	FKM FDA	121FH1020	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	20	14	-10	140	FKM FDA	121FH1025	2995	481865	9	10	2.0	
	3.0	3.4	0.2	0	17	10	-10	140	FKM FDA	121FH1030	2995	481865	9	10	2.0	
	1.5	1.4	0.08	0	20	20	-10	140	Ruby	121FH0015	2995	481865	9	10	2.0	
	2.0	2.3	0.14	0	20	20	-10	140	Ruby	121FH0020	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	20	14	-10	140	Ruby	121FH0025	2995	481865	9	10	2.0	
	3.0	3.4	0.2	0	17	10	-10	140	Ruby	121FH0030	2995	481865	9	10	2.0	

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.5	2	-10
To	1/4"	4	9.5	20	140
From	SB	1.5	1.4	10	-10
To	SB	3	3.4	20	140



Drawing 1



Drawing 2



Drawing 3

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 VALVES FOR BEVERAGE DISPENSING

DIRECT OPERATED

CW510L BRASS BODY

PIPE MOUNTING

NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.					AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C		Valve Ref.	Housing Ref.	Coil Ref.	W	W		
G1/8"	1.5	0.83	0.05	0	15	15	-10	140	FDA FKM	121KH1465	2995	481865	9	10	2.0	11

Valve with manual calibration of the flow rate

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	0.83	15	-10/+140



Drawing 11

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 VALVES FOR BEVERAGE DISPENSING - LIQUIPURE®

DIRECT OPERATED

STAINLESS ST.

FLANGED (SB)

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Dwg. No.	Compatible adapter kit
					Min	Max(MOPD)		Min	Max		Valve Ref.	Housing Ref.	Coil Ref.					
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W			
SB	1.5	1.3	0.08	-	0	20	20	-10	140	Ruby	2019F1GRG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	1.5	1.3	0.08	-	0	20	20	-10	140	FKM FDA	2019F1GVG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	2	2.3	0.14	-	0	15	15	-10	140	Ruby	2019F1JRG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	2	2.3	0.14	-	0	15	15	-10	140	FKM FDA	2019F1JVG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	2.5	3.2	0.19	-	0	10	10	-10	140	FKM FDA	2019F1LRG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	2.5	3.2	0.19	-	0	10	10	-10	140	FKM FDA	2019F1LVG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	3	4.2	0.25	-	0	7	7	-10	140	Ruby	2019F1NRG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	3	4.2	0.25	-	0	7	7	-10	140	FKM FDA	2019F1NVG7	-	481865	9	10	2.0	071	XGSPG1-XGSPG2
	4	6.5	0.39	-	0	5	5	-10	140	FKM FDA	2019F1QVG7	-	481865	9	10	2.0	071	XGSPG3
	4	6.5	0.39	-	0	5	5	-10	140	EPDM	2019F1QEG7	-	481865	9	10	2.0	071	XGSPG3
	5	7.2	0.43	-	0	3	3	-10	140	FKM FDA	2019F1SVG7	-	481865	9	10	2.0	071	XGSPG3
	5	7.2	0.43	-	0	3	3	-10	140	EPDM	2019F1SEG7	-	481865	9	10	2.0	071	XGSPG3

Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.3	3	-10
To	SB	5	7.2	20	140



Drawing 071

SUB-BASES FOR LIQUIPURE VALVES

Port Size	Part Number	Material	Kit Including	Compatible with Valves with
1/8"G	XGSPG1	AISI 304	fixing screws	any < 3.0 mm orifice
1/4"G	XGSPG2	AISI 304	fixing screws	any < 3.0 mm orifice
1/4"G	XGSPG3	AISI 304	fixing screws	4.0 mm to 5 mm orifice

Liquipure® Adapter

N° 2 Fixing holes M5x0.8









All dimensions are in mm

NOTES

NOTES

VALVES FOR BEVERAGE DISPENSING AND LIQUIPURE®

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Stainless St/Pipe Mounting	Normally Closed	1/8"	1.5 to 2.5	0.5 to 2.3	8	140	234
			1/4"	1.5 to 3	1 to 4.5	8	140	236
	LLB Brass/Pipe Mounting	Normally Closed	1/8"	1.5 to 3	1.4 to 3.7	20	140	236
			1/4"	1.5 to 5	1.4 to 4.3	20	140	236
	LLB Brass/Sub-Base Mounting	Normally Closed	SB	1.5 to 3	1.3 to 3.7	20	140	238
	Stainless St./Sub-base Mounting	Normally Closed	SB	1.5 to 5	7.2	14	140	240

Food Compliance: NSF 169 certified, 1935/2004/CE

3/2 VALVES FOR BEVERAGE DISPENSING

DIRECT OPERATED

CW510L BRASS BODY

PIPE MOUNTING

NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C					W	W		
G1/8''	1.5	1.4	0.08	0	20	20	-10	140	FDA FKM	131ZH1115	2995	481865	9	10	2.0	5
	2.0	2.0	0.12	0	14	14	-10	140	FDA FKM	131ZH1120	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	8.5	8.5	-10	140	FDA FKM	131ZH1125	2995	481865	9	10	2.0	
	3.0	3.7	0.22	0	6	6	-10	140	FDA FKM	131ZH1130	2995	481865	9	10	2.0	
	1.5	1.4	0.08	0	20	20	-10	140	Ruby	131ZH0115	2995	481865	9	10	2.0	
	2.0	2.0	0.12	0	14	14	-10	140	Ruby	131ZH0120	2995	492425	9	8	2.0	
	2.5	3.0	0.18	0	8.5	8.5	-10	140	Ruby	131ZH0125	2995	481865	9	10	2.0	
	3.0	3.7	0.22	0	6	6	-10	140	Ruby	131ZH0130	2995	481865	9	10	2.0	
G1/8''	1.5	1.4	0.10	0	20	20	-10	140	FDA FKM	131ZH1315	2995	481865	9	10	2.0	6
	2.0	2.0	0.10	0	14	14	-10	140	FDA FKM	131ZH1320	2995	481865	9	10	2.0	
	2.5	3.0	0.20	0	8.5	8.5	-10	140	FDA FKM	131ZH1325	2995	481865	9	10	2.0	
	3.0	3.7	0.20	0	6	6	-10	140	FDA FKM	31ZH1330	2995	481865	9	10	2.0	
	1.5	1.4	0.1	0	20	20	-10	140	Ruby	131ZH0315	2995	481865	9	10	2.0	
	2.0	2.0	0.1	0	14	14	-10	140	Ruby	131ZH0320	2995	481865	9	10	2.0	
	2.5	3.0	0.2	0	8.5	8.5	-10	140	Ruby	131ZH0325	2995	481865	9	10	2.0	
	3.0	3.7	0.2	0	6	6	-10	140	Ruby	131ZH0330	2995	481865	9	10	2.0	
NPT 1/8"	1.5	1.4	0.08	0	20	20	-10	140	FDA FKM	U131ZH1115	2995	481865	9	10	2.0	5
	2.0	2.0	0.12	0	14	14	-10	140	FDA FKM	U131ZH1120	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	8.5	8.5	-10	140	FDA FKM	U131ZH1125	2995	481865	9	10	2.0	
	3.0	3.7	0.22	0	6	6	-10	140	FDA FKM	U131ZH1130	2995	481865	9	10	2.0	
	1.5	1.4	0.08	0	20	20	-10	140	Ruby	U131ZH0115	2995	481865	9	10	2.0	
	2.0	2.0	0.12	0	14	14	-10	140	Ruby	U131ZH0120	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	8.5	8.5	-10	140	Ruby	U131ZH0125	2995	481865	9	10	2.0	
	3.0	3.7	0.22	0	6	6	-10	140	Ruby	U131ZH0130	2995	481865	9	10	2.0	

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.5	1.4	6	-10
To	1/8"	3	3.7	20	140



Drawing 5



Drawing 6

3/2 VALVES FOR BEVERAGE DISPENSING

DIRECT OPERATED

CW510L BRASS BODY
PIPE MOUNTING
NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C					W	W		
G1/4"	1.5	1.4	0.08	0	20	20	-10	140	FKM FDA	131KH1115	2995	481865	9	10	2.0	7
	2.0	2.0	0.12	0	14	14	-10	140	FKM FDA	131KH1120	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	8.5	8.5	-10	140	FKM FDA	131KH1125	2995	481865	9	10	2.0	
	3.0	3.7	0.22	0	6	6	-10	140	FKM FDA	131KH1130	2995	481865	9	10	2.0	
	4.0	5.2	0.31	0	3.5	3.5	-10	140	FKM FDA	131KH1140	2995	481865	9	10	2.0	8
	5.0	9.3	0.56	0	2	2	-10	140	FKM FDA	131KH1150	2995	492425	14	14	2.0	
	1.5	1.4	0.08	0	20	20	-10	140	Ruby	131KH0115	2995	481865	9	10	2.0	7
	2.0	2.0	0.12	0	14	14	-10	140	Ruby	131KH0120	2995	481865	9	10	2.0	
	2.5	3.0	0.18	0	8.5	8.5	-10	140	Ruby	131KH0125	2995	481865	9	10	2.0	
	3.0	3.7	0.22	0	6	6	-10	140	Ruby	131KH0130	2995	481865	9	10	2.0	

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	1.5	1.4	2	-10
To	1/8"	3	3.7	20	140



Drawing 7



Drawing 8

3/2 VALVES FOR BEVERAGE DISPENSING - DIRECT OPERATED

CW510L BRASS BODY FLANGED (SB)

NORMALLY CLOSED



Port Size	Orifice Ø	Flow Factors		Operating Pressure Differential			Fluid Temperature		Seat Seal	Parker Valves			Power		Coil Group	Dwg N°
		Kv	KV	Min.	Max. (MOPD)		Min.	Max.		Valve Ref.	Housing Ref.	Coil Ref.	AC	DC		
	mm	l/min	m³/h	Bar	AC bar	DC bar	°C	°C					W	W		
SB	1.5	1.4	0.08	0	20	20	-10	140	FKM FDA	131FH1115	2995	481865	9	10	2.0	9
	2.0	2.0	0.12	0	15	15	-10	140	FKM FDA	131FH1120	2995	481865	9	10	2.0	
	2.5	3.0	0.16	0	10	10	-10	140	FKM FDA	131FH1125	2995	481865	9	10	2.0	
	3.0	3.7	0.18	0	7.5	7.5	-10	140	FKM FDA	131FH1130	2995	481865	9	10	2.0	
	1.5	1.4	0.08	0	20	20	-10	140	Ruby	131FH0115	2995	481865	9	10	2.0	
	2.0	2.0	0.12	0	15	15	-10	140	Ruby	131FH0120	2995	481865	9	10	2.0	
	2.5	3.0	0.16	0	10	10	-10	140	Ruby	131FH0125	2995	481865	9	10	2.0	
	3.0	3.7	0.18	0	7.5	7.5	-10	140	Ruby	131FH0130	2995	481865	9	10	2.0	
SB	1.5	1.4	0.08	0	20	20	-10	140	FKM FDA	131FH1315	2995	481865	9	10	2.0	10
	2.0	2.0	0.12	0	15	15	-10	140	FKM FDA	131FH1320	2995	481865	9	10	2.0	
	2.5	3.0	0.16	0	10	10	-10	140	FKM FDA	131FH1325	2995	481865	9	10	2.0	
	3.0	3.7	0.18	0	7.5	7.5	-10	140	FKM FDA	131FH1330	2995	481865	9	10	2.0	
	1.5	1.4	0.08	0	20	20	-10	140	Ruby	131FH0315	2995	481865	9	10	2.0	
	2.0	2.0	0.12	0	15	15	-10	140	Ruby	131FH0320	2995	481865	9	10	2.0	
	2.5	3.0	0.16	0	10	10	-10	140	Ruby	131FH0325	2995	481865	9	10	2.0	
	3.0	3.7	0.18	0	7.5	7.5	-10	140	Ruby	131FH0330	2995	481865	9	10	2.0	

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.3	7.5	-10
To	SB	3	3	20	140



Drawing 9



Drawing 10

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 VALVES FOR BEVERAGE DISPENSING - LIQUIPURE®
DIRECT OPERATED

STAINLESS ST.
FLANGED (SB)
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Dwg. No.	Compatible adapter kit
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max		Valve Ref.	Hou Ref.	Coil Ref.					
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C					AC W	DC W			
	1.5	2.5	1.3	2.9	0.08	0.17	0	14	14	-10	140	Ruby	3019F1GRG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	1.5	2.5	1.3	2.9	0.08	0.17	0	14	14	-10	140	FKM FDA	3019F1GVG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	2	2.5	2.2	2.9	0.13	0.17	0	10	10	-10	140	Ruby	3019F1JRG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	2	2.5	2.2	2.9	0.13	0.17	0	10	10	-10	140	FKM FDA	3019F1JVG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	2	2.5	2.2	2.9	0.13	0.17	0	10	10	-10	140	Ruby	301XGFRTJ7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	2.5	2.5	2.8	2.9	0.17	0.17	0	6.5	6.5	-10	140	Ruby	3019F1LRG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
SB	2.5	2.5	2.8	2.9	0.17	0.17	0	6.5	6.5	-10	140	FKM FDA	3019F1LVG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	3	2.5	3.3	2.9	0.2	0.17	0	4	4	-10	140	Ruby	3019F1NRG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	3	2.5	3.3	2.9	0.2	0.17	0	4	4	-10	140	FKM FDA	3019F1NVG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	4	2.5	6.5	2.9	0.39	0.17	0	3	3	-10	140	FKM FDA	3019F1QVG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	4	4.0	6.5	2.9	0.39	0.17	0	3	3	-10	140	EPDM	3019F1QEG7	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	5	2.5	7.2	2.9	0.43	0.17	0	2	2	-10	140	FKM FDA	3019F1SVG7[1]	-	481865	9	10	2.0	72	XGSPG1-XGSPG2
	5	5.0	7.2	2.9	0.43	0.17	0	2	2	-10	140	EPDM	3019F1SEG7	-	481865	9	10	2.0	72	XGSPG1-XGSPG2

Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.

Notes:

1. NSF Certified

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.3	2	-10
To	SB	5	7.2	14	140



Drawing 72

3/2 VALVES FOR BEVERAGE DISPENSING - LIQUIPURE®
DIRECT OPERATED

STAINLESS ST.
FLANGED (SB)
NORMALLY CLOSED



Port size	Orifice Ø		Flow factors				Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Compatible adapter kit
	1	(2)	1	(2)	1	(2)	Min	Max (MOPD)		Min	Max		Valve Ref.	Hou Ref.	Coil Ref.				
BSP	mm		Kv l/min		KV m³/h		bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	1.5	1.5	1.4	0.08	1.3	0.8	0	9.5	9.5	-10	140	FKM FDA	3039F1GVG7$_1$	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	1.5	1.5	1.4	0.08	1.3	0,08	0	9.5	9.5	-10	140	EPDM	3039F1GEG7	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	2.0	2.0	2.1	0.13	2.0	0.12	0	3.5	3.5	-10	140	FKM FDA	3039F1JVG7$_1$	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	2.0	2.0	2.1	0.13	2.0	0.12	0	3.5	3.5	-10	140	EPDM	3039F1JEG7	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	2.5	2.5	2.8	0.17	2.8	0.17	0	2	2	-10	140	FKM FDA	3039F1LVG7$_1$	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	2.5	2.5	2.8	0.17	2.8	0.168	0	2	2	-10	140	EPDM	3039F1LEG7	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	3.0	2.5	3.3	0.2	2.8	0.17	0	2	2	-10	140	FKM FDA	3039F1NVG7$_1$	-	481865	9	10	2.0	XGSPG1 - XGSPG2
	3.0	2.5	3.3	0.2	2.8	0.168	0	2	2	-10	140	EPDM	3039F1NEG7	-	481865	9	10	2.0	XGSPG1 - XGSPG2

Nominal Pressure = 20 bar
Important: pressure vessels included in this page are supplied with the standard 2995 housing integrated.

Notes:

1. NSF Certified

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	1.5	1.4	2	-10
To	SB	3	3.3	9.5	140





All dimensions are in mm

SUB-BASES FOR LIQUIPURE VALVES

Port Size	Part Number	Material	Kit Including	Compatible with Valves with
1/8"G	XGSPG1	AISI 304	fixing screws	any < 3.0 mm orifice
1/4"G	XGSPG2	AISI 304	fixing screws	any < 3.0 mm orifice
1/4"G	XGSPG3	AISI 304	fixing screws	4.0 mm to 5 mm orifice

Liquipure® Adapter









All dimensions are in mm

NOTES

NOTES

TECHNOPOLYMER VALVES

Steam Water Air

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Technopolymer/Pipe mounting	Normally Closed	4 to 6mm	1.2 to 2.5	0.7 to 2.3	15	145	248
Direct Operated	Technopolymer/Cartridge	Normally Closed	4 to 6mm	1.2	0.7 to 2.3	15	145	250

Food Compliance: NSF 169 certified, 1935/2004/CE

2/2 TECHNOPOLYMER VALVES

DIRECT OPERATED

TECHNOPOLYMER

PIPE MOUNTING

NORMALLY CLOSED



Port Size (PTC)	Orifice Ø mm	Flow Factors Kv l/min	Flow Factors KV m³/h	Operating Pressure Differential Min. Bar	Operating Pressure Differential Max. (MOPD) AC bar	Operating Pressure Differential Max. (MOPD) DC bar	Fluid Temperature Min. °C	Fluid Temperature Max. °C	Seat Seal	Parker Valves Valve Ref.	Parker Valves Housing Ref.	Parker Valves Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg N°
4.0 mm	1.2	0.7	0.04	0	15	12	-10	145	FKM FDA	121Q0112	1878	497510	4.5	9.3	1.2	1
	1.5	1	0.06	0	15	10	-10	145	FKM FDA	121Q0115	1878	497510	4.5	9.3	1.2	
	2.5	2.3	0.14	0	10	4	-10	145	FKM FDA	121Q0125	1878	497510	4.5	9.3	1.2	
6.0 mm	1.2	0.7	0.04	0	15	12	-10	145	FKM FDA	121Q0512	1878	497510	4.5	9.3	1.2	2
	1.5	1	0.06	0	15	10	-10	145	FKM FDA	121Q0515	1878	497510	4.5	9.3	1.2	
	2.5	2.3	0.14	0	10	4	-10	145	FKM FDA	121Q0525	1878	497510	4.5	9.3	1.2	



Drawing 1



Drawing 2

2/2 TECHNOPOLYMER VALVES
DIRECT OPERATED

TECHNOPOLYMER CARTRIDGE
NORMALLY CLOSED



Port Size (PTC)	Orifice Ø mm	Flow Factors Kv l/min	Flow Factors KV m³/h	Operating Pressure Differential Min. Bar	Operating Pressure Differential Max. (MOPD) AC bar	Operating Pressure Differential Max. (MOPD) DC bar	Fluid Temperature Min. °C	Fluid Temperature Max. °C	Seat Seal	Parker Valves Valve Ref.	Parker Valves Housing Ref.	Parker Valves Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg N°
	1.2	0.7	0.042	0	15	12	-10	145	FKM FDA	121C0712	1878	497510	4.5	9.3	1.2	
Cartridge	1.5	1	0.06	0	15	10	-10	145	FKM FDA	121C0715	1878	497510	4.5	9.3	1.2	7
	2.5	2.3	0.138	0	10	4	-10	145	FKM FDA	121C0725	1878	497510	4.5	9.3	1.2	



SEAT PRESCRIPTIONS



Drawing 7

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

NOTES

TECHNOPOLYMER VALVES

Steam Water Air

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Technopolymer/Pipe mounting	Normally Closed	4 to 6mm	1.2 to 2.5	0.7 to 2.3	14	145	254
	Technopolymer/Cartridge	Normally Closed	4 to 6mm	1.2 to 2.5	0.7 to 2.3	14	145	256

Food Compliance: NSF 169 certified, 1935/2004/CE

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 TECHNOPOLYMER VALVES

DIRECT OPERATED

TECHNOPOLYMER
PIPE MOUNTING
NORMALLY CLOSED



Port Size (PTC)	Discharge Port Spec	Orifice Ø 1 mm	Orifice Ø (2) mm	Flow Factors Kv l/min	Kv l/min	KV m^3/h	KV m^3/h	Operating Pressure Differential Min. Bar	Max. (MOPD) AC bar	Max. (MOPD) DC bar	Fluid Temperature Min. °C	Fluid Temperature Max. °C	Seat Seal	Parker Valves Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg N°
4.0 mm	Ø 6.0mm barb fitting	1.2	1.6	0.7	1.1	0.04	0.066	0	14	14	-10	145	FKM FDA	131Q5112	1878	497510	4.5	9.3	1.2	
		1.5	1.6	1	1.1	0.06	0.066	0	8	8	-10	145	FKM FDA	131Q5115	1878	497510	4.5	9.3	1.2	3
		2.5	1.6	2.3	1.1	0.14	0.066	0	3	3	-10	145	FKM FDA	131Q5125	1878	497510	4.5	9.3	1.2	
	Ø 6.0mm type C	1.2	1.6	0.7	1.1	0.04	0.066	0	14	14	-10	145	FKM FDA	131Q7112	1878	497510	4.5	9.3	1.2	
		1.5	1.6	1	1.1	0.06	0.066	0	8	8	-10	145	FKM FDA	131Q7115	1878	497510	4.5	9.3	1.2	4
		2.5	1.6	2.3	1.1	1.38	0.066	0	3	3	-10	145	FKM FDA	131Q7125	1878	497510	4.5	9.3	1.2	
6.0 mm	Ø 6.0mm barb fitting	1.2	1.6	0.7	1.1	0.04	0.066	0	14	14	-10	145	FKM FDA	131Q5512	1878	497510	4.5	9.3	1.2	
		1.5	1.6	1	1.1	0.06	0.066	0	8	8	-10	145	FKM FDA	131Q5515	1878	497510	4.5	9.3	1.2	5
		2.5	1.6	2.3	1.1	1.38	0.066	0	3	3	-10	145	FKM FDA	131Q5525	1878	497510	4.5	9.3	1.2	
	Ø 6.0mm type C	1.2	1.6	0.7	1.1	0.04	0.066	0	14	14	-10	145	FKM FDA	131Q7512	1878	497510	4.5	9.3	1.2	
		1.5	1.6	1	1.1	0.06	0.066	0	8	8	-10	145	FKM FDA	131Q7515	1878	497510	4.5	9.3	1.2	6
		2.5	1.6	2.3	1.1	0.14	0.066	0	3	3	-10	145	FKM FDA	131Q7525	1878	497510	4.5	9.3	1.2	



Drawing 3



Drawing 4



Drawing 5



Drawing 6

3/2 TECHNOPOLYMER VALVES

DIRECT OPERATED

TECHNOPOLYMER CARTRIDGE

NORMALLY CLOSED



Port Size (PTC)	Discharge Port Spec	Orifice Ø 1 mm	Orifice Ø (2) mm	Flow Factors Kv l/min	Kv l/min	KV m^3/h	KV m^3/h	Operating Pressure Differential Min. Bar	Max. (MOPD) AC bar	Max. (MOPD) DC bar	Fluid Temperature Min. °C	Fluid Temperature Max. °C	Seat Seal	Parker Valves Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg N°
Cartridge	Ø 6.0mm barb fitting	1.2	1.6	0.7	1.1	0.042	0.066	0	14	14	-10	145	FKM FDA	131C5712	1878	497510	4.5	9.3	1.2	8
		1.5	1.6	1	1.1	0.06	0.066	0	8	8	-10	145	FKM FDA	131C5715	1878	497510	4.5	9.3	1.2	
		2.5	1.6	2.3	1.1	0.138	0.066	0	3	3	-10	145	FKM FDA	131C5725	1878	497510	4.5	9.3	1.2	
	Ø 6.0mm type C	1.2	1.6	0.7	1.1	0.04	0.066	0	14	14	-10	145	FKM FDA	131C7712	1878	497510	4.5	9.3	1.2	9
		1.5	1.6	1	1.1	0.06	0.066	0	8	8	-10	145	FKM FDA	131C7715	1878	497510	4.5	9.3	1.2	
		2.5	1.6	2.3	1.1	1.38	0.066	0	3	3	-10	145	FKM FDA	131C7725	1878	497510	4.5	9.3	1.2	



Drawing 8



Drawing 9

Coil assembly kit & Accessories

Coil assembly kit

The coil assembly kit part number is 1878. It corresponds to the “housing” in the valve housing of Parker valve numbering system (pressure vessel-housing-coil) Q Series and C series are compatible with 1878 housing system, which consists in a blocking clip shaped to ensure its usage for cartridge removal purposes. See example in the chapter “disposable cartridge replacement”.
The 1878 housing is always supplied with the Q Series pressure vessel or can be ordered separately.

Installation kit (Q Series)

The Q series installation kit part number is 3287. It is optional and it consists in a stand-alone clip compatible with 10mm DIN46277-3 rails in order to properly allocate the valve inside the machine.
The clip can be ordered separately.

DIN Plug connector

The DIN Plug connector compatible with 22mm coils, according to EN175301-803 -B is optional and is not being supplied with the valve assembly. It can be ordered separately, kit reference 48104340.

NOTES

NOTES

2 WAY VALVES FOR TRANSPORTATION

2/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Pilot Operated	Brass/Quick Coupling	Normally Closed	10 mm	11	12	3	90	262
	Brass/Barb Fitting	Normally Closed	10 mm	11	12	3	90	262
	Brass/Pipe Mounting	Normally Closed	1/2"	11	36	3	90	264
			12.7 mm	11	33	3	90	264
			15.9 mm	11	36	3	90	264

2/2 2 WAY VALVES FOR TRANSPORTATION

PILOT OPERATED

BRASS
QUICK COUPLING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Voltage	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max									
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C						AC W	DC W		
10 mm	11	12	0.72	-	0.2	-	3	-40	90	EPDM	**321K1543**	**2168**	**495294**	12 VDC	-	9	13.0	8242
	11	12	0.72	-	0.2	-	3	-40	90	EPDM	**321K1543**	**2169**	**495294**	24 VDC	-	9	13.0	8242
	11	12	0.72	-	0.2	-	3	-40	90	EPDM	**321K1543**	**2168**	**496193**	12 VDC	-	9	13.0	8242
	11	12	0.72	-	0.2	-	3	-40	90	EPDM	**321K1543**	**2169**	**496193**	24 VDC	-	9	13.0	8242

BRASS
BARB FITTING
NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Voltage	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max									
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C						AC W	DC W		
10 mm	11	12	0.72	-	0.2	-	3	-40	90	EPDM	321K1535	2168	495294	12 VDC	-	9	13.0	8241
	11	12	0.72	-	0.2	-	3	-40	90	EPDM	321K1535	2169	495294	24 VDC	-	9	13.0	8241
	11	12	0.72	-	0.2	-	3	-40	90	EPDM	321K1535	2168	496193	12 VDC	-	9	13.0	8241
	11	12	0.72	-	0.2	-	3	-40	90	EPDM	321K1535	2169	496193	24 VDC	-	9	13.0	8241

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	10 mm	11	12	3	-40
To	10 mm	11	12	3	90



Drawing 8242



Drawing 8241

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

2/2 2 WAY VALVES FOR TRANSPORTATION

PILOT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Voltage	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max									
	mm	Kv l/min	KV m³/h	Qn l/min	bar	AC bar	DC bar	°C	°C						AC W	DC W		
1/2" BSP	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1523	2168	495294	12 VDC	-	9	13.0	8238
	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1523	2169	495294	24 VDC	-	9	13.0	8238
	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1523	2168	496193	12 VDC	-	9	13.0	8238
	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1523	2169	496193	24 VDC	-	9	13.0	8238
12.7 mm	11	33	1.98	-	0.2	-	3	-40	90	EPDM	321K1536	2168	495294	12 VDC	-	9	13.0	8282
	11	33	1.98	-	0.2	-	3	-40	90	EPDM	321K1536	2169	495294	24 VDC	-	9	13.0	8282
	11	33	1.98	-	0.2	-	3	-40	90	EPDM	321K1536	2168	496193	12 VDC	-	9	13.0	8282
	11	33	1.98	-	0.2	-	3	-40	90	EPDM	321K1536	2169	496193	24 VDC	-	9	13.0	8282
15.9 mm	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1537	2168	495294	12 VDC	-	9	13.0	8281
	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1537	2169	495294	24 VDC	-	9	13.0	8281
	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1537	2168	496193	12 VDC	-	9	13.0	8281
	11	36	2.16	-	0.2	-	3	-40	90	EPDM	321K1537	2169	496193	24 VDC	-	9	13.0	8281

For this page	Port size	Orifice (mm)	Kv (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	11	33	3	-40
To	15.9 mm	11	36	3	90



Drawing 8238



Drawing 8282



Drawing 8281

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

NOTES

3 WAY VALVES FOR TRANSPORTATION

3/2

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves	Page
Direct Operated	Brass/Quick Coupling	Normally Closed	1/8"	1.8	110	8	80	-	**268**

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 3 WAY VALVES FOR TRANSPORTATION

DIRECT OPERATED

BRASS

QUICK COUPLING

NORMALLY CLOSED



Port size	Orifice Ø		Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1	(2)		Min	Max (MOPD)		Min	Max								
BSP	mm		Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8"	1.8	1.5	110	0	-	8	-30	80	TPE/PVDF	131K0648	2161	495294	-	9	13.0	7872
	1.8	1.5	110	0	-	8	-30	80	TPE/PVDF	131K0648	2161	496193	-	9	13.0	7872

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	1.8	110	8	-30
To	1/8"	1.8	110	8	80



Drawing 7872

NOTES

5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

5/2

Actuation	Body	Function	Port Size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Pilot Operated	Anodized Aluminium/ Pipe Mounting	Normally Closed	1/8-1/4"	6	630	10	75	272
			1/4"	6 to 14	2500	40	75	272 and 274
			1/2"	14	2500	15	75	274
		Control by Electric Impulse	1/8-1/4"	6	630	10	75	276
			1/4"	8	1000	15	75	276
			1/2"	14	2500	15	75	276
	Anodized Aluminium/ Pipe Mounting/Poppet	Normally Closed	1/8"	4	400	10	75	278
			1/4"	8	1400	10	75	278
		Dual Solenoids	1/8"	4	315	10	75	278
			1/4"	8	1400	10	100	280
	Anodized Aluminium/ Sub-base Mounting	Normally Closed	SB	6	630	10	75	282
		Control by Electric Impulse	SB	6	630	10	75	282
	Anodized Aluminium/ Sub-base Mounting/ Poppet	Normally Closed	SB	4 to 15	5000	10	75	282
		Dual Solenoids	SB	4	400	10	75	282
		Control by Electric Impulse	SB	15	5000	10	75	286
	Anodized Aluminium/ CETOP/Poppet	Dual Solenoids	SB	6	800	10	75	286
	POM/CETOP/Poppet	Normally Closed	SB	6	800	10	75	290
		Control by Electric Impulse	SB	6	800	10	75	292
Externally Operated	Anodized Aluminium/ Sub-base Mounting	Normally Closed	SB	7	800	10	75	294

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

SPRING RETURN





Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4"	6	630	1	10	10	-10	75	NBR	341B34$_{2}$	4270	481000		8	8	2.0	3286
	6	630	1	10	10	-10	75	NBR	341B34$_{2}$	2995	481865		9	10	2.0	3286
	6	630	1	10	10	-10	75	NBR	341B34$_{2}$	4270	486265		14	14	2.0	3286
	6	630	1	10	10	-10	75	NBR	341B3403$_{3}$	4270	481000		8	8	2.1	3286
	6	630	1	10	10	-10	75	NBR	341B3403$_{3}$	2995	481865		9	10	2.0	3286
	6	560	1	-	10	-10	55	NBR	341B3490$_{4}$	2995	48358001	*	-	0.5-3	6.0/7.0/8.0	3561
	6	560	1	-	10	-10	75	NBR	341B3490$_{4}$	-	495910	*	-	0.3-1.2	6.0/7.0/8.0	3561
	6	630	1	10	10	-25	75	PUR	341B3440$_{2}$	4270	481000		8	8	2.1	3286
	6	630	1	10	10	-25	75	PUR	341B3440$_{2}$	2995	481865		9	10	2.0	3286
	8	640	1	40	40	-10	75	NBR	341B02$_{1}$	4270	481000		8	8	2.1	8115
	8	640	1	40	40	-10	75	NBR	341B02$_{1}$	2995	481865		9	10	2.0	8115

Notes:
1.Valve with pilot return pipe on exhaust port
2.With Flow regulator e manual override
3.With manual override
4.With flow regulator

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8-1/4"	6	560	10	-25
To	1/4"	8	640	40	75



Drawing 3286



Drawing 3561



Drawing 8115

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max								
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	8	1000	1	15	15	-10	75	NBR	E341B01	2995	481865	9	10	2.0	3309
	8	1000	1	15	15	-10	75	NBR	E341B01	4270	485100	8	8	2.1	3309
	14	2500	2	15	15	-10	75	NBR	E341F21	4270	481000	8	8	2.1	3310
1/2"	14	2500	1	15	15	-10	75	NBR	E341F21 [1]	2995	481865	9	10	2.0	3315
	14	2500	1	15	15	-10	65	NBR	E341F21 [1]	-	483371	8	8	2.1	3315

Notes:
1.Valve only compatible with air and neutral gases

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	1000	15	-10
To	1/2"	14	2500	15	75



Drawing 3309



Drawing 3310



Drawing 3315

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max								
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/8-1/4"	6	630	1	10	-	-10	75	NBR	345B34 $_{12}$	4269	484990	11	-	4.0	3286
	6	630	1	-	10	-10	75	NBR	345B34 $_{12}$	4269	485400	-	13	4.0	3286
1/4"	8	1000	1	15	-	-10	75	NBR	345B04	4269	484990	11	-	4.0	3309
	8	1000	1	-	15	-10	75	NBR	345B04	4269	485400	-	13	4.0	3309
1/2"	14	2500	1	15	-	-10	75	NBR	345B24	4269	484990	11	-	4.0	3315
	14	2500	1	-	15	-10	75	NBR	345B24	4269	485400	-	13	4.0	3315

Notes:
1.Valve only compatible with air and neutral gases
2.With flow regulator e manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8-1/4"	6	630	10	-10
To	1/2"	14	2500	15	75



Drawing 3286



Drawing 3309



Drawing 3315

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM
PIPE MOUNTING
SPRING RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8"	4	400	1	10	10	-10	65	NBR	341L9101 [1]	-	482605	4	5	1.1	3894
	4	400	1	10	10	-10	65	NBR	341L9101 [1]	-	482606	2	2.5	1.1	3894
	4	400	1	10	10	-10	75	NBR	341L9101 [1]	8993	488980	2	2.5	1.1	3894
	4	400	1	10	10	-10	50	NBR	341L9101 [1]	8993	495865	2	2.5	1.1	3894

Notes:
1.With manual override

ANODIZED ALUMINIUM
PIPE MOUNTING
DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8"	4	315	2	10	10	-10	65	NBR	347L9101 [1]	-	482605	4	5	1.1	3896
	4	315	2	10	10	-10	65	NBR	347L9101 [1]	-	482606	2	2.5	1.1	3896
	4	315	2	10	10	-10	75	NBR	347L9101 [1]	8993	488980	2	2.5	1.1	3896
	4	315	2	10	10	-10	50	NBR	347L9101 [1]	8993	495865	2	2.5	1.1	3896

Notes:
1.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8"	4	315	10	-10
To	1/8"	4	400	10	75



Drawing 3894



Drawing 3896

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
SPRING RETURN



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	6	630	1	10	10	-10	75	NBR	341F34 $_{12}$	2995	481865	9	10	2.0	3287
	6	630	1	10	10	-10	75	NBR	341F34 $_{12}$	4270	481000	8	8	2.1	3287
	6	630	1	10	10	-10	75	NBR	341F3403 $_{2}$	2995	481865	9	10	2.0	3287
	6	630	1	10	10	-10	75	NBR	341F3403 $_{2}$	4270	481000	8	8	2.1	3287
	6	630	1	10	10	-25	75	NBR	341F3440 $_{12}$	2995	481865	9	10	2.0	3287

Notes:
1.With flow regulator
2. With manual override

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	6	630	1	10	-	-10	75	NBR	345F34 $_{1}$	4269	484990	11	-	4.0	3287
	6	630	1	-	10	-10	75	NBR	345F34 $_{1}$	4269	485400	-	13	4.0	3287

Notes:
1.With flow regulator e manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	6	630	10	-25
To	SB	6	630	10	75



Drawing 3287

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
SPRING RETURN



Port size	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	15	5000	0.5	10	10	-10	75	FKM	E341L21 [1]	2995	481865		9	10	2.0	3299
	15	5000	0.5	10	10	-10	75	FKM	E341L21 [1]	-	495905		8	8	2.0/2.1	3299
SB	15	5000	0.5	-	10	-10	55	NBR	341L2190	2995	48358001	*	-	0.5-3	6.0/7.0/8.0	8271
	15	5000	0.5	-	10	-10	75	NBR	341L2190	-	495910	*	-	0.3-1.2	6.0/7.0/8.0	8271
SB	4	400	1	10	10	-10	65	NBR	341L9201	-	482605		4	5	1.1	3895
	4	400	1	10	10	-10	65	NBR	341L9201	-	482606		2	2.5	1.1	3895
	4	400	1	10	10	-10	75	NBR	341L9201	8993	488980		2	2.5	1.1	3895
	4	400	1	10	10	-10	50	NBR	341L9201	8993	495865		2	2.5	1.1	3895

Notes:
1.With manual override

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	4	400	1	10	10	-10	75	NBR	341L9201 [1]	-	482605	-	5	1.1	3895
	4	400	1	10	10	-10	75	NBR	341L9201 [1]	-	482606	2	2.5	1.1	3895
	4	400	1	10	10	-10	75	NBR	341L9201 [1]	8993	488980	2	2.5	1.1	3895
	4	400	1	10	10	-10	75	NBR	341L9201 [1]	8993	495865	2	2.5	1.1	3895

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	4	400	10	-10
To	SB	15	5000	10	75



Drawing 3299



Drawing 8271





Drawing 3895

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
DUAL SOLENOIDS



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	4	315	2	10	10	-10	65	NBR	347L9201 [1]	-	482605	4	5	1.1	3897
	4	315	2	10	10	-10	65	NBR	347L9201 [1]	-	482606	2	2.5	1.1	3897
	4	315	2	10	10	-10	75	NBR	347L9201 [1]	8993	488980	2	2.5	1.1	3897
	4	315	2	10	10	-10	50	NBR	347L9201 [1]	8993	495865	2	2.5	1.1	3897

Notes:
1.With manual override

ANODIZED ALUMINIUM
SUB-BASE MOUNTING
CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	15	5000	0.5	10	-	-10	75	NBR	345L21	4269	484990	11	-	4.0	3299
	15	5000	0.5	-	10	-10	75	NBR	345L21	4269	485400	-	13	4.0	3299

ANODIZED ALUMINIUM
CETOP
DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	6	800	1	10	10	-10	75	NBR	347L04 [1]	8993	488980	2	2.5	1.1	3694

Notes:
1.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	4	315	10	-10
To	SB	15	5000	10	75



Drawing 3897



Drawing 3299



Drawing 3694

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max								
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
1/4"	8	1400	1	10	10	-10	75	NBR	341L11 [1]	8993	488980	2	2.5	1.1	3434
	8	1400	1	10	10	-10	50	NBR	341L11 [1]	8993	495865	2	2.5	1.1	3434
	8	1400	1	10	10	-10	65	NBR	341L11 [1]	-	482605	4	5	1.1	3434
	8	1400	1	10	10	-10	65	NBR	341L11 [1]	-	482606	2	2.5	1.1	3434
	8	1400	1	10	10	-10	75	NBR	E341L1130 [1]	2995	481865	9	10	2.0	3539
	8	1400	1	10	10	-10	65	NBR	E341L1130 [1]	-	483371	8	8	2.0/2.1	3539
1/4" NPT	8	1400	1	10	10	-10	75	FKM	U341L1130 [1]	2995	481865	9	10	2.0	8297
	8	1400	1	10	10	-10	75	FKM	U341L1130 [1]	2995	491514	11	12	2.1	8297

Notes:
1.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	1400	10	-10
To	1/4"	8	1400	10	75



Drawing 3434



Drawing 3539



Drawing 8297

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4"	8	1400	1	10	10	-10	65	NBR	347L11 [1]	-	482605	4	5	1.1	3461
	8	1400	1	10	10	-10	65	NBR	347L11 [1]	-	482606	2	2.5	1.1	3461
	8	1400	1	10	10	-10	75	NBR	347L11 [1]	8993	488980	2	2.5	1.1	3461
	8	1400	1	10	10	-10	50	NBR	347L11 [1]	8993	495865	2	2.5	1.1	3461

Notes:
1.With manual override

POM

CETOP

SPRING RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	6	800	1	10	10	-10	75	FKM	E341L02 [1]	2995	481865		9	10	2.0	3513
	6	800	1	10	10	-10	75	FKM	E341L02 [1]	4270	481000		8	8	2.1/3.0	3513

Notes:
1.Manual override and flow regulating screws standard

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	6	800	10	-10
To	1/4"	8	1400	10	100



Drawing 3461



Drawing 3541



Drawing 3513

5/2

5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

POM

CETOP



SPRING RETURN

Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	IS	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	8	800	1	10	10	-10	65	FKM	341L04 1	-	482605		4	5	1.1	3437
	8	800	1	10	10	-10	65	FKM	341L04 1	-	482606		2	2.5	1.1	3437
	8	800	1	10	10	-10	75	FKM	341L04 1	8993	488980		2	2.5	1.1	3437
	8	800	1	10	10	-10	50	FKM	341L04 1	8993	495865		2	2.5	1.1	3437
SB	6	800	1	-	10	-10	75	NBR	341L0197	2995	482740		-	1.6	6.0/8.0	8021
	6	800	1	10	10	-10	75	NBR	341L0197	-	495900		2.5	2	6.0/8.0	8021
	6	800	1	-	10	-10	75	NBR	341L0197	-	495910	*	-	0.3-1.2	6.0/8.0	8021
	6	800	1	-	10	-10	65	NBR	341L0197	2995	496125		-	1.6	6.0/8.0	8021
	6	800	1	10	10	-10	65	NBR	341L05 2	-	482605		4	5	1.1	3430
	6	800	1	10	10	-10	65	NBR	341L05 2	-	482606		2	2.5	1.1	3430
	6	800	1	10	10	-10	75	NBR	341L05 2	8993	488980		2	2.5	1.1	3430
	6	800	1	10	10	-10	50	NBR	341L05 2	8993	495865		2	2.5	1.1	3430
	6	800	1	10	-	-10	75	FKM	E341L01 1	2995	481865		9	-	2.0	3255
	6	800	1	10	10	-10	65	FKM	E341L01 1	-	483371		8	8	2.1/3.0	3255
	6	800	1	10	10	-10	75	FKM	E341L01 1	299533	491514		11	12	2.1/3.0	3255

Notes:
1.Manual override and flow regulating screws standard



Drawing 3255

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	6	800	10	-10
To	SB	8	800	10	75



Drawing 3437



Drawing 8021



Drawing 3430

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

PILOT OPERATED

POM

CETOP

CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max								
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C					AC W	DC W		
SB	6	800	1	-	10	-10	75	FKM	345L01 [1]	4269	485400	-	13	4.0	3255

Notes:
1.Manual override and flow regulating screws standard

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	6	800	10	-10
To	SB	6	800	10	75



Drawing 3255

5/2 5 WAY PNEUMATIC DISTRIBUTORS (PIPE MOUNTING/SUB-BASE MOUNTING)

EXTERNALLY OPERATED

ANODIZED ALUMINIUM

SUB-BASE MOUNTING

SPRING RETURN



Port size	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Operating Pressure Differential Max (MOPD) AC bar	Operating Pressure Differential Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	7	800	1	10	10	-10	75	FKM/ NBR	541L01	-	-	-	-	-	3254

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	7	800	10	-10
To	SB	7	800	10	75



Weight: 0,36 kg

PLAN DE POSE SELON CETOP 1/8"

Drawing 3254

NOTES

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

3/2
5/2

Actuation	Body	Function	Port Size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	Brass/Pipe mounting	Normally Closed	1/8''	1.2 to 1.5	70	10	75	298
			1/8''-1/4''	2.5	220	7	75	298
			1/4''	1	36	10	120	298
		Normally Open/Universal	1/4''	2.5 - 6	680	7-10	75	304
		Control by Electric Impulse	1/4''	2.5	220	7	100	306
	Brass/Sub-base mounting	Normally Closed	5 mm	2.5	180	2	75	308
		Universal	1/8''	2	140	7	120	308
	Anodized aluminium/ Pipe mounting	Universal	1/4''	6	680	10	75	310
Pilot Operated	Anodized aluminium/ Pipe mounting/Spool	Normally Closed	1/8''	4 to 15	600	10	80	312
			1/4''	7 to 8	1400	10	80	314
			1/2''	12	3000	10	50	318
		Dual Solenoids	1/8''	4	400	10	80	320
			1/4''	7 to 8	1400	10	80	322
			1/2''	12	3000	10	50	324
		Control by Electric Impulse	1/8''	4	600	10	80	324
Manual Reset	Brass/Pipe mounting	Universal	1/4''	6	680	10	65	324

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''	1.2	50	0	10	10	-10	75	FKM	131M15	8993	488980	-	-	2	2.5	1.1	3382
	1.2	50	0	10	10	-10	75	FKM	131M1550[1]	8993	488980	-	-	2	2.5	1.1	3382
	1.5	70	0	7	7	-10	75	FKM	131M14	8993	488980	-	-	2	2.5	1.1	3382
1/8''-1/4''	2.5	220	0	7	7	-40	75	PUR	E131K0358[1]	2995	481865	-	-	9	10	2.0	3510
	2.5	220	0	7	7	-40	75	PUR	E131K0358[1]	4270	481000	-	-	8	8	2.1	3510
1/4''	1	36	0	-	10	-10	55	FKM	131K0490	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7058
	1	36	0	-	10	-10	75	FKM	131K0490	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7058
	1	36	0	-	10	-10	75	FKM	131K0490	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7058

Notes:
1.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''	1	36	7	-40
To	1/4''	2.5	220	10	75



Drawing 3382



Drawing 3510



Drawing 7058

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
BSP	1 mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
	1.5	80	0	-	7	-20	75	PUR	131K0497	2995	482740	-	-	-	1.6	6.0/8.0	8023
	1.5	80	0	7	7	-20	75	PUR	131K0497	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8023
	1.5	80	0	-	7	-20	75	PUR	131K0497	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8023
	1.5	80	0	-	7	-20	75	PUR	131K0497	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8023
	1.5	80	0	16	16	-10	100	FKM	E131K04	2995	481865	-	-	9	10	2.0	3510
	1.5	80	0	16	16	-10	120	FKM	E131K04	4270	481000	-	-	8	8	2.0	3510
1/4''	1.5	80	0	16	16	-10	120	FKM	E131K04	4270	486265	-	-	14	14	2.0	3510
	1.5	80	0	15	15	-10	100	FKM	E131K0450 [1]	2995	481865	-	-	9	10	2.0	3510
	1.5	80	0	15	15	-10	120	FKM	E131K0450 [1]	4270	481000	-	-	8	8	2.1	3510
	2	140	0	10	10	-10	100	FKM	E131K06	2995	481865	-	-	9	10	2.0	8119
	2	140	0	10	10	-10	120	FKM	E131K06	4270	481000	-	-	8	8	2.0	8119
	2	140	0	10	10	-10	120	FKM	E131K06	4270	486265	-	-	14	14	2.0	8119
	2	140	0	10	10	-10	100	FKM	E131K0650 [1]	2995	481865	-	-	9	10	2.0	3510
	2	140	0	10	10	-10	120	FKM	E131K0650 [1]	4270	481000	-	-	8	8	2.1	3510

Notes:
1.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	1.5	80	7	-20
To	1/4''	2	140	16	120



Drawing 8023



Drawing 3510



Drawing 8119

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4''	2.5	220	0	7	7	-40	75	PUR	E131K0308	2995	481865	-	-	9	10	2.0	3510
	2.5	220	0	7	7	-40	75	PUR	E131K0308	4270	481000	-	-	8	8	2.1	3510
	2.5	220	0	7	7	-10	100	FKM	E131K0350 [1]	2995	481865	-	-	9	10	2.0	3510
	2.5	220	0	7	7	-10	120	FKM	E131K0350 [1]	4270	481000	-	-	8	8	2.1	3510
	4.5	500	0	2	2	-10	75	FKM	131T2101 [1]	2995	481865	-	-	9	10	2.0	3223
	4.5	500	0	2	2	-10	75	FKM	131T2101 [1]	4270	481000	-	-	8	8	2.1	3223

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	2.5	220	2	-40
To	1/4''	4.5	500	7	120



Drawing 3525



Drawing 3510



Drawing 3223

3/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

BRASS

PIPE MOUNTING

NORMALLY OPEN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4"	2.5	220	0	7	3.5	-10	75	FKM	132T29	2995	481865	-	-	9	10	2.0	3223
	2.5	220	0	7	3.5	-10	75	FKM	132T29	4270	481000	-	-	8	8	2.0	3223
	2.5	220	0	-	7	-10	75	FKM	132T29	4270	486265	-	-	-	14	2.0	3223

BRASS

PIPE MOUNTING

UNIVERSAL



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4'' NPT	6	680	0	12	12	-25	65	NBR	U133X0111	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1/10.2	7422
	6	680	0	-	12	-25	75	NBR	U133X0111	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	7422

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	2.5	220	3.5	-25
To	1/4''	6	680	10	75



Drawing 3223





Drawing 7422

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

BRASS

PIPE MOUNTING

CONTROL BY ELECTRIC IMPULSE



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
BSP	1 mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4''	2.5	220	0	-	7	-10	100	FKM	135K03	4269	485400	-	-	-	13	4.0	3510

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	2.5	220	7	-25
To	1/4''	2.5	220	7	100





Drawing 3510

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

BRASS

SUB-BASE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	2.5	180	0	-	2	-20	75	PUR	131F4397	2995	482740	-	-	-	1.6	6.0/8.0	8022
	2.5	180	0	2	2	-20	75	PUR	131F4397	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8022
	2.5	180	0	-	2	-20	75	PUR	131F4397	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8022
	2.5	180	0	-	2	-20	75	PUR	131F4397	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8022

BRASS

SUB-BASE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
SB	2	140	0	7	7	-10	100	FKM	133F4650[1]	2995	481865	-	-	9	10	2.0	3509
	2	140	0	7	7	-10	120	FKM	133F4650[1]	4270	481000	-	-	8	8	2.1	3509

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	2	140	2	-20
To	SB	2.5	180	7	120



Drawing 8022



Drawing 3509

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

DIRECT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

UNIVERSAL



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4''	6	680	0	12	12	-25	75	NBR	133X01	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1/10.2	6960
	6	680	0	12	12	-25	65	NBR	133X01	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	6960
	6	680	0	12	12	-25	65	NBR	133X01	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	6960
	6	680	0	12	12	-25	65	NBR	133X01	-	496895	-	-	8	8	9.0/10.1/10.2	6960
1/4'' NPT	6	680	0	12	12	-25	65	NBR	U133X01	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	7422

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-25
To	1/4''	6	680	10	75





Drawing 6960





Drawing 7422

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/8''	4	600	2	10	10	-25	50	NBR	341P01 [2]	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7302
	4	600	2	10	10	-25	80	NBR	341P01 [2]	8993	488980	-	-	2	2.5	1.1	7302
	4	600	2	10	10	-25	80	NBR	341P21 [12]	2995	481865	-	-	9	10	2.0	7296
	4	600	2	10	10	-25	80	NBR	341P21 [12]	4270	481000	-	-	8	8	2.1	7296
	4	600	2	10	10	-40	65	NBR/ PUR	341P2108 [2]	2995	481865	-	-	9	10	2.0	7296
	4	600	2	10	10	-40	65	NBR/ PUR	341P2108 [2]	4270	481000	-	-	8	8	2.1	7296
	4	600	2	-	10	-25	65	NBR/ PUR	341P2197 [2]	2995	482740	-	-	-	1.6	6.0/8.0	8027
	4	600	2	10	10	-25	65	NBR/ PUR	341P2197 [2]	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8027
	4	600	2	-	10	-25	65	NBR/ PUR	341P2197 [2]	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8027
	4	600	2	-	10	-25	65	NBR/ PUR	341P2197 [2]	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8027
	4	600	2	-	10	-25	55	NBR/ PUR	341P2197 [23]	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8027

Notes:
1.Pilot seat in FKM
2.With manual override
3.A minimum current of 65 mA is required with this coil configuration

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''	4	600	10	-40
To	1/8''	4	600	10	80



Drawing 7302



Drawing 7296



Drawing 8027

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4'''	15	600	2	-	10	-10	55	NBR	341P2190 12	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7351
	15	600	2	-	10	-10	75	NBR	341P2190 12	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7351
	15	600	2	-	10	-10	75	NBR	341P2190 12	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7351

Notes:
1.Pilot seat in FKM
2.A minimum current of 65 mA is required with this coil configuration



Drawing 7314

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''	7	600	10	-25
To	1/4''	15	1400	10	80



Drawing 7351



Drawing 8218



Drawing 8219

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4"	7	1250	2.5	10	10	-10	50	NBR	341P03$_{1}$	-	496131	-	-	3	3	1.2	8218
	7	1250	2.5	10	10	-10	50	NBR	341P03$_{1}$	-	496482	-	-	3	3	1.2	8218
	7	1250	2.5	10	10	-10	50	NBR	341P03$_{1}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8218
	7	1250	2.5	10	10	-20	50	NBR	341P33$_{1}$	2995	481865	-	-	9	10	2.0	8219
	7	1250	2.5	10	10	-20	50	NBR	341P33$_{1}$	-	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8219
	7	1250	2.5	10	10	-20	50	NBR	341P33$_{1}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8219
	8	1400	2	10	10	-25	80	NBR	341P02$_{1}$	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7314
	8	1400	2	10	10	-25	80	NBR	341P02$_{1}$	8993	488980	-	-	2	2.5	1.1	7314

Notes:
1.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	8	1400	10	-25
To	1/4''	8	1400	10	80



Drawing 7319



Drawing 7352



Drawing 8030

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4''	8	1400	2	10	10	-25	80	NBR	341P22$_{1}$	2995	481865	-	-	9	10	2.0	7319
	8	1400	2	10	10	-25	80	NBR	341P22$_{1}$	4270	481000	-	-	8	8	2.1	7319
	8	1400	2	-	10	-25	55	NBR	341P2290	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7352
	8	1400	2	-	10	-25	75	NBR	341P2290	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7352
	8	1400	2	-	10	-25	75	NBR	341P2290	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7352
	8	1400	2	-	10	-20	80	NBR/ PUR	341P2297$_{1}$	2995	482740	-	-	-	1.6	6.0/8.0	8030
	8	1400	2	10	10	-20	80	NBR/ PUR	341P2297$_{1}$	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8030
	8	1400	2	-	10	-20	80	NBR/ PUR	341P2297$_{1}$	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8030
	8	1400	2	-	10	-20	80	NBR/ PUR	341P2297$_{1}$	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8030
	8	1400	2	-	10	-20	55	NBR/ PUR	341P2297$_{12}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8030
1/2''	12	3000	2.5	10	10	-10	50	NBR	341P04$_{1}$	-	496131	-	-	3	3	1.2	8220
	12	3000	2.5	10	10	-10	50	NBR	341P04$_{1}$	-	496482	-	-	3	3	1.2	8220
	12	3000	2.5	10	10	-10	50	NBR	341P04$_{1}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8220
	12	3000	2.5	10	10	-10	50	NBR	341P34$_{1}$	2995	481865	-	-	9	10	2.0	8221
	12	3000	2.5	10	10	-10	50	NBR	341P34$_{1}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8221
	12	3000	2.5	10	10	-10	50	NBR	341P34$_{1}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8221

Notes:
1.With manual override
2.A minimum current of 65 mA is required with this coil configuration

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	8	1400	10	-10
To	1/2''	12	3000	10	50



Drawing 8220



Drawing 8221

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING

DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''	4	400	2	10	10	-25	80	NBR	347P01 [2]	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7306
	4	400	2	10	10	-25	80	NBR	347P01 [2]	8993	488980	-	-	2	2.5	1.1	7306
	4	400	2	10	10	-25	80	NBR	347P21 [12]	2995	481865	-	-	9	10	2.0	7298
	4	400	2	10	10	-25	80	NBR	347P21 [12]	4270	481000	-	-	8	8	2.1	7298
	4	400	2	-	10	-25	55	NBR	347P2190	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7353
	4	400	2	-	10	-25	75	NBR	347P2190	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7353
	4	400	2	-	10	-25	75	NBR	347P2190	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7353
	4	400	2	-	10	-20	65	NBR/ PUR	347P2197 [2]	2995	482740	-	-	-	1.6	6.0/8.0	8028
	4	400	2	10	10	-20	65	NBR/ PUR	347P2197 [2]	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8028
	4	400	2	-	10	-20	65	NBR/ PUR	347P2197 [2]	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8028
	4	400	2	-	10	-20	65	NBR/ PUR	347P2197 [2]	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8028
	4	400	2	-	10	-20	55	NBR/ PUR	347P2197 [23]	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8028

Notes:
1.Pilot seat in FKM
2.With manual override
3. A minimum current of 65 mA is required with this coil configuration



Drawing 8028

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''	4	400	10	-25
To	1/8''	4	400	10	80



Drawing 7306





Drawing 7298



Drawing 7353

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM

PIPE MOUNTING



DUAL SOLENOIDS

Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4"	7	1250	2.5	10	10	-20	50	NBR	347P03$_{2}$	-	496131	-	-	3	3	1.2	8222
	7	1250	2.5	10	10	-20	50	NBR	347P03$_{2}$	-	496482	-	-	3	3	1.2	8222
	7	1250	2.5	10	10	-20	50	NBR	347P03$_{2}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8222
	7	1250	2.5	10	10	-20	50	NBR	347P33$_{2}$	2995	481865	-	-	9	10	2.0	8223
	7	1250	2.5	10	10	-20	50	NBR	347P33$_{2}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8223
	7	1250	2.5	10	10	-20	50	NBR	347P33$_{2}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8223
	8	1400	2	10	10	-25	80	NBR	347P02$_{2}$	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7316
	8	1400	2	10	10	-25	80	NBR	347P02$_{2}$	8993	488980	-	-	2	2.5	1.1	7316
	8	1400	2	10	10	-25	80	NBR	347P22$_{12}$	2995	481865	-	-	9	10	2.0	7321
	8	1400	2	10	10	-25	80	NBR	347P22$_{12}$	4270	481000	-	-	8	8	2.1	7321

Notes:
1.Pilot seat in FKM
2.With manual override



Drawing 7321

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	7	1250	10	-25
To	1/4''	8	1400	10	80



Drawing 8222





Drawing 8223



Drawing 7316

5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

PILOT OPERATED

ANODIZED ALUMINIUM
PIPE MOUNTING
DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/2''	12	3000	2.5	10	10	-20	50	NBR	347P04 [1]	-	496131	-	-	3	3	1.2	8224
	12	3000	2.5	10	10	-20	50	NBR	347P04 [1]	-	496482	-	-	3	3	1.2	8224
	12	3000	2.5	10	10	-20	50	NBR	347P04 [1]	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8224
	12	3000	2.5	10	10	-20	50	NBR	347P34 [1]	2995	481865	-	-	9	10	2.0	8225
	12	3000	2.5	10	10	-20	50	NBR	347P34 [1]	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8225
	12	3000	2.5	10	10	-20	50	NBR	347P34 [1]	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8225

Notes:
1.With manual override

ANODIZED ALUMINIUM
PIPE MOUNTING
CONTROL BY ELECTRIC IMPULSE



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''	4	600	2	-	10	-25	80	NBR	345P21	4269	485400	-	-	-	13	4.0	8123

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''	4	600	10	-25
To	1/2''	12	3000	10	80



Drawing 8224



Drawing 8225



Drawing 8123

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING)

MANUAL RESET

BRASS

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4'' NPT	6	680	0	12	12	-25	65	NBR	U033X0111	-	492310	1-21	Ex e mb II T3 to T6	6	6	10.1/10.2/12.0	7641
	6	680	0	12	12	-25	65	NBR	U033X0111	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	10.1/10.2/12.0	7641

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-25
To	1/4''	6	680	10	65





Drawing 7641

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

NOTES

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

3/2
5/2
5/3

Actuation	Body	Function	Port Size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page
Direct Operated	Anodized aluminium/ NAMUR	Normally Closed	1/4''	6	680	10	75	330
Pilot Operated	Anodized aluminium/ NAMUR/Spool	Solenoid operated - spring return	1/8''-1/4''	4 to 8	1400	10	80	336
			1/4''	7 to 8	1400	10	80	332
			1/2''	12	3000	10	50	332
		Dual Solenoids	1/8''-1/4''	4	400	10	80	348
			1/4''	7 to 8	1400	10	120	350
			1/2''	12	3000	10	120	352
		W1 closed center position	1/8''-1/4''	4	400	10	80	354
			1/4''	4 to 7	1250	10	120	354
		W3 exhausted in center position	1/4''	7	1250	10	50	356
		Control by Electric Impulse	1/8''-1/4''	4	600	10	80	358
	Anodized aluminium/ NAMUR/Poppet	Solenoid operated - spring return	1/8''-1/4''	4	355	10	75	358
Air Operated	Anodized aluminium/ NAMUR	Air operated - spring return	1/8''-1/4''	4	600	10	80	364
			1/4''	7	1250	10	50	364
			1/2''	12	3000	10	50	364
		Air operated and return	1/4''	7	1250	10	50	364
		W1 closed center position	1/4''	7	1250	10	50	368

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
DIRECT OPERATED

ANODIZED ALUMINIUM
NAMUR
NORMALLY CLOSED



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4''	6	680	0	12	12	-25	75	NBR	131X1101	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1	7336
	6	680	0	12	12	-25	75	NBR	131X1101	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1	7336
	6	680	0	12	12	-25	75	NBR	131X1101	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1	7336
	6	680	0	12	12	-25	75	NBR	131X1101	-	496895	-	-	8	8	9.0/10.1	7336
	6	680	0	12	12	-25	65	NBR	131X1131 [1]	-	492310	1-21	Ex e mb II T3 to T6	-	6	10.1/10.2	7336
	6	680	0	12	12	-25	65	NBR	131X1131 [1]	-	496700	1-21	Ex d mb IIC T4 to T6	-	6	10.1/10.2	7336
	6	680	0	12	12	-25	65	NBR	131X1131 [1]	-	496895	-	-	-	8	10.1/10.2	7336
1/4'' NPT	6	680	0	12	12	-25	75	NBR	U131X1101	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	10.1/10.2	7336
	6	680	0	12	12	-25	65	NBR	U131X1101	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	10.1/10.2	7336
	6	680	0	12	12	-25	65	NBR	U131X1101	-	496895	-	-	8	8	10.1/10.2	7336

Notes:
1.DC voltage only. Minimum drop off voltage is 15% of nominal voltage (former DIN 19251)

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	6	680	10	-25
To	1/4"	6	680	10	75





Drawing 7336

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

SOLENOID OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4''	7	1250	2.5	10	10	-10	50	NBR	331N03$_{1}$	-	496131	-	-	3	3	1.2	8056
	7	1250	2.5	10	10	-10	50	NBR	331N03$_{1}$	-	496482	-	-	3	3	1.2	8056
	7	1250	2.5	10	10	-10	50	NBR	331N03$_{1}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8056
1/2''	12	3000	2	10	10	-10	50	NBR	331N04$_{1}$	-	496131	-	-	3	3	1.2	8060
	12	3000	2	10	10	-10	50	NBR	331N04$_{1}$	-	496482	-	-	3	3	1.2	8060
	12	3000	2	10	10	-10	50	NBR	331N04$_{1}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8060

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	7	1250	10	-10
To	1/2"	12	3000	10	50



Drawing 8056



Drawing 8060

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

SOLENOID OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/2''	12	3000	2.5	10	10	-10	50	NBR	331N34$_{1}$	2995	481865	-	-	9	10	2.0	8210
	12	3000	2.5	10	10	-10	50	NBR	331N34$_{1}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8210
	12	3000	2.5	10	10	-10	50	NBR	331N34$_{1}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8210

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	12	3000	10	-10
To	1/2"	12	3000	10	50



Drawing 8210

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
PILOT OPERATED

ANODIZED ALUMINIUM
NAMUR
SOLENOID OPERATED - SPRING RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''-1/4''	4	600	2	10	10	-25	80	NBR	341N01 12	8993	488980	-	-	2	2.5	1.1	7301
	4	600	2	10	10	-25	80	NBR	341N11 12	8993	488980	-	-	2	2.5	1.1	7300
	4	600	2	10	10	-25	80	NBR	341N21 2	2995	481865	-	-	9	10	2.0	7311
	4	600	2	10	10	-25	80	NBR	341N21 2	4270	481000	-	-	8	8	2.1	7311
	4	600	2	-	10	-25	55	NBR	341N2190 2	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0/8.0	7874
	4	600	2	-	10	-25	55	NBR	341N2190 2	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0/8.0	7874

Notes:
1.With captured exhaust
2.With manual override



Drawing 7874

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	600	10	-25
To	1/8''-1/4''	4	600	10	80



Drawing 7301





Drawing 7300



Drawing 7311

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
PILOT OPERATED

ANODIZED ALUMINIUM
NAMUR
SOLENOID OPERATED - SPRING RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
	4	600	2	10	10	-25	80	NBR	341N31$_{3}$	2995	481865	-	-	9	10	2.0	7295
	4	600	2	10	10	-25	80	NBR	341N31$_{3}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	7295
	4	600	2	10	10	-25	65	NBR	341N31$_{3}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	7295
	4	600	2	10	10	-25	80	NBR	341N3102	2995	481865	-	-	9	10	2.0	7295
	4	600	2	10	10	-40	65	NBR	341N3108$_{3}$	2995	481865	-	-	9	10	2.0	7295
	4	600	2	10	10	-40	65	NBR	341N3108$_{3}$	4270	481000	-	-	8	8	2.1	7295
	4	600	2	10	10	-40	65	NBR	341N3128	2995	481865	-	-	9	10	2.0	7295
	4	600	2	10	10	-40	65	NBR	341N3128	4270	481865	-	-	9	10	2.0	7295
	4	600	2	-	10	-25	80	NBR	341N3130$_{13}$	2995	481865	-	-	-	10	2.0	7295
	4	600	2	-	10	-25	40	NBR	341N3130$_{13}$	-	492190	1-21	Ex e mb IIC T3/T4	-	9	2.1	7295
	4	600	2	-	10	-25	80	NBR	341N3130$_{13}$	-	495905	1-21	Ex d mb IIC T4	-	8	2.1	7295
1/8''-1/4''	4	600	2	-	10	-10	55	NBR	341N3190	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7349
	4	600	2	-	10	-10	75	NBR	341N3190	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7349
	4	600	2	-	10	-10	75	NBR	341N3190	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7349
	4	600	2	-	10	-25	65	NBR	341N3196	2995	482740	-	-	-	1.6	6.0/8.0	8017
	4	600	2	10	10	-25	65	NBR	341N3196	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8017
	4	600	2	-	10	-25	65	NBR	341N3196	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8017
	4	600	2	-	10	-25	55	NBR	341N3196$_{24}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8017
	4	600	2	-	10	-25	65	NBR	341N3196	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8017
	4	600	2	-	10	-25	65	NBR	341N3197$_{3}$	2995	482740	-	-	-	1.6	6.0/8.0	8017
	4	600	2	10	10	-25	65	NBR	341N3197$_{3}$	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8017
	4	600	2	-	10	-25	65	NBR	341N3197$_{3}$	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8017
	4	600	2	-	10	-25	65	NBR	341N3197$_{3}$	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8017
	4	600	2	-	10	-25	55	NBR	341N3197$_{34}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8017

Notes:
1.DC voltage only. Minimum drop off voltage is 15% of nominal voltage (former DIN 19251)
2.With captured exhaust
3.With manual override
4. A minimum current of 65 mA is required with this coil configuration

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	600	10	-40
To	1/8''-1/4''	4	600	10	80



Drawing 7295



Drawing 7349



Drawing 8017

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
PILOT OPERATED

ANODIZED ALUMINIUM
NAMUR
SOLENOID OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
BSP	1 mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4"	8	1400	2	-	10	-25	55	NBR	341N3290	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7350
	8	1400	2	-	10	-25	75	NBR	341N3290	-	488660.01	0-20	Ex ia IIC T6	-	0.3 to 3	7.0	7350
	8	1400	2	-	10	-25	75	NBR	341N3290	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	7350
	8	1400	2	-	10	-25	65	NBR	341N3296	2995	482740	-	-	-	1.6	6.0/8.0	8029
	8	1400	2	10	10	-25	65	NBR	341N3296	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8029
	8	1400	2	-	10	-25	65	NBR	341N3296	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8029
	8	1400	2	-	10	-20	80	NBR	341N3296	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8029
	8	1400	2	-	10	-20	55	NBR	341N3296$_{2}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8029
	8	1400	2	-	10	-25	65	NBR	341N3297$_{1}$	2995	482740	-	-	-	1.6	6.0/8.0	8029
	8	1400	2	10	10	-25	65	NBR	341N3297$_{1}$	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8029
	8	1400	2	-	10	-25	65	NBR	341N3297$_{1}$	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8029
	8	1400	2	-	10	-20	80	NBR	341N3297$_{1}$	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8029
	8	1400	2	-	10	-20	55	NBR	341N3297$_{12}$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	8029
	7	1250	2.5	10	10	-10	50	NBR	341N05$_{1}$	-	496131	-	-	3	3	1.2	8162
	7	1250	2.5	10	10	-10	50	NBR	341N05$_{1}$	-	496482	-	-	3	3	1.2	8162
	7	1250	2.5	10	10	-10	50	NBR	341N05$_{1}$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8162

Notes:
1.With manual override
2. A minimum current of 65 mA is required with this coil configuration

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	7	1250	10	-25
To	1/4''	8	1400	10	80



Drawing 7350



Drawing 8029





Drawing 8162

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
PILOT OPERATED

ANODIZED ALUMINIUM
NAMUR
SOLENOID OPERATED - SPRING RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4"	7	1200	2.5	10	10	-10	50	NBR	341N0502	-	496131	-	-	3	3	1.2	8253
	7	1200	2.5	10	10	-10	50	NBR	341N0502	-	496482	-	-	3	3	1.2	8253
	7	1200	2.5	10	10	-10	50	NBR	341N35$_3$	2995	481865	-	-	9	10	2.0	8213
	7	1200	2.5	10	10	-10	50	NBR	341N35$_3$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8213
	7	1200	2.5	10	10	-10	50	NBR	341N35$_3$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8213
	7	1200	2.5	10	10	-10	50	NBR	341N3502	2995	481865	-	-	9	10	2.0	8254
	7	1200	2.5	10	10	-10	50	NBR	341N3502	4270	481000	-	-	8	8	2.1	8254
	8	1400	2	10	10	-25	80	NBR	341N02$_{23}$	8993	488980	-	-	2	2.5	1.1	7313

Notes:
2.With captured exhaust
3.With manual override



Drawing 7313

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	7	1200	10	-25
To	1/4"	8	1400	10	80





Drawing 8253



Drawing 8213



Drawing 8254

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR



SOLENOID OPERATED - SPRING RETURN

Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
BSP	1 mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4"	8	1400	2	10	10	-25	80	NBR	341N12$_{23}$	8993	488980	-	-	2	2.5	1.1	7312
	8	1400	2	10	10	-25	80	NBR	341N22$_{3}$	2995	481865	-	-	9	10	2.0	7318
	8	1400	2	10	10	-25	80	NBR	341N22$_{3}$	4270	481000	-	-	8	8	2.1	7318
	8	1400	2	10	10	-25	80	NBR	341N32$_{3}$	2995	481865	-	-	9	10	2.0	7317
	8	1400	2	10	10	-25	80	NBR	341N32$_{3}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	7317
	8	1400	2	10	10	-25	80	NBR	341N32$_{3}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	7317
	8	1400	2	10	10	-25	80	NBR	341N3202	2995	481865	-	-	9	10	2.0	7317
	8	1400	2	10	10	-25	80	NBR	341N3202	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	7317
	8	1400	2	10	10	-25	80	NBR	341N3202	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	7317

Notes:
2.With captured exhaust
3.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	8	1400	10	-25
To	1/4"	8	1400	10	80



Drawing 7312



Drawing 7318



Drawing 7317

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

SOLENOID OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4''	7	1250	2.5	10	10	-20	50	NBR	341N03$_3$	-	496131	-	-	3	3	1.2	8063
	7	1250	2.5	10	10	-20	50	NBR	341N03$_3$	-	496482	-	-	3	3	1.2	8063
	7	1250	2.5	10	10	-20	50	NBR	341N03$_3$	-	496637	22	Ex nAc nCc IIC T5 IP65	3	3	1.2	8063
1/2''	12	3000	2	10	10	-10	50	NBR	341N04$_3$	-	496131	-	-	3	3	1.2	8065
	12	3000	2	10	10	-10	50	NBR	341N04$_3$	-	496482	-	-	3	3	1.2	8065
	12	3000	2	10	10	-10	50	NBR	341N04$_3$	-	496637	22	Ex tD A22 IP65 - T95°C	3	3	1.2	8065
	12	3000	2.5	10	10	-20	50	NBR	341N34$_3$	2995	481865	-	-	9	10	2.0	8211
	12	3000	2.5	10	10	-20	50	NBR	341N34$_3$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8211
	12	3000	2.5	10	10	-20	50	NBR	341N34$_3$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8211

Notes:
3.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	7	1250	10	-10
To	1/2"	12	3000	10	50



Drawing 8063



Drawing 8065



Drawing 8211

5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''-1/4''	4	400	2	10	10	-25	50	NBR	347N11 12	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7305
	4	400	2	10	10	-25	80	NBR	347N11 12	8993	488980	-	-	2	2.5	1.1	7305
	4	400	2	10	10	-25	80	NBR	347N31 2	2995	481865	-	-	9	10	2.0	7297
	4	400	2	10	10	-25	80	NBR	347N31 2	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	7297
	4	400	2	10	10	-25	80	NBR	347N31 2	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	7297
	4	400	2	-	10	-25	55	NBR	347N3190	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	8141
	4	400	2	-	10	-25	65	NBR	347N3197 2	2995	482740	-	-	-	1.6	3.0/6.0/8.0	7297
	4	400	2	10	10	-25	65	NBR	347N3197 2	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	3.0/6.0/8.0	7297
	4	400	2	-	10	-25	65	NBR	347N3197 2	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	3.0/6.0/8.0	7297
	4	400	2	-	10	-25	65	NBR	347N3197 2	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	3.0/6.0/8.0	7297
	4	400	2	-	10	-25	55	NBR	347N3197 23	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	7297

Notes:
1.With captured exhaust
2.With manual override
3.A minimum current of 65 mA is required with this coil configuration

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	400	10	-25
To	1/8''-1/4''	4	400	10	80





Drawing 7305



Drawing 7297



Drawing 8141

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
PILOT OPERATED

ANODIZED ALUMINIUM
NAMUR
DUAL SOLENOIDS



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4"	7	1250	1.5	10	10	-10	50	NBR	347N03 $_{2}$	-	496131	-	-	3	3	1.2	8057
	7	1250	1.5	10	10	-10	50	NBR	347N03 $_{2}$	-	496482	-	-	3	3	1.2	8057
	7	1250	1.5	10	10	-10	50	NBR	347N03 $_{2}$	-	496637	22	Ex nAc nCc IIC T5 IP65	3	3	1.2	8057
	7	1250	2.5	10	10	-10	120	NBR	347N33 $_{2}$	2995	481865	-	-	9	10	2.0	8209
	7	1250	2.5	10	10	-10	120	NBR	347N33 $_{2}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8209
	7	1250	2.5	10	10	-10	120	NBR	347N33 $_{2}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8209
	8	1400	2	10	10	-10	65	NBR	347N12 $_{12}$	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7315
	8	1400	2	10	10	-25	80	NBR	347N12 $_{12}$	8993	488980	-	-	2	2.5	1.1	7315
	8	1400	2	10	10	-25	80	NBR	347N32 $_{2}$	2995	481865	-	-	9	10	2.0	7320
	8	1400	2	10	10	-25	80	NBR	347N32 $_{2}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	7320
	8	1400	2	10	10	-25	80	NBR	347N32 $_{2}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	7320

Notes:
1.With captured exhaust
2.With manual override
3.A minimum current of 65 mA is required with this coil configuration





Drawing 7320

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	7	1250	10	-25
To	1/4"	8	1400	10	120





Drawing 8057





Drawing 8209





Drawing 7315

5/2

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

DUAL SOLENOIDS



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/2"	12	3000	1.5	10	10	-10	50	NBR	347N04$_2$	-	496131	-	-	3	3	1.2	8154
	12	3000	1.5	10	10	-10	50	NBR	347N04$_2$	-	496482	-	-	3	3	1.2	8154
	12	3000	1.5	10	10	-10	50	NBR	347N04$_2$	-	496637	22	Ex nAc nCc IIC T5 IP65	3	3	1.2	8154
	12	3000	2.5	10	10	-10	120	NBR	347N34$_2$	2995	481865	-	-	9	10	2.0	8212
	12	3000	2.5	10	10	-10	120	NBR	347N34$_2$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8212
	12	3000	2.5	10	10	-10	120	NBR	347N34$_2$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8212

Notes:
1.With captured exhaust
2.With manual override
3.A minimum current of 65 mA is required with this coil configuration

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/2"	12	3000	10	-10
To	1/2"	12	3000	10	120



Drawing 8154



Drawing 8212

5/3

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

W1 CLOSED CENTER POSITION



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''-1/4''	4	400	2	10	10	-25	80	NBR	342N11 [12]	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7305
	4	400	2	10	10	-25	80	NBR	342N11 [12]	8993	488980	-	-	2	2.5	1.1	7305
1/4''	4	400	2	-	10	-10	65	NBR	342N3197 [2]	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	7297
	4	400	2	-	10	-10	55	NBR	342N3197 [23]	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	6.0/7.0/8.0	7297
	7	1250	3	10	10	-20	50	NBR	342N03 [2]	-	496131	-	-	3	3	1.2	8057
	7	1250	3	10	10	-20	50	NBR	342N03 [2]	-	496482	-	-	3	3	1.2	8057
	7	1250	3	10	10	-10	50	NBR	342N03 [2]	-	496637	22	Ex nAc nCc IIC T5 IP65	3	3	1.2	8057
	7	1250	2.5	10	10	-20	50	NBR	342N33 [2]	2995	481865	-	-	9	10	2.0	8209
	7	1250	2.5	10	10	-20	50	NBR	342N33 [2]	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1	8209
	7	1250	2.5	10	10	-20	50	NBR	342N33 [2]	-	495905	1-21	Ex d mb IIC T4	8	8	2.1	8209

Notes:
1.With captured exhaust
2.With manual override
3.A minimum current of 65 mA is required with this coil configuration





Drawing 8209

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	400	10	-25
To	1/4''	7	1250	10	120





Drawing 7305



Drawing 7297



Drawing 8057

5/3 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR



W3 EXHAUSTED IN CENTER POSITION

Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
	7	1250	3	10	10	-20	50	NBR	343N03$_{1}$	-	496131	-	-	3	3	1.2	8057
1/4''	7	1250	3	10	10	-20	50	NBR	343N03$_{1}$	-	496482	-	-	3	3	1.2	8057
	7	1250	3	10	10	-10	50	NBR	343N03$_{1}$	-	496637	22	Ex nAc nCc IIC T5 IP65	3	3	1.2	8057

Notes:
1.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	7	1250	10	-10
To	1/4''	7	1250	10	50





Drawing 8057

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR

CONTROL BY ELECTRIC IMPULSE



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''-1/4''	4	600	2	-	10	-25	80	FKM/NBR	345N31 $_{12}$	4269	485400	-	-	-	13	4.0	7295

Notes:
1.Pilot seat in FKM
2.With manual override

ANODIZED ALUMINIUM

NAMUR

SOLENOID OPERATED - SPRING RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/8''-1/4''	4	355	1	10	10	-10	75	NBR	341L9504 $_{12}$	-	482605	1-21	Ex mb IIC T4	4	5	1.1	7009
	4	355	1	10	10	-10	75	NBR	341L9504 $_{12}$	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7009
	4	355	1	10	10	-10	75	NBR	341L9504 $_{12}$	8993	488980	-	-	2	2.5	1.1	7009
	4	355	1	10	10	-10	75	NBR	341L9504 $_{12}$	8993	495865	2-22	Ex nAC IIC T5	2	2.5	1.1	7009
	4	355	1	10	10	-10	75	NBR	341L9534 $_{12}$	2995	481865	-	-	9	10	2.0	3990
	4	355	1	10	10	-10	75	NBR	341L9534 $_{12}$	2995	495870	2-22	Ex nAC IIC T3/T4	8	9	2.1/7.0	3990
	4	355	1	10	10	-10	75	NBR	341L9534 $_{12}$	-	495905	1-21	Ex d mb IIC T4	8	8	2.1/7.0	3990

Notes:
1.Pilot seat in FKM
2.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	355	10	-25
To	1/8''-1/4''	4	600	10	80



Drawing 7295



Drawing 7009



Drawing 3990

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

PILOT OPERATED

ANODIZED ALUMINIUM

NAMUR



SOLENOID OPERATED - SPRING RETURN

Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/8''-1/4''	4	355	2	-	10	-10	55	NBR	341L9594 [1]	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	3992
	4	355	1	-	10	-10	75	NBR	341L9594 [1]	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	7.0	3992
	4	355	2	-	10	-10	75	NBR/PUR	341L9597 [2]	2995	482740	-	-	-	1.6	6.0/8.0	8025
	4	355	2	10	10	-10	75	NBR/PUR	341L9597 [2]	-	495900	1-21	Ex d mb IIC T4 to T6	2.5	2	6.0/8.0	8025
	4	355	2	-	10	-10	75	NBR/PUR	341L9597 [2]	-	495910	0-20	Ex ia IIC T4 to T6	-	0.3 to 3	6.0/8.0	8025
	4	355	2	-	10	-10	75	NBR/PUR	341L9597 [2]	2995	496125	2-22	Ex nAC IIC T5/T6	-	1.6	6.0/8.0	8025
	4	355	2	-	10	-25	55	NBR/PUR	341L9598	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	3992

Notes:
1.Pilot seat in FKM
2.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	355	10	-25
To	1/8''-1/4''	4	355	10	75



Drawing 3992



Drawing 8025

3/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

EXTERNALLY OPERATED

ANODIZED ALUMINIUM

NAMUR

AIR OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4''	7	1250	2.5	10	10	-10	50	NBR	531N03	-	-	-	-	-	-	-	8058
1/2''	12	3000	2.5	10	10	-10	50	NBR	531N04	-	-	-	-	-	-	-	8061

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	7	1250	10	-10
To	1/2"	12	3000	10	50



Drawing 8058



Drawing 8061

3/2-5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

EXTERNALLY OPERATED

ANODIZED ALUMINIUM

NAMUR

AIR OPERATED - SPRING RETURN



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
BSP	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/8''-1/4''	4	600	2	10	10	-40	50	NBR	541N0108	-	-	-	-	-	-	-	7309

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/8''-1/4''	4	600	10	-40
To	1/8''-1/4''	4	600	10	80



Drawing 7309

5/2 3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)

EXTERNALLY OPERATED

ANODIZED ALUMINIUM

NAMUR

AIR OPERATED - SPRING RETURN

5/2 FUNCTION



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4''	7	1250	2.5	10	10	-10	50	NBR	**541N03**	-	-	-	-	-	-	-	8064
1/2''	12	3000	2.5	10	10	-10	50	NBR	**541N04**	-	-	-	-	-	-	-	8066

ANODIZED ALUMINIUM

NAMUR

AIR OPERATED AND RETURN



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4''	7	1250	2.5	10	10	-10	50	NBR	**547N03**	-	-	-	-	-	-	-	8059

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	7	1250	10	-10
To	1/2"	12	3000	10	50



Drawing 8064



Drawing 8066



Drawing 8059

5/3

3 & 5 WAY PNEUMATIC VALVES FOR ACTUATOR CONTROL (NAMUR)
EXTERNALLY OPERATED

ANODIZED ALUMINIUM
NAMUR
W1 CLOSED CENTER POSITION



Port size BSP	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4''	7	1250	2.5	10	10	-10	50	NBR	542N03	-	-	-	-	-	-	-	8059

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	7	1250	10	-10
To	1/4''	7	1250	10	50



Drawing 8059

NOTES

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

3/2
5/2

Actuation	Body	Function	Port Size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Max Fluid Temp. (°C)	Page Parker Valves
Direct Operated	316L Stainless St./Pipe mounting	Universal	1/4''	2 to 6	680	12	75	371
			3/8''	6	680	10	75	380
	316L Stainless St./Sub-base mounting	Normally Closed	5 mm	2.5	220	12	14	382
		Universal	1/4''	6	680	10	65	382
	316L Stainless St./ NAMUR	Normally Closed	3/8''	6	680	10	75	384
Pilot Operated	316L Stainless St./Pipe mounting	Normally Closed	3/8''	8	1400	10	80	386
	316L Stainless St./Pipe mounting/Spool	Normally Closed	3/8''	8	1400	10	80	386
		Dual Solenoids	3/8''	8	1400	10	80	390
	316L Stainless St./ NAMUR/Spool	Normally Closed	3/8''-1/4''	8	1400	10	80	392
		Solenoid operated - spring return	3/8''-1/4''	8	1400	10	80	394
		Dual Solenoids	3/8''-1/4''	8	1400	10	80	396
Manual Reset	316L Stainless St./Pipe mounting	Universal	1/4''	6	680	10	65	398
			3/8''	6	680	10	65	404

3/2 3 WAY VALVES DIRECT OPERATED

V SERIES - STAINLESS STEEL VALVES FOR PIPE MOUNTING

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø	Flow factor			Operating Pressure Differential Min	Max(MOPD)		Fluid Temp. Min	Max	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	mm	Kv l/min	KV m³/h	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
	2	2.5	0.15	140	0	-	12	-25	65	FKM	U133V5595 [1]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1	8024
	2	2.5	0.15	140	0	12	12	-25	65	FKM	U133V5595 [1]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1	6713
	2	2.5	0.15	140	0	12	12	-25	65	FKM	U133V5595 [1]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1	8024
	2	2.5	0.15	140	0	12	12	-25	65	FKM	U133V5595 [1]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1	8024
	2	2.5	0.15	140	0	12	12	-25	50	FKM	U133V5595 [1]	-	496895	-	-	8	8	9.0/10.1	8024
	2	2.5	0.15	140	0	-	12	-25	65	FKM	U133V7595	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.3	8166
	2	2.5	0.15	140	0	12	12	-25	65	FKM	U133V7595	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.3	8166
	2	2.5	0.15	140	0	12	12	-25	65	FKM	U133V7595	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.3	8299
1/4" NPT	2	2.5	0.15	140	0	12	12	-25	50	FKM	U133V7595	-	496895	-	-	8	8	9.0/10.1/10.3	8166
	2.5	3.5	0.21	220	0	-	8.5	-25	65	FKM	U133V5695 [1]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1	8024
	2.5	3.5	0.21	220	0	8.5	8.5	-25	75	FKM	U133V5695 [1]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1	6713
	2.5	3.5	0.21	220	0	8.5	8.5	-25	65	FKM	U133V5695 [1]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1	8024
	2.5	3.5	0.21	220	0	8.5	8.5	-25	65	FKM	U133V5695 [1]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1	8024
	2.5	3.5	0.21	220	0	8.5	8.5	-25	50	FKM	U133V5695 [1]	-	496895	-	-	8	8	9.0/10.1	8024
	2.5	3.5	0.21	220	0	-	8.5	-25	65	FKM	U133V7695	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.3	8166
	2.5	3.5	0.21	220	0	8.5	8.5	-25	65	FKM	U133V7695	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.3	8166
	2.5	3.5	0.21	220	0	8.5	8.5	-25	65	FKM	U133V7695	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.3	8299
	2.5	3.5	0.21	220	0	8.5	8.5	-25	50	FKM	U133V7695	-	496895	-	-	8	8	9.0/10.1/10.3	8166

Notes:
1. Valve delivered with an individual material traceability certificate (2.2 following EN10204)

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4"	2	140	8.5	-25
To	1/4"	2.5	220	12	75



Drawing 8024



Drawing 6713



Drawing 8299

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4" NPTF	6	680	0	12	12	-25	65	NBR	U133X5156$_{24}$	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	7770
	6	680	0	12	12	-25	65	NBR	U133X5156$_{24}$	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	7770
	6	680	0	12	12	-25	65	NBR	U133X5196$_{2}$	-	492210	1-21	Ex e mb II T3 to T6	-	1.8	9.0/10.1/10.2	6904
	6	680	0	12	12	-25	65	NBR	U133X5196$_{2}$	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	6904
	6	680	0	12	12	-25	65	NBR	U133X5196$_{2}$	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	6904

Notes:
1.DC voltage only (or coil with rectifier). Minimum drop off voltage is 15% of nominal voltage (former DIN 19251)
2.Valve delivered with an individual material traceability certificate (2.2 following EN10204)
3.Valve only compatible with hydraulic oil and air/neutral gases
4.With manual override

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-25
To	1/4''	6	680	10	75





Drawing 7770





Drawing 6904

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max(MOPD)		Min	Max										
NPT	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4" NPTF	6	680	0	12	12	-40	65	VMQ	U133X7759$_{1-2}$	-	496895	-	-	8	8	9.0/10.1/10.2/10.3	8544
	6	680	0	-	12	-40	65	VMQ	U133X7759$_{1-2}$	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2/10.3	8539
	6	680	0	12	12	-40	65	VMQ	U133X7759$_{1-2}$	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.2/10.3	8537
	6	680	0	12	12	-40	65	VMQ	U133X7759$_{1-2}$	-	496700	1-21	Ex db mb IIC T4 to T6	6	6	9.0/10.1/10.2/10.3	8545
	6	680	0	12	12	-40	65	VMQ	U133X7759$_{1-2}$	-	492310	1-21	Ex mb II T4 to T5	9	8	9.0/10.1/10.2/10.3	8546
	6	680	0	-	12	-40	65	VMQ	U133X7759$_{1-2}$	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1.8	9.0/10.1/10.2/10.3	8546
	6	680	0	12	12	-40	65	VMQ	U133X7709$_{1}$	-	496895	-	-	8	8	9.0/10.1/10.2/10.3	8551
	6	680	0	-	12	-40	65	VMQ	U133X7709$_{1}$	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2/10.3	8550
	6	680	0	12	12	-40	65	VMQ	U133X7709$_{1}$	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.2/10.3	8538
	6	680	0	12	12	-40	65	VMQ	U133X7709$_{1}$	-	496700	1-21	Ex db mb IIC T4 to T6	6	6	9.0/10.1/10.2/10.3	8549
	6	680	0	12	12	-40	65	VMQ	U133X7709$_{1}$	-	492310	1-21	Ex mb II T4 to T5	9	8	9.0/10.1/10.2/10.3	8548
	6	680	0	-	12	-40	65	VMQ	U133X7709$_{1}$	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1.8	9.0/10.1/10.2/10.3	8548

Notes:
1. Valve delivered with an individual material traceability certificate (2.2 following EN10204)
2. With manual override



Drawing 8539

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	12	-25
To	1/4''	6	680	12	65





Drawing 8537



Drawing 8545





Drawing 8546

3/2 316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)



Drawing 8551



Drawing 8550





Drawing 8538

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-25
To	1/4''	6	680	10	65



Drawing 8549





Drawing 8548

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

DIRECT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8'' NPTF	6	680	0	12	12	-25	75	NBR	U133X5296 [1]	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1/10.2	7669
	6	680	0	12	12	-25	65	NBR	U133X5296 [1]	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	7669
	6	680	0	12	12	-25	65	NBR	U133X5296 [1]	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	7669

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''	6	680	10	-25
To	3/8''	6	680	10	75





Drawing 7669

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

DIRECT OPERATED

316L STAINLESS ST.

SUB-BASE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factor			Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max										
	mm	Kv l/min	KV m³/h	Qn l'min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
SB	2.5	3.5	0.21	220	0	-	12	-25	75	FKM	U131F5295 [1]	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2	8174
	2.5	3.5	0.21	220	0	12	12	-25	65	FKM	U131F5295 [1]	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8174
	2.5	3.5	0.21	220	0	12	12	-25	65	FKM	U131F5295 [1]	-	496560	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2	8174
	2.5	3.5	0.21	220	0	-	12	-25	75	FKM	U131F5295 [1]	-	492210	1-21	Ex eb mb IIC T5 to T6	-	1 to 1.8	9.0/10.1/10.2	8343
	2.5	3.5	0.21	220	0	12	12	-25	75	FKM	U131F5295 [1]	-	492310	1-21	Ex mb II T4 to T5	6	6	9.0/10.1/10.2	8343
	2.5	3.5	0.21	220	0	12	12	-25	50	FKM	U131F5295 [1]	-	496895	-	-	8	8	9.0/10.1/10.2	8174
	2.5	3.5	0.21	220	0	-	12	-25	50	FKM	U131F7695	-	496565	0-20	Ex ia IIC T4 to T6	-	0.3	9.0/10.1/10.2/10.3	8174
	2.5	3.5	0.21	220	0	12	12	-25	75	FKM	U131F7695	-	497105	1-21	Ex db IIC T4 to T6	8	8	9.0/10.1/10.2/10.3	8302
	2.5	3.5	0.21	220	0	12	12	-25	65	FKM	U131F7695	-	496800	1-21	Ex db mb IIC T4	8	8	9.0/10.1/10.2/10.3	8174
	2.5	3.5	0.21	220	0	12	12	-25	50	FKM	U131F7695	-	496895	-	-	8	8	9.0/10.1/10.2/10.3	8174

Notes:
1. Valve only compatible with air and neutral gases

316L STAINLESS ST.

SUB-BASE MOUNTING

UNIVERSAL



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
	1		Min	Max (MOPD)		Min	Max										
	mm	Qn l/min	bar	AC bar	DC bar	°C	°C							AC W	DC W		
1/4" NPTF	6	680	0	12	12	-25	65	FKM	U133X5195 [1]	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1/10.2	3572
	6	680	0	12	12	-25	65	FKM	U133X5195 [1]	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	3572

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)



Drawing 8343

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	SB	2.5	220	10	-25
To	SB	6	680	14	80



Drawing 8174





Drawing 3572



Drawing 8302

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

DIRECT OPERATED

316L STAINLESS ST.

SUB-BASE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4'' NPTF	6	680	0	12	12	-25	65	FKM	U133X7195	-	492210	1-21	Ex e mb II T3 to T6	-	1.8	9.0/10.1/10.2	8172
	6	680	0	12	12	-25	65	FKM	U133X7195	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	8172
	6	680	0	12	12	-25	65	FKM	U133X7195	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	8172

316L STAINLESS ST.

NAMUR

NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8'' NPT	6	680	0	12	12	-25	65	NBR	U131X1201 [1]	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1/10.2	7668
	6	680	0	12	12	-25	75	NBR	U131X1201 [1]	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1/10.2	7668
	6	680	0	12	12	-25	65	NBR	U131X1201 [1]	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	9.0/10.1/10.2	7668

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-25
To	3/8''	6	680	10	75



Drawing 8172





Drawing 7668

5/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8" NPT	8	1400	2	10	10	-25	80	NBR	U441P3250 $_{12}$	4270	481000	-	-	8	8	2.1	7565
	8	1400	2	10	10	-25	80	NBR	U441P3250 $_{12}$	2995	481865	-	-	9	10	2.0	7565

Notes:
1.Pilot seat in FKM
2.Valve with external pilot pressure minimum 4 bar

316L STAINLESS ST.
PIPE MOUNTING
NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8" 1/4" NPT	8	1400	2	10	10	-25	80	NBR	U341P0250 $_{123}$	8993	481045	-	-	2	2.5	1.1	7578
	8	1400	2	10	10	-25	80	NBR	U341P0250 $_{123}$	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7578
1/4" 3/8" NPT	8	1400	2	10	10	-25	80	NBR	U341P3250 $_{1}$	4270	481000	-	-	8	8	2.1	7558
	8	1400	2	10	10	-25	80	NBR	U341P3250 $_{1}$	2995	481865	-	-	9	10	2.0	7558
	8	1400	2	10	10	-25	80	NBR	U341P3250 $_{1}$	2995	481865	-	-	9	10	2.0	7558

Notes:
1.Pilot seat in FKM
2.With captured exhaust
3.With manual override

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''	8	1400	10	-25
To	3/8''	8	1400	10	80





Drawing 7565



Drawing 7578



Drawing 7558

5/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8" NPT	8	1400	2	-	10	-25	55	NBR	U341P3292$_1$	2995	483580.01	0-20	Ex ia IIC T6	-	0.5 to 3	7.0	7560
	8	1400	2	10	10	-25	75	NBR	U341P3295$_1$	-	492310	1-21	Ex e mb II T3 to T6	6	6	9.0/10.1	7561
	8	1400	2	-	10	-25	75	NBR	U341P3295$_1$	-	492965.01	0-20	Ex ia IIC T6	-	0.3 to 3	9.0/10.1	7561

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''	8	1400	10	-25
To	3/8''	8	1400	10	75



Drawing 7560





Drawing 7561

5/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.

PIPE MOUNTING

DUAL SOLENOIDS



Port size	Orifice Ø 1 mm	Flow factor Qn l'min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8'' NPT	8	1400	2	10	10	-25	80	NBR	U347P3250 [1]	4270	481000	-	-	8	8	2.1	7563
	8	1400	2	10	10	-25	80	NBR	U347P3250 [1]	-	483371	1-21	Ex e mb IIC T4	8	8	2.1	7563
	8	1400	2	10	10	-25	75	NBR	U347P3295 [1]	-	492310	1-21	Ex e mb II T3 to T6	6	6	10.1	7564
	8	1400	2	10	10	-25	75	NBR	U347P3295 [1]	-	496800	1-21	Ex d mb IIC T4	8	8	10.1	7564

Notes:
1.Pilot seat in FKM

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''	8	1400	10	-25
To	3/8''	8	1400	10	80



Drawing 7563





Drawing 7564

3/2-5/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.

NAMUR

NORMALLY CLOSED



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8''-1/4'' NPT	8	1400	2	10	10	-25	80	NBR	U341N3250 [1]	2995	481865	-	-	9	10	2.0	7554
	8	1400	2	10	10	-25	80	NBR	U341N3250 [1]	-	492190	1-21	Ex e mb IIC T3/T4	11	9	2.1	7554
	8	1400	2	-	10	-25	55	NBR	U341N3292 [1]	2995	483580.01	0-20	Ex ia IIC T6	-	0.5	7.0	7556
	8	1400	2	10	10	-25	75	NBR	U341N3295 [1]	-	492310	1-21	Ex e mb II T3 to T6	6	6	10.1	7696
	8	1400	2	10	10	-25	75	NBR	U341N3295 [1]	-	496800	1-21	Ex d mb IIC T4	8	8	10.1	7696

Notes:
1.Pilot seat in FKM
2.With captured exhaust
3.With manual override

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''-1/4''	8	1400	10	-25
To	3/8''-1/4''	8	1400	10	80



Drawing 7554



Drawing 7556





Drawing 7696

3/2-5/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.

NAMUR

SOLENOID OPERATED - SPRING RETURN



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8''-1/4''NPT	8	1400	2	10	10	-25	80	NBR	U341N0250 123	-	482606	1-21	Ex mb IIC T4/T5	2	2.5	1.1	7577
	8	1400	2	10	10	-25	80	NBR	U341N0250 123	8993	488980	-	-	2	2.5	1.1	7577

Notes:
1.Pilot seat in FKM
2.With captured exhaust
3.With manual override

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''-1/4''	8	1400	10	-25
To	3/8''-1/4''	8	1400	10	80



Drawing 7577

5/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

PILOT OPERATED

316L STAINLESS ST.

NAMUR

DUAL SOLENOIDS



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
	1			AC	DC									AC	DC		
	mm	Qn l/min	bar	bar	bar	°C	°C							W	W		
3/8''-1/4''NPT	8	1400	2	10	10	-25	80	NBR	U347N3250 [1]	4270	481000	-	-	8	8	2.1	7557
	8	1400	2	10	10	-25	80	NBR	U347N3250 [1]	2995	481865	-	-	9	10	2.0	7557

Notes:
1.Pilot seat in FKM

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''-1/4''	8	1400	10	-25
To	3/8''-1/4''	8	1400	10	80



Drawing 7557

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

MANUAL RESET

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Operating Pressure Differential Max (MOPD) AC bar	Operating Pressure Differential Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4" NPTF	6	680	0	-	10	-25	65	NBR	U033X5156$_1$	-	482870.01	0-20	Ex ia IIC T6	-	0.3 to 3	10.1/10.2/12.0	7771
	6	680	0	10	10	-25	65	NBR	U033X5156$_1$	-	492310	1-21	Ex e mb II T3 to T6	6	6	10.1/10.2/12.0	7771
	6	680	0	10	10	-25	65	NBR	U033X5156$_1$	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	10.1/10.2/12.0	7771

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-25
To	1/4''	6	680	10	65





Drawing 7771

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

MANUAL RESET

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL - MANUAL RESET



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
1/4" NPTF	6	680	0	12	12	-40	65	VMQ	U033X7759$_1$	-	496895	-	-	8	8		8544
	6	680	0	12	12	-40	65	VMQ	U033X7759$_1$	-	497105	1-21	Ex db IIC T4 to T6	8	8		8537
	6	680	0	12	12	-40	65	VMQ	U033X7759$_1$	-	496700	1-21	Ex db mb IIC T4 to T6	6	6		8545
	6	680	0	12	12	-40	65	VMQ	U033X7759$_1$	-	492310	1-21	Ex mb II T4 to T5	9	8		8546

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)



Drawing 8544

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	680	10	-40
To	1/4''	6	680	10	65



Drawing 8545





Drawing 8546





Drawing 8537

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

MANUAL RESET

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø	Flow factor	Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power		Coil Group	Dwg. No.
			Min	Max (MOPD)		Min	Max										
	1			AC	DC									AC	DC		
	mm	Qn l/min	bar	bar	bar	°C	°C							W	W		
1/4'' NPTF	6	560	0	12	12	-25	65	FKM	U033X5195[1]	-	492310	1-21	Ex e mb II T3 to T6	6	6	10.1/10.2/12.0	3594
	6	560	0	12	12	-25	65	FKM	U033X5195[1]	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	10.1/10.2/12.0	3594

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	1/4''	6	560	10	-25
To	1/4''	6	680	10	65



Drawing 3594

3/2

316L STAINLESS STEEL 3 & 5 WAY VALVES FOR ACTUATOR CONTROL (PIPE MOUNTING AND NAMUR)

MANUAL RESET

316L STAINLESS ST.

PIPE MOUNTING

UNIVERSAL



Port size	Orifice Ø 1 mm	Flow factor Qn l/min	Operating Pressure Differential Min bar	Max (MOPD) AC bar	Max (MOPD) DC bar	Fluid Temp. Min °C	Fluid Temp. Max °C	Seat Seal	Valve Ref.	Housing Ref.	Coil Ref.	ATEX Zone	Protection Mode	Power AC W	Power DC W	Coil Group	Dwg. No.
3/8'' NPTF	6	680	0	-	10	-25	65	NBR	U033X5256$_1$	-	482870.01	0-20	Ex ia IIC T6	-	0.3 to 3	10.1/10.2/12.0	7671
	6	680	0	10	10	-25	65	NBR	U033X5256$_1$	-	492310	1-21	Ex e mb II T3 to T6	6	6	10.1/10.2/12.0	7671
	6	680	0	10	10	-25	65	NBR	U033X5256$_1$	-	496700	1-21	Ex d mb IIC T4 to T6	6	6	10.1/10.2/12.0	7671

Notes:
1.Valve delivered with an individual material traceability certificate (2.2 following EN10204)

IECEx certified

For this page	Port size	Orifice (mm)	Qn (l/min)	MOPD (bar)	Fluid Temp (°C)
From	3/8''	6	680	10	-25
To	3/8''	6	680	10	65





Drawing 7671

NOTES

ELECTROPNEUMATIC PRESSURE REGULATORS

aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding

Basic	1/4" 1/2"
Comfort	1/4" 1/2"
Comfort	1/2" 1" HP 2"
Comfort ATEX	1/2" 1" 2"

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

ELECTROPNEUMATIC PRESSURE REGULATORS

EPP4 Programmable Pressure Regulator



EPP4 is an electro pneumatic pressure regulator with integrated electronic system.
A pulsed width modulated solenoid valve controls the output pressure proportionally to an analog input signal.
Very high accuracy is guaranteed thanks to a high precision closed loop signal provided by a built in pressure sensor.

Market

Robotics
Paper industry
Machine tools
Mobile
Buildings
Textile
Instrumentation
Semi conductor

Description of Applications

Welding
Speed and brake control
Sanding
Cutting
Humidification
Tension regulation
Painting
Presses
Polishing
Adaptative suspension control

Value Propositions for the EPP4 Range of Proportional Pressure Regulators

- All parameters fully adjustable through the PC software Calys
- Easy to use software
- Long life expectancy
- Compact and light
- Limited inventory
- Low power
- Flexible remote display positioning
- Proven expertise of Parker, a pioneer in pressure regulation technology



calys Software for EPP Comfort

Calys is a unique software in house developed to configurate all the parameters of the EPP4 Comfort range.
Calys is an option of the EPP4. To use CALYS, you need to order cable reference 496449 wich permits the communication between the EPP4 and a PC.

Calys offers many capabilities:

- It enables distributors to reduce inventory by keeping a generic EPP4 in stock and adjust it to the needs of each customer application. They can switch for example from 0-10 V to 4-20 mA, or from 0-7 bar pressure range to 0-5 bar.
- Engineers designing a pneumatic system are able to monitor precisely all the important values (electrical or pneumatical) directly on their laptop.
- After sales technicians are able to receive via email all the parameters measured by the EPP4 installed on a machine wherever its location allowing remote ma intenance operation.
- PID regulation parameters can be adjusted with Calys to match required regulator response (like slow or reactive).



To download free Calys software click on **www.parker.com**

ELECTROPNEUMATIC PRESSURE REGULATORS

TABLE OF CONTENT

Introduction EPP ..... page 412

EPP4 Basic Range ..... page 414

EPP4 Comfort Range ..... page 418

EPP4 Comfort HP Range ..... page 422

EPP4 Comfort Range ATEX ..... page 428

Accessories ..... page 434

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

INTRODUCTION

Description Operation

The EPP4 Series is a family of electrically remote-controlled pneumatic pressure regulators with closed loop integrated electronic control.

It allows regulating the outlet pressure proportionally to an electrical control signal.
The EPP4 regulator comprises a traditional servo-operated pneumatic pressure regulator, where the pilot chamber is fed y one or the other of two pulse width modulated 2-way solenoid valves.

The pressure sensor measures the outlet pressure of the regulator and provides a feedback signal to the controller.
Any difference between the control signal and the feedback signal is converted to a digital signal to energise the coil of one or the other 2-way valves to correct the position of the regulator.

The control signal can be a voltage (0-10 V) or a current (4-20 mA). The inlet of the "Filling Valve" is connected directly to the main inlet P of the regulator; when energised this valve will fill the servo-chamber for increasing the pressure at the outlet A of the regulator.

When the other "exhaust valve" is energised (reduction of pressure at the outlet A of the regulator), the pressure of the servo-chamber will be exhausted through a discharge orifice located between the cover and the body and directly fed to the atmosphere without silencer.

The exhaust of the main regulated pressure will be made through the quick exhaust R.
The use of a conventional silencer is recommended.
Both solenoid valves assure the Filling or Emptying of the servo-chamber in order to increase or decrease the pressure at the outlet of the regulator.

In rest position of the valves all ports are blocked.



Filling positon



Stand by position



Emptying position

Block Diagram

The controller receives both the control signal (set pressure) and the feedback signal from the sensor (outlet pressure).

Any difference between the two amplifier inputs results in a corresponding output which drives the appropriate 2-way pulse width modulated solenoid valve so that the pilot piston moves to correct the pressure.

The same feedback signal from the sensor is used for the output feedback in voltage and current.

The digital signal (alarm) is activated when the conditions (out of pressure or time tolerance) are met.



EPP4 possible executions : Basic and Comfort

EPP4 Basic and Comfort ranges share the same reliable mechanical parts. Proportional regulation is also identical for the two different executions, giving the same characteristics for hysteresis or precision for instance.

Comfort range regulators have a second M12 connector, that can be used to connect a remote display showing the current regulated pressure, or a PC to easily set the regulation's parameters. These are the key feature options for a comfortable use.



The B connector offers connection to the remote display or the PC.

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 BASIC 1/4" & 1/2"



TECHNICAL DATA

	Basic 1/4"	Basic 1/2"
Fluids:	Lubricated or non lubricated air and neutral gases Recommended fi ltration: 50 µm	
Temperature range:	Ambient: 0°C to +50°C Fluid: 0°C to +50°C	
Inlet pressure range: The inlet pressure must always be at least 1 bar above the regulated pressure.	1 to 12 bar	1 to 12 bar
Outlet pressure range:	0.05 to 10 bar	
Hysteresis:	± 50 mbar (factory set up)	
Air consumption at constant control signal:	0	
Supply voltage:	24 V DC ± 15% (Max. ripple 1 V)	
Power consumption:	Max. 2.8 W with 24 V DC and constant changes of the control signal < 1.5 W without change of control signal	
Control signal:	Analog 0 - 10 V Analog 4 - 20 mA	
Max. flow: Indicative response time: With a volume of 330 cm³ at the outlet of the regulator	70 m³/h	150 m³/h
Filling 2 to 4 bar: Filling 2 to 8 bar: Emptying 4 to 2 bar: Emptying 8 to 2 bar:	50 msec 100 msec 70 msec 130 msec	60 msec 120 msec 90 msec 190 msec
Safety position:	In case of control signal failure or if it is less than 50mV, the regulated pressure drops automatically to 0 bar (atmospheric pressure). In case of voltage supply failure, the regulated pressure will be kept constant.	
Electrical connection:	M12 - 4 pin; 4 x 0.34 mm²	
Life expectancy:	> 50 Million changes of control signal steps	
Mounting position:	Indifferent (recommended position: upright; electronic part on top)	
Resistance to vibrations:	30 g in all directions	
Degree of protection:	IP 65	
Assembly:	Silicone free	
Electromagnetic compatibility: In accordance with:	EN 61000-6-1: 2001 EN 61000-6-2: 2001 EN 61000-6-3: 2001 EN 61000-6-4: 2001	
Installation and setting instructions:	See our "Notice 408038, 408014" and appendix supplied with the product.	

Note: Parker reserves the right to change specifications without notification.

EPP4 BASIC 1/4" & 1/2"



FLOW CURVES

Flow Curve Basic 1/4"



Flow Curve Basic 1/2"



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 BASIC 1/4" & 1/2"

REFERENCES

Codes	Pipe	Pressure Range (bar)		Control Signal (see options)	Drawing Number
P4BG2001A001	G 1/4''	0	4 bar	4 - 20 mA	1
P4BG2001A002	G 1/4"	0	10 bar	0 - 10 V	1
P4BG2001A003	G 1/4"	0	10 bar	4 - 20 mA	1
P4BG2001A004	G 1/4"	0	6 bar	0 - 10 V	1
P4BG2001A005	G 1/4"	0	6 bar	4 - 20 mA	1
P4BG2001A006	G 1/4"	0	5 bar	0 - 10 V	1
P4BG2001A007	G 1/4"	0	5 bar	4 - 20 mA	1
P4BG2001A008	G 1/4"	0	7 bar	0 - 10 V	1
P4BG2001A009	G 1/4"	0	7 bar	4 - 20 mA	1
P4BG2003A002 *	G 1/4''	0	10 bar	0 - 10 V	1
P4BG2003A003 *	G 1/4''	0	10 bar	4 - 20 mA	1
P4BG4001A002	G 1/2"	0	10 bar	0 - 10 V	2
P4BG4001A003	G 1/2"	0	10 bar	4 - 20 mA	2
P4BG4001A004	G 1/2"	0	6 bar	0 - 10 V	2
P4BG4001A005	G 1/2"	0	6 bar	4 - 20 mA	2
P4BG4001A006	G 1/2''	0	5 bar	0 - 10 V	2
P4BG4001A007	G 1/2''	0	5 bar	4 - 20 mA	2
P4BG4001A008	G 1/2"	0	7 bar	0 - 10 V	2
P4BG4001A009	G 1/2"	0	7 bar	4 - 20 mA	2
P4BG4004A010 ***	G 1/2''	0	4 bar	0 - 10 V	2
P4BG4051A002 **	G 1/2''	0	10 bar	4 - 20 mA	2
P4BN2001A002	NPT 1/4''	0	10 bar	0 - 10 V	2
P4BN2001A003	NPT 1/4''	0	10 bar	4 - 20 mA	2
P4BN4001A002	NPT 1/2''	0	10 bar	0 - 10 V	2
P4BN4001A003	NPT 1/2''	0	10 bar	4 - 20 mA	2

* Integrated pilot exhaust
** O2
*** External pressure supply

EPP4 BASIC 1/4" & 1/2"

DIMENSIONS DRAWINGS EPP4 BASIC 1/4"



Drawing 1

DIMENSIONS DRAWINGS EPP4 BASIC 1/2"



Drawing 2

EPP4 COMFORT 1/4" & 1/2"



TECHNICAL DATA

	Comfort 1/4"	Comfort 1/2"
Fluids:	Lubricated or non lubricated air and neutral gases - Recommended fi ltration: 50 µm	
Temperature range:	Ambient: 0°C to +50 °C Fluid: 0°C to +50 °C	
Inlet pressure range: **The inlet pressure must always be at least 1 bar above the regulated pressure.**	1 to 12 bar	1 to 12 bar
Outlet pressure range:	0.05 bis 10 bar	
Hysteresis:	± 50 mbar (factory set up)	
Air consumption at constant control signal:	0	
Supply voltage:	24 V DC ± 15 % (Max. ripple 1 V)	
Power consumption:	Max. 2.8 W with 24 V DC and constant changes of the control signal < 1.5 W without change of control signal	
Control signal:	Analog 0 - 10 V Analog 4 - 20 mA	
Outlet sensor signal:	Analog 0 - 10 V Standard for 0 - 10 bar; Adjustable Analog 4 - 20 mA Standard for 0 - 10 bar; Adjustable	Digital 0/24 V for alarm features: Adjustable pressure error (+/-) Adjustable delay ON Adjustable delay OFF Adjustable logic (+/-)
Max. flow:	70 m^3/h	150 m^3/h
Indicative response time:	With a volume of 330 cm^3 at the outlet of the regulator	
Filling 2 to 4 bar : **Filling 2 to 8 bar:** **Emptying 4 to 2 bar:** **Emptying 8 to 2 bar:**	50 msec 100 msec 70 msec 130 msec	60 msec 120 msec 90 msec 190 msec
Safety position:	In case of control signal failure or if it is less than 50 mV, the regulated pressure drops automatically to 0 bar (atmospheric pressure). In case of voltage supply failure, the regulated pressure will be kept constant.	
Electrical connection:	M12 - 8 pin; male connector power supply/control signal M12 - 5 pin; male connector communication	
Life expectancy:	> 50 Million changes of control signal steps	
Mounting position:	Indifferent (recommended position: upright; electronic part on top)	
Resistance to vibrations:	30 g in all directions	
Degree of protection:	IP 65	
Assembly:	Silicone free	
Electromagnetic compatibility: **In accordance with:**	EN 61000-6-1: 2001 EN 61000-6-2: 2001 EN 61000-6-3: 2001 + A11 2004 edition (01/07/07) EN 61000-6-4: 2001	
Installation and setting instructions:	See our "Notice 408128, 408134" and appendix supplied with the product.	

Note: Parker reserves the right to change specifications without notification.

EPP4 COMFORT 1/4" & 1/2"

Flow Curves

Flow Curve 1/4"



Flow Curve 1/2"



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 COMFORT1/4" & 1/2"

REFERENCES

Codes	Pipe	Pressure Range (bar)		Control Signal (see options)	Display	Drawing Number
P4CG2001C001	G 1/4	0	10	0-10 V	-	3
P4CG2001C002	G 1/4	0	10	4-20 mA	-	3
P4CG2001C005	G 1/4	0	7	0-10 V	-	3
P4CG2001C006	G 1/4	0	7	4-20 mA	-	3
P4CG2003C001 *	G 1/4	0	10	0-10 V	-	3
P4CG2003C002 *	G 1/4	0	10	4-20 mA	-	3
P4CN2001C001	1/4 NPT	0	10	0-10 V	-	3
P4CN2001C002	1/4 NPT	0	10	4-20 mA	-	3
P4CG4001C001	G 1/2	0	10	0-10 V	-	4
P4CG4001C002	G 1/2	0	10	4-20 mA	-	4
P4CG4001C005	G 1/2	0	7	0-10 V	-	4
P4CG4001C006	G 1/2	0	7	4-20 mA	-	4
P4CG4002C005	G 1/2	0	7	0-10 V	-	4
P4CG4002C006	G 1/2	0	7	4-20 mA	-	4
P4CG4051C001 **	G 1/2	0	10	0-10 V	-	4
P4CG4051C002 **	G 1/2	0	10	4-20 mA	-	4
P4CN4001C001	1/2 NPT	0	10	0-10 V	-	4
P4CN4001C002	1/2 NPT	0	10	4-20 mA	-	4
P4CN4002C001	1/2 NPT	0	10	0-10 V	included	4

* Integrated pilot exhaust
** O2

EPP4 COMFORT 1/4" & 1/2"

DIMENSIONS DRAWINGS EPP4 COMFORT RANGE 1/4"



Drawing 3

DIMENSIONS DRAWINGS EPP4 COMFORT RANGE 1/2"





Drawing 4

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 COMFORT 1/2"HP, 1" & 2"

TECHNICAL DATA

	Comfort 1/2" HP	Comfort 1"	Comfort 2"
Fluids:	Lubricated or non lubricated air and neutral gases - Recommended fi ltration: 50 µm		
Temperature range:	Ambient: 0°C to +50°C Fluid: 0°C to +50°C		
Inlet pressure range: **The inlet pressure must always be at least 1 bar above the regulated pressure.**	1 to 21 bar	1 to 21 bar	1 to 12 bar
Outlet pressure range:	0.05 to 20 bar	0.05 to 20 bar	0.05 to 10 bar
Hysteresis:	⩽ 100 mbar if P inlet ⩽ 10 bar ⩽ 200 mbar if P inlet > 10 bar		
Air consumption at constant control signal:	0		
Supply voltage:	24V DC ± 15%		
Power consumption:	Max. 6 W with 24 V DC and constant changes of thecontrol signal < 2 W without change of control signal		
Control signal:	Analog 0 - 10 V Analog 4 - 20 mA		
Outlet sensor signal:	Analog 0 - 10 V Standard for 0 - 10 bar; Adjustable Analog 4 - 20 mA Standard for 0 - 10 bar; Adjustable	Digital 0/24 V for alarm features: Adjustable pressure error (+/-) Adjustable delay ON Adjustable delay OFF Adjustable logic (+/-)	
Max. flow:	150 m^3/h	1 000 m^3/h	2 700 m^3/h
Indicative response time:	With a volume of 330 cm^3 at the outlet of the regulator		
Filling 2 to 8 bar: **Emptying 8 to 2 bar:**	120 msec 190 msec	250 msec 400 msec	250 msec 400 msec
Safety position:	In case of control signal failure or if it is less than 50 mV, the regulated pressure drops automatically to 0 bar atmospheric pressure (for pressure ranges from 0-10 bar, 100 mV for pressure range over 10 bar). In case of voltage supply failure, the regulated pressure will be kept constant.		
Electrical connection:	M12 - 8 pin; male connector power supply/control signal M12 - 5 pin; male connector communication		
Life expectancy:	> 20 Million changes of control signal steps		
Mounting position:	Indifferent (recommended position: upright; electronic part on top)		
Resistance to vibrations:	30 g in all directions		
Degree of protection:	IP 65		
Assembly:	Silicone free		
Electromagnetic compatibility: **In accordance with:**	EN 61000-6-1: 2001 EN 61000-6-2: 2001 EN 61000-6-3: 2001 + A11 2004 edition (01/07/07) EN 61000-6-4: 2001		
Installation and setting instructions:	See our "408 193" and appendix supplied with the product.		

Note: Parker reserves the right to change specifications without notification.

EPP4 COMFORT 1/2"HP, 1" & 2"

FLOW CURVES

Flow Curve 1/2"HP



Flow Curve 1"



Flow Curve 2"



EPP4 COMFORT 1/2"HP

REFERENCES

Codes	Pipe	Max inlet pressure (bar)	Pressure range (bar)		Control signal (see options)	Dimensional Drawing
P4CG4101D001	G1/2	15	0	12	0-10 V	5
P4CG4201D005	G1/2	21	0	16	0-10 V	6
P4CG4201D003	G1/2	21	0	20	0-10 V	6
P4CG4201D004	G1/2	21	0	20	4-20 mA	6

Other specific settings or specialties are available, please contact us.

EPP4 COMFORT 1/2"HP

DIMENSIONS DRAWINGS



Drawing 5





Drawing 6

EPP4 COMFORT 1" & 2"

REFERENCES

Codes	Pipe	Max inlet pressure (bar)	Pressure range (bar)		Control signal (see options)	Dimensional Drawing
P4CG6101C009	G1	12	0	3.5	4-20 mA	7
P4CG6101C011	G1	12	0	5.0	0-10 V	7
P4CG6101C010	G1	12	0	6.0	4-20 mA	7
P4CG6101C001	G1	12	0	10	0-10 V	7
P4CG6101C002	G1	12	0	10	4-20 mA	7
P4CG6201D001	G1	21	0	12	0-10 V	7
P4CG6201D003	G1	21	0	20	0-10 V	7
P4CG9101C010	G2	12	0	6.0	4-20 mA	8
P4CG9101C001	G2	12	0	10	0-10 V	8
P4CG9101C002	G2	12	0	10	4-20 mA	8

Other specific settings or specialties are available, please contact us.

EPP4 COMFORT 1" & 2"

DIMENSIONS DRAWINGS EPP4 COMFORT RANGE 1"





Drawing 7

DIMENSIONS DRAWINGS EPP4 COMFORT RANGE 2"



Drawing 8

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 COMFORT 1/2", 1" & 2" ATEX



TECHNICAL DATA

	Comfort 1/2" ATEX	Comfort 1" ATEX	Comfort 2" ATEX
Fluids:	Lubricated or non lubricated air and neutral gases - Recommended fi ltration: 50 µm		
Temperature range:	Ambient: 0°C to +50°C Fluid: 0°C to +50°C		
Inlet pressure range: **The inlet pressure must always be at least 1 bar above the regulated pressure.**	Inlet pressure range: 1 to 12 bar		
Outlet pressure range:	Outlet pressure range: 0.05 to 10 bar		
Hysteresis:	⩽ 100 mbar		
Air consumption at constant control signal:	0		
ATEX certification:	Ex II 3 G/D Ex nA IIC T4 Gc Ex tc IIIB T130°C Dc		
Supply voltage:	24V DC ± 15 %		
Power consumption:	Max. 6 W with 24 V DC and constant changes of thecontrol signal < 2 W without change of control signal		
Control signal:	Analog 0 - 10 V Analog 4 - 20 mA		
Outlet sensor signal:	Analog 0 - 10 V Standard for 0 - 10 bar; Adjustable Analog 4 - 20 mA Standard for 0 - 10 bar; Adjustable		Digital 0/24 V for alarm features: Adjustable pressure error (+/-) Adjustable delay ON Adjustable delay OFF Adjustable logic (+/-)
Max. flow:	150 m^3/h	1 000 m^3/h	2 700 m^3/h
Indicative response time:	With a volume of 330 cm^3 at the outlet of the regulator		
Filling 2 to 8 bar: **Emptying 8 to 2 bar:**	120 msec 190 msec	250 msec 400 msce	250 msec 400 msec
Safety position:	In case of control signal failure or if it is less than 50 mV, the regulated pressure drops automatically to 0 bar atmospheric pressure (for pressure ranges from 0-10 bar, 100 mV for pressure range over 10 bar). In case of voltage supply failure, the regulated pressure will be kept constant.		
Electrical connection:	M12 - 8 pin; male connector power supply/control signal M12 - 5 pin; male connector communication		
Life expectancy:	> 20 Million changes of control signal steps		
Mounting position:	Indifferent (recommended position: upright; electronic part on top)		
Resistance to vibrations:	30 g in all directions		
Degree of protection:	IP 54		
Assembly:	Silicone free		
Electromagnetic compatibility: **In accordance with:**	EN 61000-6-1: 2001 EN 61000-6-2: 2001 EN 61000-6-3: 2001 + A11 2004 edition (01/07/07) EN 61000-6-4: 2001		
Installation and setting instructions:	See our "408 283" and appendix supplied with the product.		

Note: Parker reserves the right to change specifications without notification.

EPP4 COMFORT 1/2", 1" & 2" ATEX

FLOW CURVES

Flow Curve 1/2"



Flow Curve 1"



Flow Curve 2"



EPP4 COMFORT 1/2" ATEX

REFERENCES

Codes	Pipe	Max inlet pressure (bar)	Pressure range (bar)		Control signal (see options)	Dimensional Drawing
P4CG4461C001	G1/2	12	0	10	0-10 V	9
P4CG4461C002	G1/2	12	0	10	4-20 mA	9
P4CG4465C001 **	G1/2	12	0	10	0-10 V	9
P4CG4465C002 **	G1/2	12	0	10	4-20 mA	9

** 02

Other specific settings or specialties are available, please contact us.

EPP4 COMFORT 1/2" ATEX

DIMENSIONS DRAWINGS





Drawing 9

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 COMFORT 1" & 2" ATEX

REFERENCES

Codes	Pipe	Max inlet pressure (bar)	Pressure range (bar)		Control signal (see options)	Dimensional Drawing
P4CG6161C001	G1	12	0	10	0-10 V	11
P4CG6161C002	G1	12	0	10	4-20 mA	11
P4CG9161C001	G2	12	0	10	0-10 V	12
P4CG9161C002	G2	12	0	10	4-20 mA	12

Other specific settings or specialties are available, please contact us.

EPP4 COMFORT 1" & 2" ATEX

DIMENSIONS DRAWINGS EPP4 COMFORT RANGE 1"



Drawing 11

DIMENSIONS DRAWINGS EPP4 COMFORT RANGE 2"



Drawing 12

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

EPP4 ACCESSORIES

MOUNTING BRACKETS FOR EPP4 1/4" BASIC / COMFORT

This mounting bracket is delivered as a standard with all EPP4 1/4".

EPP4 ACCESSORIES

MOUNTING BRACKETS FOR EPP4 1/2" BASIC / COMFORT



Order reference 491366

EPP4 ACCESSORIES

POWER SUPPLY/CONTROL SIGNAL CABLE FOR BASIC AND COMFORT VERSIONS.

Cable for Comfort EPP4

- 2 m cable with moulded straight M12-8 pole

Order Reference 496796K

EPP4 COMFORT ACCESSORIES

calys SOFTWARE

Calys is a unique software in house developed to configurate all the parameters of the EPP4 Comfort range. Calys is an option of the EPP4. A specific cable is needed for the communication between the EPP4 and a PC.

Calys offers many capabilities:

- Live monitoring (control signal, regulated pressure, supply voltage,...)
- Recording of the main parameters (control signal, regulated pressure, supply voltage,...) in an Excel file
- Free calibration for the inputs and outputs
- Adjustable alarm (positive-negative, pressure limits, delays)
- Configuration files easy to duplicate
- Complete and interactive help file



Data in 4 different pressure units

Menus in 4 languages (English, German, French and Italian)

Specific communication cable PC-EPP4 with RS232 and USB connection

Order Reference 496449

This option is for safe area only.

NOTES

A COMPLETE RANGE OF COILS, HOUSINGS AND ELECTRICAL PARTS FOR SOLENOID VALVES

DEFINITIONS

HOUSINGS OR COIL ASSEMBLY KITS, COILS AND ELECTRICAL PARTS



Housing:

We define a **housing** as the combination of the fixing elements including the nameplate 1, the cover 2 or the subplate 6 and the envelope itself 4 or 5 which protects the coil and its electrical components. The housings may be made of metal or plastic material.

Coil assembly kit:

The coil assembly kit 7 or 9 is the set comprising a plate, washer and nut. Sometimes coil assembly kits consist only of a nut or a special fixing device.

Coil:

This consists of the winding and its plastic moulding. There are three different types of coils distinguished by their shape and dimensions: 40 mm 3, 32 mm 8 and 22 mm 10.

Electric part:

The electric part is the set comprising the housing, the assembly kit and the coil.

Attention:

Any coil or electrical part must be energised only when properly mounted on a valve.

If not, a risk of damaging the product and its surroundings (overheating, explosion, fire, etc.) can take place.

TABLE OF CONTENT

INTRODUCTION

Index for Explosion Proof Electrical Parts 442

List of Coil Groups 443

COILS

Coils for DIN plug connection 446

Coils with flying leads 460

Coils with screw terminal 462

Coils with ISO-DIN connector 469

EXPLOSION PROOF ELECTRICAL PARTS

Level of protection "nAc nCc" 472

Level of protection "db" 480

Level of protection "mb" 481

Level of protection "db mb" 485

Level of protection "eb" 490

Level of protection "eb mb" 491

Level of protection "ia" 494

HOUSINGS 502

COIL ACCESSORIES 506

EXPLOSIVE ENVIRONMENTS 508

COIL APPENDICES

Guidance chart for IS-Barriers 518

INDEX FOR EXPLOSION PROOF ELECTRICAL PARTS

Coil Reference	Coil Group	Designation	Power DC Pn (W)	Power AC Pn (W)	Ambient Temperature	UL	Degree of Protection	ATEX or NEMA 4X Protection (Gas)	Page
496637	1.2	Explosion proof electrical part "nAc nCc", 22 mm, double frequency	3.0	3.0	-40°C to +50°C	-	IP65	Ex nAc nCc IIC T5 IP65	473
495880	2.0/2.2	Explosion proof electrical part "nAc nCc", 32 mm	14.0	14.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3	477
496155	2.0/2.2	Explosion proof increased safety electrical part "nAc nCc", 50 mm	14.0	14.0	-40°C to +65°C	-	IP67	II 3 G Ex nAc nCc IIC T3	479
495915	4.0	Explosion proof increased safety electrical part "nAc nCc", 50 mm	13.0	11.0	-40°C to +65°C	-	IP67	II 3 G Ex nAc nCc IIC T3	478
495870	2.0/2.1	Explosion proof electrical part "nAc nCc", 32 mm	9.0	8.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	474
495875	3.0	Explosion proof electrical part "nAc nCc", 32 mm	7.0	6.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	476
496110	2.0/2.1	Explosion proof electrical part "nAc nCc", 32 mm	-	9.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	474
495865	1.1	Explosion proof electrical part "nAc nCc", low power, 22 mm	2.5	2.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5	472
496125	6.0	Explosion proof electrical part "nAc nCc", low power, 32 mm	1.6	-	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5/T6	475
482605	1.1	Explosion proof encapsulated electrical part "mb", 32 mm	5.0	4.0	-40°C to +65°C	-	IP65	II 2 G Ex mb IIC T4/T5	481
482606	1.1	Explosion proof encapsulated electrical part "mb", low power, 32 mm	2.5	2.0	-40°C to +65°C	-	IP65	II 2 G Ex mb IIC T4/T5	481
492070	2.0/2.1	Explosion proof encapsulated electrical part "mb", with water proof metal housing, 50 mm	8.0	9.0	-40°C to +65°C	-	IP67	II 2 G Ex mb IIC T4/T5	482
HZ10	2.0/2.1	Explosion proof encapsulated electrical part "mb", double frequency	8.0	8.0	-40°C to +85°C	-	IP65	II 2 G - Ex mb IIC T3/T4/T5	483
HZ11	2.0/2.2	Explosion proof encapsulated electrical part "mb", double frequency	14.0	14	-40°C to +85°C	-	IP65	II 2 G - Ex mb IIC T3/T4/T5	484
497105	10.3	Flame proof electrical part "db", 50 mm	8.0	8.0	-50°C to +80°C	-	IP66	II 2 G Ex db IIC T4/T5/T6	480
493640	2.0/2.1	Flame proof encapsulated electrical part "db mb", double frequency	8.0	8.0	-40°C to +75°C	-	IP65	II 2 G Ex db mb IIC T4/T5	489
495905	2.0/2.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4	486
496560	10.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +80°C	-	IP67	II 2 G Ex db mb IIC T4	487
496800	10.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4	488
495900	6.0	Flame proof encapsulated electrical part "db mb", low power, 37 mm	2.0	2.5	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4/T5/T6	485
496555	10.2	Flame proof encapsulated electrical part "db mb", 37 mm	6.0	6.0	-40°C to +80°C	-	IP67	II 2 G Ex db mb IIC T4/T5/T6	487
496700	10.2	Flame proof encapsulated electrical part "db mb", 37 mm	6.0	6.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4/T5/T6	488
494040	2.0/2.1	Explosion proof increased safety electrical part "eb", 50 mm	8.0	8.0	-40°C to +90°C	-	IP67	II 2 G Ex eb IIC T3/T4	490
483371	2.0/2.1	Explosion proof increased safety electrical part "eb", 50 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex eb IIC T4	490
492190	2.0/2.1	Explosion proof increased safety and encapsulated elect. part "eb", 50 mm	9.0	11.0	-40°C to +75°C	-	IP66	II 2 G Ex eb mb IIC T3/T4	493
492310	10.1	Explosion proof increased safety and encapsulated electrical part "eb", 50 mm	6.0	6.0	-40°C to +75°C	-	IP66	II 2 G Ex eb mb IIC T4/T5	491
492210	9.0	Explosion proof increased safety and encapsulated electrical part "eb", " Booster", 50 mm	1.0 to 1.8	-	-40°C to +75°C	-	IP66	II 2 G Ex eb mb IIC T5/T6	492
495910	8.0	Explosion proof intrinsically safe electrical part "ia", "booster", 37 mm	0.3 to 1.2	-	-40°C to +80°C	-	IP67	II 1 G Ex ia IIC T4/T5/T6	495
496565	9.0	Explosion proof intrinsically safe electrical part "ia", " Booster", 37 mm	0.77 to 2.58	-	-40°C to +80°C	-	IP67	II 1 G Ex ia IIC T4/T5/T6	496
483580.01	7.0	Explosion proof intrinsically safe electrical part "ia", 32 mm	3.0	-	-40°C to +55°C	-	IP65	II 1 G Ex ia IIC T6	494
488650.01	7.0	Explosion proof intrinsically safe electrical part "ia", 50 mm	0.3 to 3.0	-	-40°C to +65°C	-	IP66	II 1 G Ex ia IIC T6	498
492965.01	9.0	Explosion proof intrinsically safe electrical part "ia", " Booster", 50 mm	0.3 to 2.3	-	-40°C to +65°C	-	IP66	II 1 G Ex ia IIC T6	497
482870.01	12.0	Explosion proof intrinsically safe electrical part "ia", 50 mm	3.0	-	-40°C to +65°C	-	IP66	II 1 G Ex ia IIC T6	499
490885	7.0	Explosion proof intrinsically safe electrical part, "NEMA", 50 mm	3.0	-	-40°C to +60°C	-	NEMA 4 - 4X	Cl. I, Div.I, Gr. A, B, C, D	498

LIST OF COIL GROUPS

Parker coils and electrical parts are classified by groups determining their compatibility with Parker solenoid valves.

Group	For application with
1.1	Standard valves or on 2000 Series with standard pilot
1.2	Standard valves or on 2000 Series for high flow
1.3	Standard valves or on 2000 Series of W coil
2.0	Standard valves or on 7000 Series with standard pilot
2.1	Standard valves or on 7000 Series, for coils 8 - 9 W
2.2	Standard valves or on 7000 Series, for coils 14 W
3.0	Standard valves or on 7000 Series with reduced power
4.0	Standard valves or on 7000 Series, for bistable (Impulse) coils or electrical parts
6.0	Special valves "97" or on 7000 Series, for Intrinsicaly safe coils or electrical parts
7.0	Special valves "90", for coils and intrinsically safe electrical parts
8.0	Special valves "97" or on 7000 Series, for Intrinsicaly safe coils or electrical parts with booster
9.0	Special valves "xx" or on 9000 Series, for Intrinsicaly safe coils or electrical parts with booster
10.1	Standard valves or on 9000 Series with standard pilot
10.2	Standard valves or on 9000 Series "db mb"
10.3	Special valves or on 8000 Series ''d''
12.0	Standard valves or on 9000 Series with manual reset
13.0	Special valves or on 7000 Series for Transportation
14.1	Special valves or on 7000 Series for Oil Burners
14.2	Special valves or on 7000 Series for Oil Burners
14.3	Special valves or on 7000 Series for Oil Burners

NOTES

TABLE OF CONTENT

INTRODUCTION

Index for Explosion Proof Electrical Parts 442

List of Coil Groups 443

COILS

Coils for DIN plug connection 446

Coils with flying leads 460

Coils with screw terminal 462

Coils with ISO-DIN connector 469

EXPLOSION PROOF ELECTRICAL PARTS

Level of protection "nAc nCc" 472

Level of protection "db" 480

Level of protection "mb" 481

Level of protection "db mb" 485

Level of protection "eb" 490

Level of protection "eb mb" 491

Level of protection "ia" 492

HOUSINGS 502

COIL ACCESSORIES 506

EXPLOSIVE ENVIRONMENTS 508

COIL APPENDICES

Guidance chart for IS-Barriers 518

COILS FOR DIN PLUG CONNECTION

COILS 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.
The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Reference (Without DIN Plug)			481865	
Coil Group			2.0	
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			H 180°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	-	10 W
		P (cold) 20°C	-	14 W
	AC	Pn (holding)	8 to 11 W	-
		Attraction cold	13 W	-
Weight			130 g (without plug)	

Voltages "Un"	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un	12V 50-60Hz 24V 50-60Hz 48V 50-60Hz 110V 50Hz 115-120V 60Hz 100V 50Hz 100-120V 60Hz 200V 50-60Hz 220-240V 50Hz 240V 60Hz 380V 50Hz	1W P0* S4 T8* T7 P6 S6* A9	12V 24V 48V 72V 96V 110V	C1* C2* C4* 0N* 1T* C5*

To Order a Coil choose Coil Ref + Voltage Code, example: 481865 for 24 VDC = 481865C2
* = UL Approved

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP

2.0/2.2 COILS FOR DIN PLUG CONNECTION

HIGH TEMPERATURE COILS 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			High temperature + high power							
Ref. (without DIN plug) Ref. (with DIN plug)			492425							
Coil Group			2.0 / 2.2							
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).							
Class of insulation			H 180°C							
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A							
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.							
Elect. Power	DC	Pn (hot)	14 W							
		P (cold) 20°C	21 W							
	AC	Pn (holding)	14 W							
		Attraction cold	55 VA (18 W)							
Weight			130 g (without plug)							
Voltages "Un"			VAC/Hz	Code	VDC	Code	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50 110/50 220/50-230/50	A2 A5 3D	24 110	C2 C5	24/50 110/50 230/50	A2 A5 F4	24 12	C2 C1

To Order a Coil choose Coil Ref + Voltage Code, example: 492425 for 24 VDC= 492425C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

REDUCED POWER COIL 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Reduced power			
Ref. (without DIN plug) Ref. (with DIN plug)			482730			
Coil Group			3.0			
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).			
Class of insulation			H 180°C			
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	7 W			
		P (cold) 20°C	9 W			
	AC	Pn (holding)	6 W			
		Attraction cold	20 VA (7 W)			
Weight			130 g (without plug)			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			220-230/50	3D	24	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 482730 for 24 VDC = 482730C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



COIL GROUP

6.0

COILS FOR DIN PLUG CONNECTION

LOW POWER COIL 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Miniwatt	
Reference (without DIN plug) Reference (with DIN plug)			**482740**	
Coil Group			**6.0**	
Degree of protection			**IP65** according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			H 180°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	1.6 W	
		P (cold) 20°C	2.1 W	
	AC	Pn (holding)	-	
		Attraction cold	-	
Weight			130 g (without plug)	
Voltages "Un" -10% to +10% of the Un			VDC	Code
			24	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 482740 for 24 VDC = 482740C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

UL COIL 32 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.
DIN plug connector to be ordered separately (see coil accessories section)

Specification			UL-recognized coil			
Reference (without DIN plug)			491514			
Coil Group			2.0 / 2.1			
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).			
Class of insulation			H 180°C			
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A			
Ambient temperature			-40°C to 50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	-		12 W	
		P (cold) 20°C	-		16 W	
	AC	Pn (holding)	11 W		-	
		Attraction cold	40 VA (13 W)		-	
Weight			130 g (without plug)			
Voltages "Un"			VAC/Hz	Code	VDC	Code
- 15% to +10% of the Un			110/50-120/60 220/50-240/60 24/60 208-240/60	P3 Q3 B2 U3	12 24	C1 C2

To Order a Coil choose Coil Ref + Voltage Code, example: 491514 for 24 VDC = 491514C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995** with non UL valve and Ref. 2995.03 with UL valve.

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP

2.2

COILS FOR DIN PLUG CONNECTION

COIL 32 mm FOR JET VALVES

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.
DIN plug connector to be ordered separately (see coil accessories section)

Specification			32 mm coil 14 W	
Reference			483816	
Coil Group			2.2	
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			H 180°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type A	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	14 W	
		P (cold) 20°C	-	
	AC	Pn (holding)	14 W	
		Attraction cold	-	
Weight			160 g	
Voltages "Un"			VDC	Code
-10% to +10% of the Un			24 V	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 483816 for 24 VDC = 483816C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 2995.**

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.



COILS FOR DIN PLUG CONNECTION

COILS 22 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.
DIN plug connector to be ordered separately (see coil accessories section)

Specification			Low power	High power
Ref. (without DIN plug) Ref. (with DIN plug)			488980	481180
Coil Group			1.1	
Degree of protection			**IP65** according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			F 155°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	2.5 W	5 W
		P (cold) 20°C	3 W	6.5 W
	AC	Pn (holding)	2 W	4 W
		Attraction cold	5.7 VA (2.5 W)	8.9 VA (5 W)
Weight			100 g with DIN Plug	

Voltages "Un"	VAC/Hz	Code	VDC	Code	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un	24/50 48/50 110/50-115/50 220/50-230/50 24/60 110-115/60 220-230	A2 A4 0A 3D B2 6J 7J	12 24 48 110	C1 C2 C4 C5	24/50 110/50-115/50 220/50-230/50	A2 0A 3D	12 24 110	C1 C2 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 488980 for 24 VDC = 488980C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 8993.**

It is composed of a nameplate with the details of the valve type, a washer and a nut to secure the 22 mm coil to the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP

1.1

COILS FOR DIN PLUG CONNECTION

COIL 22 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This coil is designed for valves equipped with a miniature tube assembly (2000 series valves). This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coil conforms to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Standard (only if used with 321K, 121M, 131M valves)			
Reference (without DIN plug) Reference (with DIN plug)			492912			
Coil Group			1.1			
Degree of protection			**IP65** according to IEC / EN 60529 standards (with DIN plug).			
Class of insulation			A 105°C for UL/CSA			
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	4 W			
		P (cold) 20°C	4.5 W			
	AC	Pn (holding)	3 W			
		Attraction cold	7.5 VA (4 W)			
Weight			100 g with DIN Plug			
Voltages "Un"			VAC/Hz	Code	VDC	Code
- 15% to +10% of the Un			230/50-240/60	T1	24	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 492912 for 24 VDC = 492912C2

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 8993**.

It is composed of a nameplate giving details of the valve type,

a round washer and a nut to ensure the fixing between 22 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

DOUBLE FREQUENCY COIL 22 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This coil is designed for valves equipped with a miniature tube assembly (2000 series valves). This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coil conforms to the IEC/CENELEC safety standards and complies with European low-voltage directive.

DIN plug connector to be ordered separately (see coil accessories section).

Specification			Double frequency	
Reference (without DIN plug)			483590	
Coil group			1.1	
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			F 155°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	-	
		P (cold) 20°C	-	
	AC	Pn (holding)	3 W	
		Attraction cold	7.5 VA (4 W)	
Weight			100 g with DIN Plug	
Voltages "Un"			VAC/Hz	Code
-10% to +10% of the Un			24/50-60 48/50-60 110-115/50, 120/60 220-240/50, 240/60	P0 S4 S5 S6

To Order a Coil choose Coil Ref + Voltage Code, example: 483590 for 24/50,24/60 = 483590P0

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 8993.**

It is composed of a nameplate giving details of the valve type,

a round washer and a nut to ensure the fixing between 22 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP

1.1

COILS FOR DIN PLUG CONNECTION

DOUBLE FREQUENCY COIL 22 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This coil is designed for valves equipped with a miniature tube assembly (2000 series valves). This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coil conforms to the IEC/CENELEC safety standards and complies with European low-voltage directive.

DIN plug connector to be ordered separately (see coil accessories section).

Specification			Double frequency	
Reference (without DIN Plug)			488143	
Coil group			1.1	
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).	
Class of insulation			F 155°C	
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	-	
		P (cold) 20°C	-	
	AC	Pn (holding)	2.5 W	
		Attraction cold	-	
Weight			60 g	
Voltages "Un"			VAC/Hz	Code
-10% to +10% of the Un			200/50-60	P6

To Order a Coil choose Coil Ref + Voltage Code, example: 488143 for 200/50-60 = 488143P6

These coils must be used with suitable housings, see example below:

Please use the coil assembly kit **Ref. 8993.**

It is composed of a nameplate giving details of the valve type,

a round washer and a nut to ensure the fixing between 22 mm coil and the valve.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

DOUBLE FREQUENCY COIL 22 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This coil is designed for valves equipped with a miniature tube assembly (2000 series valves). This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coil conforms to the IEC/CENELEC safety standards and complies with European low-voltage directive.
DIN plug connector to be ordered separately (see coil accessories section).

Specification			Double frequency			
Reference (without DIN Plug)			496131			
Coil group			1.2			
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).			
Class of insulation			F 155°C			
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	3 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	3 W			
		Attraction cold	-			
Weight			60 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50-60	P0	12 V	C1
			110/50-60	P2	24 V	C2
			230/50-60	P9	48 V	C4
			48/50-60	S4	110 V	C5

To Order a Coil choose Coil Ref + Voltage Code, example: 496131 for 24 VDC = 496131C2

"The housing kit is already included in the valve reference, it is not needed to order it separately."



COIL GROUP

1.2

COILS FOR DIN PLUG CONNECTION

DOUBLE FREQUENCY COIL 22 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This coil is designed for valves equipped with a miniature tube assembly (2000 series valves). This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coil conforms to the IEC/CENELEC safety standards and complies with European low-voltage directive.

DIN plug connector included.

Specification			Double frequency			
Reference			496482			
Coil group			1.2			
Degree of protection			IP65 according to IEC / EN 60529 standards (with DIN plug).			
Class of insulation			F 155°C			
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	3 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	3 W			
		Attraction cold	-			
Weight			75 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50-60 110/50-60 230/50-60 48/50-60 115/60	P0 P2 P9 S4 K8	12 V 24 V 48 V 110 V	C1 C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 496482 for 24 VDC = 496482C2

"The housing kit is already included in the valve reference, it is not needed to order it separately."



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

DOUBLE FREQUENCY COIL 22 MM

This coil is designed for valves equipped with a miniature tube assembly (2000 series valves). This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.

Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.

Coil conforms to the IEC/CENELEC safety standards and complies with European low-voltage directive.

DIN plug connector to be ordered separately.

Specification			Double frequency			
Reference (with DIN plug)			**497510**			
Coil group			**1.2**			
Degree of protection			**IP65** according to IEC / EN 60529 standards (with DIN plug)			
Class of insulation			F 155°C / H 180°C			
Electrical connection			The coil is connected with a 2 P + E plug according to EN 175301-803 type B.			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	**DC**	**Pn** (hot)	-			
		P (cold) 20°C	9,3 W			
	AC	**Pn** (holding)	4,5 W			
		Attraction cold	7,5 VA			
Weight			90 g			
Voltages "Un"			**VAC/Hz**	**Code**	**VDC**	**Code**
-10% to +10% of the Un			24/50-60 110-120/60 220-230/50-60 208-240/60	P0 3K (UL) 3P U3 (UL)	24 V	C2 (UL)

To order a Coil choose Coil Ref + Voltage Code, example: **497510** for **24 VDC** = **497510C2**
The housing kit is already included in the valve reference, it is not needed to order it separately.»



COIL GROUP

10.1

COILS FOR DIN PLUG CONNECTION

COIL FOR OIL AND GAS 37 mm

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.

Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.

Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive. DIN plug connector included (The AC electrical connection is delivered with a rectifier bridge).

Specification			Coil for Oil and Gas			
Reference (with DIN plug)			496895			
Coil group			10.1			
Degree of protection			**IP65** according to IEC / EN 60529 standards			
Class of insulation			H 180°C			
Electrical connection			With DIN plug 492459 (AC) or 486586 (DC)			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	**Pn** (hot)	8 W			
		P (cold) 20°C	-			
	AC	**Pn** (holding)	8 W			
		Attraction cold	-			
Weight			273 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			230/50-60 110/50-60 24/50-60 48/50-60	P9 P2 P0 S4	24 V 48 V 110 V	C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: **496895** for **24 VDC** = **496895C2**

The fixing nut (housing kit) is already inclued in the coil kit.



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL 32 mm IP67

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Coil with two 500 mm flying leads			
Reference			496081			
Coil Group			2.0 / 2.1			
Degree of protection			IP67 according to IEC / EN 60529 standards			
Class of insulation			F 155°C			
Ambient temperature			-40 °C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	9 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	9 W			
		Attraction cold	32 VA			
Weight			180 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of Un for AC - 5 % to + 10 % for Un DC			24/50 - 24/60 110-115/50 - 120/60 220-240/50 - 240/60	P0 S5 S6	12 24	C1 C2

To Order a Coil: Coil Ref + Voltage Code, example: 496081 for 24 VDC = 496081C2

To assemble this coil on our solenoid valves, please order housing Ref: 2995



COIL GROUP

2.0/2.1

COIL 32 MM IP67 UL

This coil can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

This is an encapsulated assembly comprising a coil, integral magnetic iron path and snap-on plug connection.

The synthetic material encapsulation provides an effective compact housing, offering full protection against dust, oil, water, etc.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements , etc.
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			UL Coil with two 500 mm flying leads			
Reference			496082			
Coil Group			2.0/2.2			
Degree of protection			**IP67** according to IEC / EN 60529 standards			
Class of insulation			F 155°C			
Ambient temperature			-40 °C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	16 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	13-14 W			
		Attraction cold	40 VA			
Weight			180 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of Un for AC - 5 % to + 10 % for Un DC			110/50 220/50	P3 Q3	24 12	C2 C1

To Order a Coil: Coil Ref + Voltage Code, example: 496082 for 24 VDC = 496082C2







STANDARD COILS 40 mm

These coils can be mounted with every Parker Solenoid Valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

They can be mounted with all metal housings.

The coil winding is completely encapsulated in synthetic material.

Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².

Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Standard				Double Frequency	
Reference			481000				483520	
Coil Group			2.0 / 2.1					
Class of insulation			F 155°C					
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.					
Elect. Power	DC	Pn (hot)	8W				-	
		P (cold) 20°C	9W				-	
	AC	Pn (holding)	8W				9W	
		Attraction cold	32 VA (9 W)				36 VA (10 W)	
Weight			130 g				130 g	
Voltages "Un"			VAC/Hz	Code	VDC	Code	VAC/Hz	Code
-10% to +10% of the Un (-15 % to +5 % for double-frequency coil with voltage code S6 if 240 V/50/Hz is used).			24/50 48/50 110/50-115/50 220/50-230/50 24/60 42-48/60 110-115/60 220-240/60	A2 A4 0A 3D B2 S7 6J 4K	6 12 24 48 110 220	C0 C1 C2 C4 C5 C7	24/50-60 220-240/50-240/60	P0 S6

To Order a Coil choose Coil Ref + Voltage Code, example: 4828 for 24 VDC = 481000C2

These coils must be used with suitable housings, see examples below:



Ref. 4270 - Protection **IP 44** according to IEC / EN 60529 standard (with cable gland)

Ref. 4538 - Protection **IP 67** according to IEC / EN 60529 standard

COIL GROUP

2.0/2.2

COILS WITH SCREW TERMINALS

HIGH POWER COILS 40 mm

This coil can be mounted with every Parker Solenoid Valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

They can be mounted with all metal housings.

The coil winding is completely encapsulated in synthetic material.

Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².

Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			High Power	
Reference			481044	
Coil Group			2.0 / 2.2	
Class of insulation			F 155°C	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	-	
		P (cold) 20°C	-	
	AC	Pn (holding)	14 W	
		Attraction cold	56 VA (20 W)	
Weight			130 g	
Voltages "Un"			VAC/Hz	Code
-10% to +10% of the Un			24/50 220/50 230/50 380/60 24/60 220/60 230/60 - 200/50 115/60 - 100/50	A2 A7 F4 A9 B2 B7 S2 0P

To Order a Coil choose Coil Ref + Voltage Code, example: 481044 for 24VAC/50Hz = 481044A2

These coils must be used with suitable housings, see examples below:



Ref. 4270 - Protection **IP 44** according to IEC / EN 60529 standard (with cable gland)

Ref. 4538 - Protection **IP 67** according to IEC / EN 60529 standard

HIGH TEMPERATURE COILS 40 mm

These coils can be mounted with every Parker Solenoid Valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

They can be mounted with all metal housings.

The coil winding is completely encapsulated in synthetic material.

Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².

Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			High Temperature & High Power			
Reference			486265			
Coil Group			2.0 / 2.2			
Class of insulation			H 180°C			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	14 W			
		P (cold) 20°C	21 W			
	AC	Pn (holding)	14 W			
		Attraction cold	56 VA (20 W)			
Weight			140 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50 110/50 220/50 230/50 380/60 220/60 230/60 - 200/50 115/60 - 100V/50	A2 A5 A7 F4 A9 B7 S2 0P	12 24 36 48	C1 C2 C3 C4

To Order a Coil choose Coil Ref + Voltage Code, example:486265 for 24VAC/50Hz = 486265

These coils must be used with suitable housings, see examples below:



Ref. 4270 - Protection **IP 44** according to IEC / EN 60529 standard (with cable gland)

Ref. 4538 - Protection **IP 67** according to IEC / EN 60529 standard

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP

14.1

COILS WITH SCREW TERMINALS

HIGH TEMPERATURE & HIGH POWER COILS 40 mm OIL BURNER

This coils can be mounted with every Parker Solenoid Valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

It can be mounted with all metal housings.

The coil winding is completely encapsulated in synthetic material.

Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².

Coil conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.
This coil is used only in safety application according to DIN/EN/ISO 23551-1:2009-10 (Oil burners)

Specification			High Temperature & High Power	
Reference			483824	
Coil Group			14.1	
Class of insulation			H 180°C	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	19 W	
		P (cold) 20°C	19 W	
	AC	Pn (holding)	19 W	
		Attraction cold	56 VA (20 W)	
Weight			130 g	
Voltages "Un"			VAC/Hz	Code
-10% to +10% of the Un			120/50 240/50 110/60 220/60 58/50-60/60 55/60 115/50 - 120/60 230/50 - 240/60	A6 A8 B5 B7 T6 4J P8 T1

To Order a Coil choose Coil Ref + Voltage Code, example: 483824 for 120/50 = 483824A6

These coils must be used with suitable housings, Ref: 8760.24 and Ref: 8520.23



Ref. 8760.24

Ref. 8520.23

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

HIGH TEMPERATURE & HIGH POWER COILS 40 mm OIL BURNER

This coils can be mounted with every Parker Solenoid Valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

It can be mounted with all metal housings.

The coil winding is completely encapsulated in synthetic material.

Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².

Coil conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.
This coil is used only in safety application according to DIN/EN/ISO 23551-1:2009-10 (Oil burners)

Specification			High Temperature & High Power	
Reference			483541	
Coil Group			14.3	
Class of insulation			H 180°C	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	20 W	
		P (cold) 20°C	20 W	
	AC	Pn (holding)	20 W	
		Attraction cold	56 VA (20 W)	
Weight			130 g	
Voltages "Un"			VAC/Hz	Code
-10% to +10% of the Un			120/50 240/50 110/60 220/60 58/50-60/60 55/60 115/50 - 120/60 230/50 - 240/60	A6 A8 B5 B7 T6 4J P8 T1

To Order a Coil choose Coil Ref + Voltage Code, example: 483541 for 120/50 = 483541A6

These coils must be used with suitable housings, Ref: 8760.24 and Ref: 8520.23



Ref. 8760.24

Ref. 8520.23

COIL GROUP
2.0/2.1

COILS WITH
SCREW TERMINALS

COIL DOUBLE FREQUENCY 40 mm H CLASS

This coil can be mounted with every Parker Solenoid Valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

They can be mounted with all metal housings.

The coil winding is completely encapsulated in synthetic material.

Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².

Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Double Frequency 100 V - 200 V	
Reference			488553	
Coil Group			2.0/2.1	
Class of insulation			H 180°C	
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	-	
		P (cold) 20°C	-	
	AC	Pn (holding)	9 W	
		Attraction cold	-	
Weight			130 g	
Voltages "Un"			VAC/Hz	Code
-10% to +10% of the Un			100/50-60 200/50-60	P1 P6

To Order a Coil choose Coil Ref + Voltage Code, example: 488553 for 110/50-60 = 488553P1

These coils must be used with suitable housings, see examples below:



Ref. 4270 - Protection **IP 44**

Ref. 8520 - Protection **IP 54**

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

BISTABLE COILS 40 mm FOR IMPULSE APPLICATIONS

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

These coils are specially designed for Lucifer® bistable (or impulse or magnetic latch) solenoid valves for Heating Applications.

They can be mounted only with the Lucifer® metallic housing 4269 or 4538.
The coil winding is completely encapsulated in synthetic material.
Easy mounting in confined spaces. Electrical connection with screw terminals for wire up to 1.5 mm².
Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Bistable (Impulse)			
Reference			484990		485400	
Coil Group			4.0			
Class of insulation			F 155°C			
Ambient temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Length of impulses			Switch on (terminals A-B): minimum 50 ms Switch off (terminals A-C): minimum 35 ms			
Electr. Power consuption	DC	Attraction (hot)	-		13 W	
		Attraction (cold)	-		19 W	
		Release (hot)	-		8 W	
		Release (cold)	-		10 W	
	AC	Attraction (hot)	11 W		-	
		Attraction (cold)	17 W		-	
		Release (hot)	4 W		-	
		Release (cold)	7 W		-	
Weight			150 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50-24/60 110-115/50-115/60 220-230/50-60 48/50-60	P0 1P 3P S4	24 48 110	C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 485400 for 24 VDC = 485400C2

These coils must be used with suitable housings, see examples below:

DIAGRAM

Alternating Current



Direct Current



Only an electrical impulse given to terminals A-C reverses the magnetic field. This magnetic field demagnetises the reversible magnet enough to allow the return spring to bring the plunger back to its initial position and close the valve.

Ref. 4269 - Protection **IP 44**

Ref. 4538 - Protection **IP 67**

COIL GROUP

13.0

COILS WITH ISO-DIN CONNECTORS

COILS 12 V - 24 V FOR TRANSPORTATION APPLICATIONS 32 mm

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

These coils are specially designed for Lucifer® solenoid valves for Transportation Applications.
They can be mounted with the standard Lucifer® housing 2161 or customized housing.

The coil winding is completely encapsulated in epoxy.
Easy mounting and dismounting in confined spaces. Bayonet twist and lock coupling for tight, vibration resistant connection.

Coils conform to the IEC/CENELEC safety standards and complies with European low-voltage directive.

Specification			Transportation			
Reference			496193 with diode		495294 without diode	
Coil Group			13.0			
Degree of protection			IP69K for DIN 400050 part 9			
Ambiant temperature			- 40°C to +120°C The application is limited also by the temperature range of the valve and duty cycle of the valve.			
Insulation Class			F 155°C			
Electrical connection			ISO 15170-A1-2.3-Sn/K2		DIN 72585-A3-2.1	
Elect. Power	DC	Pn (hot)	9 w			
		P (cold) 20°C	-			
	AC	Pn (holding)	-			
		Attraction cold	-			
Weight			147 g			
Voltages "Un"			VDC	Code	VDC	Code
- 30% to + 30% of the Un			12 24	C1 C2	12 24	C1 C2

To Order a Coil choose Coil Ref + Voltage Code, example: 496193 for 24 VDC = 496193C2

These coils must be used with suitable housings Ref.2168 for 12Vdc and 2169 for 24 VDC.





Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

TABLE OF CONTENT

INTRODUCTION

Index for Explosion Proof Electrical Parts 442

List of Coil Groups 443

COILS

Coils for DIN plug connection 446

Coils with flying leads 460

Coils with screw terminal 462

Coils with ISO-DIN connector 469

EXPLOSION PROOF ELECTRICAL PARTS

Level of protection "nAc nCc" 472

Level of protection "db" 480

Level of protection "mb" 481

Level of protection "db mb" 485

Level of protection "eb" 490

Level of protection "eb mb" 491

Level of protection "ia" 494

HOUSINGS 502

COIL ACCESSORIES 506

EXPLOSIVE ENVIRONMENTS 508

COIL APPENDICES

Guidance chart for IS-Barriers 518

ELECTRICAL PART LOW POWER 22 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

Application:
Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T5 is required.

Benefits:
The synthetic material encapsulation of the coil provides an effective compact housing, offering full protection against dust, oil, water, etc.
Small size for ease of mounting in confined spaces.

Reference			495865			
Certificate			LCIE 05 ATEX 6003 X			
Coil Group			1.1			
Type of protection	Gas		II 3 G Ex nAc nCc IIC T5			
	Dust		II 3 D - Ex tc IIIC - T 95°C			
Degree of protection			IP65 (with plug) according to IEC/EN 60529 Standards			
Ambiant temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Insulation Class			F 155°C			
Electrical connection			These coils with connection 2P + G - when mounted together with the supplied Pg 9 plug (delivered with the coil),			
Elect. Power	DC	Pn (hot)	2.5 W			
		P (cold) 20°C	3 W			
	AC	Pn (holding)	2 W			
		Attraction cold	5.7 VA (2.5 W)			
Weight			120 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50 110/50-115/50 220/50-230/50	A2 0A 3D	24	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 495865 for 24 VDC = 495865C2





COIL GROUP

1.2

ELECTRICAL PARTS
"nAc nCc"

ELECTRICAL PART DOUBLE FREQUENCY 22 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

Application:
Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T5 is required.

Benefits:
The synthetic material encapsulation of the coil provides an effective compact housing, offering full protection against dust, oil, water, etc.
Small size for ease of mounting in confined spaces.

Specification			Double Frequency			
Reference			496637			
Certificate			ATEX			
Coil group			1.2			
Type of protection		Gas	Ex nAc nCc IIC T5			
		Dust	II 3 D - Ex tc IIIC - T 95°C			
Degree of protection			IP65 (with plug) according to IEC/EN 60529 Sandards			
Ambiant temperature			-40°C to +50°C The application is limited also by the temperature range of the valve.			
Insulation Class			F 155°C			
Elect. Power	DC	Pn (hot)	3 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	3 W			
		Attraction cold	5.7 VA (2.5 W)			
Weight			75 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50-60 110/50-60 230/50-60 48/50-60 115/60	P0 P2 P9 S4 K8	 12 V 24 V 48 V	 C1 C2 C4

To Order a Coil choose Coil Ref + Voltage Code, example: 496637 for 24 VDC = 496637C2





Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

ELECTRICAL PART 32 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T3/T4 is required.
Ease of mounting in confined space - offers shock and corrosion protection- simplifies conversion of existing equipment to other requirements, etc.

Benefits:
The synthetic material encapsulation of the coil provides an effective compact housing, offering full protection against dust, oil, water, etc.
Small size for ease of mounting in confined spaces.

Reference			495870	496110
Certificate			LCIE 05 ATEX 6003 X	
Coil Group			2.0 / 2.1	
Type of protection		Gas	II 3 G Ex nAc nCc IIC T3/T4	II 3 G Ex nAc nCc IIC T3/T4
		Dust	II 3 D - Ex tc IIIC - T195°C / T130°C	II 3 D - Ex tc IIIC - T195°C / T130°C
Degree of protection			**IP65** (with plug) according to IEC/EN 60529 Standards	
Insulation Class			F (155°C)	
Duty cycle			100%	
Ambiant temperature			-40°C to +65°C / 50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	9 W	-
		P (cold) 20°C	12 W	-
	AC	Pn (holding)	8 W	9 W
		Attraction cold	26 VA (9 W)	32 VA (10 W)
Weight			150 g	

Voltages "Un"	VAC/Hz	Code	VDC	Code	VAC/Hz	Code
-10% to +10% of the Un	220-230/50	3D	24 48 110	C2 C4 C5	24/50-60 48/50-60 110-115/50, 120/60 220-240/50, 240/60	P0 S4 S5 S6

To Order a Coil choose Coil Ref + Voltage Code, example: 495870 for 24 VDC = 495870C2



ELECTRICAL PART LOW POWER 32 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T5/T6 is required.
Ease of mounting in confined space - offers shock and corrosion protection- simplifies conversion of existing equipment to other requirements, etc.

Benefits:
The synthetic material encapsulation of the coil provides an effective compact housing, offering full protection against dust, oil, water, etc.
Small size for ease of mounting in confined spaces.

Reference			496125	
Certificate			LCIE 05 ATEX 6003 X	
Coil group			6.0	
Type of protection		Gas	II 3 G Ex nAc nCc IIC T5/T6	
		Dust	II 3 D Ex tc IIIC T95°C/80°C	
Degree of protection			IP65 (with plug) according to IEC/EN 60529 Standards	
Insulation Class			F (155°C)	
Duty cycle			100%	
Ambiant temperature			-40°C to +65°C / 50°C The application is limited also by the temperature range of the valve.	
Elect. Power	DC	Pn (hot)	1.6 W	
		P (cold) 20°C	2.1 W	
	AC	Pn (holding)	-	
		Attraction cold	-	
Weight			150 g	
Voltages "Un"			VDC	Code
-10% to +10% of the Un			24 48 110	C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 496125 for 24 VDC = 496125C2



ELECTRICAL PART 32 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T3/T4 is required.
Ease of mounting in confined space - offers shock and corrosion protection- simplifies conversion of existing equipment to other requirements, etc.

Benefits:
The synthetic material encapsulation of the coil provides an effective compact housing, offering full protection against dust, oil, water, etc.
Small size for ease of mounting in confined spaces.

Specification			32 mm Coil "nAc nCc"			
Reference			495875			
Certificate			LCIE 05 ATEX 6003 X			
Coil Group			3.0			
Type of protection		Gas	II 3 G Ex nAc nCc IIC T3/T4			
		Dust	II 3 D - Ex tc IIIC - T195°C / T130°C			
Degree of protection			IP65 (with plug) according to IEC/EN 60529 Standards			
Insulation Class			F 155°C			
Duty cycle			100%			
Ambiant temperature			-40°C to +65°C / 50°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	7 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	6 W			
		Attraction cold	-			
Weight			180 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			220-230/50	3D	24	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 495875 for 24 VDC = 495875C2



COIL GROUP
2.0/2.2

NON ENCAPSULATED ELECTRICAL PARTS "nAc nCc"

ELECTRICAL PART 32 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T3 is required.
Ease of mounting in confined space - offers shock and corrosion protection - simplifies conversion of existing equipment to other requirements, etc.

Benefits:
The synthetic material encapsulation of the coil provides an effective compact housing, offering full protection against dust, oil, water, etc.
Small size for ease of mounting in confined spaces.

Specification			32 mm Coil "nAc nCc"			
Reference			495880			
Certificate			LCIE 05 ATEX 6003X			
Coil Group			2.0 / 2.2			
Type of protection		Gas	II 3 G Ex nAc nCc IIC T3			
		Dust	II 3 D - Ex tc IIIC - T195°C			
Degree of protection			IP65 (with plug) according to IEC/EN 60529 Standards			
Insulation Class			H 180°C			
Duty cycle			100%			
Ambiant temperature			-40°C to +65°C The application is limited also by the temperature range of the valve.			
Elect. Power	DC	Pn (hot)	14 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	14 W			
		Attraction cold	-			
Weight			180 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50 110/50 230/50	A2 A5 F4	24	C2

To Order a Coil choose Coil Ref + Voltage Code, example: 495880 for 24 VDC = 495880C2



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

495915 - ELECTRICAL PARTS 50 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection - Ex nAc nCc IIC T3 is required.

Benefits: Rotatable housing 360°, epoxy vernished steel with internal and external screw terminals for earth connection.

Small size for ease of mounting in confined space. Simplifies conversion of existing equipment to hazardous area requirements.

Reference			495915	
Certificate			LCIE 05 ATEX 6010 X	
Coil group			4.0	
Type of protection		Gas	II 3 G Ex nAc nCc IIC T3	
		Dust	II 3 D - Ex tc IIIC - T 195°C	
Degree of protection			**IP67** according to IEC/EN 60529 Standards	
Ambient temperature			-40°C to +65°C The application is limited also by the temperature range of the valve.	
Insulation Class			F 155°C	
Electrical connection			By special cable gland M20 x 1.5 on screw terminals for wires up to 1.5 mm². Cable with outside diameter 6.5 mm to 13.5 mm can be simply sealed using the rubber gland with resilient sealing rings supplied	
Consomation Electrique	AC	Attraction (hot)	11 W	-
		Attraction (cold) 20°C	17 W	-
		Release (hot)	4 W	-
		Release (cold) 20°C	7 W	-
	DC	Attraction (hot)	-	13 W
		Attraction (cold) 20°C	-	19 W
		Release (hot)	-	8 W
		Release (cold) 20°C	-	10 W
Weight			320 g	
Duty cycle			Continuous duty solenoid (ED 100%)	

Voltages "Un"	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un	110-115/50-60	1P		
	220-230/50-60	3P	24	C2
	48/50-60	S4	48	C4
	24/50-60	P0		

To Order a Coil choose Coil Ref + Voltage Code,
example: 495915 for 24 VDC = 495915C2

Schema

As soon as an electrical impulse is given to the terminals A-B, the electromagnetical force attracts the plunger and simultneously magnetizes a reversible permanent magnet ring. This magnet retains the plunger in place. It stays in position even without current. Only an electrical impulse given to terminals A-C reserves the magnetic field. This magnetic field demagnetises the reversible magnet enough to allow the return spring to bring the plunger back to its initial position and close the valve.

Switch: Switch on (terminals A-B): Minimum 50 ms (maximum 1 s)
AC: Switch off (terminals A-C): Minimum 35 ms (maximum 1 s)



COIL GROUP
2.0/2.2

INCREASED SAFETY ELECTRICAL PARTS "nAc nCc"

3.5.1 ELECTRICAL PARTS 496155

These coils can be mounted with every Parker solenoid valves corresponding to the specified Coil Group.
See column "Coil Compatibility Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex nAc nCc IIC T3 is required.

Benefits: Rotatable housing 360°, epoxy vernished steel with internal and external screw terminals for earth connection.

Small size for ease of mounting in confined space.Simplifies conversion of existing equipment to hazardous area requirements.

Reference			496155			
Certificate			LCIE 05 ATEX 6010 X			
Coil Group			2.0/2.2			
Type of protection		Gas	II 3 G Ex nAc nCc IIC T3			
		Dust	II 3 G D - Ex tc IIIC - T 195 °C			
Degree of protection			**IP67** according to IEC/EN 60529 Standards			
Ambiant temperature			-40°C to +65°C The application is limited also by the temperature range of the valve.			
Insulation Class			H 180°C			
Electrical connection			By special cable gland or M20x1.5 on screw terminals for wires up to 1.5 mm². Cables with outside diameter 6.5 mm to 13.5 mm can be simply sealed using the rubber gland with resilient sealing rings supplied.			
Elect. Power	DC	Pn (hot)	14 W			
		P (cold) 20°C	21 W			
	AC	Pn (holding)	14 W			
		Attraction cold	56 VA (20 W)			
Weight			320 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50 230/50 110/50	A2 F4 A5	24 48	C2 C4

To Order a Coil choose Coil Ref + Voltage Code, example: 496155 for 24VAC/50Hz = 496155A2

Fuses:

Both electrical parts have to be connected in series with a safety fuse according to IEC 60127-3.



497105 & 497105.02 - ELECTRICAL PARTS

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex db IIC T4 / T5 / T6 is required.

Benefits: Rotatable 360°, stainless steel with internal and external screw terminals for earth connection.

Small size for ease of mounting in confined space. Simplifies conversion of existing equipement to hazardous area requirements.

Reference			497105 (M20x1.5) 497105.02 (NPT 1/2")			
Certificate			INERIS 12ATEX0041X - IECEx INE 12.0034X			
Coil Group			10.3			
Type of protection		Gas	II 2 G - Ex db IIC T4 / T5 / T6			
		Dust	II 2 D - Ex tb IIIC - 130°C / 95°C / 80°C			
Degree of protection			IP66 (with relevant cable gland) according to IEC/EN 60529 Standards			
Ambient temperature			-50°C to +80°C / +60°C / +40°C The operating temperature of the valve/coil can be limited by that of the valve			
Insulation Class			H 180°C			
Electrical connection			Electric connection is done in the connection chamber on an easily accessible connector terminals. The cable entry to the connection chamber is made through a 1/2" NPT or M20x1.5 thread in which an approved Exdb IIC cable gland must be installed.			
Electrical consumption	DC	Pn (hot)	8 W			
		P (cold) 20°C	9 W			
	AC	Pn (holding)	8 W			
		Attraction cold	9 W			
Voltage Tolerance			+/- 10% of nominal voltage			
Emergising Cuty			ED 100%			
Voltages			VAC/Hz	Code	VDC	Code
			24/50-60 110-115 / 50-60 220-230 / 50-60	P0 1P 3P	12 24 48 110	C1 C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 497105 for 24 VDC = 497105C2



COIL GROUP
1.1

ENCAPSULATED ELECTRICAL PARTS "mb"

RoHS CE Ex IECEx certified

ELECTRICAL PART LOW POWER 22 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application:
Control of solenoid valves in dangerous areas where explosion-proof protection Ex mb IIC T4 / T5 is required.

Benefits:
Coil and magnetic circuit encapsulated in synthetic material - offering shock and corrosion protection. AC coils with integrated thermal fuse. Small size for ease of mounting in confined spaces.

Reference			482605		482606 or 482606.160*			
Certificate			LCIE 02 ATEX 6014 X - IECEx LCI 07.0026 X					
Coil Group			1.1					
Type of protection		Gas	II 2 G - Ex mb IIC T4 / T5					
		Dust	II 2 D - Ex tb IIIC - T130°C / 95°C					
Degree of protection			**IP65** (with plug) according to IEC/EN 60529 Standards					
Ambiant temperature			-40°C to +65°C / +40°C The application is limited also by the temperature range of the valve.		-40°C to +65°C / +35°C			
Insulation Class			F 155°C					
Electrical connection			Cable connection (3 x 0.75 mm²) encapsulated with coil, cable material according to application					
Elect. Power	DC	Pn (hot)	5 W		2.5 W			
		P (cold) 20°C	6.5 W		3 W			
	AC	Pn (holding)	4 W		2 W			
		Attraction cold	8.9 VA (5 W)		5.7 VA (2.5 W)			
Weight			150 g					
Voltages "Un"			VDC	Code	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			12 24	C1 C2	24/50 48/50 110/50-115/50 220/50-230/50 220-230/60 24/60	A2 A4 0A 3D 7J B2	12 24 48 110	C1 C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 482605 for 24 VDC = 482605C2

* 482606.160 - 6 m cable length - available only in C2 and 3D
* 482606 - 1.5 m cable length

Fuses:
Both electrical parts 482605 & 482606 have to be connected in series with a safety fuse according to CEI 60127-3. Indicating example bellow:

482605:

DC: 12 V, 1000 mA - 24 V, 500 mA

482606:

DC: 12 V, 400 mA - 24 V, 200 mA - 48 V, 100 mA - 110 V, 50 mA
AC 50 HZ: 24 V, 250 mA - 48 V, 125 mA - 110/115 V, 63 mA - 220/230 V, 32 mA
AC 60 Hz: 24 V, 315 mA - 110/115 V, 63 mA - 220/230 V, 32 mA



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP
2.0/2.1

ENCAPSULATED ELECTRICAL PARTS "mb"

ZONE 1/21

WITH WATER PROOF METAL HOUSING 50 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex mb IIC T4/ T5 is required.

Benefits: Epoxy-vernished steel housing - solenoid coil, rectifier (silicium diodes), fuse and varistor protection element are completely encapsulated in the coil housing by means of epoxy resin.

Small size for ease of mounting in confined space. Simplifies conversion of existing equipment to hazardous area requirements.

Reference			492070 (with 3 m cable length) 492070.60 (with 6 m cable length)			
Certificate			LCIE 02 ATEX 6017 X - IECEx LCI 09.0024 X			
Coil Group			2.0 / 2.1			
Type of protection		Gas	II 2 G - Ex mb IIC T4/ T5			
		Dust	II 2 D - Ex tb IIIC - T130 / 95°C			
Degree of protection			IP67 according to IEC/EN 60529 standards			
Ambient temperature			-40°C to +65°C / 40°C The application is limited also by the temperature range of the valve.			
Insulation Class			H 180°C			
Electrical connection			Cable connection (3 x 1.5 mm²) with cable gland M20 x 1.5, external earth screw connection.			
Elect. Power	DC	Pn (hot)	8 W			
		P (cold) 20°C	10 W			
	AC	Pn (holding)	9 W			
		Attraction cold	11 W			
Weight			500 g			
Voltages "Un" -10% to +10% of the Un			VAC/Hz	Code	VDC	Code
			110/50-60 220/50-60 230/50-60 240/50-60	P2 R5 P9 Q1	24 48 110	C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: 492070 for 24 VDC = 492070C2





COIL GROUP
2.0/2.1

ENCAPSULATED
ELECTRICAL PARTS
"mb"

RoHS CE Ex IECEx certified

HZ10 COIL DOUBLE FREQUENCY

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex mb IIC T3/T4/T5 is required.

The coil is delivered with a 3m cable.

Specification			Double Frequency			
Reference			HZ10			
Certificate			LCIE 02 ATEX 6020 X - IECEx LCI 08.0027 X			
Coil Group			2.0 / 2.1			
Type of protection		Gas	II 2 G - Ex mb IIC T3/T4/T5			
		Dust	II 2 D - Ex tb IIIC T195°C / 130°C / 95°C			
Degree of protection			**IP65** (with plug) according to IEC/EN 60529 Standards			
Ambient temperature			-40°C to +80°C / 65°C / 40°C The application is limited also by the temperature range of the valve.			
Insulation Class			H 180°C			
Duty cycle			100% continuous			
Electrical connection			Cable connection (3 x 1.5 mm²) with cable gland M20 x 1.5, external earth screw connection.			
Elect. Power	DC	Pn (hot)	8 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	8 W			
		Attraction cold	-			
Weight			299 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/60 110/50-120/60 220/50-240/60	B2 P3 Q3	12 24 120	C1 C2 C6

To Order a Coil choose Coil Ref + Voltage Code, example: HZ10 for 24 VDC = HZ10C2



Dimensions in Inches.

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

HZ11 COIL DOUBLE FREQUENCY

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex mb IIC T3/T4/T5 is required.

The coil is delivered with a 3m cable.

Specification			Double Frequency			
Reference			HZ11			
Certificate			LCIE 02 ATEX 6020 X - IECEx LCI 08.0027 X			
Coil Group			2.0 / 2.2			
Type of protection		Gas	II 2 G - Ex mb IIC T3/T4/T5			
		Dust	II 2 D - Ex tb IIIC T195°C / 130°C / 95°C			
Degree of protection			IP65 (with plug) according to IEC/EN 60529 Standards			
Ambient temperature			-40°C to + 65°C / 40°C The application is limited also by the temperature range of the valve..			
Insulation Class			H 180 °C			
Duty cycle			100% continuous			
Elect. Power	DC	Pn (hot)	22 W			
		P (cold) 20°C	-			
	AC	Pn (holding)	14 W			
		Attraction cold	-			
Weight			299 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/60	B2	12	C1
			110/50-120/60	P3	24	C2
			220/50-240/60	Q3	120	C6

To Order a Coil: Coil Ref + Voltage Code, example: HZ11 for 24 VDC = HZ11C2



Dimensions in Inches.

COIL GROUPS
6.0

FLAME PROOF ENCAPSULATED ELECTRICAL PARTS "db mb"

495900 - LOW POWER ELECTRICAL PARTS 37 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex db mb IIC T4 to T6 Gb is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing (class H). Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

The plastic housing is delivered with M20 x 1.5 cable gland certified together with the equipment. Small size for ease of mounting in confined space.

Reference			495900 (VAC)		495900 (VDC)	
ATEX/IECEx Certificates			IMQ 22 ATEX 020 X - IECEx IMQ 22.0002 X			
KCs Certificates			KTL 24-KA4BO-0457X / 0458X		KTL 24-KA4BO-0459X / 0460X	
CCC Certificate			CCC 2021322307004013			
Coil Group			6.0			
Type of protection	II 2 G		Ex db mb IIC T4 / T5 / T6 Gb		Ex db mb IIC T4 / T5 / T6 Gb	
	II 2 D		Ex tb IIIC - 130°C / 95°C / 80°C Db		Ex tb IIIC - T130°C / 95°C / 80°C Db	
Degree of protection			**IP66/IP67** according to IEC/EN 60529 Standards			
Ex d enclosure			The «Ex d» enclosure can withstand a maximum pressure of 58 bar			
Environmental temperature			-40°C to +80°C /60°C / 40°C		-40°C to +80°C / 65°C / 55°C	
			The thermal class depends on the environmental temperature as shown above The application is limited also by the temperature range of the valve			
Insulation Class			H (180°C)			
Electrical connection			Electric connection is done in the connection box on easily accessible connector terminal. The introduction of the cable (Ø min 5 mm, Ø max 11 mm, section max. 2.5 mm², 2P+E) in the connection box passes by the built-in M20x1.5 cable gland			
Elect. Power	DC	Pn (hot)	-		2 W	
		P (cold) 20°C	-		2.5 W	
	AC	Pn (holding)	2.5 W		-	
		Attraction cold	3 W		-	
Voltages "Un"			VAC/Hz	Code	VDC	Code
Voltage tolerance: +/- 10% Un			24/50 48/50 115/50 230/50 115/60 240/60	A2 A4 E5 F4 K8 B8	12 24 48 110	C1 C2 C4 C5

To Order a Coil: Coil Ref + Voltage Code495900 24VDC = **495900C2**





COIL GROUPS
2.0/2.1

FLAME PROOF ENCAPSULATED
ELECTRICAL PARTS
"db mb"

RoHS IECEx certified JPEx certified*

ZONE 1/21

495905 - ELECTRICAL PARTS 37 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex db mb IIC T4 Gb is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing (class H). Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

The plastic housing is delivered with M20 x 1.5 cable gland certified together with the equipment. Small size for ease of mounting in confined space.

Reference			495905 (VAC)	495905 (VDC) & 495905.05**
ATEX/IECEx Certificates			IMQ 22 ATEX 020 X - IECEx IMQ 22.0002 X	
KCs Certificates			KTL 24-KA4BO-0457X / 0458X	KTL 24-KA4BO-0459X / 0460X
CCC Certificate			CCC 2021322307004013	
JPEx Certificate*			DEK24, 0036X	
Coil Group			2.0 / 2.1	
Type of protection		II 2 G	Ex db mb IIC T4 Gb	
		II 2 D	Ex tb IIIC - 130°C Db	
Degree of protection			**IP66/IP67** according to IEC/EN 60529 Standards	
Ex d enclosure			The «Ex d» enclosure can withstand a maximum pressure of 58 bar	
Environmental temperature			-40°C to +80°C The thermal class depends on the environmental temperature as shown above The application is limited also by the temperature range of the valve	
Insulation Class			H (180°C)	
Electrical connection			Electric connection is done in the connection box on easily accessible connector terminal. The introduction of the cable (Ø min 5 mm, Ø max 11 mm, section max. 2.5 mm², 2P+E) in the connection box passes by the built-in M20x1.5 cable gland	
Elect. Power	DC	**Pn** (hot)	8 W	
		P (cold) 20°C	9 W	
	AC	**Pn** (holding)	8 W	
		Attraction cold	9 W	

Voltages "Un"	VAC/Hz	Code	VDC	Code
Voltage tolerance: +/- 10% Un	24/50	A2	24	C2
	48/50	A4	48	C4
	115/50	E5	110	C5
	230/50	F4		
	115/60	K8		
	240/60	B8		

To Order a Coil choose Coil Ref + Voltage Code, example: **495905** for **24VDC** = **495905C2**

*JPEx for 495905C2, C4, C5 only
** 495905.05 available only in C4



495905



*495905.05



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP
10.2/10.1

FLAME PROOF ENCAPSULATED ELECTRICAL PARTS "db mb"

496555 & 496560 - ELECTRICAL PARTS 37 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex db mb IIC T4 to T6 Gb is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing (class H). Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

The plastic housing is delivered with M20 x 1.5 cable gland certified together for the equipement. Small size for ease of mounting in confined space.

Reference			496555				496560			
ATEX/IECEx Certificates			IMQ 22 ATEX 020 X – IECEx IMQ 22.0002 X							
KCs Certificates			KTL 24-KA4BO-0465X / 0466X / 0467X / 0468X							
CCC Certificate			CCC 2021322307004013							
Coil Group			10.2				10.1			
Type of protection		II 2 G	Ex db mb IIC T4 / T5 / T6 Gb				Ex db mb IIC T4 Gb			
		II 2 D	Ex tb IIIC - T130°C / 95°C / 80°C Db				Ex tb IIIC - T130°C Db			
Degree of protection			IP66/IP67 according to IEC/EN 60529 Standards							
Ex d enclosure			The «Ex d» enclosure can withstand a maximum pressure of 58 bar							
Environmental temperature			-40°C to +65 / 50 / 35°C The thermal class depends on the environmental temperature as shown above The application is limited also by the temperature range of the valve				-40°C to +65°C			
Insulation Class			H (180°C)							
Electrical connection			Electric connection is done in the connection box on easily accessible connector terminal. The introduction of the cable (Ø min 5 mm, Ø max 11 mm, section max. 2.5 mm², 2P+E) in the connection box passes by the built-in M20x1.5 cable gland							
Elect. Power	DC	Pn (hot)	-		6 W		-		8 W	
		P (cold) 20°C	-		7.5 W		-		10.5 W	
	AC	Pn (holding)	6 W		-		8 W		-	
		Attraction cold	7.5 W		-		10.5 W		-	
Voltages "Un"			VAC/Hz	Code	VDC	Code	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			230/50-60 110/50-60 24/50-60 48/50-60	P9 P2 P0 S4	24 48 110	C2 C4 C5	230/50-60 110/50-60 24/50-60 48/50-60	P9 P2 P0 S4	24 48 110	C2 C4 C5

To Order a Coil choose Coil Ref + Voltage Code, example: **496555** for **24VDC** = **496555C2**





Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP
10.2/10.1

FLAME PROOF ENCAPSULATED
ELECTRICAL PARTS
"db mb"

496700 & 496800 - ELECTRICAL PARTS 37 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex db mb IIC T4 to T6 Gb is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing (class H). Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

The plastic housing is delivered with 1/2" NPT or M20 x 1.5 threaded hole for wide range of cable glands. Small size for ease of mounting in confined space.

Reference			496700 or 496700.02 (NPT)		496800 or 496800.02 (NPT)	
ATEX/IECEx Certificates			IMQ 22 ATEX 020 X – IECEx IMQ 22.0002 X			
KCs Certificates			KTL 24-KA4BO-0461X / 0462X / 0463X / 0464X			
CCC Certificate			CCC 2021322307004013			
Coil Group			10.2		10.1	
Type of protection		II 2 G	Ex db mb IIC T4 / T5 / T6 Gb		Ex db mb IIC T4 Gb	
		II 2 D	Ex tb IIIC - T130 / 95 / 80°C Db		Ex tb IIIC - T130°C Db	
Degree of protection			IP66/IP67 according to IEC/EN 60529 Standards			
Environmental temperature			-40°C to +35°C / +50°C / +65°C The thermal class depends on the environmental temperature as shown above The application is limited also by the temperature range of the valve		-40°C to +65°C	
Insulation Class			H (180°C)			
Electrical connection			Electric connection is done in the connection box on easily accessible connector terminals. The introduction of the cable (Ø min 5 mm, Ø max 11 mm, section max. 2.5 mm², 2P+E) in the connection box passes by the M20x1.5 (or ½" NPT for .02 models) cable gland (not included).			
Elect. Power	DC	Pn (hot)	-	6 W	-	8 W
		P (cold) 20°C	-	7.5 W	-	10.5 W
	AC	Pn (holding)	6 W	-	8 W	-
		Attraction cold	7.5 W	-	10.5 W	-

Voltages "Un"	VAC/Hz	Code	VDC	Code	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un	230/50-60	P9	24	C2	230/50-60	P9	24	C2
	110/50-60	P2	48	C4	110/50-60	P2	48	C4
	24/50-60	P0	110	C5	24/50-60	P0	110	C5
	48/50-60	S4			48/50-60	S4		

To Order a Coil choose Coil Ref + Voltage Code, example: **496700** for **24VDC** = **496700C2**





Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

COIL GROUP
2.0/2.1

FLAME PROOF ENCAPSULATED ELECTRICAL PART "db mb"

493640 OR HZ09 - ELECTRICAL PARTS

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex db mb IIC T4/T5 is required.

Benefits: Metal armature encapsulated in synthetic material provides high shock and corrosion protection.

Small size for ease of mounting in confined space.

Reference			493640 493640.60*			
Certificate			LCIE 02 ATEX 6009 X			
Coil Group			2.0 / 2.1			
Type of protection		Gas	II 2 G Ex db mb IIC T4/T5			
		Dust	II 2 D - Ex tb IIIC - T130°C / T95°C			
Degree of protection			**IP65** according to IEC/EN 60529 Standards			
Ambiant temperature			-40°C +75°C / +40°C The application is limited also by the temperature range of the valve.			
Class of insulation			F (155 °)			
Electrical connection			Special "Ex db" cable gland, galvanized steel, with EPDM sealing. (EPR) cable, outside diameter 7.3 ± 0.5 mm and 3000 mm long.			
Elect. Power	DC	Pn (hot)	8 W			
		P (cold) 20°C	9 W			
	AC	Pn (holding)	8 W			
		Attraction cold	32 VA (9 W)			
Weight			500 g			
Voltages "Un"			**VAC/Hz**	**Code**	**VDC**	**Code**
- 15% to +10% of the Un			110/50	A5	24	C2
			110-120/50-60	P3	48	C4
			220-240/50-60	Q3	120	C6

To Order a Coil choose Coil Ref + Voltage Code, example: 493640 for 24 VDC = 493640C2

* 493640.60 - 6 m cable length - Available only in C2



Fuses

This electrical part is equipped with a standard thermal cut-off fuse on all models and voltages

This electrical part must be connected in series with a safety fuse according to IEC 60127-3.

DC: 24V, 400 mA

AC: 110/50-120/60, 200 mA
220/50-240/60, 100 mA
230/50, 95 mA

483371 & 494040 - ELECTRICAL PARTS 50 MM

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex eb IIC T3 orT4 is required.

Benefits: Rotatable housing 360°, epoxy vernished steel with internal and external screw terminals for earth connection.

Small size for ease of mounting in confined space.Simplifies conversion of existing equipment to hazardous area requirements.

Reference			483371	494040
Certificate			LCIE 02 ATEX 6011 X	LCIE 02 ATEX 6013 X
Coil Group			2.0 / 2.1	
Type of protection		Gas	II 2 G - Ex eb IIC T4	II 2 G - Ex eb IIC T3 / T4
		Dust	II 2 D - Ex tb IIIC - T130°C	II 2 D - Ex tb IIIC - T195°C / T130 °C
Degree of protection			**IP67** according to IEC/EN 60529 Standards	
Ambiant temperature			-40°C to +65°C The application is limited also by the temperature range of the valve.	-40°C to +90°C / to +65°C
Class of insulation			F 155°C	H (180°)
Electrical connection			By special cable gland or M20 x 1.5 "Ex eb" on screw terminals for wires up to 1.5 mm². Cables with outside diameter 6.5 mm to 13.5 mm can be simply sealed using the ru bber gland with resilient sealing rings supplied.	
Elect. Power	DC	Pn (hot)	8 W	8 W
		P (cold) 20°C	9 W	9 W
	AC	Pn (holding)	8 W	8 W
		Attraction cold	32 VA (9 W)	32 VA (9 W)
Weight			320 g	

Voltages "Un"	VAC/Hz	Code	VDC	Code	VAC/Hz	Code	VDC	Code
-10% to +10% of the Un	24/50	A2	6	C0				
	48/50	A4	12	C1				
	110-115/50	OA	24	C2	220-230/50	3D	24	C2
	220-230/50	3D	48	C4	380/50	5P	125	3N
	24/60	B2	110	C5				
	220-240/60	4K	220	C7				

To Order a Coil choose Coil Ref + Voltage Code, example: 483371 for 24 VDC = 483371C2

Fuses:
Both electrical parts have to be connected in series
with a safety fuse according to IEC 60127-3.

483371:

DC: 24 V, 400 mA - 48V, 250 mA - 110 V, 100 mA
AC 50HZ: 24 V, 630 mA - 48V, 315 mA - 110 V, 160 mA - 220/230 V, 80 mA

494040:

DC: 12 V, 400 mA - 24V, 200 mA - 48 V, 100 mA - 110V, 50 mA
AC 50HZ: 24 V, 250 mA - 48V, 125 mA - 110/115 V, 63 mA - 220/230 V, 32 mA



COIL GROUP
10.1

INCREASED SAFETY AND ENCAPSULATED ELECTRICAL PARTS **"eb mb"**

492310 - ELECTRICAL PARTS 50 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex eb mb II T4 to T5 is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing. Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

Small size for ease of mounting in confined space.

Reference			492310			
Certificate			LCIE 02 ATEX 6023 X - IECEx LCI 06.0011 X			
Coil group			10.1			
Type of protection		Gas	II 2 G - Ex eb mb II T4 / T5			
		Dust	II 2 D - Ex tb IIIC - T130°C / T95°C			
Degree of protection			**IP66** according to IEC/EN 60529 Standards			
Ambiant temperature			-40°C to +75°C / to +40°C The operating temperature of the valve/coil can be limited by that of the valve			
Class of insulation			H 180°C			
Electrical connection			Connection box with terminals and cable entry via gland M20 x 1.5 - Possibility for additional earth via external screw.			
Elect. Power	DC	Pn (hot)	6 W			
		P (cold) 20°C	7.5 W			
	AC	Pn (holding)	6 W			
		Attraction cold	7.5 W			
Weight			500 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50-60 48/50-60 230/50-60 110/50-60 240/50-60 220/50-60	P0 S4 P9 P2 Q1 R5	12 24 48 110 220	C1 C2 C4 C5 C7

To Order a Coil choose Coil Ref + Voltage Code, example: 492310 for 24 VDC = 492310C2





492210 - ELECTRICAL PARTS "BOOSTER" 50 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection - Ex eb mb IIC T5/T6 is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing. Solenoid coil, fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.Small size for ease of mounting in confined space. Simplifies conversion of existing equipment to hazardous area requirements.

Available only in 24 VDC (suffix code : C2)

Reference		492210
Certificate		LCIE 02 ATEX 6023 X - IECEx LCI 06.0011 X
Coil group		9.0
Type of protection	Gas	II 2 G - Ex eb mb IIC T5 / T6
	Dust	II 2 D - Ex tb IIIC - T95°C / T80°C
Degree of protection		IP66 according to IEC/EN 60529 Standards
Ambient temperature		-40°C to +75°C / +40°C The operating temperature of the valve/coil can be limited by that of the valve
Insulation Class		H 180°C
Electrical connection		Connection box with terminals and cable entry via gland M20 x 1.5 Possibility for additional earth via external screw
Power consumption DC		1 to 1.8 W according to length of cable
Attraction current		I min = 60 mA (I nominal = 75 mA)
Voltage DC		U nominal = 24 VDC (C2), Umin = 21.6 VDC
Resistance		23 Ω + (R = 270 Ω)
Inductance		0 mH
Capacitance		0 µF
Response time		2 - 4 s
Weight		500 g

To Order a Coil choose Coil Ref + Voltage Code, example: 492210 for 24 VDC = 492210C2



Indications:

Booster for Offshore valves



These electrical parts need an external fuse of I = 100 mA

COIL GROUP
2.0/2.1

INCREASED SAFETY AND ENCAPSULATED ELECTRICAL PARTS "eb mb"

RoHS IECEx certified

492190 - ELECTRICAL PARTS 50 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex eb mb IIC T3 to T4 is required.

Benefits: Rotatable 360°, fiberglass -reinforced plastic housing. Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

Small size for ease of mounting in confined space.

Reference			492190			
Certificate			LCIE 02 ATEX 6023 X - IECEx LCI 06.0011 X			
Coil Group			2.0 / 2.1			
Type of protection		Gas	II 2 G - Ex eb mb IIC T3 / T4			
		Dust	II 2 D - Ex tb IIIC - 195°C / 130°C			
Degree of protection			**IP66** according to IEC/EN 60529 Standards			
Ambient temperature			-40°C to +75°C / +40°C The operating temperature of the valve/coil can be limited by that of the valve			
Insulation Class			H 180°C			
Electrical connection			Connection box with terminals and cable entry via gland M20 x 1.5 Possibility for additional earth via external screw			
Electrical consumption	DC	Pn (hot)	9 W			
		P (cold) 20°C	11 W			
	AC	Pn (holding)	11 W			
		Attraction cold	13 W			
Weight			320 g			
Voltages "Un"			VAC/Hz	Code	VDC	Code
-10% to +10% of the Un			24/50-60	P0		
			110/50-60	P2	24	C2
			230/50-60	P9	48	C4
			48/50-60	S4	110	C5
			220/50-60	R5	220	C7
			240/50-60	Q1		

To Order a Coil choose Coil Ref + Voltage Code, example: 492190 for 24 VDC = 492190C2







483580 - 483960 ELECTRICAL PARTS 32 mm "IS"

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex ia IIC T6 is required.

Benefits: Fully encapsulated assembly comprising a coil, metal armature, three diodes circuit and DIN plug connection.

The encapsulation provides an effective compact housing offering full protection against dust, oil, water, etc.

Small size for ease of mounting in confined space. Available only in 28 VDC (suffix code : N7)

Reference (without plug) (with plug)			483580.01 483960.01
Certificate			LCIE 02 ATEX 6065 X - IECEx LCI 07.0025 X
Coil Group			7.0
Type of protection		Gas	II 1 G - Ex ia IIC - T6
		Dust	II 1 D - Ex ta IIIC - T80°C
Degree of protection			**IP65** with plug according to IEC/EN 60529 Standards
Ambiant temperature			- 40°C à + 55°C The operating temperature of the valve/coil can be limited by that of the valve.
Electrical connection			The coil is connected with a 2P + E plug according to EN 175301-803 type A Contact 1 is marked as the positive pole .
Maximum supply voltage			28 VDC (N7) - 110 mA The minimum operating voltage at maximum 60°C is 14 VDC.
Power	DC	Minimum	500 mW
		Maximum	3 W
			Depending on applied voltage, IS barrier type and resistance of connected cable
Coil resistance at 20°C Impedance Apparent inductance Apparent capacitance			340 Ω 340 Ω 0 mH 0 µF
Weight			160 g (with plug)

To Order a Coil choose Coil Ref + Voltage Code, example: 483580 for 28 VDC = 483580N7



Important

The intrinsically safe supply circuit should have enough capacity in all environmental conditions to assure a minimum operating current of 35 mA through the coil.

For Valves with operator «96» and «97», a minimum current of 65 mA is required.

The minimal holding current is 20 mA.



For the barrier compatibility see the corresponding table in in appendix section.

These coil must be used with suitable housing : Ref. 2995

COIL GROUP
8.0

INTRINSICALLY SAFE
ELECTRICAL PARTS
"ia"

RoHS IECEx certified

495910 - MINIWATT - 0.3 W
ELECTRICAL PARTS "IS" "BOOSTER" 37 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex ia IIC T4 to T6 is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing (class H). Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

Small size for ease of mounting in confined space. Available only in 28 VDC (code: N7).

Reference			495910
Certificate			LCIE 03 ATEX 6464 X - IECEx LCI 07.0006 X
Coil Group			8.0
Type of protection		Gas	II 1 G - Ex ia IIC - T4 / T5 / T6
		Dust	II 1 D - Ex ta IIIC T80 / 95 / 130°C
Degree of protection			**IP67** according to IEC/EN 60529 Standards
Ambiant temperature			- 40°C to +80°C / 75°C / 65°C The application is limited also by the temperature range of the valve..
Class of insulation			H 180°C
Electrical connection			Electric connection is done in the connection box on an easily accessible connector terminals. The introduction of the cable (Ø min 7 mm, Ømax. 11 mm, section max. 2.5 mm²) in the connection box passes by the built in M20 x 1.5 cable gland
Maximum supply voltage			28 VDC (N7) - 110 mA
Power	DC	Minimum	0.3 W (with 13 VDC)
		Maximum	1.2 W (with 24 VDC)
			Depending on applied voltage, IS barrier type and resistance of connected cable
Line check			4 mA or 5 VDC max
Coil resistance at 20°C Impedance Apparent inductance Apparent capacitance			Charge ~ 550 Ω - Holding ~ 500 Ω 0 mH 0 µF
Response time			2 - 3 s
Weight			500 g

To Order a Coil choose Coil Ref + Voltage Code, example: 495910 for 28 VDC = 495910N7





Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

496565 ELECTRICAL PARTS "BOOSTER" "IS" 37 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex ia IIC T4 to T6 is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing (class H).
Solenoid coil, rectifier (silicium diodes), fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.

The plastic housing is delivered with M20 x 1.5 cable gland. Small size for ease of mounting in confined space. Available only in 28 VDC (code: N7).

Reference		496565	
Certificate		LCIE 08 ATEX 6071 X - IECEx LCI 08.0030 X	
Coil group		9.0	
Type of protection	Gas	II 1 G - Ex ia IIC - T4 / T5 / T6	
	Dust	II 1 D - Ex ta IIIC - T80 / T95 /T130°C	
Degree of protection		IP67 according to IEC/EN 60529 Standards	
Ambiant temperature		- 40°C to +80 / 75 / 65°C The application might also be limited by the temperature range of the valve.	
Electrical connection		Cable connection through a plastic cable gland M20 x 1.5 allowing use of cable diameter from 7 to 12 mm. Additional earth connection possible with external screw terminal.	
Class of insulation		H 180°C	
Minimum Courant of function		20 mA	
Minimum voltage of function at 60°C		13 VDC (N7)	
Safety parameters Maximum acceptable values: Ui (V) / Ii (mA) / Pi (W)		28 V / 110 mA / 0.77 W 27 V / 120 mA / 0.81 W 26 V / 135 mA / 0.88 W 25 V / 150 mA / 0.94 W 24 V / 170 mA/ 1.02 W	28 V / 280 mA / 1.96 W 27 V / 320 mA / 2.16 W 26 V / 350 mA / 2.27 W 25 V / 390 mA / 2.43 W 24 V / 430 mA/ 2.58 W
Line check		4 mA or 5 VDC max	
Apparent Impedance Typ. Apparent Inductance Apparent Capacitance		Attraction ~ 600 Ω - Holding ~ 570 Ω 0 mH 0 µF	
Response Time Typ.		2 - 4 s	
Weight		500 g	

To Order a Coil choose Coil Ref + Voltage Code,
example: 496565 for 28 VDC = 496565N7



COIL GROUP
9.0

INTRINSICALLY SAFE ELECTRICAL PARTS "ia"

RoHS CE IECEx certified

492965 ELECTRICAL PART "BOOSTER" "IS" 50 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex ia IIC - T6 is required.

Benefits: Rotatable 360° fibreglass-reinforced plastic housing. Solenoid coil, fuses and varistor protection are completely encapsulated into the coil housing by epoxy resin for shock and corrosion protection.Small size for ease of mounting in confined space. Simplifies conversion of existing equipment to hazardous area requirements.

Small size for ease of mounting in confined space. Available only in 28 VDC.

Reference			492965.01 - (Stainless steel fixation) 492965.02 - (Plastic fixation)
Certificate			LCIE 02 ATEX 6066 X - IECEx LCI 07.0007 X
Coil Group			9.0
Type of protection		Gas	II 1 G - Ex ia IIC - T6
		Dust	II 1 D - Ex ta IIIC - T80°C
Degree of protection			IP66 according to IEC/EN 60529 Standards
Ambiant temperature			- 40°C to +65°C The application is limited also by the temperature range of the valve.
Electrical connection			Cable connection through a plastic or stainless steel cable gland M20 x 1.5 allowing use of cable diameter from 10 to 12 mm. Additional earth connection possible with external screw terminal.
Class of insulation			H 180°C
Maximum supply voltage			28 VDC (N7) - 110 mA
Power	DC	Minimum	0.3 W (with 13 VDC)
		Maximum	2.3 W (with 24 VDC)
			Depending on applied voltage, IS barrier type and resistance of connected cable
Line check			4 mA or 5 VDC max
Coil resistance at 20°C Impedance Apparent inductance Apparent capacitance			85 Ω 275 Ω (with 13 VDC) - 260 Ω (with 24 VDC) 0 mH 0 µF
Response time			2 - 4 s
Weight			500 g

To Order a Coil choose Coil Ref + Voltage Code, example: 492965.01 for 28 VDC = 492965.01N7



Important

The intrinsically safe supply circuit should have enough capacity in all environmental conditions to assure a minimum operating current of 29 mA through the coil.

The minimal holding current is 20 mA.



For the barrier compatibility see the corresponding table in appendix section.

488650.01 & 490885 "NEMA" ELECTRICAL PARTS "IS" 50 mm

This coil can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.

See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where explosion-proof protection Ex ia IIC - T6 is required.

Benefits: Rotatable 360° housing, polyamid with fibreglass housing and cover. Coil, electronic circuits and other elements required for intrinsic safety are completely encapsulated in the housing with epoxy material for shock and corrosion protection.

Small size for ease of mounting in confined space.

Reference			488650.01	490885
Certificate			LCIE 02 ATEX 6024 X	LCIE / FM / CSA
Coil Group			7.0	
Type of protection		Gas	II 1 G - Ex ia IIC - T6	Cl. I, Div.I, Gr. A, B, C, D, Cl. II, Div.I, Gr. E, F, G
		Dust	II 1 D - Ex ta IIIC - T80°C	
Degree of protection			**IP66** according to IEC/EN 60529 Standards	NEMA 4 - 4X
Ambiant temperature			- 40°C to +65°C The operating temperature of the valve/coil can be limited by that of the valve.	60°C
Electrical connection			Cable entry through a cable gland M20 x1.5. Screw terminals for leads 3 x 1.5 mm² max. Additional earth connection possible with external screw terminal	
Class of insulation			H 180°C	
Maximum supply voltage			28 VDC (N7) - 110 mA The minimum operating voltage at maximum 60°C is 11.5 VDC.	30 VDC(L8) - 100 mA
Power	DC	Minimum	300 mW	
		Maximum	3 W	
			Dependent on the applied voltage, type of barrier IS and the resistance of the connected cable	
Coil resistance at 20°C Impedance Apparent inductance Apparent capacitance			295 Ω 345 Ω 0 mH 0 µF	
Weight			500 g	

To Order a Coil choose Coil Ref + Voltage Code, example: 490885 for 30VDC = 490885L8



Important

The intrinsically safe supply circuit should have enough capacity in all environmental conditions to assure a minimum operating current of 29 mA through the coil.

The minimal holding current is 20 mA.



For the barrier compatibility see the corresponding table in appendix section.

COIL GROUP
12.0

INTRINSICALLY SAFE
ELECTRICAL PARTS
"ia"

482870.01 ELECTRICAL PARTS "IS" 50 mm

These coils can be mounted with every Parker ATEX solenoid valves corresponding to the specified Coil Group.
See column "Coil Group" within valve pages.

Application: Control of solenoid valves in dangerous areas where an explosion-proof protection Ex ia IIC - T6 is required.

Benefits: Rotatable 360° housing, polyamid with fibreglass housing and cover. Coil, electronic circuits and other elements required for intrinsic safety are completely encapsulated in the housing with epoxy material for shock and corrosion protection.

Small size for ease of mounting in confined space.

Reference			482870.01
Certificate			LCIE 02 ATEX 6024 X
Coil Group			12.0
Type of protection		Gas	II 1 G - Ex ia IIC - T6
		Dust	II 1 D - Ex ta IIIC - T80°C
Degree of protection			**IP66** according to IEC/EN 60529 Standards
Ambiant temperature			- 40°C to +65°C The application is limited also by the temperature range of the valve.
Class of insulation			H 180°C
Electrical connection			Cable connection through a stainless steel cable gland M20 x 1.5 allowing use of cable diameter from 10 to 12 mm. Additional earth connection possible with external screw terminal.
Maximum supply voltage			28 VDC (N7) - 110 mA
Power	DC	Minimum	300 mW
		Maximum	3 W
			Depending on applied voltage, IS barrier type and resistance of connected cable
Coil resistance at 20°C Impedance Apparent inductance Apparent capacitance			295 Ω 345 Ω 0 mH 0 µF
Weight			500 g

To Order a Coil choose Coil Ref + Voltage Code, example: 482870.01 for 30VDC =482870L8



Important

The intrinsic safety supply circuit must have sufficient capacitance in all ambient conditions to guarantee a minimum operating current in excess of 29 mA across the coil.

The minimum current for holding in the energised position is 20 mA



For the barrier compatibility see the corresponding table in appendix section.

TABLE OF CONTENT

INTRODUCTION

Index for Explosion Proof Electrical Parts 442

List of Coil Groups 443

COILS

Coils for DIN plug connection 446

Coils with flying leads 460

Coils with screw terminal 462

Coils with ISO-DIN connector 469

EXPLOSION PROOF ELECTRICAL PARTS

Level of protection "nAc nCc" 472

Level of protection "db" 480

Level of protection "mb" 481

Level of protection "db mb" 485

Level of protection "eb" 490

Level of protection "eb mb" 491

Level of protection "ia" 494

HOUSINGS 502

COIL ACCESSORIES 506

EXPLOSIVE ENVIRONMENTS 508

COIL APPENDICES

Guidance chart for IS-Barriers 518

HOUSING

4270 COIL STANDARD HOUSING WITH SCREW TERMINALS

Standard housing:

Reference:	4270
Material:	Epoxy vernished steel with cataphoresis traitement
Degree of protection:	**IP** according to IEC/EN 60529 **IP 10** with armoured conduit **IP 44** with cable gland
Electrical connection:	Can be made with armoured conduit or cable gland M12x1.5. Parts No. 495740 (cable gland M12x1.5) and 484093 to be ordered separately. Grounding connection by screw M3 on the inside of housing base plate.
Weight:	120 g

Benefits:

This metal housing offers the ideal protection against shocks and corrosion- rotatable 360° - easy mounting in confined spaces - single-nut mounting - light weight - simplifies conversion of existing equipment to other requirements.

Application:

The majority of our valves can be fitted with this standard housing, and can be mounted with several compatible coils group.

Compatible coils:

- **481000 - Standard Coil**
  8 W Class F (155°C)
- **483520 - Double-Frequency Coil**
  9 W Class F (155°C)
- **481044 - Standard High-Power Coil**
  14 W Class F (155°C)
- **485100 - Standard High-Temperature Coil**
  8 W Class H (180°C)
- **486265 - High-Temperature and High-Power Coil**
  14 W Class H (180°C)



HOUSING

4269

HOUSING FOR BISTABLE (IMPULSE) COILS

Housing for bistable coil:

Reference:	4269
Material:	Epoxy vernished steel
Degree of protection:	**IP** according to IEC/EN 60529 **IP 10** with armoured conduit **IP 44** with cable gland
Electrical connection:	Can be made with armoured conduit or cable gland M12x1.5. Parts No. 484092 and 484093 to be ordered separately. Grounding connection by screw M3 on the inside of housing base plate.
Weight:	120 g

Benefits:

This metal housing offers the ideal protection against shocks and corrosion- rotatable 360° - easy mounting in confined spaces - single-nut mounting - light weight - simplifies conversion of existing equipment to other requirements.

Application:

This housing is specially designed for group 4.0 coils and can be mounted only with valves controlled by electrical impulses.

Compatible coils:

- **484990 - Impulse coil for AC**
  11 W Class F (155°C)
- **485400 - Impulse coil for DC**
  13 W Class F (155°C)



HOUSING

4538 WATERPROOF AND DUSTPROOF HOUSING

Waterproof housing:

Reference:	4538
Material:	Epoxy vernished steel
Degree of protection:	**IP** according to IEC/EN 60529 **IP 67** with cable gland
Electrical connection:	Cable connection by cable gland M20x1.5 according to DIN 46320. Cable with outer diameter 6.5 - 13.5 mm can be simply sealed using a rubber gland with resilient sealing rings. The enclosure is internally and externally fitted with grounding and earthing screw terminals.
Weight:	180 g

Benefits:

This enclosure is dust- and waterproof. It corresponds to the degree of "International Protection" IP 67 according to IEC / EN 60529. Corrosion resistant, the metal housing offers good protection for the coil against shocks and other outside influences - rotatable 360° - easy mounting in confined spaces - easy access to the screw terminals - single-nut mounting - light weight - simple conversion of existing electrical equipment to other requirements without interruption of fluid passage in the valve.

Application:

This housing can be equipped with several coils of our range, like the standard, double-frequency and magnetic latch coils.

Compatible coils:

- **481000 - Standard Coil**
  8 W Class F (155°C)
- **483520 - Double-Frequency Coil**
  9 W Class F (155°C)
- **484990 - Impulse Coil for AC**
  11 W Class F (155°C)
- **485400 - Impulse Coil for DC**
  13 W Class H (180°C)



HOUSING

8520 WATERPROOF HOUSING FOR HIGH-TEMPERATURE COILS

Waterproof housing:

Reference:	8520
Material:	Epoxy vernished steel
Degree of protection:	**IP** according to IEC/EN 60529 **IP 67** with cable gland
Electrical connection:	Cable connection by cable gland M20x1.5 according to European standards. Cable with outer diameter 6.5 - 13.5 mm can be simply sealed using a rubber gland with resilient sealing rings. The enclosure is internally and externally fitted with grounding and earthing screw terminals.
Weight:	180 g

Benefits:

This enclosure is dust- and waterproof. It corresponds to the degree of "International Protection" IP 67 according to IEC / EN 60529. Corrosion resistant, the metal housing offers good protection for the coil against shocks and other outside influences - rotatable 360° - easy mounting in confined spaces - easy access to the screw terminals - single-nut mounting - light weight - simple conversion of existing electrical equipment to other requirements without interruption of fluid passage in the valve.

Application:

The majority of our valves can be fitted with this housing and can be mounted with several compatible coils for high temperature (14 W, 8 W Class F or H).

Compatible coils:

- **481044 - Standard High-Power Coil**
  14 W Class F (155°C)
- **486265 - High-Temperature and High-Power Coil**
  14 W Class H (180°C)
- **485100 - Standard High-Temperature Coil**
  8 W Class H (180°C)



22 mm
32 mm

COIL ASSEMBLY KITS

COIL ASSEMBLY KIT FOR 22 mm COIL

The coil assembly kit corresponds to the "housing" of Parker valve numbering system (Valve - housing - coil/voltage).

It is composed of a nameplate with the details of the valve type, a washer and a nut to secure the 22 mm coil to the valve.

Caution: This coil assembly kits for 22 mm coils are not adapted for our "Namur High Flow Range".

Reference	Specification	Application
8993	Standard - aluminium nameplate - passivated washer and nut - pressure indication in [bar]	Standard valves

COIL ASSEMBLY KIT FOR 32 mm COIL

The coil assembly kit corresponds to the "housing" of Parker valve numbering system (Valve - housing - coil/voltage).

It is composed of a nameplate giving details of the valve type, a round washer and a nut to ensure the fixing between 32 mm coil and the valve.

Reference	Specification	Application
2995	Standard - Aluminium nameplate - Passivated iron washer and nut - Pressure indication in [bar]	Standards valves

ACCESSORIES

DIN PLUG CONNECTOR ACCORDING TO EN 175301-803 -B

Part Number 48104340 (Q.ty 1 KIT = 25pcs)

Electrical connection suitable for all 22 mm coils
(e.g. 488980, 481180)

DIN PLUG CONNECTOR ACCORDING TO EN 175301-803 - A

Part Number 600003K (BOX = 10pcs) or
Part Number 49264540 (Q.ty 1 KIT = 25pcs) to be used with ATEX coils only

Electrical connection suitable for all 32 mm coils
(e.g. 481865, 492425)

EXPLOSIVE ENVIRONMENTS

INTRODUCTION

The current European Directive concerning equipment to be installed in potentially explosive atmospheres is **2014/34/EU**. It came into force on April 19th, **2016**. With respect to the previous version, it implies the switching from EC to EU Declarations of Conformity and Type Examination Certificates; moreover, it better defines the manufacturer's, importer's and distributor's responsibilities.

Electrical and mechanical equipment for use in potentially explosive atmospheres is certified by a notified body in accordance to the relevant European technical standards concerning each protection mode (m, d, e, i, n, t, h), EN 60079-0 etc. After certification project completion, and EU Type Examination Certificate is released, entitling it to carry the distinctive marking.

EUROPEAN MEMBER COUNTRIES

DEFINITIONS

EXPLOSIVE ENVIRONMENTS

Mixture with air, under atmospheric conditions, of flammable substances in the form of gases, vapours, mists or dusts in which, after combustion has occurred, combustion spreads to the entire unburned mixture.

HAZARDOUS AREAS

A hazardous area is an area in which an explosive gas environment is present, or may be expected to be present, in quantities such as to require special precautions for construction, installation and use of electrical apparatus.

INGREDIENTS FOR AN EXPLOSION

- When combustible materials are mixed with air, an explosive mixture is produced. Danger of explosion therefore exists wherever these hazardouas materials are handled: such a condition is to be found on the biggest chemical plant as well as at the smallest filling station.
- Nowadays with the use of electronic and electrical instrumentation in process control, the risk of combustion by electrical energy has increased sharply.
- To protect personnel and expensive equipment special precautions should be taken to prevent combustion of those dangerous substances. Conditions likely to ignite explosive mixtures are as follows:

Three conditions are enough to create an explosion.



ZONES

The hazardous areas are classified in zones based on the frequency of the occurrence and the duration of an explosive gas environment as follows:

Zone 0 (20)	Zone 1 (21)	Zone 2 (22)
An area in wich an explosive **gas** (dust) atmosphere is present CONTINUOUSLY or is present for LONG PERIODS (~1000 h/y).	An area in wich an explosive **gas** (dust) atmosphere is present LIKELY TO OCCUR in normal operation (~10 to 999 h/y).	An area in wich an explosive **gas** (dust) atmosphere is not LIKELY TO OCCUR and if it does occur it will exist for short period only (~1 to 10 h/y).
Mode of protection: **ia - ta ...**	Mode of protection: **db - mb - eb - tb...**	Mode of protection: **ec - tc...**

HAZARDOUS LOCATION CLASSIFICATION

Explosive Environment	Continuous Presence	Intermittent Presence (normal operation conditions)	Occasional Presence (abnormal operation)
IEC	**Zone 0** (gas) **Zone 20** (dust)	**Zone 1** (gas) **Zone 21** (dust)	**Zone 2** (gas) **Zone 22** (dust)
Europe	**Zone 0** (gas) **Zone 20** (dust)	**Zone 1** (gas) **Zone 21** (dust)	**Zone 2** (gas) **Zone 22** (dust)
Canada (CEC)[1] USA (NEC) [2]	**Cl. I Div. 1** (gas) **Cl. II Div. 1** (dust) **Cl.III Div. 1** (fibres)	**Cl. I Div. 1** (gas) **Cl. II Div. 1** (dust) **Cl.III Div. 1** (fibres)	**Cl. I Div. 2** (gas) **Cl. II Div. 2** (dust) **Cl.III Div. 2** (fibres)

[1] (CEC): Code Canadien d'Electricité / [2] (NEC): National Electrical Code

Example:



HAZARDOUS LOCATION CLASSIFICATION

Category	Fault protection	Atmosphere	Zone	Example of protections
EC Type examination by Notified Body annex III				
1 **Very high level**	2 types of protection or 2 indépendant faults	**G** (Gas)	**0**	"ia", "ta"...
		D (Dust)	**20**	
EC Type examination by Notified Body annex III				
2 **High level**	One type of protection Habitual frequent malfunction	**G** (Gas)	**1**	One type of protection "db", "mb", "tb"...
		D (Dust)	**21**	
Internal production inspection EC declaration of conformity				
3 **Normal**	Required level of protection	**G** (Gas)	**2**	"ec", "tc"...
		D (Dust)	**22**	

Hazardous Location Classification

Group	Gas Reference
I	Methane
IIA	Propane
IIB	Ethylene
IIC	Hydrogen / Acethylene

Hazardous Location Classification

Group	Dust Reference
-	-
IIA	Fibres
IIB	Non-conductive dust
IIC	Conductive dust

Surface Temperature Classes

Class Temperature	Max. Temperature
T1	450°C
T2	300°C
T3	200°C
T4	135°C
T5	100°C
T6	85°C



Gas & Ignition Temperature		
560°C	Hydrogen	T1
537°C	Methane	T1
425°C	Ethylene	T2
305°C	Acetylene	T2
210°C	Kerozene	T3
160°C	Ethylether	T4
95°C	Carbon disulphide	T6

PROTECTION MODES IN PARKER FCSE PRODUCTS

Concept	Code		Zones	
	Gas	Dust	Gas	Dust
Flameproof enclosure	db	tb	1/2	21/22
Encapstulation	mb	tb	0/1/2	20/21/22
Increased Safety	eb	tb	1/2	21/22
Intrinsic Safety	ia	ta	0/1/2	20/21/22
Concept Cat.3 apparatus	nc	tc	2	22
Mechanical Part	h	h	0/1/2	20/21/22

In red, protection modes used by Parker FCSE.

ELECTRICAL EQUIPMENT FOR EXPLOSIVE GAS ATMOSPHERE EQUIPMENT GROUP II

EPL	Standards EN / IEC	Protection	Title
	60079-0	-	General requirements
Ga	60079-11	ia	Intrinsic safety
	-	-	-
	-	-	-
Gb	60079-1	db	Flameproof enclosures
	60079-7	eb	Increased safety
	60079-18	mb	Encapsulation
Gc	60079-7	ec	Increased safety
	60079-15	nc	Non sparking (C) or protected sparking (A)
	-	-	-

EPL = Equipement Protection Level
In red, protection modes used by Parker FCSE.

ELECTRICAL EQUIPMENT FOR EXPLOSIVE DUST ATMOSPHERE - EQUIPMENT GROUP III

EPL	Standards EN / IEC	Protection	Title
	60079-0	-	General requirements
Da	60079-31	ta	Protection by enclosure
	60079-11	ia	Intrinsic safety
	-	-	-
Db	60079-31	tb	Protection by enclosure
	60079-18	mb	Protection by encapsulation
	-	-	-
Dc	60079-31	tc	Protection by enclosure
	-	-	-
	-	-	-

EPL = Equipement Protection Level
In red, protection modes used by Parker FCSE.

NON ELECTRICAL EQUIPMENT FOR USE IN POTENTIALLY EXPLOSIVE ATMOSPHERE

Standards	Protection	Title
ISO / EN ISO 80079-36	h	Basic method and requirement
ISO / EN ISO 80079-37	c, b, k	Constructional safety, control of ingition sources, liquid immersion

ZONES AND EQUIPEMENT PROTECTION LEVEL (EPL)

Gas		Dust	
Zone	EPL	Zone	EPL
0	Ga	20	Da
1	Ga and Gb	21	Da and Db
2	Ga, Gb and Gc	22	Da, Db and Dc

CATEGORIES AND EQUIPEMENT PROTECTION LEVEL (EPL)

Categories	Gas	Dust	Safety
1	Ga	Da	Very high
2	Gb	Db	High
3	Gc	Dc	Normal

ELECTRICAL APPARATUS FOR EXPLOSIVE GAS ATMOSPHERES EQUIPMENT GROUP II



Equipment Groups (Gas)	
IIA	Aceton, ethane, benzene, petrol, butane, propane, methane
IIB	Ethylene, town gas
IIC	Hydrogen, acetylene

Temperature Class	Ignition Temperature of Gas or Vapour	Maximum admissible surface temperature for permanently hot surfaces
T1	> 450°C	440°C
T2	> 300°C	290°C
T3	> 200°C	195°C
T4	> 135°C	130°C
T5	> 100°C	95°C
T6	> 85°C	80°C

Zone	Equipment Protection Level (EPL)
0	Ga
1	Gb and Ga
2	Gc, Gb and Ga

ELECTRICAL EQUIPMENT FOR USE IN AREAS WITH COMBUSTIBLE DUST - EQUIPMENT GROUP III



Equipment Groups (Dust)	
IIA	Fibres
IIB	Non-conductive dust
IIC	Conductive dust

Zone	Equipment Protection Level (EPL)
20	Da
21	Db and Da
22	Dc, Db and Da

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

WHAT ABOUT THE DIRECTIVE ?
(2014/34/EU - 19.04.16)



THE FRAMEWORK OF THE DIRECTIVE

The main principles of the new directive can be summarized as follows:

- It applies to **electric** and **non-electric** equipment.
- It defines **essential health and safety requirements**.
- It takes into consideration **all potential hazards** equipment may cause, in particular at design and production level.
- **The one directive** applies to both **mines** susceptible to fire damp and **surface industries**.
- It stresses the importance of equipment being **used in accordance with its intended purpose**.
- It recognises The European Standards Committee **CEN** and the European Committee for Electrotechnical Standardisation **CENELEC** as competent bodies to fix the required harmonised standards.
- It provides for the **contribution of labour and management**.
- It defines **procedures for assessing conformity** to essential requirements, on the basis of modules which qualify equipment to carry the **CE** mark of conformity.

APPLICATIONS

The directive applies to the industrial field and concerns the following equipment:

- **Equipment** (machines, apparatus, etc.)
- **Protective systems** (discharge devices, explosion suppression devices, etc.)
- **Components** (parts with no autonomous function, terminals, etc.)
- **Safety devices, controlling devices and regulating devices** intended for use outside potentially explosive environments but required for safety with respect to explosions (relays, barriers, pressure switches, thermostats, etc.)

EXCLUDED FROM THE SCOPE OF THE NEW DIRECTIVE

The following equipment falls outside the scope of the new directive:

- Medical devices intended for use in a medical environment.
- Equipment and protective systems relating only to the risk of explosion of unstable chemical substances (explosives, etc.)
- Equipment intended for use in domestic and non-commercial environments.
- Personal protective equipment covered by directive 89/686/EC.
- Seagoing vessels and mobile offshore units.
- Means of transport, except for vehicles intended for use in a potentially explosive environment.

POTENTIAL IGNITION SOURCES AND OTHER HAZARDS TO BE CONTROLLED

The following all represent potential hazards:

- Various sources of ignition, such as sparks, flames, electric arcs, high surface temperature, acoustic energy, optical radiation or electromagnetic waves.
- Static electricity.
- Pressure compensation operations.
- Disturbance from external sources, such as changing environmental conditions, extraneous voltage, humidity, vibration or contamination.

Provision is also made for specific requirements governing devices used to provide additional equipment safety.

These requirements necessitate detailed analysis to asses the operational reliability of such devices and their interaction with other components connected with the equipment.

GUIDANCE CHART FOR IS-BARRIERS

Manufacturer	Reference	Ex	IS Standard Electrical Parts							IS Booster Electrical Parts		
			Ex ia IIC T6 488650.01/02 LCIE/AUS	Ex ia IIC T6 490885 (490895) LCIE/FM/CSA	Ex ia IIC T6 483580.01/03 483960.01/03 LCIE/AUS	Ex ia 490880 (493997) LCIE/FM/CSA	Ex ia IIB T6 482160,01 LCIE	Ex ia IIC T6 482870,01 LCIE	Ex ia LCIE/FM/CSA	Ex ia IIC T6 492965.01/02 LCIE	Ex ia IIC T6 496565 LCIE	Ex ia IIC T6 495910 LCIE
A puissance 3	NAEV 22-140	ia	●	-	●	-	●	●	-	●	●	●
	NAEV 26-100	ia	●	-	●	-	●	●	-	●	●	●
ABB	V171132-54	ib	●	-	●	-	●	●	-	●	●	●
	V171132-55	ib	●	-	-	-	●	●	-	●	●	●
	V171132-61	ia	●	-	-	-	●	●	-	●	●	●
	DO 890	ib	●	-	●	-	●	●	-	●	●	●
	S900-DO4-EX	ib	●	-	●	-	●	●	-	●	●	●
BRADLEY	FEX-EX 24V	ia	●	●	●	●	●	●	-	●	●	●
COOPER	LB 2101	ia	●	●	●	●	●	●	●	●	●	●
	LB 2105	ia	●	●	●	●	●	●	●	●	●	●
	LB 2112	ia	●	●	●	●	●	●	●	●	●	●
ELCON	1881 / 1882	ia	●	●	●	●	●	●	●	●	●	●
	471 / 472	ia	●	●	●	●	●	●	●	●	●	●
	2871/2872	ia	●	●	●	●	●	●	●	●	●	●
	2874/2875/2876	ia	●	●	●	●	●	●	●	●	●	●
GEORGIN	AVB 122	ia	●	-	●	-	●	●	-	●	●	●
	AVB 125	ia	●	-	●	-	●	●	-	●	●	●
	AVB 128	ia	●	-	●	-	●	●	-	●	●	●
Hima	F3328A	ib	●	-	●	-	●	●	-	●	●	●
	F3335	ib	●	-	-	-	●	●	-	●	●	●
	H4007	ib	●	-	●	-	●	●	-	●	●	●
MTL	728P, 7128P, 7728P	ia	-	-	-	-	●	-	-	●	●	●
	728, 7028, 7128, 7728	ia	●	●	●	●	●	●	●	●	●	●
	3021, 4021, 4021S	ia	●	-	●	-	●	●	-	●	●	●
	3022	ia	-	-	-	-	●	-	-	-	-	-
	4023	ia	-	-	-	-	●	-	-	-	-	-
	4024	ia	●	-	●	-	●	●		●	●	●
	4025	ia	●	●	●	●	●	●	●	●	●	●
	5021, 5023, 5024	ia	●	-	●	-	●	●	-	●	●	●
	5025	ia	●	-	●	-	●	●	●	●	●	●
	4521 / 4523 / 4524	ia	●	-	-	-	●	●	●	●	●	●
	5521 / 5523 / 5524	ia	●	-	-	-	●	●	●	●	●	●
Pepperl & Fuchs	Z 728	ia	●	●	●	●	●	●	●	●	●	●
	Z 779	ia	●	●	●	●	●	●	●	●	●	●
	EGA-041-3	ia	-	●	●	●	●	●	●	●	●	●
	KFD2-SD-EX1.36	ia	-	-	-	-	-	●	-	-	-	-
	KFD2-SL-EX1.36	ia	-	-	-	-	-	●	-	-	-	-
	KFD2-SD-EX1.48	ia	-	●	-	●	-	●	●	●	●	●
	KFD2-SL-EX1.48	ia	-	●	-	●	-	●	●	●	●	●
	KFD2-SL-EX1.48.90A	ia	-	-	-	-	-	-	-	●	●	●
	KFD2-SL-EX1.48.90A	ia	-	-	-	-	-	-	-	●	●	●
	KFD2-SL2-EX1.LK	ia	-	●	-	●	-	●	●	●	●	●
	KFD2-SL2-EX2	ia	-	●	-	●	-	●	●	●	●	●
	KSD2-BO-EX	ia	-	●	●	●	●	●	●	●	●	●
	RSD-BO-EX4	ib	-	●	-	●	-	●	●	●	●	●
	RSD-VO-EX8	ib	-	-	-	-	-	-	-	●	●	●

GUIDANCE CHART FOR IS-BARRIERS

Manufacturer	Reference	Ex	IS Standard Electrical Parts							IS Booster Electrical Parts		
			Ex ia IIC T6 488650.01/02 LCIE/AUS	Ex ia IIC T6 490885 (490895) LCIE/FM/CSA	Ex ia IIC T6 483580.01/03 483960.01/03 LCIE/AUS	Ex ia 490880 (493997) LCIE/FM/CSA	Ex ia IIB T6 482160,01 LCIE	Ex ia IIC T6 482870,01 LCIE	Ex ia LCIE/FM/CSA	Ex ia IIC T6 492965.01/02 LCIE	Ex ia IIC T6 496565 LCIE	Ex ia IIC T6 495910 LCIE
SIEMENS	5RD00-0AB0	ib	-	-	-	-	-	-	-	●	-	-
	7RD00-0AB0	ia	-	-	-	-	-	-	-	●	●	●
	7RD01-0AB0	ia	-	-	-	-	-	-	-	●	●	●
	7RD10-0AB0	ia	-	-	-	-	-	-	-	●	●	●
	7RD11-0AB0	ia	-	-	-	-	-	-	-	●	●	●
	7RD20-0AB0	ia	-	-	-	-	-	-	-	●	●	●
	7RD21-0AB0	ia	-	-	-	-	-	-	-	●	●	●
STAHL	9001/01-252-100-14	ia	●	●	27 V	27 V	●	●	●	●	●	●
	9001/01-280-100-10	ia	●	●	24 V	24 V	●	●	●	●	●	●
	9001/01-280-110-10	ia	●	-	24 V	-	●	●	-	●	●	●
	9002/13-280-100-04	ia	24 V	24 V	27 V	27 V	24 V	24 V	24 V	17 V	17 V	17 V
	9311/52-11-10	ia	-	●	●	25 V	25 V	●	●	15 V	15 V	15 V
	9111/63-11-00	ia	-	●	●	25 V	25 V	●	●	15 V	15 V	15 V
	9351/10-15-10	ia	-	●	●	-	-	●	●	●	●	●
	9351/10-16-10	ia	-	●		●	-	●	●	●	●	●
	9351/10-17-10	ia	-	-	-	-	-	●	-	-	-	-
	9381/10-187-050-10	ib	-	●	●	●	●	●	●	●	●	●
	9381/10-246-055-10	ib	-	●	●	●	●	●	●	●	●	●
	9381/10-246-070-10	ib	-	●	●	●	●	●	●	●	●	●
	9465/12-04-11	ib	-	●	●	-	-	●	●	●	●	●
	9475/12-04-21	ia/ib	-	●	-	●	-	●	●	●	●	●
	9475/12-04-31	ia/ib	-	-	-	-	-	-	-	●	●	●
	9475/12-08-41	ia/ib	-	-	-	-	-	-	-	-	-	-
	9475/12-08-51	ib	-	-	-	-	-	-	-	●	●	●
	9475/12-08-61	ia/ib	-	-	-	-	-	-	-	-	●	●
Turck	MK72-S01-EX	ib	-	-	-	-	●	●	-	●	●	●
	MK72-S02-EEX	ib	-	-	-	-	●	●	-	●	●	●
	MK72-S04-EEX	ib	●	-	●	-	●	●	-	●	●	●
	MK72-S05-EEX	ib	●	-		-	●	●	-	●	●	●
	MK72-S06-EEX	ib	●	-	●	-	●	●	-	●	●	●
	MK72-S07-EEX	ib	●	-		-	●	●	-	●	●	●
	MK72-S09-EEX	ia		-		-			-	-	-	-
	MK72-S12-EEX	ia	●	-	●	-	●	●	-	●	●	●
	MC72 - 41	ia	●	-	●	-	●	●	-	●	●	●
	MC72 - 43	ia	●	-	●	-	●	●	-	●	●	●
	MC72 - 44	ia		-	-	-			-	●	●	●
BARTEC	07-7331-2301/1000	ia	●	-	-	-	●	●	-	●	-	-
	07-7331-2301/1100	ia	●		●		●	●		●	-	-

If barrier reference not listed, consult factory for compatibility (FCCE.FCSE.Technical@support.parker.com)

TECHNICAL INFORMATION ABOUT SOLENOID VALVES

General Information

Solenoid valves are electro-mechanical devices used for interrupting or diverting the flow of fluids by opening or closing one or more orifices.

The solenoid valve is a combination of three basic components:

1. An electromagnet consisting of a solenoid (windings) and a magnetic yoke.
2. A pilot with a moveable plunger (which, in some cases directly opens and closes the valve).
3. A valve body with an orifice opened or closed by plunger or diaphragm to enable or prevent flow of the medium.



Operating principles

The term solenoid refers to operator and coil, also known as pilot or magnetic actuator.

The coil consists of copper wire wound on a support reel. When electric current is applied into the coil, magnetic flow lines are generated which are stronger in the coil center.

This magnetic flow raises the moveable plunger in the coil until it brings it into contact with the pole piece. The valve body has an orifice through which the fluid flows when the valve is open.

The moveable plunger has an integral seat which when the solenoid coil is energised, moves off the valve (direct operated) orifice or diaphragm (pilot operated) orifice opening the valve.

When the coil is de-energised, a return spring brings the plunger back to the original closing position, thus cutting off the flow of the fluid.

BASIC COMPONENTS OF A SOLENOID VALVE

Valve body: Main part of the solenoid valve including ports, seat and orifices.

Solenoid tube assembly: Cylinder, in stainless steel, hermetically sealed and closed at one extremity. It is the guide channel of the moveable plunger which is moved magnetically. The solenoid coil is fitted on the external side of the enclosing tube.

Moveable plunger: Made by ferritic stainless steel, it is attracted by the solenoid magnetic field and slides inside the tube.

Plunger spring (or return spring): Used to hold the moveable plunger in position and to return it when de-energized.

Seat seal: Part of the moveable plunger, it is used to close a valves main orifice or pilot orifice.

Electromagnet (or solenoid coil): Electrical part consisting of a copper windings (solenoid) along, with a magnetic yoke (armature), when electric current flows through, it generates a magnetic field atracting the moveable plunger.

Housing: Part that contains and protects the coil.

Yoke: Metalic case surrounding the coil and concentring electro-magnetic force on the moveable plunger.



TECHNICAL VOCABULARY USED IN TABLES

Actuation	Body	Function	Port Size	Orifice (mm)	Flow Factor Kv(l/min)	MOPD (bar)	Max Fluid Temp. (°C)

NORMALLY CLOSED

Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max		Valve Ref.	Housing Ref.	Coil Ref.				
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		

The basic technical features of each solenoid valve are indicated in the tables, the terminology used is shown and explained below. Please notice that in certain sections you will have the choice between two product ranges: Parker valves, within blue tables and the Parker valves, within orange tables.

Actuation: The mechanical method used to control the flow.

Body: Main part of the solenoid valve with the ports, seats and orifice needed.

Function: The way the valve operates when de-energised.

Port Size: Fitting dimensions are defined as threaded in inches (G), in BSP or Sub-base, when a flat interface for ports is adopted.

Orifice (mm): Main orifice diameter in millimetres (nominal diameter).

Flow Factors: Define the quantity of water which flows through the solenoid valve with a pressure drop of 1 bar during one minute. Expressed in l/min and m^3/h.

Max Fluid Temperature: Maximum fluid temperature the valve can withstand.

Max Ambient Temperature: Maximum ambient temperature the valve can withstand typical value for pressure vessel is 50°C.

Minimum Operating Pressure Differential: The lowest differential pressure required for operation (bar).

Maximum Operating Pressure Differential (MOPD): The highest working differential pressure with 90% of the rated voltage (-10% Vn) applied to the solenoid coil (for AC) and 95% of the rated voltage (-5% Vn)(for DC).

TECHNICAL INFORMATION

Solenoid valves are highly engineered products that can be used in many diverse applications.
In addition to operational functionality, media compatibility and suitability for the operating environement when selecting the best product for a given application.
This section provides a brief overview of the components, actuation and function modes of solenoid valves avaible from Parker Hanninfin - FCSE.

Different Technologies:

Solenoid valves are electrically operated devices used to control flow.
The most common types of solenoid valve are:

Direct Operated Valves

Magnalift Valves



Pilot Operated Valves

DIRECT OPERATED VALVE

Magnetic force is used directly to open or close the plunger which controls the passage of the fluid. Performances are limited by the coil, the pressure, and the valve orifice size. For direct operated valves, the minimum working pressure is 0 bar and the maximum pressure relies on the combination (valve/coil) chosen.

Direct Operated Valve

De-energised



Energised



Example:

- 121 Series



PILOT OPERATED VALVE

To control a higher flow, it is necessary to use pilot operated valves. The supply pressure enters the direct operated "pilot stage" which directs the flow to a "pilot chamber" which,in turn, applies the pilot pressure over a large area (generally a diaphragm or piston). Therefore, a large force is generated to move the main sealing elements against higher pressure or over a large orifice.
One condition of operation is to have a minimum pressure available to shift the valve (indicated in the catalogue). In most applications, this presents no particular problems (refer to magnalift valve section).
The pressure rating of the valve starts between 0.1 to 0.5 bar (depending on the valve).
(NB. Pilote Operated Valves are also called Servo Operated Valves).

Pilot Operated Valve



Example:
- 321 Series
- 7321B Series



MAGNALIFT VALVE

The magnalift valves combine the features of the direct operated and pilot operated valves. A mechanical link between the plunger and diaphragm retainer allows the valve to operate as a direct operated valve at low pressures and as a pilot operated valve at higher pressures. Magnalift valves are specially designed for applications where 0 pressure is needed to operate the valve, as well as bigger flow than a direct operated valve.

Magnalift Operated Valve

De-energised **Energised**



Example:
- 221 Series



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

NORMALLY CLOSED VALVE

Most of our valves are available in normally closed and normally open configuration when not energized. In certain applications, you may require a normally open valve (open function in case of current failure). The differentiating factor of design of this technology, is based upon the design of the seat seal, which is reversed in comparaison to a normally closed valve.

Normally Closed Valve

De-energised



Energised



Example:
• 121 Series



NORMALLY OPEN VALVE

Normally Open Valve

De-energised



Energised



Example:
- 122 Series



Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

FLOW AND PRESSURE RANGES

Area of operation:

Each valve principle, as described in the previous pages, has a defined area of operation related to its pressure and flow capabilities. The following graph shows which type of valve is suitable for a certain situation.



Areas of operation of Parker solenoid valves.

SIZING SOLENOID VALVES

The correct choice of solenoid valve is essential as it determines the regulation and performance required for practical application on a system. In order to decide on the exact type of solenoid valve, various parameters have to be known.

However the calculation method, based on the flow coefficient Kv, has proved highly practical as it can be determined on the basis of:

- Required flow rate
- Flow resistance
- Type of fluid and relative viscosity
- Specific gravity and temperature

This flow coefficient Kv is determined as defined in the VDI/VDE 2173 standards.
It represents the flow of water in m3/h or L/min with a temperature from 5 to 30°C which passes through the solenoid valve with a pressure drop of 1 bar.



FG = Grid Filter Mp = Pump Vs = Safety Valve Nr = Check Valve Sp = Pressure Tank Ps = Static Pressure Manometer

Note:

The flow coefficient used in the USA is known as Cv and represents the water flow rate in US gallons per minute with a pressure drop ΔP of 1 psi.

To convert C_V in Kv and vice versa use:

1 K_V = 0.862 C_V
1 C_V = 1.16 K_V

After existing conditions have been converted into this factor Kv, the type of valve is found by referring to the pages in the related sections in this catalogue.

Parameters used for selecting the solenoid valve are in the table next page.

Consult conversion tables of the various units of measurement as defined by the ISO (International Standards Organisation) - I.S. (International System) set out in this catalogue.

FLOW AND PRESSURE RANGES

Pressure
symbol (P)
unit of measurement [bar]
Working pressure

Pressure drop
symbol (ΔP)
unit of measurement [bar]
Pressure difference between inlet (P_1) and outlet (P_2) of the solenoid valve when a medium is flowing through the valve ($\Delta P = P_1 - P_2$).

Flow cœfficient
symbol (Kv)
unit of measurement [l/min]

Specific gravity of the medium
symbol (γ)
unit of measurement [Kg/dm³]

Temperature of the medium
symbol (t)
unit of measurement [°C]

Flow rate

- for liquids
  symbol (Q)
  unit of measurement [l/min]
- for gases
  symbol (Qn)
  unit of measurement [Nm³/h]
- for steam
  symbol (Qv)
  unit of measurement [Kg/h]

Specific volume
symbol (Vs)
unit of measurement [m³/Kg]

a) Solenoid valves for liquids:

Flow rate: $Q = Kv \cdot \sqrt{\frac{\Delta P}{\gamma}}$ where: Q = l/min, ΔP = bar, γ = Kg/dm³

Flow coefficient:

$$Kv = Q \cdot \sqrt{\frac{\gamma}{\Delta P}}$$

In the case of liquids with viscosity greater than 3°E (22 cStokes) the Kv is modified according to the formula:

$$Kv_1 = Kv + C \qquad C = \frac{\delta \cdot \sqrt{Kv}}{200 \cdot Q} + 1$$

where C is the viscosity correction factor calculated by means of the formula:
where:
δ = kinematic viscosity of the fluid expressed in centistokes
Kv = flow rate factor of the solenoid valve
Q = flow rate in l/min

Pressure drop:

$$\Delta P = \gamma \cdot \left(\frac{Q}{Kv}\right)^2$$

b) Solenoid valves for gases:

If $\Delta P \leqslant 1/2\ P_1$ use the following formulae:

Flow rate: $Qn = 514 \cdot Kv \cdot \sqrt{\frac{\Delta P \cdot P_2}{\gamma n \cdot (273 + t)}}$

Pressure drop: $\Delta P = \frac{(273 + t) \cdot \gamma n}{P_2} \cdot \frac{Qn^2}{(514 \cdot Kv)^2}$

where: $Qn = Nm^3/h$ $P_1 = bar$ $P_2 = bar$

Flow coefficient: $Kv = \frac{Qn}{514} \cdot \sqrt{\frac{(273+t) \cdot \gamma n}{\Delta P \cdot P_2}}$

If $\Delta P > 1/2\ P_1$ use the following formula:

$Qn = 757 \cdot Kv \cdot \sqrt{\frac{\Delta P \cdot P_2}{(273 + t) \cdot \gamma n}}$

$t = °C$
$\gamma n = Kg/dm^3$

c) Solenoid valves for steam:

If $\Delta P \leqslant 1/2\ P_1$ use the following formulae:

Flow rate: $Qv = 31,7 \cdot Kv \cdot \sqrt{\frac{\Delta P}{Vs}}$

Pressure drop: $\Delta P = Vs \cdot \frac{Qv^2}{(31,7 \times Kv)^2}$

where: $Qv = Kg/h$ $\Delta P = bar$ $Vs = m^3/Kg$

If $\Delta P > 1/2\ P_1$ use the following formula:

$Qv = 22,4 \cdot Kv \sqrt{\frac{P_1}{Vs}}$

Flow coefficient: $Kv = \frac{Qv}{31,7} \cdot \sqrt{\frac{Vs}{\Delta P}}$

Notes:

1) Should the value ΔP not be specified, use the following, which is based on experience:

- For liquids only in the case of free discharge ΔP = 90% of the input pressure (P_1).
- For gases never use a ΔP of more than 50% of the absolute inlet pressure, since the excessive pressure drop may cause an irregular flow rate. In most cases, ΔP can be considered as 10% of the input pressure.

2) Specific volume value (Vs) for dry saturated steam, see the table in diagram 3.

FLOW RATE FOR LIQUIDS

The liquid flow through a pipe or a valve is given by:

$$Q = Kv \cdot \sqrt{\frac{\Delta P}{\gamma}}$$

Where
- Q = Flow [l/min]
- ΔP = Differential Pressure [bar]
- γ = Density of the fluid [kg/dm^3] (water γ = 1 [kg/dm^3])
- kv = Flow Factor [l/min]

Flow factor kv:

The kv flow factor of a valve is defined as the flow rate of water in litres per minute with a pressure drop of 1 bar across the valve.

Valve manufactuerers use different definitions for kv. It may be expressed in l/h or m^3/h.

Care should therefore be taken when comparing values.

Maximum flow rate Qmax.

For particular 2-way valves the maximum flow must be limited for reasons of mechanical resistance and durability.

A very high flow velocity may dislocate a popet sealing or a diaphragm.

Maximum flow rates are indicated in the catalogue.

Flow factors
Kv l/min | KV m^3/h | Qn l/min

NORMALLY CLOSED

Port size	Orifice Ø	Flow factors			Operating Pressure Differential			Fluid Temp.		Seat Seal	Parker Valves			Power		Coil Group	Dwg. No.
					Min	Max(MOPD)		Min	Max		Valve Ref.	Housing Ref.	Coil Ref.				
BSP	mm	Kv l/min	KV m^3/h	Qn l/min	bar	AC bar	DC bar	°C	°C					AC W	DC W		



Monogram for liquid flow calculation

Specific gravity of the most common fluids (□ = Kg/dm³) - (t = 15°C - P = 760 mm Hg)					
Acetone	0.76	Benzenol	0.90	Naphtha	0.76
Water	1.00	Beer	1.02	Pentane	0.63
Sea water	1.02	Hexane	0.66	Vegetable oil	0.92
Ethyl alcohol	0.79	Ethane	0.68	Hydraulic oil	0.92
Methyl alcohol	0.81	Diesel oil	0.70	Wine	0.95
Petrol	0.68	Milk	1.03		

FLOW RATE FOR GASES

The gas flow through a valve is given by:

$$Q = C \cdot P_1 \cdot k_T \cdot w \cdot \gamma_{air} / \gamma_{gas}$$

Where
- Q = Flow Rate [dm^3/s]
- C = Conductance [$dm^3/s.bar$]
- P_1 = Inlet Pressure [bar abs]
- γ = Specific Weight [Kg/dm^3]
- k_T = Temperature Correction Factor

$$w = \sqrt{1 - \frac{P_2/P_1 - b}{1 - b}} \qquad k_T = \sqrt{\frac{293}{273 + \text{Temp. °C}}}$$

Nominal Flow Qn:

Calculations can be made with specific flow factors based on the CETOP RP 50P standard.

For practical purposes and ease of valve selection the catalogue shows the nominal flow Qn.

The nominal flow Qn is defined as the flow rate (L/min) of air across the valve when the inlet pressure P_1 = 6 bar and the pressure drop ΔP = 1 bar.

N.B.
The values of the flow factors and flow rates mentioned in catalogues are subjet to +/-15% tolerances.

Pneumatic application: $\gamma_{air} / \gamma_{gas} = 1$

a) **Choked flow conditions** $P_2 \leq b.P_1$
in this case $w = 1$ --> $Q = C \cdot P_1 \cdot kT$

b) Free flow conditions $P_2 > b.P_1$
in this case --> $Q = C \cdot P_1 \cdot kT \cdot w$



t = Fluid Temperature γ_N = Specific Gravity Kv = Flow Cœfficient Qn = Flow Rate Δp = Pressure Drop P_1 = Inlet Pressure

Specific gravity of the most common gases (□ = Kg/m³) - (t = 0°C - P = 760mm Hg)					
Acetylene	1.176	Helium	0.179	Natural gas	0.723
Carbon dioxide	1.965	Ethane	1.035	Methane	0.722
Air	1.293	Ethylene	1.259	Carbon monoxide	1.250
Argon	1.780	Hydrogen	0.089	Oxygen	1.429
Nitrogen	1.255			Propane	1.520
Butane	2.000			Steam	0.805

TECHNICAL INFORMATION

Diagram 3 for Dry Satured Steam



Steam (Dry Satured) Data

P_2 bar	Temp. °C	Vs m³/Kg	P_2 bar	Temp. °C	Vs m³/Kg
0.01	6.6	131.600	10.00	179.0	0.200
0.02	17.1	68.300	110.00	183.2	0.181
0.03	23.7	46.500	120.00	187.1	0.176
0.04	28.6	35.500	13.00	190.7	0.155
0.05	32.5	28.700	14.00	194.1	0.144
0.06	35.8	24.200	15.00	197.4	0.135
0.08	41.1	18.500	16.00	200.4	0.126
0.10	45.4	15.000	17.00	203.4	0.119
0.20	5 9.7	7.800	18.00	206.2	0.113
0.30	68.7	5.330	19.00	208.8	0.107
0.40	75.4	4.070	20.00	211.4	0.102
0.50	80.9	3.300	22.00	216.2	0.093
0.60	85.5	2.790	24.00	220.8	0.085
0.70	89.5	2.410	26.00	225.0	0.079
0.80	93.0	2.130	28.00	229.0	0.073
0.90	96.2	1.910	30.00	232.8	0.068
1.00	99.1	1.730	32.00	236.4	0.064
1.50	110.8	1.180	34.00	239.8	0.060
2.00	119.6	0.900	36.00	243.1	0.057
2.50	126.8	0.730	38.00	246.2	0.053
3.00	132.9	0.620	40.00	249.2	0.051
3.50	138.2	0.530	45.00	256.2	0.045
4.00	142.9	0.470	50.00	262.7	0.040
4.50	147.2	0.420	55.00	268.7	0.036
5.00	151.1	0.380	60.00	274.3	0.033
5.50	154.7	0.350	65.00	279.6	0.030
6.00	158.1	0.320	70.00	284.5	0.028
6.50	161.2	0.300	80.00	293.6	0.024
7.00	164.2	0.280	90.00	301.9	0.021
7.50	167.0	0.260	100.00	309.5	0.018
8.00	169.6	0.250	150.00	340.5	0.011
8.50	172.1	0.230	200.00	364.2	0.006
9.00	174.5	0.220	225.00	374.0	0.003
9.50	176.8	0.210			

Kv = Flow Coefficient **Qv** = Flow Rate **Δp** = Pressure Drop **Vs** = Specific Volume P_2 = Outlet Pressure

VISCOSITY CONVERSION TABLE

Centistokes cStokes mm²/S	°Engler °E	Saybolt Universal Second SSU	Rewood Second N°1 SRW N°1
1	1	-	-
12	2	65	55
22	3	100	90
30	4	140	120
28	5	175	155
45	6	210	185
60	8	275	245
75	10	345	305
90	12	415	370
115	15	525	465
150	20	685	610
200	26	910	810
300	39	1 385	1 215
400	53	1 820	1 620
500	66	2 275	2 025
750	97	3 365	2 995
1 500	197	6 820	6 075

OTHER USEFUL FORMULAS

Formulas:

°C	=	(°F - 32) x 5/9
°F	=	(°C x 9/5) + 32
m³/h	=	l/min x 0.06
l/min	=	m³/h x 16,67
m³/sec	=	m³/h x 2,778 x 10^{-4}
m³/sec	=	l/min x 1,667 x 10^{-5}

Examples:

(167°F-32) x 5/9	=	**75°C**
(30°C x 9/5) + 32	=	**86°F**
100 l/min x 0.06	=	**6 m³/h**
9 m³/h x 16,67	=	**150 l/min**
18.000 m³/h x 2.778 x 10 -4	=	**5 m³/sec**
479.904 l/min x 1.667 x 10-5	=	**8 m³/sec**

INDEX BY COIL REFERENCE

Coil Reference	Coil Group	Designation	Power DC Pn (W)	Power AC Pn (W)	Ambient Temperature	UL	Degree of Protection	ATEX or NEMA 4X Protection (Gas)	Page
481000	2.0/2.1	Coil with screw terminal, 40 mm	8.0	8.0	-40°C to +50°C	-	IP 44 to 67	-	462
481044	2.0/2.2	Coil with screw terminal High power, 40 mm	-	14.0	-40°C to +50°C	-	IP 44 to 67	-	463
481180	1.1	Coil for DIN plug connection, 22 mm	5.0	4.0	-40°C to +50°C	-	IP65	-	452
481865	2.0	COILS FOR DIN PLUG CONNECTION 32 mm	10.0	9.0	-40°C to +50°C	Y	IP65	-	446
482605	1.1	Explosion proof encapsulated electrical part "mb", 22 mm	5.0	4.0	-40°C to +65°C / +40°C -40°C to +65°C/+35°C	-	IP65	II 2 G Ex mb IIC T4/T5	481
482606	1.1	Explosion proof encapsulated electrical part "mb", low power, 22 mm	2.5	2.0		-	IP65	II 2 G Ex mb IIC T4/T5	481
482730	3.0	COILS FOR DIN PLUG CONNECTION, REDUCED POWER, 32 mm	7.0	6.0	-40°C to +50°C	-	IP65	-	448
482740	6.0	COILS FOR DIN PLUG CONNECTION, low power, 32 mm	1.6	-	-40°C to +50°C	-	IP65	-	449
483371	2.0/2.1	Explosion proof increased safety electrical part "eb", 40 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex eb IIC T4	490
483520	2.0/2.1	Coil with screw terminal, double frequency, 40 mm	-	9.0	-40°C to +50°C	-	IP 44 to 67	-	462
483541	14.3	Coil with screw terminal, high temperature-high power, 40 mm	20.0	20.0	-40°C to +50°C	Y	IP 44 to 67	-	466
483590	1.1	Coil for DIN plug connection,double frequency, 22 mm	-	3.0	-40°C to +50°C	-	IP65	-	454
483816	2.2	Coil for DIN plug connection for Jet Valves, 32 mm	14.0	14.0	-40°C to +50°C	-	IP65	-	451
483824	14.1	Coil with screw terminal, high temperature-high power, 40 mm	19.0	19.0	-40°C to +50°C	Y	IP 44 to 67	-	465
484990	4.0	Coil with screw terminal,bistable,for impulse applications, 40 mm	-	11.0	-40°C to +50°C	-	IP 44 to 67	-	468
485400	4.0	Coil with screw terminal,bistable,for impulse applications, 40 mm	13.0	-	-40°C to +50°C	-	IP 44 to 67	-	468
486265	2.0/2.2	Coil with screw terminal,high temperature-high power, 40 mm	14.0	14.0	-40°C to +50°C	-	IP 44 to 67	-	464
488143	1.1	Coil for DIN plug connection,double frequency, 22 mm	-	2.5	-40°C to +50°C	-	IP65	-	455
488553	2.0/2.1	Coil with screw terminal,double frequency, H class, 40 mm	-	9.0	-40°C to +50°C	-	IP 44 to 67	-	467
488980	1.1	Coil for DIN plug connection, low power, 22 mm	2.5	2.0	-40°C to +50°C	-	IP65	-	452
490885	7.0	Explosion proof intrinsically safe electrical part, "NEMA", 50 mm	3.0	-	-40°C to +60°C	-	NEMA 4 - 4X	Cl. I, Div.I, Gr. A, B, C, D	498
491514	2.0/2.1	COILS FOR DIN PLUG CONNECTION, 32 mm, UL	-	11.0	-40°C to +50°C	Y	IP65	-	450
492070	2.0/2.1	Explosion proof encapsulated electrical part "mb", with water proof metal housing, 50mm (with 3 m cable length)	8.0	9.0	-40°C to +65°C	-	IP67	II 2 G Ex mb IIC T4/T5	482
492190	2.0/2.1	Explosion proof increased safety and encapsulated electrical part "eb mb", 50 mm	9.0	11.0	-40°C to +75°C	-	IP66	II 2 G Ex eb mb IIC T3/T4	493
492210	9.0	Explosion proof increased safety and encapsulated electrical part "eb mb", "Booster", 50 mm	1.0 to 1.8	-	-40°C to +75°C	-	IP66	II 2 G Ex eb mb IIC T5/T6	492
492310	10.1	Explosion proof increased safety and encapsulated electrical part "eb mb", 50 mm	6.0	6.0	-40°C to +75°C	-	IP66	II 2 G Ex eb mb IIC T4/T5	491
492425	2.0/2.2	COILS FOR DIN PLUG CONNECTION, HIGH TEMPERATURE, 32 mm	14.0	14.0	-40°C to +50°C	-	IP65	-	447
492912	1.1	Coil for DIN plug connection, 22 mm	4.0	3.0	-40°C to +50°C	-	IP65	-	453
493640	2.0/2.1	Flame proof encapsulated electrical part "db mb", double frequency	8.0	8.0	-40°C to +75°C	-	IP65	II 2 G Ex db mb IIC T4/T5	489
494040	2.0/2.1	Explosion proof increased safety electrical part "eb", 50 mm	8.0	8.0	-40°C to +90°C	-	IP67	II 2 G Ex eb IIC T3/T4	490
495294	13.0	Coil with ISO-DIN connector, 12-24VDC for transportation applications, 32 mm	9.0	-	-40°C to +120°C	-	IP69K	-	469
495865	1.1	Explosion proof electrical part "nAc nCc", low power, 22 mm	2.5	2.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5	472
495870	2.0/2.1	Explosion proof electrical part "nAc nCc", 32 mm	9.0	8.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	474
495875	3.0	Explosion proof electrical part "nAc nCc", 32 mm	7.0	6.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	476
495880	2.0/2.2	Explosion proof electrical part "nAc nCc", 32 mm	14.0	14.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3	477
495900	6.0	Flame proof encapsulated electrical part "db mb", low power, 37 mm	2.0	2.5	-40°C to +80°C	-	IP67	II 2 G Ex db mb IIC T4 / T5/T6	485

INDEX BY COIL REFERENCE

Coil Reference	Coil Group	Designation	Power DC Pn (W)	Power AC Pn (W)	Ambient Temperature	UL	Degree of Protection	ATEX or NEMA 4X Protection (Gas)	Page
495905	2.0/2.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +80C	-	IP67	II 2 G Ex db mb IIC T4	486
495910	8.0	Explosion proof intrinsically safe electrical part "ia", "booster", 37 mm	0.3 to 1.2	-	-40°C to +80°C	-	IP67	II 1 G Ex ia IIC T4/T5/T6	495
495915	4.0	Explosion proof increased safety electrical part "nAc nCc", 40 mm	13.0	11.0	-40°C to +65°C	-	IP67	II 3 G Ex nAc nCc IIC T3	478
496081	2.0/2.1	Coil with flying leads,IP 67, 32 mm	9.0	9.0	-40°C to +50°C	-	IP67	-	460
496082	2.0/2.1	Coil with flying leads,IP 67, 32 mm, UL certified	16	13	-40°C to +50°C	Y	IP65	-	461
496110	2.0/2.1	Explosion proof electrical part "nAc nCc", 32 mm	-	9.0	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	474
496125	6.0	Explosion proof electrical part "nAc nCc", low power, 32 mm	1.6	-	-40°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5/T6	475
496131	1.2	Coil for DIN plug connection, double frequency, 22 mm	3.0	3.0	-40°C to +50°C	-	IP65	-	456
496155	2.0/2.2	Explosion proof increased safety electrical part "nAc nCc", 40 mm	14.0	14.0	-40°C to +65°C	-	IP67	II 3 G Ex nAc nCc IIC T3	479
496193	13.0	Coil with ISO-DIN connector, 12-24VDC, for transportation applications, 32 mm	9.0	-	-40°C to +120°C	-	IP69K	-	469
496482	1.2	Coil for DIN plug connection, double frequency coil, 22 mm	3.0	3.0	-40°C to +50°C	-	IP65	-	457
496555	10.2	Flame proof encapsulated electrical part "db mb", 37 mm	6.0	6.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4/T5/T6	487
496560	10.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4	487
496565	9.0	Explosion proof intrinsically safe electrical part "ia", " Booster", 37 mm	0.77 to 2.58	-	-40°C to +80°C	-	IP67	II 1 G Ex ia IIC T4/T5/T6	496
496637	1.2	Explosion proof electrical part "nAc nCc", double frequency, 22 mm	3.0	3.0	-20°C to +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5	473
496700	10.2	Flame proof encapsulated electrical part "db mb", 37 mm	6.0	6.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4 / T5 / T6	488
496800	10.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4	488
496895	10.1	Coil for DIN plug connection for oil and gas, 37 mm	8.0	8.0	-40°C to +50°C	-	IP65	-	459
497105	10.3	Flame proof stainless steel electrical part "db", M20x1.5	8.0	8.0	-50°C to +80°C /+60 °C/+40°C	-	IP66	II 2 G Ex db IIC T4/T5/T6	480
497510	1.2	Double frequency coil 22 mm	-	4.5	-40°C to +50°C	-	IP66	-	458
482606.160	1.1	Explosion proof encapsulated electrical part "mb", low power, 22 mm	2.5	2.0	-40°C to +65°C/+35°C		IP65	II 2 G Ex mb IIC T4/T5	481
492070.60	2.0/2.1	Explosion proof encapsulated electrical part "mb", with water proof metal housing, 50mm (with 6 m cable length)	8.0	9.0	-40°C to +65°C	-	IP67	II 2 G Ex mb IIC T4/T5	482
483580.01	7.0	Explosion proof intrinsically safe electrical part "ia", 32 mm	3.0	-	-40°C to +55°C	-	IP65	II 1 G Ex ia IIC T6	494
483960.01	7.0	Explosion proof intrinsically safe electrical part "ia", 32 mm	3.0	-	-40°C to +55°C	-	IP65	II 1 G Ex ia IIC T6	494
488650.01	7.0	Explosion proof intrinsically safe electrical part "ia", 50 mm	0.3 to 3.0	-	-40°C to +65°C	-	IP66	II 1 G Ex ia IIC T6	498
492965.01	9.0	Explosion proof intrinsically safe electrical part "ia", " Booster", 50 mm (stainless steel fixation)	0.3 to 2.3	-	-40°C to +65°C	-	IP66	II 1 G Ex ia IIC T6	497
492965.02	9.0	Explosion proof intrinsically safe electrical part "ia", " Booster", 50 mm (Plastic fixation)	0.3 to 2.3	-	-40°C to +65°C	-	IP66	II 1 G Ex ia IIC T6	497
493640.60*	2.0/2.1	Flame proof encapsulated electrical part "db mb", double frequency	8.0	8.0	-40°C to +75°C	-	IP65	II 2 G Ex db mb IIC T4/T5	489
495905.05*	2.0/2.1	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4	486
496700.02	10.2	Flame proof encapsulated electrical part "db mb", 37 mm, NPT 1/2"	6.0	6.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4 / T5 / T6	488
496800.02	10.1	Flame proof encapsulated electrical part "db mb", 37 mm, NPT 1/2"	8.0	8.0	-40°C to +65°C	-	IP67	II 2 G Ex db mb IIC T4	488
497105.02	10.3	Flame proof stainless steel electrical part "db", NPT 1/2"	8.0	8.0	-50°C to +80°C /+60 °C/+40°C	-	IP66	II 2 G Ex db IIC T4/T5/T6	480
HZ10	2.0/2.1	Explosion proof encapsulated electrical part "mb", double frequency	8.0	8.0	-40°C to +85°C	-	IP65	II 2 G Ex mb IIC T3/T4/T5	483
HZ11		Explosion proof encapsulated electrical part "mb", double frequency	14.0	14.0	-40°C to +85°C	-	IP65	II 2 G Ex mb IIC T3/T4/T5	484

INDEX BY COIL GROUP

Coil Group	Coil Reference	Designation	Power DC Pn (W)	Power AC Pn (W)	Ambient Temperature	UL	Degree of Protection	ATEX or NEMA 4X Protection (Gas)	Page
1.1	481180	COIL FOR DIN PLUG CONNECTION, 22 mm	5.0	4.0	-40°C TO +50°C	-	IP65	-	452
1.1	483590	COIL FOR DIN PLUG CONNECTION,DOUBLE FREQUENCY, 22 mm	-	3.0	-40°C TO +50°C	-	IP65	-	454
1.1	488143	COIL FOR DIN PLUG CONNECTION,DOUBLE FREQUENCY, 22 mm	-	2.5	-40°C TO +50°C	-	IP65	-	455
1.1	495865	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", LOW POWER, 22 mm	2.5	2.0	-40°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5	472
1.1	482605	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", 22 mm	5.0	4.0	-40°C TO +65°C / +40°C	-	IP65	II 2 G Ex mb IIC T4/T5	481
1.1	482606	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", LOW POWER, 22 mm	2.5	2.0	-40°C TO +65°C/+35°C	-	IP65	II 2 G Ex mb IIC T4/T5	481
1.1	482606.160	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", LOW POWER, 22 mm	2.5	2.0	-40°C TO +65°C/+35°C	-	IP65	II 2 G Ex mb IIC T4/T5	481
1.1	488980	COIL FOR DIN PLUG CONNECTION, LOW POWER, 22 mm	2.5	2.0	-40°C TO +50°C	-	IP65	-	452
1.1	492912	COIL FOR DIN PLUG CONNECTION, 22 mm	4.0	3.0	-40°C TO +50°C	-	IP65	-	453
1.2	496482	COIL FOR DIN PLUG CONNECTION, DOUBLE FREQUENCY COIL, 22 mm	3.0	3.0	-40°C TO +50°C	-	IP65	-	457
1.2	496637	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", DOUBLE FREQUENCY, 22 mm	3.0	3.0	-20°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5	473
1.2	496131	COIL FOR DIN PLUG CONNECTION, DOUBLE FREQUENCY, 22 mm	3.0	3.0	-40°C TO +50°C	-	IP65	-	456
2.0/2.1	481865	COILS FOR DIN PLUG CONNECTION 32 mm	9.0	8.0	-40°C TO +50°C	Y	IP65	-	446
2.0/2.1	491514	COILS FOR DIN PLUG CONNECTION, 32 mm, UL	-	11.0	-40°C TO +50°C	Y	IP65	-	450
2.0/2.1	496081	COIL WITH FLYING LEADS,IP 67, 32 mm	9.0	9.0	-40°C TO +50°C	-	IP67	-	460
2.0/2.1	481000	COIL WITH SCREW TERMINAL, 40 mm	8.0	8.0	-40°C TO +50°C	-	IP 44 TO 67	-	462
2.0/2.1	483520	COIL WITH SCREW TERMINAL, DOUBLE FREQUENCY, 40 mm	-	9.0	-40°C TO +50°C	-	IP 44 TO 67	-	462
2.0/2.1	495870	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", 32 mm	9.0	8.0	-40°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	474
2.0/2.1	496110	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", 32 mm	-	9.0	-40°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	474
2.0/2.1	492070	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", WITH WATER PROOF METAL HOUSING, 50 mm (WITH 3 M CABLE LENGTH)	8.0	9.0	-40°C TO +65°C	-	IP67	II 2 G Ex mb IIC T4/T5	482
2.0/2.1	492070.60	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", WITH WATER PROOF METAL HOUSING, 50 mm (WITH 6 M CABLE LENGTH)	8.0	9.0	-40°C TO +65°C	-	IP67	II 2 G Ex mb IIC T4/T5	482
2.0/2.1	HZ10	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", DOUBLE FREQUENCY	8.0	8.0	-40°C TO +85°C	-	IP65	II 2 G Ex mb IIC T3/T4/T5	482
2.0/2.1	HZ11	EXPLOSION PROOF ENCAPSULATED ELECTRICAL PART "MB", DOUBLE FREQUENCY	14.0	14.0	-40°C TO +85°C	-	IP65	II 2 G Ex mb IIC T3/T4/T5	483
2.0/2.1	495905	Flame proof encapsulated electrical part "db mb", 37 mm	8.0	8.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4	458
2.0/2.1	495905.05*	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	8.0	8.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4	458
2.0/2.1	493640	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", DOUBLE FREQUENCY	8.0	8.0	-40°C TO +75°C	-	IP65	II 2 G Ex db mb IIC T4/T5	489
2.0/2.1	493640.60*	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", DOUBLE FREQUENCY	8.0	8.0	-40°C TO +75°C	-	IP65	II 2 G Ex db mb IIC T4/T5	489
2.0/2.1	483371	EXPLOSION PROOF INCREASED SAFETY ELECTRICAL PART "EB", 50 mm	8.0	8.0	-40°C TO +65°C	-	IP67	II 2 G Ex eb IIC T4	490
2.0/2.1	494040	EXPLOSION PROOF INCREASED SAFETY ELECTRICAL PART "EB", 50 mm	8.0	8.0	-40°C TO +90°C	-	IP67	II 2 G Ex eb IIC T3/T4	490
2.0/2.1	492190	EXPLOSION PROOF INCREASED SAFETY AND ENCAPSULATED ELECTRICAL PART "EB", 50 mm	9.0	11.0	-40°C TO +75°C	-	IP66	II 2 G Ex eb mb IIC T3/T4	493
2.0/2.1	488553	COIL WITH SCREW TERMINAL,DOUBLE FREQUENCY, H CLASS, 40 mm	-	9.0	-40°C TO +50°C	-	IP 44 TO 67	-	467
2.0/2.2	492425	COILS FOR DIN PLUG CONNECTION, HIGH TEMPERATURE, 32 mm	14.0	14.0	-40°C TO +50°C	-	IP65	-	447
2.0/2.2	481044	COIL WITH SCREW TERMINAL HIGH POWER, 40 mm	-	14.0	-40°C TO +50°C	-	IP 44 TO 67	-	463
2.0/2.2	486265	COIL WITH SCREW TERMINAL,HIGH TEMPERATURE-HIGH POWER, 40 mm	14.0	14.0	-40°C TO +50°C	-	IP 44 TO 67	-	464
2.0/2.2	495880	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", 32 mm	14.0	14.0	-40°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3	477
2.0/2.2	496155	EXPLOSION PROOF INCREASED SAFETY ELECTRICAL PART "NAC NCC", 40 mm	14.0	14.0	-40°C TO +65°C	-	IP67	II 3 G Ex nAc nCc IIC T3	479

INDEX BY COIL GROUP

Coil Group	Coil Reference	Designation	Power DC Pn (W)	Power AC Pn (W)	Ambient Temperature	UL	Degree of Protection	ATEX or NEMA 4X Protection (Gas)	Page
2.2	483816	COIL FOR DIN PLUG CONNECTION FOR JET VALVES, 32 mm	14.0	14.0	-40°C TO +50°C	-	IP65	-	451
3.0	482730	COILS FOR DIN PLUG CONNECTION, REDUCED POWER, 32 mm	7.0	6.0	-40°C TO +50°C	-	IP65	-	448
3.0	495875	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", 32 mm	7.0	6.0	-40°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T3/T4	476
4.0	484990	COIL WITH SCREW TERMINAL,BISTABLE,FOR IMPULSE APPLICATIONS, 40 mm	-	11.0	-40°C TO +50°C	-	IP 44 TO 67	-	468
4.0	495915	EXPLOSION PROOF INCREASED SAFETY ELECTRICAL PART "NAC NCC", 50 mm	13.0	11.0	-40°C TO +65°C	-	IP67	II 3 G Ex nAc nCc IIC T3	478
4.0	485400	COIL WITH SCREW TERMINAL,BISTABLE,FOR IMPULSE APPLICATIONS, 40 mm	13.0	-	-40°C TO +50°C	-	IP 44 TO 67	-	468
6.0	482740	COILS FOR DIN PLUG CONNECTION, LOW POWER, 32 mm	1.6	-	-40°C TO +50°C	-	IP65	-	449
6.0	496125	EXPLOSION PROOF ELECTRICAL PART "NAC NCC", LOW POWER, 32 mm	1.6	-	-40°C TO +50°C	-	IP65	II 3 G Ex nAc nCc IIC T5/T6	475
6.0	495900	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", LOW POWER, 37 mm	2.0	2.5	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4 / T5/T6	485
7.0	483580.01	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", 32 mm	3.0	-	-40°C TO +55°C	-	IP65	II 1 G Ex ia IIC T6	494
7.0	483960.01	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", 32 mm	3.0	-	-40°C TO +55°C	-	IP65	II 1 G Ex ia IIC T6	494
7.0	488650.01	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", 50 mm	0.3 TO 3.0	-	-40°C TO +65°C	-	IP66	II 1 G Ex ia IIC T6	498
7.0	490885	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART, "NEMA", 50 mm	3.0	-	-40°C TO +60°C	-	NEMA 4 - 4X	CL. I, DIV.I, GR. A, B, C, D	498
8.0	495910	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", "BOOSTER", 37 mm	0.3 TO 1.2	-	-40°C TO +80°C	-	IP67	II 1 G Ex ia IIC T4/T5/T6	495
9.0	492210	EXPLOSION PROOF INCREASED SAFETY AND ENCAPSULATED ELECTRICAL PART "EB", "BOOSTER", 50 mm	1.0 TO 1.8	-	-40°C TO +75°C	-	IP66	II 2 G Ex eb mb IIC T5/T6	492
9.0	496565	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", " BOOSTER", 37 mm	0.77 TO 2.58	-	-40°C TO +80°C	-	IP67	II 1 G Ex ia IIC T4/T5/T6	463
9.0	492965.01	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", " BOOSTER", 50 mm (STAINLESS STEEL FIXATION)	0.3 TO 2.3	-	-40°C TO +65°C	-	IP66	II 1 G Ex ia IIC T6	497
9.0	492965.02	EXPLOSION PROOF INTRINSICALLY SAFE ELECTRICAL PART "IA", " BOOSTER", 50 mm (PLASTIC FIXATION)	0.3 TO 2.3	-	-40°C TO +65°C	-	IP66	II 1 G Ex ia IIC T6	497
10.1	496895	COIL FOR DIN PLUG CONNECTION FOR OIL AND GAS, 37 mm	8.0	8.0	-40°C TO +50°C	-	IP65	-	459
10.1	496560	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	8.0	8.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4	487
10.1	496800	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	8.0	8.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4	488
10.1	496800.02	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	8.0	8.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4	488
10.1	492310	EXPLOSION PROOF INCREASED SAFETY AND ENCAPSULATED ELECTRICAL PART "EB", 50 mm	6.0	6.0	-40°C TO +75°C	-	IP66	II 2 G Ex eb mb IIC T4/T5	491
10.2	496555	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	6.0	6.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4/T5/T6	487
10.2	496700	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	6.0	6.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4 / T5 / T6	488
10.2	496700.02	FLAME PROOF ENCAPSULATED ELECTRICAL PART "DB MB", 37 mm	6.0	6.0	-40°C TO +65°C	-	IP67	II 2 G Ex db mb IIC T4 / T5 / T6	488
10.3	497105	FLAME PROOF STAINLESS STEEL ELECTRICAL PART "DB", M20X1.5	8.0	8.0	-50°C TO +80°C /+60 °C/+40°C	-	IP66	II 2 G Ex db IIC T4/T5/T6	480
10.3	497105.02	FLAME PROOF STAINLESS STEEL ELECTRICAL PART "DB", NPT 1/2"	8.0	8.0	-50°C TO +80°C /+60 °C/+40°C	-	IP66	II 2 G Ex db IIC T4/T5/T6	480
13.0	496193	Coil with ISO-DIN connector, 12-24VDC, for transportation applications, 32 mm	9.0	-	-40°C TO +120°C	-	IP69K	-	469
13.0	495294	COIL WITH ISO-DIN CONNECTOR, 12-24VDC FOR TRANSPORTATION APPLICATIONS, 32 mm	9.0	-	-40°C TO +120°C	-	IP69K	-	469
14.1	483824	COIL WITH SCREW TERMINAL, HIGH TEMPERATURE-HIGH POWER, 40 mm	19.0	19.0	-40°C TO +50°C	-	IP 44 TO 67	-	465
14.3	483541	COIL WITH SCREW TERMINAL, HIGH TEMPERATURE-HIGH POWER, 40 mm	20.0	20.0	-40°C TO +50°C	-	IP 44 TO 67	-	466

INDEX BY VALVE REFERENCE

	Valve Reference	Page
U	033X0111	326
U	033X5156	398
U	033X5195	402
U	033X5256	404
U	033X7759	400
	121F2523	194
E	121F43	30,150
E	121F4302	30,102
E	121F44	30,150
E	121F4406	30,102
	121F4417	30
	121F47	30
	121F4706	30,150
	121F63	30,150
	121F64	30,150
	121F67	30,150
	121FH0015	224
	121FH0020	224
	121FH0025	224
	121FH0030	224
	121FH1015	224
	121FH1020	224
	121FH1025	224
	121FH1030	224
	121G2520	192
	121G2523	192
	121K01	24,96
	121K0103	136,
	121K0150	24,96
	121K02	24,96
	121K0250	24,96
E	121K03	24,146
E	121K0302	24,96
	121K0323	136
E	121K0352	24,96
	121K0397	24
E	121K04	22,146
E	121K0402	22,96
	121K0497	22
E	121K07	22
	121K0706	22,96
	121K1302	22,96
E	121K14	22,146
E	121K23	22,146
	121K2423	192
	121K3106	26,98,148
	121K3206	26,98,148
	121K3303	136
	121K3306	26,98,148
	121K3321	192
E	121K45	26,98
E	121K4503	136
E	121K46	26,98
E	121K4603	136
	121K6220	192
E	121K63	24,146
E	121K64	24,146
	121K6423	156
E	121K65	22,146
E	121K67	22,146
	121KH0015	224
	121KH0020	224
	121KH0025	224
	121KH0030	224
	121KH1015	224
	121KH1020	224
	121KH1025	224
	121KH1030	224
	121KH1040	224
	121KH1050	224
	121M13	22,96
	121M14	22,96
	121V5106	168
	121V5112	168
	121V5163	104,168
	121V5206	168
	121V5212	168
	121V5263	138,168
	121V5306	166
	121V5363	138,166,168
	121V5397	168
	121V5406	166
	121V5463	138,166
	121V5497	166
U	121V5595	176
	121V5706	166
	121V5763	138,166
U	121V7595	176
U	121VS3750A	176
	121ZH0010	222
	121ZH0015	222
	121ZH0020	222
	121ZH0025	222
	121ZH0030	222
	121ZH1010	222
	121ZH1015	222
	121ZH1020	222
	121ZH1025	222
	121ZH1030	222
	122F44	32
	122K83	28
	122K8306	28,98
	122K8321	194
	122K84	28,148
	122K8406	28
	122K9321	194
	122K9363	28,148
	122V8306	170
	125K01	28,100
	125K03	28
	131B04	82
	131B14	82
E	131F26	86
E	131F43	78
E	131F4350	78
	131F4397	308
E	131F44	78
	131F4410	76
E	131F4450	78
	131F4490	76
	131F46	78
	131F4650	78
U	131F5295	382
	131F5406	84
U	131F7695	382
	131FH0315	238
	131FH0320	238
	131FH0325	238
	131FH0330	238
	131FH1115	238
	131FH1120	238
	131FH1125	238
	131FH1130	238
	131FH1315	238
	131FH1320	238
	131FH1325	238
	131FH1330	238
E	131K03	68
E	131K0308	68,302
E	131K0350	68,302

INDEX BY VALVE REFERENCE

Valve Reference	Page
E 131K0358	66,298
131K0397	62,66
E 131K04	64,300
E 131K0450	64,300
131K0490	62,298
131K0497	64,300
E 131K06	66,300
131K0648	268
E 131K0650	66,300
E 131K13	62
E 131K14	62
131K16	62
131K1650	62
E 131K63	68
E 131K6350	68
E 131K64	64
E 131K6450	64
131KH0115	236
131KH0120	236
131KH0125	236
131KH0130	236
131KH1115	236
131KH1120	236
131KH1125	236
131KH1130	236
131KH1140	236
131KH1150	236
131M14	62,298
131M15	62,298
131M74	76
131M7450	76
131M75	76
131M7550	76
131T21	68
131T2101	302
131T22	68
131T23	64
131T2301	64
131T29	66
131T2901	66
131V5306	184
131V5363	184
131V5397	184
131V5406	184
131V5463	184
131V5490	184
131V5497	184
131X1101	330
U 131X1101	330
131X1131	330
U 131X1201	384
131ZH0125	234
131ZH0130	234
131ZH0315	234
131ZH0320	234
131ZH0325	234
131ZH0330	234
131ZH1115	234
131ZH1120	234
131ZH1125	234
131ZH1130	234
131ZH1315	234
131ZH1320	234
131ZH1325	234
132F43	78
132F44	78
132F46	78
132K03	70
132K04	70
132K06	70
132T22	70
132T23	70
132T2301	70
132T29	304
133F4650	308
E 133K03	72
E 133K0350	72
E 133K04	72
E 133K0450	72
133K0497	72
E 133K05	72
E 133K06	72
E 133K0650	72
E 133K13	72
E 133K14	72
E 133K16	72
133T21	72
133T2101	74
133T23	72
133T2301	72
133V5306	186
133V5363	186
133V5406	186
133V5463	186
U 133V5595	372
U 133V5695	372
U 133V7595	372
U 133V7695	372
133X01	310
U 133X01	310
U 133X0111	304
U 133X5156	374
U 133X5195	382
U 133X5196	374
U 133X5296	380
U 133X7195	384
U 133X7709	376
135K03	306
135K04	74
2019F1GRG7	228
2019F1GVG7	228
2019F1JRG7	228
2019F1JVG7	228
2019F1LRG7	228
2019F1LVG7	228
2019F1NRG7	228
2019F1NVG7	228
2019F1QEG7	228
2019F1QVG7	228
2019F1SEG7	228
2019F1SVG7	228
201LG1GVG2	172
201LG1JVG2	172
201LG1LVG2	172
201LG2GVG2	172
201LG2LVG2	172
201LG2NVG7	172
201LG3SVG7	172
201LG3UVG7	172
201LG4SVG6	172
201LG4UVG7	172
202LG2NVG7	174
202LG2SVG7	174
202LG4SVG7	174
202LG4UVG7	174
221G13	34
221G1303	140
221G1330	140
221G15	34
221G1503	140

INDEX FOR VALVES

Valve Reference	Page
221G1530	34
221G16	36
221G1603	140
221G1610	36
221G1630	36
221G1631	36
221G17	38
221G1703	140
221G1710	38
221G1730	38
221G1731	124
221G21	38
221G2103	124
221G2106	38
221G2110	38
221G2130	38
221G2131	124
221G2136	38
221G23	34
221G2330	34
221G25	34
221G2523	196
221G2530	34
221G26	36
221G2630	36
221G27	38
221G2730	38
221G6106	180
221G6136	180
221G6306	178
221G6336	178
221G6506	178
221G6536	178
221G6606	180
221G6636	180

Valve Reference	Page
221J3301E	210
3019F1GRG7	240
3019F1GVG7	240
3019F1JRG7	240
3019F1JVG7	240
3019F1LRG7	240
3019F1LVG7	240
3019F1NRG7	240
3019F1NVG7	240
3019F1QEG7	240
3019F1QVG7	240
3019F1SEG7	240
3019F1SVG7	240
301LG1GVG2	188
301LG1LVG2	188
301LG2GVG2	188
301LG2GVG7	188
301LG2LVG2	188
301LG2NVG7	188
301XGFRTJ7	240
3039F1GEG7	240
3039F1GVG7	242
3039F1JEG7	242
3039F1JVG7	242
3039F1JVG7	242
3039F1LEG7	242
3039F1LVG7	242
3039F1LVG7	242
3039F1NEG7	242
3039F1NVG7	242
3039F1NVG7	242
321F2523	200
E 321F32	58,120
E 321F3202	58,158
321F35	58

Valve Reference	Page
E 321G36	46,112
E 321G3606	46
E 321G3610	128
E 321G37	48,114
E 321G3706	48
E 321G3710	130
321G3790	48
E 321G38	48
E 321G3806	48
E 321G3810	130
E 321G39	50,114
E 321G3906	50
E 321G3910	130
321G3990	50
E 321G40	50,114
E 321G4006	50
E 321G4010	130
321G4090	50
E 321H11	40,152
E 321H13	42,152
E 321H15	44,154
321H1590	44
E 321H21	152,198
E 321H23	152,198
321H2322	198
E 321H25	154,200
321H2522	200
321H2523	200
321H35	44
321H36	46
E 321K10	40,108
E 321K13	42,108
E 321K15	44,110
E 321K1503	142
321K1523	264

Valve Reference	Page
321K1535	262
321K1536	264
321K1537	264
321K1543	262
E 321K25	44,110
321K31	40,108
321K3106	40
321K33	42,108
321K3306	42
321K35	44,110
321K3506	44
321K36	46,112
321K3606	46
321K37	48,114
321K3706	48
321K4106	108,128
321K4156	40
321K4306	108,128
321K4356	42
321K4506	110,128
321K4556	110,128
321K4606	112,128
321K4656	112,128
321K4706	114,130
321K4756	114,130
E 321K63	152
322F35	58
322F72	58
322F7206	58,158
322G36	54,118
322G3606	54
322G3610	132
322G37	54,120
322G3706	54
322G3710	132

INDEX FOR VALVES

Valve Reference	Page
322G38	54
322G3806	54
322G3810	132
322G39	54,120
322G3906	54
322G3910	132
322G40	54
322G4006	54
322G4010	132
322G75	52,118
322G7506	52,156
322H35	52
322H36	54
322H71	52
322H7106	52,156
322H73	52,156
322H7306	52,156
322H75	52,156
322H7506	52,156
322K4106	118
322K4306	118
322K4506	118
322K4606	118
322K4706	120
325K4106	120
325K4306	120
325K4506	120
325K4606	120
325K4706	120
E 331B01	88
331B02	162
331B0216	162
E 331B21	90
E 331B74	88
331B7490	88
E 331L21	92
331N03	306
331N04	306
331N34	308
E 332B01	90
332B02	90
E 332B21	92
E 341B01	274
341B02	272
341B34	272
341B3403	272
341B3440	272
341B3490	272
E 341F21	274
341F34	280
341F3403	280
341F3440	280
E 341L01	290
341L0197	290
E 341L02	288
341L04	300
341L05	300
341L11	286
E 341L1130	284
U 341L1130	284
E 341L21	282
341L2190	282
341L9101	278
341L9201	282
341L9504	258
341L9534	358
341L9594	360
341L9597	360
341L9598	332
341N01	336
341N02	342
U 341N0250	394
341N04	346
341N05	340
341N0502	342
341N11	336
341N12	344
341N21	336
341N2190	336
341N22	344
341N31	338
341N3102	338
341N3108	338
341N3128	338
341N3130	338
341N3190	338
341N3196	338
341N3197	338
341N32	344
341N3202	344
U 341N3250	392
341N3290	340
U 341N3292	392
U 341N3295	392
341N3297	340
341N34	346
341N35	342
341N3502	342
341P01	312
341P02	316
U 341P0250	386
341P03	316
341P04	318
341P21	312
341P2108	312
341P2190	314
341P2197	312
341P22	318
341P2290	318
341P2297	318
U 341P3250	388
U 341P3292	388
U 341P3295	388
341P33	316
341P34	318
342N03	354
342N11	354
342N3197	354
342N33	354
343N03	356
345B04	276
345B34	276
345F34	280
345L01	292
345L21	284
345N31	358
345P21	324
347L04	284
347L11	288
347L9101	278
347L9201	284
347N03	350
347N04	352
347N11	348
347N12	350
347N31	348
347N3190	348
347N3197	348
347N32	350
U 347N3250	396

Parker Hannifin Corporation
Fluid Control Solutions Europe
General Catalogue FCSE/0112/UK V3 04/2026

INDEX FOR VALVES

	Valve Reference	Page
	347N33	350
	347N34	352
	347P01	320
	347P02	322
	347P03	322
	347P04	324
	347P21	320
	347P2190	320
	347P2197	320
	347P22	322
U	347P3250	390
U	347P3295	390
	347P33	382
	347P34	324
	421F35	58
U	441P3250	386
	443776W	104
	443777W	104
	443778W	104
	443779W	104
	443780W	104
	443781W	104
	443782W	104
	443783W	104
	443784W	126
	443785W	104
	443786W	104
	443787W	104
	443788W	126
	443789W	104
	443790W	106
	443791W	106
	443792W	126
	443793W	106
	443794W	106

Valve Reference	Page
443795W	106
443796W	126
443797W	106
443798W	106
443799W	106
443800W	126
443801W	106
443802W	126
443803W	126
443804W	104
443805W	116
443806W	116
443807W	116
443808W	116
443809W	116
443810W	116
443811W	116
444492W	104
444494W	104
444497W	104
444499W	116
444500W	116
444501W	116
444502W	116
444503W	116
444513W	116
444576W	116
444600W	116
444601W	116
444602W	116
444603W	116
444604W	116
444605W	116
531N03	362
531N04	362

Valve Reference	Page
541L01	294
541N0108	364
541N03	366
541N04	366
542N03	368
547N03	366

NOTES

WARNING - USER RESPONSIBILITY

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

- This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.
- The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.
- To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

www.parker.com

General Catalogue FCSE/0112/UK V3 06/2026
© 2026 Parker Hannifn EMEA Sarl. All Rights Reserved.