
hymatik

Parker Store



Hose Fittings Overview

DIN


CA

DKOL
Female Metric 24°
Light Series with O-ring
Swivel – Straight


CE


DKOL 45°
Female Metric 24°
Light Series with O-ring
Swivel – 45° Elbow


CF


DKOL 90°
Female Metric 24°
Light Series with O-ring
Swivel – 90° Elbow


D0

Male Metric 24°
Light Series – Rigid
Straight


C0

Female Metric Series LL
Swivel (Ball Nose)
Straight

C3

DKL
Female Metric
Light Series – Swivel
Straight (Ball Nose)

C4

DKL 45°
Female Metric
Light Series – Swivel
45° Elbow (Ball Nose)


C5

DKL 90°
Female Metric
Light Series – Swivel
90° Elbow (Ball Nose)


1D

BEL
Metric Standpipe
Light Series – Rigid
Straight

DD

BEL 45°
Metric Standpipe
Light Series – Rigid
45° Elbow

5D


BEL 90°
Metric Standpipe
Light Series – Rigid
90° Elbow


C9

DKOS
Female Metric 24°
Heavy Series with O-ring
Swivel – Straight


0C

DKOS 45°
Female Metric 24°
Heavy Series with O-ring
Swivel – 45° Elbow


1C


DKOS 90°
Female Metric 24°
Heavy Series with O-ring
Swivel – 90° Elbow


D2

CES
Male Metric 24°
Heavy Series
Rigid – Straight

C6

DKS
Female Metric
Heavy Series – Swivel
Straight (Ball Nose)


3D

BES
Metric Standpipe
Heavy Series
Rigid – Straight


49

Metric Banjo – Straight


9B

Metric – Light Series
Swivel Female 45° Elbow


9C

Light Series Metric
Swivel Female
90° Elbow


BSP


92

DKR
Female BSP Parallel
Pipe – Swivel – Straight
(60° Cone)

B1

DKR 45°
Female BSP
Parallel Pipe
Swivel – 45° Elbow
(60° Cone)

B2

DKR 90°
Female BSP
Parallel Pipe
Swivel – 90° Elbow
(60° Cone)


B4

DKR 90°
Female BSP
Parallel Pipe – Swivel
90° Elbow Block Type
(60° Cone)


EA

DKOR
BSP Swivel Female
with O-ring (60° Cone)


EB

DKOR 45°
BSP Swivel Female
with O-ring – 45° Elbow
(60° Cone)


EC

DKOR 90°
BSP Swivel Female
with O-ring – 90° Elbow
(60° Cone)


D9

AGR
Male BSP Parallel Pipe
Rigid – Straight
(60° Cone)


91

AGR-K
Male BSP Taper Pipe
Rigid – Straight


B5

Female BSP Parallel
Pipe Swivel – Straight
(Flat Seat)


34

Inch Standpipe (Brass)


SAE


01

AGN
Male NPTF Pipe
Rigid – Straight


02

Female NPTF Pipe
Rigid – Straight


03

AGJ
Male JIC 37°
Rigid – Straight

04

Male SAE 45°
Rigid – Straight

05

Male SAE Straight Thread
with O-Ring – Rigid
Straight

06
68

DKJ
Female – JIC 37° / SAE
45° Dual Flare
Swivel – Straight

08

Female SAE 45°
Swivel – Straight

13

Male NPTF Pipe Swivel

33

Male JIC 37° – Rigid
45° Elbow

37
3V

DKJ 45°
Female
JIC 37° / SAE 45°
Dual Flare – Swivel
Female – 45° Elbow

39
3W

DKJ 90°
Female
JIC 37° / SAE 45°
Dual Flare – Swivel
Female – 90° Elbow

41
3Y

DKJ 90° L
Female
JIC 37° / SAE 45°
Dual Flare – Swivel
Female – 90° Elbow
long

L9

DKJ 90° M
Female JIC 37°
Swivel – 90° Elbow
Medium Drop

93

Female JIC 37° -
Swivel (Block Type)

Flange

15
4A

SFL
SAE Code 61
Straight (5000 psi)

16

SFL 22.5° / 3000 psi
SAE Code 61
22.5° Elbow

17
4F

SFL 45° / 3000 psi
SAE Code 61
45° Elbow

19
4N

SFL 90°
SAE Code 61
90° Elbow (5000 psi)

6A

SFS / 6000 psi
SAE Code 62
Straight

6F

SFS 45° / 6000 psi
SAE Code 62
45° Elbow

6N

SFS 90° / 6000 psi
SAE Code 62
90° Elbow

89

SAE Code 61
90° Elbow (Long)
Standard Series

XA

Caterpillar ®
Flange Head – Straight

XF

Caterpillar ®
Flange Head 45° Elbow

XG

Caterpillar ®
Flange Head 60° Elbow

XN

Caterpillar ®
Flange Head 90° Elbow

ORFS

JC

Female ORFS – Swivel
Straight – Short

JS

ORFS Swivel Female
(Long)

J7

Female ORFS – Swivel
45° Elbow

J9

Female ORFS – Swivel
90° Elbow – Short Drop

J1

Female ORFS – Swivel
90° Elbow – Long Drop

J5

Female ORFS – Swivel
90° Elbow – Medium Drop

JM

ORFS Male

JD

Male ORFS – Bulkhead
with Locknut
(with O-Ring)

JIS

FU

GUI
Female BSP Parallel
Pipe – Swivel – Straight
(30° Flare)

GU

GUO
Female BSP Parallel
Pipe – Swivel – Straight
(60° Cone)

MU

Female Metric
Swivel – Straight
(30° Flare)

MZ

Female Metric
Swivel – 90° Elbow
(30° Flare)

UT

Male BSP Taper Pipe
Rigid – Straight
(60° Cone)

French Standard

FG

Male French Gas Series
Rigid – Straight
(24° Cone)

F2

Female French
Swivel Female
Gas Series – 90° Elbow

F4

Female French
Gas Series – Swivel
Straight (Ball Nose)

F6

French Male Metric
Series (24° Cone)

F9

French Swivel Female
Metric Series
(Ball Nose)

FA

Metric Male
for Agriculture Valves

High Pressure Cleaning

CW

Power Cleaner
Connection

PW

Male Kärcher Metric
Cleaning Hose Fitting
Rigid – Straight

NW

Female Kärcher
Metric Cleaning Hose
Fitting Swivel – Straight
(New Design)

Others

XU

Female Metric
Swivel – Straight
(30° Flare)

XY

Female Metric
Swivel – 90° Elbow
(30° Flare)

DK

Male Metric L – Rigid
Bulkhead with Locknut
(24° Cone)

DX

Female Metric Swivel
(M27x2) O-Ring – Light
Series

FF

Metru-Lok Swivel
Female

AF

Male BSP Parallel Pipe
Rigid – Straight
(with O-Ring Seal)

NM

Male BSP Parallel
Pipe – L Series – Rigid
Straight – ED-Seal

YW

Male Standpipe – Rigid
Straight – A-Lok

VW121

BSP Swivel Female

82

Push-Lok ®Union

DP

Metric Swivel Female
Tee / Male Stud

DR

Metric Swivel Female
Tee

5C

60° Cone Swivel Female

6C

60° Cone Swivel Female
45° Elbow

7C

60° Cone Swivel Female
90° Elbow

5S

Female Tube O-Ring
Swivel – Short Pilot

5H

Female Tube O-Ring
Swivel – 45° Elbow
Short Pilot

5T

Female Tube
O-Ring Swivel
90° Elbow Short Pilot

59PT

Male Tube O-Ring
Swivel – Long Pilot
Charge Port at 180° for R134a

5LPT

Female Tube
O-Ring Swivel
90° Elbow – Long Pilot
Charge Port at 180° for R134a

T1

Male Refrigerant Tube
Mender – Straight
(with Nut and Ferrule)