


Fittings and Tubing - Low Pressure Check Valves


Pressures to 15,000 psi (1034 bar)

O-Ring Check Valves



Minimum operating temperature for standard o-ring check valves 0°F (-17.8°C).
For low temperature option to -100°F (-73°C) add suffix LTTO (Low temperature spring & PTFE o-ring).

Ball Check Valves



Minimum operating temperature for standard ball check valves 0°F (-17.8°C).
For low temperature option to -100°F (-73°C) add suffix LT (Low temperature spring).

Provide unidirectional flow and tight shut-off for liquids and gases with high reliability. When differential drops below cracking pressure*, valve shuts off. **(Not for use as relief valve.)**

Materials: 316 Stainless Steel: body, cover, poppet and cover gland. 300 Series Stainless Steel: spring
Standard O-ring: Viton, for operation to 400° F (204°C). Buna-N or PTFE available for 250°F (121°C) or 400°F (204°C) respectively; specify when ordering.

***Cracking Pressure:** 20 psi (1.38 bar) ±30%. Springs for higher cracking pressures (up to 100 psi (6.89bar)) available on special order for O-ring style check valves only.

Prevent reverse flow where leak-tight shut-off is not mandatory. When differential drops below cracking pressure, valve closes. With all-metal components, valve can be used up to 650°F (343°C). See Technical Information section for connection temperature limitations. **(Not for use as a relief valve.)**


Ball and poppet are an integral design to assure positive, in-line seating without “chatter”. Poppet is designed essentially for axial flow with minimum pressure drop.

Materials: 316 Stainless Steel: body, cover, cover gland, ball poppet. 300 Series Stainless Steel: spring

CAUTION: While testing has shown O-Rings to provide satisfactory service life, both cyclic and shelf life may vary widely with differing service conditions, properties of reactants, pressure and temperature cycling and age of the O-ring. FREQUENT INSPECTIONS SHOULD BE MADE to detect any deterioration, and O-rings replaced as required.

CAUTION: See Tubing section for proper selection of tubing.
NOTE: For optional material see Needle Valve Options section.

Ball Type Excess Flow Valves




Protects pressure gauges and pressure instrumentation from sudden surges in flow or venting in the event of line failure.

Materials: 316 Stainless Steel: body, cover, gland nut and sleeve. 300 Series Stainless Steel: ball

Vertical Installation: Since this type of check valve employs a non-spring loaded ball, valve **MUST** be installed in VERTICAL position with arrow on valve body pointing UP. (cover gland up).

Resetting Valve: Equalize the pressure across the ball. The ball will drop and reset automatically.

O-Ring Type Excess Flow Valves



Protects pressure gauges and other pressure instrumentation from sudden surges in flow due to operator error or line failure. This valve provides dependable, tight shut-off.

Materials: 316 Stainless Steel: body, cover and sleeve.
O-Ring: Viton for operation to 400°F (204°C). Buna-N or PTFE available for 250°F (121°C) or 400°F (204°C) respectively; specify when ordering.

Vertical Installation: Since this type of check valve employs a non-spring loaded poppet, valve **MUST** be installed in VERTICAL position with arrow on valve body pointing UP. (cover gland up).

Resetting Valve: Equalize the pressure across the poppet. The poppet will drop and reset automatically.

CAUTION: While testing has shown O-Rings to provide satisfactory service life, both cyclic and shelf life may vary widely with differing service conditions, properties of reactants, pressure and temperature cycling and age of the O-ring. FREQUENT INSPECTIONS SHOULD BE MADE to detect any deterioration, and O-rings replaced as required.

CAUTION: See Tubing section for proper selection of tubing.
NOTE: For optional material see Needle Valve Options section.

Fittings and Tubing - Low Pressure Check Valves

Catalog Number	Fits Connection Type	Pressure Rating psi (bar)*	Orifice inches (mm)	Rated C _v	Dimensions - inches (mm)				
					A	B	C	D Typical	Hex

O-Ring Check Valves

SW02200	W125	15,000 (1034.19)	0.094 (2.39)	0.15	2.25 (57.15)	1.88 (47.75)	0.31 (7.87)	0.50 (12.70)	0.63 (15.88)
SW04400	SW250	15,000 (1034.19)	0.188 (4.78)	0.63	3.18 (80.77)	2.56 (65.02)	0.44 (11.18)	0.63 (16.00)	0.81 (20.57)
SW06600	SW375	15,000 (1034.19)	0.250 (6.35)	1.70	3.56 (90.42)	3.00 (76.20)	0.53 (13.46)	0.75 (19.05)	1.00 (25.40)
SW08800	SW500	10,000 (689.46)	0.375 (9.53)	3.40	4.18 (106.17)	3.50 (88.90)	0.53 (13.46)	0.93 (23.62)	1.38 (35.05)

Ball Check Valves

SWB2200	W125	15,000 (1034.19)	0.094 (2.39)	0.15	2.25 (57.15)	1.88 (47.75)	0.31 (7.87)	0.50 (12.70)	0.63 (15.88)
SWB4400	SW250	15,000 (1034.19)	0.188 (4.78)	0.63	3.18 (80.77)	2.56 (65.02)	0.44 (11.18)	0.63 (16.00)	0.81 (20.57)
SWB6600	SW375	15,000 (1034.19)	0.250 (6.35)	1.70	3.56 (90.42)	3.00 (76.20)	0.53 (13.46)	0.75 (19.05)	1.00 (25.40)
SWB8800	SW500	10,000 (689.46)	0.375 (9.53)	3.40	4.18 (106.17)	3.50 (88.90)	0.53 (13.46)	0.93 (23.62)	1.38 (35.05)

Ball Type Excess Flow Valves

SWK2202	W125	15,000 (1034.19)	0.094 (2.39)	0.012+	2.25 (57.15)	1.88 (47.75)	0.31 (7.87)	0.50 (12.70)	0.63 (15.88)
SWK4402	SW250	15,000 (1034.19)	0.188 (4.78)	0.037+	3.18 (80.77)	2.56 (65.02)	0.44 (11.18)	0.63 (16.00)	0.81 (20.57)
SWK6602	SW375	15,000 (1034.19)	0.250 (6.35)	0.104+	3.56 (90.42)	3.00 (76.20)	0.53 (13.46)	0.75 (19.05)	1.00 (25.40)
SWK8802	SW500	10,000 (689.46)	0.375 (9.53)	0.212+	4.18 (106.17)	3.50 (88.90)	0.53 (13.46)	0.93 (23.62)	1.38 (35.05)

O-Ring Type Excess Flow Valves

SWK04400	SW-250	15,000 (1034.19)	0.188 (4.78)	3++	3.12 (79.25)	2.56 (65.02)	0.44 (11.18)	0.63 (16.00)	0.81 (20.57)
SWK06600	SW-375	15,000 (1034.19)	0.250 (6.35)	5++	3.50 (88.90)	3.00 (76.20)	0.53 (13.46)	0.75 (19.05)	1.00 (25.40)
SWK08800	SW-500	10,000 (689.46)	0.375 (9.53)	10++	4.31 (109.47)	3.50 (88.90)	0.53 (13.46)	0.93 (23.62)	1.38 (35.05)

Note:

All check valves are furnished complete with connection components unless otherwise specified.

The 1/16" Tubing System is a complete system for use with all 1/8" components for pressure to 15,000 psi (1034 bar). Consult factory.

† - Check Flow** - water, GPM

†† - Check Flow** - CFM, nitrogen @ 500 psi (34.47 bar), RT

** - For flow using alternate fluids, consult Parker Autoclave Engineers.

*Maximum pressure rating is based on the lowest rating of any component.

Actual working pressure may be determined by tubing pressure rating, if lower.

All dimensions for reference only and subject to change.

For prompt service, Parker Autoclave stocks select products. Consult your local representative.

