

Parflange® F37 – SAE 3000/ISO 6162-1

TFB – Flare flange connection

Tube to port connection, bonded seal





Size		Flange incl. Insert + Bonded Seal + O-Ring + (Sleeve) Order code	D1	C	Insert incl. Bonded Seal + O-Ring Order code	Bonded Seal Order code	O-Ring Order code	Sleeve	Weight (Steel) kg/1 piece
Inch	Tube								
1/2	16X2.0	**F37-308-16X2.0TFBCF**	9.5	8.0	IN08-16X2.0TFBCF	BS08SNX	0R12X1.0X	SL08-25-16-CFX	0.24
1/2	18X2.0	**F37-308-18X2.0TFBCF**	11.5	8.0	IN08-18X2.0TFBCF	BS08SNX	0R14X1.0X	SL08-25-18-CFX	0.24
1/2	20X2.0	**F37-308-20X2.0TFBCF**	13.5	8.0	IN08-20X2.0TFBCF	BS08SNX	0R16X1.0X	SL08-25-20-CFX	0.24
1/2	20X2.5	**F37-308-20X2.5TFBCF**	13.5	8.0	IN08-20X2.5TFBCF	BS08SNX	0R16X1.0X	SL08-25-20-CFX	0.24
1/2	25X2.5	**F37-308-25X2.5TFBCF**	13.5	10.0	IN08-25X2.5TFBCF	BS08SNX	0R20X1.0X		0.25
1/2	25X3.0	**F37-308-25X3.0TFBCF**	13.0	8.0	IN08-25X3.0TFBCF	BS08SNX	0R20X1.0X		0.24
3/4	20X2.0	**F37-312-20X2.0TFBCF**	13.5	8.0	IN12-20X2.0TFBCF	BS12SNX	0R16X1.0X	SL12-30-20-CFX	0.31
3/4	20X2.5	**F37-312-20X2.5TFBCF**	12.5	8.0	IN12-20X2.5TFBCF	BS12SNX	0R16X1.0X	SL12-30-20-CFX	0.31
3/4	25X2.5	**F37-312-25X2.5TFBCF**	17.5	10.0	IN12-25X2.5TFBCF	BS12SNX	0R20X1.0X	SL12-30-25-CFX	0.31
3/4	25X3.0	**F37-312-25X3.0TFBCF**	16.5	8.0	IN12-25X3.0TFBCF	BS12SNX	0R20X1.0X	SL12-30-25-CFX	0.32
3/4	30X3.0	**F37-312-30X3.0TFBCF**	19.0	8.5	IN12-30X3.0TFBCF	BS12SNX	0R25X1.0X		0.32
3/4	30X4.0	**F37-312-30X4.0TFBCF**	19.0	8.5	IN12-30X4.0TFBCF	BS12SNX	0R22X1.0X		1.32
1	25X2.5	**F37-316-25X2.5TFBCF**	17.5	10.0	IN16-25X2.5TFBCF	BS16SNX	0R20X1.0X	SL16-38-25-CFX	0.39
1	25X3.0	**F37-316-25X3.0TFBCF**	16.5	8.0	IN16-25X3.0TFBCF	BS16SNX	0R20X1.0X	SL16-38-25-CFX	0.39
1	30X3.0	**F37-316-30X3.0TFBCF**	21.5	8.5	IN16-30X3.0TFBCF	BS16SNX	0R25X1.0X	SL16-38-30-CFX	0.39
1	30X4.0	**F37-316-30X4.0TFBCF**	19.5	8.5	IN16-30X4.0TFBCF	BS16SNX	0R22X1.0X	SL16-38-30-CFX	0.39
1	38X2.5	**F37-316-38X2.5TFBCF**	25.0	9.5	IN16-38X2.5TFBCF	BS16SNX	0R34X1.0X		0.41
1	38X3.0	**F37-316-38X3.0TFBCF**	25.0	9.0	IN16-38X3.0TFBCF	BS16SNX	0R34X1.0X		0.40
1	38X4.0	**F37-316-38X4.0TFBCF**	25.0	10.0	IN16-38X4.0TFBCF	BS16SNX	0R30X1.0X		0.40
1	38X5.0	**F37-316-38X5.0TFBCF**	25.0	8.0	IN16-38X5.0TFBCF	BS16SNX	0R28X1.0X		0.39
1 1/4	30X3.0	**F37-320-30X3.0TFBCF**	21.5	8.5	IN20-30X3.0TFBCF	BS20SNX	0R25X1.0X	SL20-42-30-CFX	0.57
1 1/4	30X4.0	**F37-320-30X4.0TFBCF**	19.5	8.5	IN20-30X4.0TFBCF	BS20SNX	0R22X1.0X	SL20-42-30-CFX	0.58
1 1/4	38X3.0	**F37-320-38X3.0TFBCF**	29.5	9.0	IN20-38X3.0TFBCF	BS20SNX	0R34X1.0X	SL20-42-38-CFX	0.56
1 1/4	38X4.0	**F37-320-38X4.0TFBCF**	27.0	10.0	IN20-38X4.0TFBCF	BS20SNX	0R30X1.0X	SL20-42-38-CFX	0.57
1 1/4	38X5.0	**F37-320-38X5.0TFBCF**	25.5	8.0	IN20-38X5.0TFBCF	BS20SNX	0R28X1.0X	SL20-42-38-CFX	0.56
1 1/4	42X3.0	**F37-320-42X3.0TFBCF**	31.5	10.0	IN20-42X3.0TFBCF	BS20SNX	0R37.82X1.78X		0.57
1 1/4	42X4.0	**F37-320-42X4.0TFBCF**	31.5	10.0	IN20-42X4.0TFBCF	BS20SNX	0R34X1.0X		0.56
1 1/2	38x3.0	**F37-324-38X3.0TFBCF**	27.5	9.0	IN24-38X3.0TFBCF	BS20SNX	0R34X1.0X	SL24-50-38-CFX	0.65
1 1/2	38X4.0	**F37-324-38X4.0TFBCF**	27.5	10.0	IN24-38X4.0TFBCF	BS24SNX	0R30.X1.0X	SL24-50-38-CFX	0.87
1 1/2	38X5.0	**F37-324-38X5.0TFBCF**	25.0	8.0	IN24-38X5.0TFBCF	BS24SNX	0R28X1.0X	SL24-50-38-CFX	0.87
1 1/2	42X3.0	**F37-324-42X3.0TFBCF**	35.0	10.0	IN24-42X3.0TFBCF	BS24SNX	0R37.82X1.78X	SL24-50-42-CFX	0.88
1 1/2	42X4.0	**F37-324-42X4.0TFBCF**	31.5	10.0	IN24-42X4.0TFBCF	BS24SNX	0R34X1.0X	SL24-50-42-CFX	0.87
1 1/2	50X3.0	**F37-324-50X3.0TFBCF**	36.0	11.0	IN24-50X3.0TFBCF	BS24SNX	0R44.17X1.78X		0.87
1 1/2	50X5.0	**F37-324-50X5.0TFBCF**	36.0	10.0	IN24-50X5.0TFBCF	BS24SNX	0R41X1.78X		0.87
1 1/2	50X6.0	**F37-324-50X6.0TFBCF**	35.0	10.0	IN24-50X6.0TFBCF	BS24SNX	0R41X1.78X		0.87
2	50X3.0	**F37-332-50X3.0TFBCF**	41.5	11.0	IN32-50X3.0TFBCF	BS32SNX	0R44.17X1.78X	SL32-60-50-CFX	1.20
2	50X5.0	**F37-332-50X5.0TFBCF**	37.5	10.0	IN32-50X5.0TFBCF	BS32SNX	0R41X1.78X	SL32-60-50-CFX	1.22
2	50X6.0	**F37-332-50X6.0TFBCF**	35.0	10.0	IN32-50X6.0TFBCF	BS32SNX	0R41X1.78X	SL32-60-50-CFX	1.25
2	60X3.0	**F37-332-60X3.0TFBCF**	46.0	12.0	IN32-60X3.0TFBCF	BS32SNX	0R53.7X1.78X		1.25
2	60X5.0	**F37-332-60X5.0TFBCF**	46.0	11.0	IN32-60X5.0TFBCF	BS32SNX	0R50.52X1.78X		1.22
2	60X6.0	**F37-332-60X6.0TFBCF**	45.5	11.0	IN32-60X6.0TFBCF	BS32SNX	0R47.37X1.78X		1.21
2 1/2	60X3.0	**F37-340-60X3.0TFBCF**	50.0	12.0	IN40-60X3.0TFBCF	BS40SNX	0R53.7X1.78X	SL40-75-60-CFX	1.98
2 1/2	60X5.0	**F37-340-60X5.0TFBCF**	46.0	11.0	IN40-60X5.0TFBCF	BS40SNX	0R50.52X1.78X	SL40-75-60-CFX	1.99
2 1/2	60X6.0	**F37-340-60X6.0TFBCF**	45.5	11.0	IN40-60X6.0TFBCF	BS40SNX	0R47.37X1.78X	SL40-75-60-CFX	1.97
2 1/2	75X3.0	**F37-340-75X3.0TFBCF**	60.0	10.0	IN40-75X3.0TFBCF	BS40SNX	0R69.57X1.78X		1.93
2 1/2	75X5.0	**F37-340-75X5.0TFBCF**	60.0	10.0	IN40-75X5.0TFBCF	BS40SNX	0R63.22X1.78X		1.95
3	75X3.0	**F37-348-75X3.0TFBCF**	66.0	10.0	IN48-75X3.0TFBCF	BS48SNX	0R69.57X1.78X	SL48-90-75-CFX	3.22
3	75X5.0	**F37-348-75X5.0TFBCF**	62.0	10.0	IN48-75X5.0TFBCF	BS48SNX	0R63.22X1.78X	SL48-90-75-CFX	3.38
3	90X3.5	**F37-348-90X3.5TFBCF**	72.0	15.0	IN48-90X3.5TFBCF	BS48SNX	0R82.27X1.78X		3.39
3	90X5.0	**F37-348-90X5.0TFBCF**	72.0	14.0	IN48-90X5.0TFBCF	BS48SNX	0R79X1.78X		3.35

Other sizes on request

Please change suffixes according to material/surface required

Order code suffixes		
Material	Suffix surface and material	Example
Steel, zinc plated, Cr(VI)-free	CF	F37-324-50X5.0TFBCF
Stainless steel	SS	F37-324-50X5.0TFBSS