
JMTX Union tee reducing

Triple-Lok® 37° Flare end (three ends)
SAE 070401 MS51510



Tube 1 O.D. mm	Tube 1 O.D. in.	Tube 2 O.D. mm	Tube 2 O.D. in.	Thread UN/UNF-2A T1	Thread UN/UNF-2A T2	D mm	D1 mm	M mm	M1 mm	Y mm	Weight (steel) g/1 piece	Triple-Lok® Steel	Triple-Lok® Stainless Steel	PN (bar) S	PN (bar) SS
10	3/8	6	1/4	9/16-18	7/16-20	8	4	27	27	14	50	**6-6-4JMTXS**	**6-6-4JMTXSS**	420	350
12	1/2	6	1/4	3/4-16	7/16-20	10	4	32	29	19	96	**8-8-4JMTXS**	**8-8-4JMTXSS**	420	350
12	1/2	10	3/8	3/4-16	9/16-18	10	8	32	29	19	102	**8-8-6JMTXS**	**8-8-6JMTXSS**	420	350
14, 15,16	5/8	6	1/4	7/8-14	7/16-20	12	4	37	31	22	156	**10-10-4JMTXS**	**10-10-4JMTXSS**	350	350
14, 15,16	5/8	10	3/8	7/8-14	9/16-18	12	8	37	31	22	167	**10-10-6JMTXS**	**10-10-6JMTXSS**	350	350
14, 15,16	5/8	12	1/2	7/8-14	3/4-16	12	10	37	34	22	175	**10-10-8JMTXS**	**10-10-8JMTXSS**	350	350
18, 20	3/4	6	1/4	1 1/16-12	7/16-20	16	4	42	33	27	234	**12-12-4JMTXS**	**12-12-4JMTXSS**	350	350
18, 20	3/4	10	3/8	1 1/16-12	9/16-18	16	8	42	33	27	249	**12-12-6JMTXS**	**12-12-6JMTXSS**	350	350
18, 20	3/4	12	1/2	1 1/16-12	3/4-16	16	10	42	36	27	265	**12-12-8JMTXS**	**12-12-8JMTXSS**	350	350
18, 20	3/4	14/15/16	5/8	1 1/16-12	7/8-14	16	12	42	39	27	283	**12-12-10JMTXS**	**12-12-10JMTXSS**	350	280
25	1	10	3/8	1 5/16-12	9/16-18	22	8	46	36	33	326	**16-16-6JMTXS**	**16-16-6JMTXSS**	280	280
25	1	12	1/2	1 5/16-12	3/4-16	22	10	46	39	33	354	**16-16-8JMTXS**	**16-16-8JMTXSS**	280	280
25	1	14/15/16	5/8	1 5/16-12	7/8-14	22	12	46	42	33	379	**16-16-10JMTXS**	**16-16-10JMTXSS**	280	280
25	1	18/20	3/4	1 5/16-12	1 1/16-12	22	16	46	45	33	396	**16-16-12JMTXS**	**16-16-12JMTXSS**	280	210
28, 30, 32	1 1/4	12	1/2	1 5/8-12	3/4-16	28	10	52	44	41	478	**20-20-8JMTXS**	**20-20-8JMTXSS**	280	210
28, 30, 32	1 1/4	14/15/16	5/8	1 5/8-12	7/8-14	28	12	52	47	41	526	**20-20-10JMTXS**	**20-20-10JMTXSS**	280	210
28, 30, 32	1 1/4	18/20	3/4	1 5/8-12	1 1/16-12	28	16	52	50	41	628	**20-20-12JMTXS**	**20-20-12JMTXSS**	280	210
28, 30, 32	1 1/4	25	1	1 5/8-12	1 5/16-12	28	22	52	51	41	673	**20-20-16JMTXS**	**20-20-16JMTXSS**	280	210

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.

K

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark