



Hydraulic Pump T7AS/T7ASW Series Vane Pumps

*Pressure up to 300 bar
Fixed Displacement from 6 to 40 ml/rev.*

*Catalogue HY29-0008/UK
December 2005*



DENISON | **Hydraulics**

GENERAL

Characteristics :
 displacements, max./min. speeds, max. pressures 2
 Minimum allowable inlet pressure 3
 General characteristics 3

T7AS

Ordering code and technical data 4
 Dimensions 5

T7ASW

Ordering code and technical data 6
 Dimensions 7
 WARNING 8

MINIMUM & MAXIMUM SPEED, PRESSURE RATINGS

Size	Series	Theoretical Displacement Vi	Minimum Speed	Maximum Speed		Maximum pressure								
				HF-0, HF-1 HF-2	HF-3, HF-4	HF-0, HF-2		HF-1, HF-4		HF-3				
		ml/rev.	RPM	RPM	RPM	Int.	Cont.	Int.	Cont.	Int.	Cont.			
						bar	bar	bar	bar	bar	bar			
T7AS*	B06	5,8	600	3600	1800	300	275	240	210	175	140			
	B10	9,8												
	B11	11,0												
	B13	12,8												
	B17	17,2												
	B20	19,8												
	B22	22,5												
B25	24,9	3000	275	240										
T7ASW*	B26	26,0	600	3600	1800	300	275	240	210	175	140			
	B28	28,0												
	B30	30,0												
	B32	31,8												
	B34	34,0												
	B36	36,0										3000	280	240
	B40	40,0												

HF-0, HF-2 = Antiwear Petroleum Base
 HF-1 = Non Antiwear Petroleum Base
 HF-3 = Water in oil Emulsions
 HF-4 = Water Glycols

* Please be careful as the cartridge designation is now in ml/rev. (example : B22 = 22,5 ml/rev.)

For further information or if the performance characteristics outlined above do not meet your particular requirements, please consult your local Parker Denison office.



MINIMUM ALLOWABLE INLET PRESSURE (BAR ABSOLUTE)

Cartridge		Speed RPM										Series										
Size	Series	1200	1500	1800	2100	2200	2300	2500	2800	3000	3600											
T7AS	B06	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	B06									
	B10												B10									
	B11												B11									
	B13												B13									
	B17																			0,88		B17
	B20																			0,94		B20
	B22																			1,00		B22
	B25																		0,85			B25
T7ASW	B26	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	0,80	B26									
	B28												B28									
	B30												B30									
	B32												B32									
	B34																			0,88		B34
	B36																			0,94		B36
	B40																			1,00		B40

Inlet pressure is measured at inlet flange with petroleum base fluids at viscosity between 10 and 65 cSt. The difference between inlet pressure at the pump flange and atmospheric pressure must not exceed 0,2 bar to prevent aeration.

Multiply absolute pressure by 1,25 for HF-3, HF-4 fluids.
by 1,10 for ester or rapeseed base.

GENERAL CHARACTERISTICS

	Mounting standard	Weight without connector and bracket kg	Moment of inertia Kgm ² x 10 ⁻⁴	Suction	Pressure
T7AS	SAE J744 ISO/3019-1 SAE A	9,5	2,6	1" - SAE 4 bolts J518 - ISO/DIS 6162-1	3/4" - SAE 4 bolts J518 - ISO/DIS 6162-1
				SAE 16 - SAE threads 1" 5/16 - 12 UNF - 2B	SAE 12 - SAE threads 1" 1/16 - 12 UNF - 2B
				NPTF threads 1" 1/4 NPTF	NPTF threads 3/4" NPTF
				1" BSP	3/4" BSP
T7ASW	SAE J744 ISO/3019-1 SAE A	11,3	3,7	1" 1/4 - SAE 4 bolts J518 - ISO/DIS 6162-1	3/4" - SAE 4 bolts J518 - ISO/DIS 6162-1
				SAE 20 - SAE threads 1" 5/8 - 12 UNF - 2B	SAE 12 - SAE threads 1" 1/16 - 12 UNF - 2B
				NPTF threads 1" 1/4 NPTF	SAE 12 - SAE threads 1" 1/16 - 12 UNF - 2B
				1" 1/4 BSP	3/4" BSP

T7AS - Ordering Code

Vane Pumps T7AS / T7ASW

Model No.

T7AS - B17 - 1 R 00 - A 1 - 00 - ..

T7AS series - SAE A 2 bolts
Mounting flange J744

Displacement *
Volumetric displacement (ml/rev.)
B06 = 5,8
B10 = 9,8
B11 = 11,0
B13 = 12,8
B17 = 17,2
B20 = 19,8
B22 = 22,5
B25 = 24,9

Type of shaft T7AS
1 = keyed (non SAE) Ø 19,05
3 = splined 16/32 (SAE B) 13 teeth
4 = splined 16/32 (SAE A) 9 teeth

Direction of rotation (view on shaft end)
R = Clockwise
L = Counter-clockwise

Modifications

Mounting w/connection variables

00 = 4 bolts SAE flanges (J518) UNC thread
S = 1" SAE
P = 3/4" SAE
02 = SAE thread
S = 1"5/16 (SAE 16)
P = 1"1/16 (SAE 12)
03 = NPTF thread
S = 1"1/4 NPTF
P = 3/4" NPTF
04 = BSP threads
S = 1" BSP
P = 3/4" BSP

Seal class


1 = S1 BUNA N - 0,7 bar max.
(for mineral oil)
5 = S5 VITON - 0,7 bar max.
(for mineral oil and fire resistant fluids)

Design letter


Porting combination

00 = standard

P = Pressure
S = Suction




INTERNAL LEAKAGE (TYPICAL)




Do not operate pump more than 5 seconds at any speed or viscosity if internal leakage is higher than 50% of theoretical flow.


NOISE LEVEL (TYPICAL) - T7AS B20



POWER LOSS HYDROMECHANICAL (TYPICAL)







PERMISSIBLE RADIAL LOAD




* Cartridge designation is now in ml/rev. (example : B22 = 22,5 ml/rev.) Maximum permissible axial load Fa = 600 N





Option : with valve



Code	00	02	03	04
A	Ø 25.40	SAE # 16 1" 5/16 - 12 UNF - 2B	1" 1/4 NPTF	1" BSP
B	Ø 19.05	SAE # 12 1" 1/16 - 12 UNF - 2B	3/4" NPTF	3/4" BSP

Shaft	Shaft torque limits [ml/rev. x bar]
1	Vi x p max. 8720
3	8720
4	6550

If inlet velocity > 1.9 m/s, please contact Parker Denison.

T7ASW - Ordering Code

Model No.

T7ASW - B32 - 1 R 00 - A 1 - 00 - ..

T7ASW series - SAE A 2 bolts
Mounting flange J744

Displacement *

Volumetric displacement (ml/rev.)

- B26 = 26,0
- B28 = 28,0
- B30 = 30,0
- B32 = 31,8
- B34 = 34,0
- B36 = 36,0
- B40 = 40,0

Type of shaft T7ASW

- 1 = keyed (non SAE) Ø 19,05
- 3 = splined 16/32 (SAE B) 13 teeth
- 4 = splined 16/32 (non SAE) 11 teeth

Direction of rotation (view on shaft end)

- R = Clockwise
- L = Counter-clockwise

Modifications

Mounting w/connection variables

- 00 = 4 bolts SAE flanges (J518) UNC threads
S = 1"1/4 SAE
P = 3/4" SAE
- 02 = SAE thread
S = 1"5/8 (SAE 20)
P = 1"1/16 (SAE 12)
- 03 = NPTF & SAE threads
S = 1"1/4 NPTF
P = 1"1/16 (SAE 12)
- 04 = BSP threads
S = 1"1/4 BSP
P = 3/4" BSP

Seal class


- 1 = S1 BUNA N - 0,7 bar max.
(for mineral oil)

Design letter


Porting combination

- 00 = standard

- P = Pressure
- S = Suction




INTERNAL LEAKAGE (TYPICAL)




Do not operate pump more than 5 seconds at any speed or viscosity if internal leakage is higher than 50% of theoretical flow.


NOISE LEVEL (TYPICAL) - T7ASW B28



POWER LOSS HYDROMECHANICAL (TYPICAL)




PERMISSIBLE RADIAL LOAD




* Cartridge designation is now in ml/rev. (example : B22 = 22,5 ml/rev.) Maximum permissible axial load Fa = 800 N






SHAFT CODE 1
(KEYED NO SAE)

MOUNTING TORQUE : 110 Nm



SHAFT CODE 3

SAE-B splined shaft
Class 1 - J498b
16/32 d.p. - 13 teeth
30° pressure angle
flat root side fit



SHAFT CODE 4

Splined shaft
Class 1 - J498b
16/32 d.p. - 11 teeth
30° pressure angle
flat root side fit

Shaft torque limits [ml/rev. x bar]	
Shaft	Vi x p max.
1	18530
3	18530
4	12660

If inlet velocity > 1,9 m/s, please contact Parker Denison.

Code	00	02	03	04
A	Ø 31,80	SAE # 16 1" 5/16 - 12 UNF - 2B	1" 1/14 NPTF	1" 1/4 BSP
B	Ø 19,05	SAE # 12 1" 1/16 - 12 UNF - 2B	SAE # 12 1" 1/16 - 12 UNF - 2B	3/4" BSP





WARNING

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin, its subsidiaries, sales offices and authorized distributors provide product or system options for further investigation by users having technical expertise. Before you select or use any product or system it is important that you analyse all aspects of your application and review the information concerning the product or system in the current product catalogue. Due to the variety of operating conditions and applications for these products or systems, the user, through his own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance and safety requirements of the application are met. The products are subject to change by Parker Hannifin at any time without notice.

Offer of Sale

Please contact your Parker representation for a detailed "Offer of Sale".



Hydraulics Group Sales Offices

Europe

Austria **Wiener Neustadt**

Tel: +43 (0)2622 23501
Fax: +43 (0)2622 66212

Belgium **Nivelles**

Tel: +32 (0)67 280 900
Fax: +32 (0)67 280 999

Czech Republic **Klečany**

Tel: +420 284 083 111
Fax: +420 284 083 112

Denmark **Ballerup**

Tel: +45 4356 0400
Fax: +45 4373 8431

Finland **Vantaa**

Tel: +358 (0)9 4767 31
Fax: +358 (0)9 4767 3200

France **Contamine-sur-Arve**

Tel: +33 (0)450 25 80 25
Fax: +33 (0)450 03 67 37

Germany **Kaarst**

Tel: +49 (0)2131 4016 0
Fax: +49 (0)2131 4016 9199

Hungary **Budapest**

Tel: +36 (06)1 220 4155
Fax: +36 (06)1 422 1525

Ireland **Dublin**

Tel: +353 (0)1 293 9999
Fax: +353 (0)1 293 9900

Italy **Corsico (MI)**

Tel: +39 02 45 19 21
Fax: +39 02 4 47 93 40

The Netherlands **Oldenzaal**

Tel: +31 (0)541 585000
Fax: +31 (0)541 585459

Norway **Ski**

Tel: +47 64 91 10 00
Fax: +47 64 91 10 90

Poland **Warsaw**

Tel: +48 (0)22 573 24 00
Fax: +48 (0)22 573 24 03

Portugal **Leca da Palmeira**

Tel: +351 22 9997 360
Fax: +351 22 9961 527

Slovakia **Ref. Czech Republic**

Spain **Madrid**

Tel: +34 91 675 73 00
Fax: +34 91 675 77 11

Sweden **Spånga**

Tel: +46 (0)8 597 950 00
Fax: +46 (0)8 597 951 10

Turkey **Mertler/Istanbul**

Tel: +90 212 482 91 06 or 07
Fax: +90 212 482 91 10

United Kingdom **Warwick**

Tel: +44 (0)1926 317 878
Fax: +44 (0)1926 317 855

International

Australia **Castle Hill**

Tel: +61 (0)2-9634 7777
Fax: +61 (0)2-9899 6184

Canada **Milton, Ontario**

Tel: +1 905-693-3000
Fax: +1 905-876-0788

China **Beijing**

Tel: +86 10 6561 0520
Fax: +86 10 6561 0526

Asia Pacific Group **Hong Kong, Kowloon**

Tel: +852 2428 8008
Fax: +852 2425 6896

India **Mumbai**

Tel: +91 22 7907081
Fax: +91 22 7907080

Japan **Tokyo**

Tel: +(81) 3 6408 3900
Fax: +(81) 3 5449 7201

Latin America Group **Brazil**

Tel: +55 12 3954-5100
Fax: +55 12 3954-5266

South Africa **Kempton Park**

Tel: +27 (0)11-961 0700
Fax: +27 (0)11-392 7213

USA **Cleveland (industrial)**

Tel: +1 216-896-3000
Fax: +1 216-896-4031

Lincolnshire (mobile)

Tel: +1 847-821-1500
Fax: +1 847-821-7600

Parker Hannifin is the world's premier supplier of motion and control systems and solutions, with sales and manufacturing facilities throughout the world. For product information and details of your nearest Parker sales office, visit us at www.parker.com or call free on 00800 2727 5374.



Catalogue HY29-0008/UK
PDF 01/06

© Copyright 2006
Parker Hannifin Corporation
All rights reserved