S 2

Must workshops and mobile service teams do without the power and reliability of large stationary crimpers? UNIFLEX's answer is a definite "no", and our compact, multi-purpose workshop crimpers prove that the advantages of the legendary slide bearing technology can also be used in light-weight, inexpensive equipment that will fit into almost any vehicle and workshop.



S 2 M



S 2 P



S 2 A

Ergonomic
The lightest crimper with the biggest opening in its class
Easy to handle
Two-stage hand pump
Compact Design
Fits in any workshop
Ideal for on-site service
Slide bearing technology
No greasing improves cleanliness of machine
Prolongs the machine's lifetime
Maximum productivity with very low maintenance costs
No risk of prematurely damaging the crimping head
End product can be used in sanitary applications without cleaning
20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers
Consistently accurate crimp result
CE compliant

We reserve the right to make technical changes without notice. Options are machine parts that can only be ordered while buying the machine.

Packages



QDS 263 B

S 2 Ecoline:

S 2 Ecoline Package = Machine
+ PB Ø 17, 20, 24
+ QDS 26X B

Others:

S 2 Package = Machine
+ PB Ø 17, 20, 24, 28, 32, 40
+ QDS 26X B

Accessories



TU Table



PTS System

Technical Data



S 2 M H



S 2 M Ecoline



S 2 P



S 2 A

NEW



S 2 LA

Technical Data	S 2 M H	S 2 M Ecoline	S 2 P	S 2 A	S 2 LA
Crimp force (kN / Ton)	900/90	900/90	900/90	900/90	450/45
No grease: 20% less friction	✓	✓	✓	✓	✓
SAE R 12/4SP* 1 piece fitting	1¼"	1¼"	1¼"	1¼"	¾"
SAE R 15/4SH* 2 piece fitting	1"	1"	1"	1"	⅝"
Industrial	1¼"	1¼"	1¼"	1¼"	1¼"
90° Elbows	1"	1"	1"	1"	1"
Max. Crimp range	63 mm**	63 mm**	63 mm**	63 mm**	63 mm**
Opening	+22 mm	+22 mm	+22 mm	+22 mm	+22 mm
Opening without dies	77 mm	77 mm	77 mm	77 mm	77 mm
Master dies length (mm)	75 mm	75 mm	75 mm	75 mm	75 mm
Type of dies	263	263	263	263	263
Speed (mm/sec)					
Close Crimp	- -	- -	0,9 0,9	5,8 0,6	2,4 0,2
Drive	manual	manual	pneumatic***	1 VAC	1 VAC
Oil	0,75 L	0,75 L	2 L	1,5 L	1,5 L
L x W x H (mm)	500 x 420 x 440	170 x 220 x 330	380 x 400 x 310	450 x 450 x 350	450 x 450 x 450
Weight	32 kg	29 kg	33 kg	41 kg	56 kg

Type of dies



263

Ø mm	mm
6,8	40
9	75
12	75
14	75
17	75
20	75
24	75
28	75
32	75
36	75
40	75
44	75
47	75

* According to the fitting.
** With master dies.
*** 7 bar/98 psi.

NEW



New standard by S 2 M

S 2 M H and S 2 M H Ecoline with special pump. (The low pressure delivery volume is around three times higher than the standard.)

32/3 cc instead of 11/3 cc

New head, less weight (2 kg)

Only 29 kg for 1" 4SP!
S 2 M Ecoline

NEW




Options



S 2 DC

Additional Information



On S 2 M models, an optical signal is given when the crimp measure is reached. The electric and pneumatic variants have an automatic stop function.



Telescopic hand-lever standard.