# SL 3-16 M | SL 3-32 M | SL 3-75

Next-generation crimper for low pressure hose assemblies. With the SL 3-16 M, UNIFLEX innovates the existing crimper: two integrated die sets in one tool. No more lost time changing the die. Just change the handle and you are already crimping the other size. No risk of losing dies, no dirty hands, no "time lost". With the built-in handle, you can easily carry it anywhere. SL 3-32 M and SL 3-75 complete the range with large opening travel up to 3".

We reserve the right to make technical changes without notice. Options are machine parts that can only be ordered while buying the machine.

| Technical Data | SL 3-16 M | SL 3-32 M | SL 3-75 |
|---|---|---|---|
| Crimp force (kN / Ton) | 30/3 | 200/20 | 500/50 |
| Opening travel | +31,7 mm | +36,7 mm | +55 mm |
| Industrial | ⅝"** | 1¼"** | 3"* |
| Opening without dies | 38,6/46,4 mm | 88 mm | 115 mm |
| Type of dies | 150 | 263 | 239 |
| Master dies length (mm) | 10 mm | 68 mm | 75 mm |
| L x W x H (mm) | 340 x 143 x 780 | 216 x 165 x 348 | 420 x 520 x 550 |
| Weight | 20 kg | 28 kg | 88 kg |

* According to the fitting
** With master dies
Dies 150: 6,9 mm and 14,9 mm

**Type of dies**



263

| Ø mm | mm |
|---|---|
| 6,8 | 40 |
| 9 | 75 |
| 12 | 75 |
| 14 | 75 |
| 17 | 75 |
| 20 | 75 |
| 24 | 75 |
| 28 | 75 |
| 32 | 75 |
| 36 | 75 |
| 40 | 75 |
| 44 | 75 |
| 47 | 75 |

**Type of dies**



239

| Ø mm | mm |
|---|---|
| 6,5 | 50 |
| 9 | 50 |
| 10 | 50 |
| 12 | 50 |
| 14 | 60 |
| 16 | 60 |
| 17 | 60 |
| 19 | 60 |
| 20 | 60 |
| 22 | 60 |
| 24 | 60 |
| 26 | 75 |
| 28 | 75 |
| 30 | 75 |
| 31 | 75 |
| 32 | 75 |
| 34 | 75 |
| 36 | 75 |
| 38 | 75 |
| 39 | 75 |
| 40 | 75 |
| 44 | 75 |
| 47 | 75 |
| 50 | 75 |
| 54 | 75 |
| 57 | 75 |
| 62 | 75 |




SL 3-16 M




SL 3-32 M




SL 3-75_A (PUU not included)