

Push-Lok® Assembly Tools 611050G and 611050HV

Tool designed for assembly of Push-Lok® fittings and hoses in all sizes. Toggle actions greatly reduce effort necessary to hold hose and press in fitting. Only a few pounds of force is needed on either handle to quickly assemble any size.



611050HV

Hose Fitting Insertion Device TH1E-5

for straight and elbow nipples and fittings.

The TH1E-5 is the first manual fitting insertion device for the assembly or pre-assembly of low, medium and high pressure hose assemblies up to size -20. Straight fittings are using an insertion cone or insertion mandrel while bended fittings are inserted into the hose using an insertion disk.

The hose is simply fixed in the clamping unit and the nipple or the fitting is slightly pushed by hand into the hose.

Subsequently the insertion unit which is equipped with insertion cone, mandrel, or disc is pushed to the left by hand lever until the nipple or fitting is completely inserted into the hose.



Technical / Order Data

Hose Fitting Insertion Device TH1E-5	Part Number	TH1E-5
	Weight	25 kg
	Dimensions	L 650 x B 250 x H 140 mm
Assembly Tool 611050HV "Rigid version"	Part Number	611050HV
	Weight	7,5 kg
	Dimensions	L 500 x B 90 x H 300 mm
Assembly Tool 611050G	Part Number	611050G
	Weight	2,2 kg
	Overall length	320 mm



Ea-33 Catalogue 4400/UK