TH 6-10-HL-10-2

Ultra Clean Kit

- Cleaning of hoses from .....size -4 up to -32
- Reduces downtime and risk of hose failure
- Full-flow quick release coupling and unique 360° rotary plug for proper air flow and non-fatigue operator use
- Aluminium, fully anodized for harsh environments and heavy use
- Unique safety release bar that locks the faceplate into a closed position for firing Ultra Clean projectiles



Standard Kit
TH6-10-HL-10-2

Primary Applications

Workshops and mobile service vehicles

Restrictions

5 micron filter and regulator with gauge are strongly suggested

Technical / Order Data

Ultra Clean Kit TH 6-10-HL-10-2 with case, launcher in size -32, nozzles in size -4, -5, -6, -8, -10, -12, -16, -20, -24 and -32 (1 each)

Air pressure	min. 0.55 MPa
	max. 0.75 MPa
Air connection	1/2“ I.D. air hose
Dimensions	L 407 x W 134 x H 343 mm
Weight	5 kg
Part Number	**TH6-10-HL-10-2**

Nozzles and Projectiles for Ultra Clean Kit TH6-10-HL-10-2

Hose Size	Nozzle **Part Number**	Projectile **Part Number**
-4	**TH6-10-H06**	**TH6-10-P10**
-5	**TH6-10-H08**	**TH6-10-P12**
-6	**TH6-10-H10**	**TH6-10-P14**
-8	**TH6-10-H13**	**TH6-10-P18**
-10	**TH6-10-H16**	**TH6-10-P22**
-12	**TH6-10-H19**	**TH6-10-P26**
-16	**TH6-10-H25**	**TH6-10-P33**
-20	**TH6-10-H32**	**TH6-10-P40**
-24	**TH6-10-H38**	**TH6-10-P50**
-32	**TH6-10-H50**	**TH6-10-P60**

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark