UC-CSS-230VE

Production Heat Shrink machine

- Simple, easy and clean alternative to cap hose and fitting assemblies
- Secure fit due to an easy to use heat shrink system
- Heat shrink technology eliminates problems due to re-contamination issues
- For use on fittings up to -24 (1-1/2")
- Fits straight and elbow fittings
- Easy pull tab removal
- Reduced environmental impact compared to traditional caps: less plastic used, more crushable
- Multiple hoses can be capped at one time



Primary Applications

For hose assembly workshops for series production.



Technical / Order Data

Production Heat Shrink machine with timer	Fitting	up to size -24
	Electrical power	230 V / 50/60 Hz
	Dimensions	241 x 520 x 180 mm
	Weight	11.8 kg
	Part Number	**UC-CSS-230VE-G2**
Electric heat gun with case	Fitting	up to size -24
	Electrical power	230 V / 50/60 Hz
	Dimensions	330 x 330 x 127 mm
	Weight	2.7 kg
	Part Number	**UC-HL-1910E-EU**
Flex vacuum pumpstand	**Part Number**	**UC-HG-STAND**
Diffuser, 95 mm, 1-1/2" heat gun connection	**Part Number**	**UC-1.5HD**



Flex vacuum pumpstand



Diffuser

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark