

Machines

Cutting TH 3E-EM6-M, TH 3E-EM6-P

TH 3E-EM6-M TH3E-EM6-P

Hose Cutting Machines

- Cuts
 - 1 and 2 steel wire or
 - textile braided hoses up to size -32
 - Compact Spiral hoses up to size -20
 - 6 steel wire multispiral hoses up to size -32
- According to the CE safety standards the blade stops within 10 seconds after switching off the brake motor
- Faster and safer cut using less energy, cutting motor with a larger shaft oversize bearing to gurantee less vibration created by radial forces
- Cutting blades approved on considered material

Primary Applications Service in hose workshops and for small series production



Restrictions

Cutting 6 layer multispiral hoses will reduce the service life of the blade.

Technical / Order Data

Cutting blade, serrated 350 x 3 x 30 mm	Part Number	TMG350x3x30
	Part Number	TH3E-EM6-P
Hose Cutting Machine TH 3E-EM6-P with pneumatic feed with cutting blade, serrated TMG 350x3x30	Weight	110 kg
	Dimensions	L 820 x B 785 x H 755 mm
	Cutting blade	350 x 3 x 30 mm
	Exhaust system Ø	60 mm
	Electrical power	400 V / 4,6 kW / 50 Hz
Cutting blade, serrated 350 x 3 x 30 mm	Part Number	TMG350x3x30
Hose Cutting Machine TH 3E-EM6-M with cutting blade, serrated TMG350x3x30	Part Number	TH3E-EM6-M
	Weight	75 kg
	Dimensions	L 745 x W 690 x H 430 mm
	Cutting blade	350 x 3 x 30 mm
	Exhaust system Ø	60 mm
	Electrical power	400 V / 4.6 kW / 50 Hz