TH 8E-200, -200VDC, -200-ECO, -200-24VDC

Strong Crimping Press

- Crimps
  – all Parker *No-Skive* hoses ..... up to size -24
  – ParLock and Compact Spiral hoses ..... up to size -16
- Easy installation on the workbench in the workshop area or in the van
- For die sets series 239

Primary Applications

Hose assembly workshops with small series production and services.

Restrictions

Not for ParLock hose fittings in size -20, -24 and -32 (fittings series V4 and V6).



All TH 8E-200 with – die set packet PBSET-TH8E-200 – quick change tool QDC239.5 Attention: Delivery without oil or connecting plug	Crimp force	130 t
	Crimp range	70 mm
	Noise level	69 dBA
	Colour	black/silver
TH 8E-200	Electrical power	400 V / 50 Hz / 3 PH / 3 kW
	Control system	Mikrometer
	Dimensions	L 800 x B 530 x H 560 mm
	Oil quantity	40 l
	Weight	140 kg
	Part Number	**TH8E-200**
TH 8E-200-ECO	Electrical power	400 V / 50 Hz / 3 PH / 3 kW
	Control system	Mikrometer
	Dimensions	L 420 x B 535 x H 520 mm
	Oil quantity	40 l
	Weight	88 kg
	Part Number	**TH8E-200-ECO**
TH 8E-200VDC, TH 8E-200-24VDC	Electrical power	12 V DC / 24 V DC
	Control system	Mikrometer
	Dimensions	L 420 x B 535 x H 520 mm
	Oil quantity	4 l
	Weight	88 kg
	Part Number	**TH 8E-200VDC/TH 8E-200-24VDC**

Adapter die set, Ø 12–54: PB239-12 PB239-14 PB239-17 PB239 -20 PB239-22 PB239-24 PB239-26 PB239-28 PB239-31 PB239-32 PB239-36 PB239-38 PB239 -40 PB239-44 PB239-50 PB239-54

	Part Number	**PBSET-TH8E-200**
Quick change tool	**Part Number**	**QDC239.3**

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark