

## Machines

## Adjustable Crimper

TH 8E-200, -200VDC, -200-ECO, -200-24VDC

# TH 8E-200, -200VDC, -200-ECO, -200-24VDC

### Strong Crimping Press

- Crimps
  - all Parker *No-Sliver* hoses ..... up to size -24
  - ParLock and Compact Spiral hoses ..... up to size -16
- Easy installation on the workbench in the workshop area or in the van
- For die sets series 239

### Primary Applications

Hose assembly workshops with small series production and services.

### Restrictions

Not for ParLock hose fittings in size -20, -24 and -32 (fittings series V4 and V6).



All TH 8E-200 with	Crimp force	130 t
	Crimp range	70 mm
– die set packet PBSET-TH8E-200	Noise level	69 dBA
– quick change tool QDC239.5	Colour	black/silver
Attention: Delivery without oil or connecting plug	Electrical power	400 V / 50 Hz / 3 PH / 3 kW
	Control system	Mikrometer
	Dimensions	L 800 x B 530 x H 560 mm
	Oil quantity	40 l
	Weight	140 kg
	<b>Part Number</b>	<b>TH8E-200</b>
	Electrical power	400 V / 50 Hz / 3 PH / 3 kW
	Control system	Mikrometer
	Dimensions	L 420 x B 535 x H 520 mm
	Oil quantity	40 l
	Weight	88 kg
	<b>Part Number</b>	<b>TH8E-200-ECO</b>
	Electrical power	12 V DC / 24 V DC
	Control system	Mikrometer
	Dimensions	L 420 x B 535 x H 520 mm
	Oil quantity	4 l
	Weight	88 kg
	<b>Part Number</b>	<b>TH 8E-200VDC/TH 8E-200-24VDC</b>
	<b>Adapter die set, Ø 12–54: PB239-12 PB239-14 PB239-17 PB239-20 PB239-22 PB239-24 PB239-26 PB239-28 PB239-31 PB239-32 PB239-36 PB239-38 PB239-40 PB239-44 PB239-50 PB239-54</b>	
	<b>Part Number</b>	<b>PBSET-TH8E-200</b>
<b>Quick change tool</b>	<b>Part Number</b>	<b>QDC239.3</b>