TH 8E-480-CM

Heavy-Duty Crimping Press

- Crimps
  - all Parkrimp and ParLock hose types including 4 and 6 spiral steel wire
  - DIN 4SP/4SH, SAE 100 R13 / R15 Multispiral hoses ..... up to size -48
  - all Parker industrial hoses ..... up to 8”
- Compact design
- Safe positioning on the fixed 6 o´clock die
- Slide bearings on the crimp tool, no service and 20% less friction



Primary Applications

Heavy Duty Crimping Press for service and series production at workshops

Technical / Order Data

TH 8E-480-CM with
- Adapter die set package PB245.237L
- Adapter die set package PB237.239.2L2
- Quick change tool QDC239.5
- Die set package PBSET-TH8-380

Attention: Delivery without oil and connecting plug

	Electrical power	230-480 V / 50-60 Hz / 3 PH / 5.5 kW
	Crimp force	450 t
	Control system	C-Touch
	Crimp range	310 mm
	Open speed	20 mm/s
	Crimp speed	1.5 mm/s
	Close speed	23 mm/s
	Noise level	62 dB (A)
	Dimensions	L 730 x W 1590 x H 2015 mm
	Weight without oil	2600 kg
	Oil capacity	300 l
	Part Number	**TH8E-480-CM**
Adapter die set PB245.237L	**Part Number**	**PB245.237L**
Adapter die set PB237.239.2L2	**Part Number**	**PB237.239.2L2**
Quick change tool	**Part Number**	**QDC239.5**
Workplace lamp	**Part Number**	**TH8-LUS**

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark