

TH 8E-480-CM

Heavy-Duty Crimping Press

- Crimps
 - all Parkrimp and ParLock hose types including 4 and 6 spiral steel wire
 - DIN 4SP/4SH, SAE 100 R13 / R15 Multispiral hoses up to size -48
 - all Parker industrial hoses up to 8"
- Compact design
- Safe positioning on the fixed 6 o'clock die
- Slide bearings on the crimp tool, no service and 20% less friction



Primary Applications

Heavy Duty Crimping Press for service and series production at workshops

Technical / Order Data

TH 8E-480-CM with • Adapter die set package PB245.237L • Adapter die set package PB237.239.2L2 • Quick change tool QDC239.5 • Die set package PBSET-TH8-380	Electrical power	230-480 V / 50-60 Hz / 3 PH / 5.5 kW
	Crimp force	450 t
	Control system	C-Touch
	Crimp range	310 mm
	Open speed	20 mm/s
	Crimp speed	1.5 mm/s
	Close speed	23 mm/s
	Noise level	62 dB (A)
	Dimensions	L 730 x W 1590 x H 2015 mm
	Weight without oil	2600 kg
Attention: Delivery without oil and connecting plug	Oil capacity	300 l
	Part Number	TH8E-480-CM
	Adapter die set PB245.237L	Part Number PB245.237L
	Adapter die set PB237.239.2L2	Part Number PB237.239.2L2
	Quick change tool	Part Number QDC239.5
	Workplace lamp	Part Number TH8-LUS