TH 2-9

Hose Skiving Machine

- Efficient skiving of hydraulic hoses (external and internal) from .....size -4 up to -32
- Easily controlled by a footpedal
- Waste collection bin



Primary Applications

For small series and service application.

Restrictions

Not recommended for series production.

Technical / Order Data

Hose Skiving Machine TH 2-9 without skiving tools	Hose capacity, external skiving	
	4 and 6 layer	size -4 up to -32
	Hose capacity, internal skiving	
	4 and 6 layer	size -6 up to -32
	Speed	125 rpm
	Colour	light grey
	Dimensions	L 600 x W 410 x H 390 mm
	Weight	35 kg
Hose Skiving Machine TH 2-9-3PH 3 phases, 400 V	Electrical power	3 PH / 400 V / 50 Hz / 16 A / 0.37 kW
	Part Number	**TH2-9-3PH**
Hose Skiving Machine TH 2-9-1PH 1 phase, 230 V	Electrical power	1 PH / 230 V / 50 Hz / 10 A / 0.37 kW
	Part Number	**TH2-9-1PH**



Internal skiving tool



External skiving tool
with one external tool

Skiving tools see page ***Ea-29***

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark