



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



DC590+ Series

DC Drives - Integrator Series



ENGINEERING YOUR SUCCESS

***WARNING – USER RESPONSIBILITY***

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

- This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.
- The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.
- To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

Contents

DC Drives - DC590+ Integrator Series 15 A - 1950 A

Overview.....	5
Technical characteristics	8
Technical Data.....	9
Dimensions	10
Overview of Frames 1 and 2.....	11
Overview of Frame 3	12
External Stack Controller - DC598+, DC599+ Series	15
Accessories and Options	16
Overview	16
Communication Cards	17
Encoder Feedback Option Card	18
Analogue Tacho Feedback Option Card	18
Operator Keypads	19
Drive System Explorer Lite (DSE Lite) Software	20
Order Codes	21
DC590+ Integrator Series, 110 V...500 V 3 phase.....	21
DC590+ Integrator Series 500 V...690 V 3 phase.....	22
DC590+ Series External Stack Controllers.....	23

Parker Hannifin

The global leader in motion and control technologies

A world class player on a local stage

Global Product Design

Parker Hannifin has more than 40 years experience in the design and manufacturing of drives, controls, motors and mechanical products. With dedicated global product development teams, Parker draws on industry-leading technological leadership and experience from engineering teams in Europe, North America and Asia.

Local Application Expertise

Parker has local engineering resources committed to adapting and applying our current products and technologies to best fit our customers' needs.

Manufacturing to Meet Our Customers' Needs

Parker is committed to meeting the increasing service demands that our customers require to succeed in the global industrial market. Parker's manufacturing teams seek continuous improvement through the implementation of lean manufacturing methods throughout the process. We measure ourselves on meeting our customers' expectations of quality and delivery, not just our own. In order to meet these expectations, Parker operates and continues to invest in our manufacturing facilities in Europe, North America and Asia.

Electromechanical Worldwide Manufacturing Locations

Europe

Littlehampton, United Kingdom
Dijon, France
Offenburg, Germany
Filderstadt, Germany
Milan, Italy

Asia

Wuxi, China
Jangan, Korea
Chennai, India

North America

Rohnert Park, California
Irwin, Pennsylvania
Charlotte, North Carolina
New Ulm, Minnesota



Offenburg, Germany

Local Manufacturing and Support in Europe

Parker provides sales assistance and local technical support through a network of dedicated sales teams and authorized technical distributors throughout Europe.

For contact information, please refer to the Sales Offices on the back cover of this document or visit www.parker.com



Milan, Italy



Littlehampton, UK



Filderstadt, Germany



Dijon, France

DC Drives - DC590+ Integrator Series 15 A - 1950 A

Overview

Description

The DC590+ Integrator Series DC drive is the latest development of the range which also includes the AC690+ AC drives. It benefits from 30 years experience of designing and manufacturing drives for process line control with dedicated function blocks which simplify the implementation of applications such as sectional drive reels, winder control etc. The function block capabilities offer unparalleled flexibility in both new installations and retrofit applications. A number of common fieldbus communications options enable connectivity to a wide range of popular control networks allowing the DC590+ to be integrated in larger control systems.

Features

- Ratings up to 1950 A and supply voltages to 690 V
- Internal controlled field supply
Function blocks programming, including open and closed-loop winder control as standard

Standards

The DC590+ series meets the following standards when installed in accordance with the relevant product manual.

CE marked to EN50178 (Safety, Low Voltage Directive) EN61800-3 (EMC Directive) with integral filters. External supply capacitors are required up to 110 A for compliance.

- Supply Voltage 220...500 V as standard
- CE marked
- UL and cUL approved up to 830 A



Technical Characteristics - Overview

Power configuration	DC590+ 4 quadrant regenerative; 2 fully controlled 3 phase thyristor bridges DC591+ 2 quadrant; 1 fully controlled 3 phase thyristor bridge
Armature rating (ADC)	Frame 1 15, 35 A Frame 2 40, 70, 110, 165 A Frame 3 180, 270 A Frame 4 380, 500, 725, 830 A Frame 6 1250, 1600, 1950 A
Overload	15...270 A; 200 % for 10 s 150 % for 30 s - from 380 A: several overload choices are available
Supply voltage (VAC) 50/60 Hz	220...500 V (±10 %) Frame 1...4 110...220 V (±10 %) Option Frame 1...4 500...600 V (±10 %) Option Frame 4 380...600 V (±10 %) Frame 6 380...690 V (±10 %) Frame 6
Field current max	4 A Frame 1 10 A Frame 2 and 3 30 A Frame 4
Field voltage max	$V_{field} = V_{AC} \times 0.82$
Operating Environment	
Operating temperature	0...45 °C (15...165 A) 0...35 °C (180...270 A) 0...40 °C (current ≥1200 A) derate by 1 %/°C up to 55 °C max
Altitude	500 m above sea level Derate by 1 %/200 m above 500 m to 5000 m max

DC Drives - Integrator Series - DC590+ Series Overview

Next Generation Technology

Building upon the highly successful DC590+ drive used in thousands of applications world-wide, the DC590+ Integrator drive takes DC motor control to the next level. With its state-of-the-art advanced 32-bit control architecture, the DC590+ drive delivers highly functional and flexible control suited to a whole host of industrial applications.

Typical Applications

- Converting machinery
- Plastics and rubber processing machinery
- Wire and cable
- Material handling systems
- Automotive

Function Block Programming

Function Block Programming is a tremendously flexible control structure that allows an almost infinite combination of user functions to be realised with ease. Each control function (an input, output, process PID for example) is represented as a software block that can be freely interconnected to all other blocks to provide any desired action.

The drive is despatched with the function blocks pre-configured as a standard DC drive so you can operate it straight from the box without further adjustments. Alternatively you can pick pre-defined Macros or even create your own control strategy, often alleviating the need for an external PLC and therefore reducing cost.

Feedback Options

The DC590+ has a range of interface options which are compatible with the most common feedback devices enabling simple motor control through to the most sophisticated multi-motor system. Armature voltage feedback is standard without the need for any interface option.

- Analogue tachogenerator
- Encoder

Interface Options

Designed with connectivity in mind, the DC590+ has a number of communications and I/O options that allow the drive to take control of the application, or be integrated into a larger system. When combined with function programming, custom functions and control can be easily created offering the user a highly flexible and versatile platform for DC motor control.

Programming/ Operator Controls

Featuring an intuitive menu structure, the ergonomically designed operator panel allows quick and easy access to all parameters and functions of the drive via a bright, easy to read backlit display and tactile keypad. Additionally, it provides local control of start/stop, speed demand and rotation direction to greatly assist with machine commissioning.

- Multi-Lingual alpha-numeric display
- Customised parameter values and legends
- On drive or remote mounting
- Local control of start/stop, speed and direction
- Quick set-up menu

Connectivity

Whatever the complexity of your control scheme, the DC590+ has the interface to suit. As standard there's enough analogue and digital I/O for the most complex applications. Alternatively, add the relevant "technology box" for immediate access to serial communications and Fieldbus networks. The DC590+ has been designed to fit seamlessly, and without compromise, into any control environment.

Analogue/Digital Control

- 5 Analogue Inputs (12bit + sign)
- 3 Analogue Outputs
- 9 Digital Inputs
- 3 Digital Outputs

Serial Communications and Fieldbus Options

- PROFIBUS
- CANopen
- Devicenet
- RS422 / RS485
- Ei Bisynch
- EtherNet



6901 Programming/ Operator Controls

Features and Benefits

Easy to use operator controls

- Detailed diagnostics
- Multi-language display

Advanced autotuning

Standard open fieldbuses



Configurable input-output terminal blocks

- 5 analogue inputs
- 3 analogue outputs
- 9 digital inputs
- 3 digital outputs



Macro function blocks

- Open-loop winder control
- Winder control - loadcell/dancer
- Section control
- Maths functions
- Embedded controller functions

Worldwide product support

The DC590+ DC Drive is available with full application and service support in over fifty countries worldwide. So wherever you are, you can be confident of full back up and support.



Rapid Commissioning, optimal control performance and easy maintenance

With its self-tuning algorithm, the DC590+ can be configured and commissioned within minutes, without turning the motor and without the need for high levels of engineering know-how.

The operator interface allows easy monitoring of machine operation and simplifies maintenance.

Easy integration into existing control networks


The DC590+ has a wide choice of common industry fieldbus communication options allowing seamless integration into existing factory control networks.

Interfacing with existing external control equipment (Dancer, gauge, etc...)

A number of input / output options gives the DC590+ the flexibility needed for integration into any variable speed system. Combined with its embedded automation functions, its input-output configurations can in many instances remove the need for an external PLC.

Years of applications expertise at your service

The DC590+ macro function blocks are the result of over 30 years of experience gained by Parker SSD of installing drives in variable speed and sectional drive systems. This unique application experience is included in the drive in the form of dedicated function blocks at no extra cost, thereby reducing the design costs of your machinery.



Technical characteristics

Electrical characteristics


Voltage	Output current [A]		Field current max [A]	Frame	Order code ¹
	Continuous 100 % without overload	Overload 150 % x 30 s 200 % x 10 s			
110 V - 220 V	15	15	4	1	590P-2321501...
	35	35	4	1	590P-2323501...
	40	40	10	2	590P-2324002...
	70	70	10	2	590P-2327002...
	110	110	10	2	590P-2331102...
	165	165	10	2	590P-2331652...
	180	180	10	3	590P-2331803...
	270	270	10	3	590P-2332703...
	420	380	30	4	590P-2333804...
	550	500	30	4	590P-2335004...
	800	725	30	4	590P-2337254...
220 V - 500 V	910	830	30	4	590P-2338304...
	15	15	4	1	590P-5321501...
	35	35	4	1	590P-5323501...
	40	40	10	2	590P-5324002...
	70	70	10	2	590P-5327002...
	110	110	10	2	590P-5331102...
	165	165	10	2	590P-5331652...
	180	180	10	3	590P-5331803...
	270	270	10	3	590P-5332703...
	420	380	30	4	590P-5333804...
	550	500	30	4	590P-5335004...
	800	725	30	4	590P-5337254...
	910	830	30	4	590P-5338304...
	1350	1250	60	6	590P-5341256...
500 V - 600 V	1750	1600	60	6	590P-5341606...
	2150	1950	60	6	590P-5341956...
	420	380	30	4	590P-6333804...
	550	500	30	4	590P-6335004...
500 V - 690 V	800	725	30	4	590P-6337254...
	910	830	30	4	590P-6338304...
	1350	1250	60	6	590P-7341256...
	1750	1600	60	6	590P-7341606...
	1950	1850	60	6	590P-7341956...

⁽¹⁾ The references are for 4Q drives
For 2Q drives, replace "590P" for "591P"


Technical Data

Protection	High energy MOV's Heatsink overtemperature Instantaneous overcurrent Thyristor trigger failure Inverse time overcurrent Interline snubber network Field Failure Zero speed detection Speed feedback failure Stall protection Motor overtemperature
Inputs/Outputs	
Analogue inputs	(5 Total - 1 x 12 bit plus sign, 4 x 10 bit plus sign) 1 - Speed demand setpoint (-10/0/+10 V) 4 - Configurable
Analogue outputs	(3 Total - 10 bit) 1 - Armature current output (-10/0/+10 V or 0-10 V) 2 - Configurable
Digital inputs	(9 Total - 24 V, max 15 mA) 1 - Program stop 1 - Coast stop 1 - External stop 1 - Start/Run 5 - Configurable
Digital outputs	(3 Total - 24 V (max 30 V) 100 mA) 3 - Configurable
Reference supplies	1 - +10 VDC 1 - -10 VDC 1 - +24 VDC


Dimensions




Frame 1/2



Frame 3



Frame 4




Frame 6

Current [A]	Frame	Dimensions [mm]			Weight [kg]
		W	H	D	
15/35	1	200	375	220	6.4
40/165	2	200	434	292	10.5
180/270	3	250	485	234	20
380/500	4	253	700	358	32
725/830					44
1250/1950	6 2Q	686	715	378	95
	6 4Q				110

Overview of Frames 1 and 2

Frames 1 and 2

1	Main drive assembly
2	Terminal cover
3	Terminal cover retaining screws
5	6901 keypad
6	COMMS technology box (optional)
7	Speed feedback technology card (optional)
8	Gland plate
9	Power terminal shield
10	Power terminals
11	Control terminals
12	Earthing points
13	Keypad port
14	RS232 programming port
15	Auxiliary power, external contactor and isolated thermistor terminals




DC Drives - Integrator Series - DC590+ Series

Overview of Frames


Overview of Frame 3

1	Main drive assembly
2	Door assembly
3	Field wiring terminals
4	Busbars - main power input
5	Busbars - main power output
6	IP20 Top cover)
7	IP20 Fan housing (where fitted)



Overview of Frame 4

1	Main drive assembly
2	Standard door assembly
3	Motor field terminals
4	Busbars - main power input
5	Busbars - main power output
6	Auxiliary supply, contactor and motor thermistor terminals
7	External vent (where fitted)
8	Contactor control select




DC Drives - Integrator Series - DC590+ Series

Overview of Frames

Overview of Frame 6

1	Phase assemblies - L1, L2, L3
2	Fishplate
3	Control panel assembly
4	Front cover
5	Standard door assembly
6	Field controller
7	Busbars - main power input
8	Busbars - main power output



External Stack Controller - DC598+, DC599+ Series

The economical solution for retrofit applications

When upgrading machines equipped with older high power DC drives, the most cost-effective and quickest way is often to reuse the existing thyristor power stack, which in most cases will be in perfect working order. To preserve your investment, Parker SSD Drives has developed a DC598+ / DC599+ power stack controller offer specially aimed at retrofit applications and based on the DC590+ controller.

Available in 2 versions, the DC599+ two quadrant non-regenerative and DC598+ four quadrant full-regenerative versions, can be used to drive the power stacks of existing DC drives manufactured by Parker SSD or other manufacturers, delivering the benefits of the recent technological innovations of the DC590+ Series drive.

The DC598+ and DC599+ offer the ability to upgrade your equipment quickly and easily and integrates with your existing control equipment or SCADA package. The DC598+ and DC599+ retrofit solutions are recommended for currents above 800 A.



Benefits

- Reuse existing DC power stacks
- Connectivity over standard common fieldbuses (Including PROFIBUS, EtherNet, DeviceNet, CANopen)
- Easy to use operator interface
- Flexible common Integrator Series programming environment

The DC598/9+ provides the following:

- Thyristor firing signals
- Thyristor firing pulse transformers
- AC current transformer feedback rectification and scaling
- Armature voltage feedback interface
- Coding and phase rotation interface
- Mains present monitoring
- Heatsink over-temperature input
- Field power modules and input/output terminals
- Field current monitoring and scaling
- All standard DC590+ I/O terminals

Technical Characteristics

Supply Voltage	110...240 VAC $\pm 10\%$ 220...500 VAC $\pm 10\%$ 380...690 VAC $\pm 10\%$ 3 ph coding or 1 ph power
Supply Frequency	50/60 Hz $\pm 10\%$
Output Field Current	60 ADC naturally cooled - 120 ADC force cooled (1 x Field Current DC value) Amps 1 ph. AC Nominal 3 ph AC
Field Output Voltage	(0.9 x 1 ph Supply Voltage) VDC
Total Losses	(3 x idc out) Watts.
Auxiliary Supply	110...240 VAC $\pm 10\%$ 1 ph - Naturally cooled 110...120 VAC $\pm 10\%$ 1 ph - Force cooled 115 V fan 220...240 VAC $\pm 10\%$ 1ph - Force cooled 230 V fan
Auxiliary Supply Current	SMPS Quiescent Current = 500 mA 115 VAC or 250 mA 230 VAC ie 50 VA. Fan current - 270 mA @115 VAC or 135 mA @230 VAC
Auxiliary Supply Fuse	3 A
Operating Temp.	0...+45 °C
Storage Temp.	-25...+55 °C
Shipping Temp.	-25...+70 °C
Enclosure Rating	IP20
Altitude Rating	Maximum Altitude 500 m De-rate the output at 1 % per 200 m
Humidity	Maximum 85 % relative humidity at 45 % non-condensing
Atmosphere	Non flammable, non-corrosive and dust free
Climatic	Class 3k3 as defined by EN60721-3-3 (1995)

Accessories and Options

Overview

Options	Fitting	Order Reference
Operator Keypad		
DC590+ keypad (removable)	Option	6901-00-G
Remote mounting kit		6052/00
Communication Cards		
EtherNet Modbus/TCP and EtherNet IP	Option	6055-ENET-00
LINKnet		6055-LNET-00
DeviceNet		6055-DNET-00
RS485 / Modbus		6055-EI00-00
PROFIBUS-DP		6055-PROF-00
CANopen DS402		6055-CAN-00
Speed Feedback Cards		
Wire-ended encoder Card	Option	AH387775U001-1
Analogue Tacho		AH500935U001-1
Drive Doors / Accessories		
Door for Frame 3	Standard	590PXD-0010-UK
Door for Frame 4		590PD-0010-UK
Frame 4 ventilation kit	Option	LA466717U001-1

Communication Cards

The communication cards allow the DC590+ to be connected to the most common industry standard fieldbuses.

Features

- Dimensions HxWxD:
127 mmx76.2 mmx25.4 mm
- LED indication of network and card status

Ethernet Communications Interface	
*Order Code: 6055-ENET-00	
Supported Protocols	Modbus/TCP and Ethernet IP
Communication Speed	10/100 M bits/s
Station Address	Selectable via switch or Internet Explorer
Suitable for	AC690+ version 4.7+ DC590+ version 7.1+

RS485/Modbus Communications Interface	
*Order Code: 6055-EI00-00	
Supported Protocols	Modbus RTU, EI Bisynch ASCII
Cabling	RS485 2 or 4 wire
Communication Speed	300 to 115200 bits/s
Station Address	Selectable via Software
Suitable for	AC690+ version 4.7+ DC590+ version 5.17+

Devicenet Communications Interface	
*Order Code: 6055-DNET-00	
Supported Protocols	DeviceNet Drive Profile Drive – Group 2 slave only
Station Address	DeviceNet Drive Profile Drive – Group 2 slave only
Suitable for Drives	AC690+ DC590+ version 5.x+

Profibus-DP Communications Interface	
*Order Code: 6055-PROF-00	
Supported Protocols	Profibus-DP
Communication Speed	Automatically Detected
Station Address	Selectable via Software
Suitable for	AC690+ version 1.x+ DC590+ version 5.x+

CANopen Communications Interface	
*Order Code: 6055-CAN-00	
Profile	DS402
Supported Messages	SDO, PDO, NMT, SYNC
Communication Speed	20 K, 50 K, 125 K, 250 K, 500 K, 1M bits/s selectable
Station Address	Selectable via Switch
Suitable for	AC690+ DC590+ version 5.x+

LINKnet Communications Interface	
*Order Code: 6055-LNET-00	
Supported Protocols	Modbus/TCP and Ethernet IP
Communication Speed	10/100 M bits/s
Station Address	Selectable
Suitable for	AC690+ DC590+ version 5.x+


Encoder Feedback Option Card

Description

The encoder feedback card allows an incremental encoder to be fitted to the drive to provide accurate measurement of motor speed. The card also provides the encoder power supply.

Specifications

Maximum input frequency	100 kHz
Receiver current consumption	10 mA per channel
Input format	2 channel differential and quadrature
Differential input voltage	Minimum 3.5 V
Encoder output voltage	+5 V to 24 V adjustable (AH387774U001-1)
Power supply rating	2 W maximum
Power supply load	1.4 x output power
Terminal size	16 AWG maximum
Tightening torque	0.4 Nm




Analogue Tacho Feedback Option Card

Description

The analogue tacho feedback card allows the connection of either an AC or DC tachogenerator to provide a measurement of motor speed to improve motor control. Switches for calibration allow for quick and easy setup.

Specifications

Tachogenerator type	AC/DC
Calibration range	10-200V



Order Codes


Order Code	Description
AH387775U001-1	Encoder Card - Adjustable supply
AH500935U001-1	Tacho Feedback Card

Operator Keypads

Standard operator keypad 6901-00-G

Features

- Local motor control: start, speed, direction, diagnostics
- Operator menus and parameter configuration
- Quick setup menu
- Password protection for parameter configuration





Drive System Explorer Lite (DSE Lite) Software

Description

DSE LITE software is an easy to use configuration, commissioning and monitoring tool with graphical interface for the Parker SSD Drives range of AC and DC drives. While the drive is in running mode the oscilloscope function allows "on-line" monitoring of selected parameters and the recording of trends.

DSE LITE, allows the user to create, parameterize and configure user defined applications thanks to function blocks dedicated to speed control, Winder, PID, Diameter calculator, Shaftless...

DSE LITE is downloadable from our website. www.parker.com



Order Codes

DC590+ Integrator Series, 110 V...500 V 3 phase

	1		2	3	4		5	6		7	8	9	10
Order example	590P	-	23	21501	0	-	P	00	-	U	4	V	0

1 Product Family	4 Auxiliary Supply
590P DC590+ Series DC Digital Drive - 4 quadrant regenerative	0 Universal 115 V...230 V 1 ph (Frames 1, 2, 6)
591P DC591+ Series DC Digital Drive - 2 quadrant non-regenerative	1 115 V 1 ph (Frames 3,4)
	2 230 V 1 ph (Frames 3,4)
2 Supply Voltage	5 Mounting
23 110...220 V 3 phase	P Panel mounting (1)
53 220...500 V 3 phase	6 Special Options
3 Current / Power Rating @110...220 VAC 3 ph	00 None
Output current [A] Frame	Documented special options (refer to local sales office)
21501 15 1	7 Languages
23501 35 1	U English (50/60 Hz) (2)
24002 40 2	8 Keypad
27002 70 2	4 6901 keypad fitted
31102 110 2	9 Speed Feedback
31652 165 2	V Armature voltage (3)
31803 180 3	10 Communications
32703 270 3	0 None (4)
33804 380 4	
35004 500 4	
37254 725 4	
38304 830 4	
3 Current / Power Rating @220...500 VAC 3 ph	
Output current [A] Frame	
21501 15 1	
23501 35 1	
24002 40 2	
27002 70 2	
31102 110 2	
31652 165 2	
31803 180 3	
32703 270 3	
33804 380 4	
35004 500 4	
37254 725 4	
38304 830 4	
41256 1250 6	
41606 1600 6	
41956 1950 6	

(1) Frame 4 ventilation duct kit sold as separate part LA466717U001-1.

(2) Product sold with English as standard. Additional languages can be selected by the user on the 6901 keypad at product commissioning. German, French, Italian and Spanish.

(3) Product supplied without feedback option fitted (armature voltage control). Encoder and tachometer feedback options sold separately.

(4) Product supplied without communications options fitted. Options sold separately.

DC590+ Integrator Series 500 V...690 V 3 phase

	1		2	3	4		5	6		7	8	9	10
Order example	590P	-	63	33804	2	-	P	00	-	U	4	V	0

1 Product Family	590P	DC590+ Series DC Digital Drive - 4 quadrant regenerative
	591P	DC591+ Series DC Digital Drive - 2 quadrant non-regenerative
2 Supply voltage	63	500...600 V 3 ph
	73	500...690 V 3 ph
3 Current / Power Rating @500-600 V 3 ph		Output current [A] Frame
	33804	380 4
	35004	500 4
	37254	725 4
	38304	830 4
3 Current / Power Rating @500-690 V 3 ph		Output current [A] Frame
	41256	1250 6
	41606	1600 6
	41956	1950 6
4 Auxiliary Supply	0	Universal 115 V...230 V 1ph (Frames 1, 2, 6)
	1	115 V 1 ph (Frames 3...4)
	2	230 V 1 ph (Frames 3...4)
5 Mounting	P	Panel mounting (1)
6 Special Options	00	None
		Documented special options (01...99) (refer to local sales office)
7 Languages	U	English (50/60 Hz) (2)
8 Keypad	4	6901 keypad fitted
9 Speed Feedback	V	Armature voltage (3)
10 Communications	0	None (4)

(1) Frame 4 ventilation duct kit sold as separate part LA466717U001-1.

(2) Product sold with English as standard. Additional languages can be selected by the user on the 6901 keypad at product commissioning. German, French, Italian and Spanish.

(3) Product supplied without feedback option fitted (armature voltage control). Encoder and tachometer feedback options sold separately.

(4) Product supplied without communications options fitted. Options sold separately.

DC590+ Series External Stack Controllers

	1		2	3	4		5	6	7		8	9	10	11
Order example	598P	-	23	26001	0	-	A	P	00	-	U	4	V	0

1 Product family														
598P	DC598+ External Stack Controller - 2Q non-regenerative													
599P	DC599+ External Stack Controller - 4Q Regenerative													
2 Supply voltage														
23	110...220 V 3 ph													
53	220...500 V 3 ph													
73	500...690 V 3 ph													
3 Current / Power Ratings @110...220 V 3 ph														
	Output current [A]							Frame Size						
26001	60							1						
31201	120							1						
4 Auxiliary Supply														
0	Universal 115 V...230 V 1 ph (60 Amp rating only)													
1	115 V 1 ph (120 Amp rating only)													
2	230 V 1 ph (120 Amp rating only)													
5 Trigger Option														
A	Amplifiers													
T	Trigger (23 and 53 supplies only)													
6 Mounting														
P	Panel mounting (1)													
7 Special Options														
00	None													
	Documented special options (01...99) (refer to local sales office)													
8 Languages														
U	English (50/60 Hz) (2)													
9 Keypad														
4	6901 keypad installed													
10 Speed Feedback														
V	Armature voltage (3)													
11 Communications														
0	None (4)													

(1) Frame 4 ventilation duct kit sold as separate part LA466717U001-1.

(2) Product sold with English as standard. Additional languages can be selected by the user on the 6901 keypad at product commissioning. German, French, Italian and Spanish.

(3) Product supplied without feedback option fitted (armature voltage control). Encoder and tach feedback options sold separately.

(4) Product supplied without communications options fitted. Options sold separately.

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates, Dubai
Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, St. Florian
Tel: +43 (0)7224 66201
parker.austria@parker.com

AZ – Azerbaijan, Baku
Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/NL/LU – Benelux, Hendrik Ido Ambacht
Tel: +31 (0)541 585 000
parker.nl@parker.com

BG – Bulgaria, Sofia
Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

CH – Switzerland, Etoy
Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany
Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst
Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup
Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid
Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa
Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve
Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Piraeus
Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaörs
Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin
Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IL – Israel
Tel: +39 02 45 19 21
parker.israel@parker.com

IT – Italy, Corsico (MI)
Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty
Tel: +7 7273 561 000
parker.easteurope@parker.com

NO – Norway, Asker
Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal
Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest
Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow
Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Borås
Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SK – Slovakia, Banská Bystrica
Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto
Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul
Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

UK – United Kingdom, Warwick
Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park
Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario
Tel: +1 905 693 3000

US – USA, Cleveland
Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill
Tel: +61 (0)2-9634 7777

CN – China, Shanghai
Tel: +86 21 2899 5000

HK – Hong Kong
Tel: +852 2428 8008

IN – India, Mumbai
Tel: +91 22 6513 7081-85

JP – Japan, Tokyo
Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul
Tel: +82 2 559 0400

MY – Malaysia, Shah Alam
Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington
Tel: +64 9 574 1744

SG – Singapore
Tel: +65 6887 6300

TH – Thailand, Bangkok
Tel: +662 186 7000

TW – Taiwan, Taipei
Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires
Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos
Tel: +55 800 727 5374

CL – Chile, Santiago
Tel: +56 2 623 1216

MX – Mexico, Toluca
Tel: +52 72 2275 4200



EMEA Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

US Product Information Centre

Toll-free number: 1-800-27 27 537

www.parker.com

Your local authorized Parker distributor