

## Manual flaring tools for Triple-Lok® tubes

These 37° flaring tools are for use with copper, aluminum alloy, and thin wall steel or stainless steel tubes. A vice block is clamped together with the tube end into a vice. Flaring pin is used with a hammer. Separate tooling sets for each tube size in metric and inch dimensions are available.

These hand tools are suitable for small on-site repair jobs. They are not suitable for thick-wall tubing and industrial production. A rigid vice must be available at the assembly site.


### Features, advantages and benefits

1. **Light** – Hand flaring tools can be used at any assembly site where a proper workshop is not available
2. **Quick** – Hand flaring tools can be used for temporary repair until a proper spare tube has been made by machine

### Applications

- Field repair of agricultural and construction vehicles
- Small, local repair workshops
- Mobile repair service

## Combination impact flarer 1004 for small dimension metric tube



### Specifications

**Design:** Hand flaring tool for small on-site repair jobs  
**Operation:** Flaring pin Impact  
**37° Flaring:** Triple-Lok® connection – ISO 8434-2/ SAE J514  
**Tube material:** copper, aluminum and low carbon steel  
**Tube diameter:** 6 to 16 mm metric tube  
**Wall thickness:** max 15% of tube O.D.  
**Requirements:** Rigid vice and hammer  
**Performance:** Overall cycle time 1–3 min  
**Economic production quantity:** 10 flarings per week

### Operation


1. Clamp tube end flush in block halves
2. Clean and lubricate tube end and flaring pin
3. Form the flare by a few sharp hammer blows
4. Release vice and unclamp tube

See chapter E for detailed instructions on Triple-Lok® assembly

### Ordering

Type	Order code
Combination impact flarer Complete device including Combination dies and pin	1004-74M
EO-NIROMONT Liquid lubricant in a brush-in-cap can (250 cc)	EONIROMONTAPPLICATOR

## Combination impact flarer 210A for small dimension inch tube



### Specifications

**Design:** Hand flaring tools for small on-site repair jobs  
**Operation:** Flaring pin Impact  
**37° Flaring:** Triple-Lok® connection – ISO 8434-2/ SAE J514  
**Tube material:** copper, aluminum and low carbon steel  
**Tube diameter:** 1/8" to 5/8" inch  
**Wall thickness:** max 15 % of tube-O.D.  
**Requirements:** Rigid vice and hammer  
**Performance:** Overall cycle time 1–3 min  
**Economic production quantity:** 10 flarings per week

### Operation

1. Clamp tube end flush in block halves
2. Clean and lubricate tube end and flaring pin
3. Form the flare by a few sharp hammer blows
4. Release vice and unclamp tube

See chapter E for detailed instructions on Triple-Lok® assembly

### Ordering

Type	Order code
Combination impact flarer Complete device including Combination dies and pin	210A
EO-NIROMONT Liquid lubricant in a brush-in-cap can (250 cc)	EONIROMONTAPPLICATOR