




## Instant Connection of 2 up to 4 High hydraulic Flow or electric lines



### Hydraulic specification



|                    |             |
|--------------------|-------------|
| Type               | NS          |
| Size               | 3/4"        |
| Quantity           | 2 to 4      |
| Operating Flow     | 110 L/min   |
| Operating Pressure | 350 bar     |
| Pressure Drop      | 1.20 bar    |
| End Termination    | BSP         |
| Fitting            | Female      |
| O'ring             | NBR / Viton |



|                    |             |
|--------------------|-------------|
| Type               | NS          |
| Size               | 1/2"        |
| Quantity           | 1 to 2      |
| Operating Flow     | 50 L/min    |
| Operating Pressure | 350 bar     |
| Pressure Drop      | 2.50 bar    |
| End Termination    | BSP         |
| Fitting            | Female      |
| O'ring             | NBR / Viton |

### Electric specification



|                     |                            |
|---------------------|----------------------------|
| Operating Intensity | 6 x 10A max<br>4 x 25A max |
| Operating Voltage   | 0V/355V                    |
| Temperature range   | - 55°C + 125°C             |
| Treatment           | Copper Nickel-Gold         |
| Fitting             | To screw                   |

Mach Connectors reserves the right to modify characteristics, equipment and prices of the models shown without prior notice. This document is under no circumstances legally binding. No part of this publication may be reproduced.

19 rue de Rennes • BP 83221 • F-35690 ACIGNÉ • tél : +33 (0)2 99 62 28 77 • mail : [contact@machconnectors.com](mailto:contact@machconnectors.com) • fax +33 (0)2 99 62 28 78  
MAILLEUX • s.a.s au capital de 5 116 800 € • rcs rennes 639 200 260 • siret 639 200 260 00029 • ape 292D • Mach Connectors © 2006 copyright

**Mach**  
connectors  
[machconnectors.com](http://machconnectors.com)