SRI42

No-Skive Multispiral

ISO 18752 type CC
ISO 3862 / EN 856 4SP (size 8)
ISO 3862 / EN 856 4SH (size 12, 16)



- *No-Skive* hose construction
- High performance
- Reinforcement of four or six spiral high-tensile steel wire
- Constant working pressure of 42.0 MPa
- Temperature range up to +120 °C

Primary Applications

General high pressure hydraulic applications

Applicable Specifications

ISO 18752 type CC
ISO 3862 / EN 856 4SP (size 8)
ISO 3862 / EN 856 4SH (size 12, 16)

Construction

Inner tube: Synthetic rubber
Reinforcement: Four or six spiral high-tensile steel wire
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +120 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Hydraulic fluids on a mineral-oil basis, water-glycol and lubricating oils, air and water. For air and gas applications with a pressure exceeding 1.7 MPa, the cover must be pin-pricked. Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series


All sizes



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
SRI42-8	12	1/2	-8	12.7	21.1	42.0	6000	168.0	24000	180	0.67
SRI42-10	16	5/8	-10	15.9	23.8	42.0	6000	168.0	24000	210	0.80
SRI42-12	19	3/4	-12	19.1	28.1	42.0	6000	168.0	24000	265	1.16
SRI42-16	25	1	-16	25.4	35.7	42.0	6000	168.0	24000	300	1.74
SRI42-20	31	1 1/4	-20	31.8	45.4	42.0	6000	168.0	24000	400	2.89

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark