



Tube to Male Pipe

Single/Double Ferrule
Instrument Compression
Fittings

NPT Male 45° Elbow For metric tube



| CPI™ PART NO. | A-LOK® PART NO. | INTER- CHANGES WITH | MILLIMETERS | | | | | | |
|------------------|--------------------|---------------------------|--------------|--------------------|------|------|------|------|----------|
| | | | TUBE O.D. | NPT PIPE THREAD | C | L | P | R | W HEX |
| VBZ 6-1/8 | M6MVEL1/8N | - | 6 | 1/8 | 17,7 | 16,0 | 16,8 | 9,5 | 14,0 |
| VBZ 6-1/4 | M6MVEL1/4N | - | 6 | 1/4 | 17,7 | 16,0 | 21,8 | 14,3 | 14,0 |
| VBZ 8-1/8 | M8MVEL1/8N | - | 8 | 1/8 | 18,6 | 16,8 | 16,8 | 9,5 | 14,0 |
| VBZ 10-1/4 | M10MVEL1/4N | - | 10 | 1/4 | 19,5 | 19,0 | 24,1 | 14,3 | 19,0 |
| VBZ 12-3/8 | M12MVEL3/8N | - | 12 | 3/8 | 22,0 | 19,0 | 24,1 | 14,3 | 19,0 |
| VBZ 12-1/2 | M12MVEL1/2N | - | 12 | 1/2 | 22,0 | 20,6 | 29,7 | 19,0 | 22,0 |
| VBZ 16-1/2 | M16MVEL1/2N | - | 16 | 1/2 | 22,0 | 20,6 | 29,7 | 19,0 | 22,0 |

NOTE: C dimension is typical finger-tight.

Dimensions for reference only, subject to change.