


Components

Single/Double Ferrule
Instrument Compression
Fittings

Tube Nut For fractional tube



| CPI™ PART NO. | A-LOK® PART NO. | INTER- CHANGES WITH | INCHES | | |
|------------------|--------------------|---------------------------|--------------|------|----------|
| | | | TUBE O.D. | A | W HEX |
| 1 BZ | 1NU1 | 102-1 | 1/16 | 0.31 | 5/16 |
| 2 BZ | 2NU2 | 202-1 | 1/8 | 0.47 | 7/16 |
| 3 BZ | 3NU3 | 302-1 | 3/16 | 0.47 | 1/2 |
| 4 BZ | 4NU4 | 402-1 | 1/4 | 0.50 | 9/16 |
| 5 BZ | 5NU5 | 502-1 | 5/16 | 0.53 | 5/8 |
| 6 BZ | 6NU6 | 602-1 | 3/8 | 0.56 | 11/16 |
| 8 BZ | 8NU8 | 812-1 | 1/2 | 0.69 | 7/8 |
| 10 BZ | 10NU10 | 1012-1 | 5/8 | 0.69 | 1 |
| 12 BZ | 12NU12 | 1212-1 | 3/4 | 0.69 | 1-1/8 |
| 14 BZ | 14NU14 | 1412-1 | 7/8 | 0.69 | 1-1/4 |
| 16 BZ | 16NU16 | 1612-1 | 1 | 0.81 | 1-1/2 |
| 20 BZ | 20NU20 | 2012-1 | 1-1/4 | 1.25 | 1-7/8 |
| 24 BZ | 24NU24 | 2412-1 | 1-1/2 | 1.50 | 2-1/4 |
| 32 BZ | 32NU32 | 3212-1 | 2 | 2.06 | 3 |

Dimensions for reference only, subject to change.

NOTE: All size 20, 24 and 32 silver plated nuts should have a system compatible lube (Permatex Anti-seize – Parker Catalog 4290-INST) or equivalent applied to the fitting body threads and the inside back of nuts. This will minimize the effort required to assemble the fitting properly.