




# Brass Adaptors

## 0123 Tailpiece Adaptor for Rubber Hose, Male BSPT Thread

Brass		ØD	ØD1	C		F	L	L1	ØT	kg
4		6	R1/8	0123 04 10		10	34	22.5	3.3	0.008
		8	R1/8	0123 06 10		10	34	22.5	5	0.009
7		9	R1/8	0123 07 10		10	34	22.5	5	0.009
		9	R1/4	0123 07 13		14	38.5	22.5	6	0.018
		9	R3/8	0123 07 17		17	39	22.5	6	0.023
10		12.2	R1/8	0123 10 10		13	34	22.5	5	0.014
		12.2	R1/4	0123 10 13		14	38.5	22.5	7	0.020
		12.2	R3/8	0123 10 17		17	39	22.5	9.5	0.023
12		14	R3/8	0123 12 17		17	46	29.5	11	0.026
		15	R1/4	0123 13 13		17	45.5	29.5	7	0.026
13		15	R3/8	0123 13 17		17	46	29.5	11	0.027
		15	R1/2	0123 13 21		22	50.5	29.5	12	0.045
		18.5	R3/8	0123 16 17		19	54.5	38	11	0.040
16		18.5	R1/2	0123 16 21		22	59	38	14	0.054
		18.5	R3/4	0123 16 27		27	62	38	15	0.084
		21.5	R3/8	0123 19 17		22	54.5	38	11	0.046
19		21.5	R1/2	0123 19 21		22	59	38	14	0.056
		21.5	R3/4	0123 19 27		27	62	38	18	0.082
		26.7	R3/4	0123 25 27		27	62	38	18	0.079
25	27	R1	0123 25 34		36	65	38	24	0.124	
32	34.5	R1	0123 32 34		36	70	43	24	0.141	



# Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

## Product Advantages

### Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution  
 Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium  
 Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium  
 Stainless steel for corrosive environments  
 BSPP, BSPT, NPT and metric threads

### Performance

Robust design  
 Suitable for low to high pressure, depending on configuration and material  
 Forged shapes for mechanical strength



Packaging  
 Robotics  
 Textile  
 Pneumatics  
 Automotive Process  
 Food Process

Applications

## Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer  -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C