


# Brass Adaptors

## 0165

### Barb Connector for Flexible Tubing



Brass



| ØD1 | ØD2 |                            | ØD3  | L    | L1 | ØT<br>min | kg    |
|-----|-----|----------------------------|------|------|----|-----------|-------|
| 4   | 4   | <a href="#">0165 04 06</a> | 4.3  | 30   | 15 | 2         | 0.002 |
| 5   | 4   | <a href="#">0165 05 06</a> | 4.3  | 30   | 15 | 2         | 0.010 |
|     | 4   | <a href="#">0165 06 06</a> | 4.3  | 30   | 15 | 2         | 0.003 |
| 6   | 6   | <a href="#">0165 06 08</a> | 6.4  | 30   | 15 | 4         | 0.004 |
|     | 8   | <a href="#">0165 06 10</a> | 8.4  | 30   | 15 | 4         | 0.004 |
|     | 6   | <a href="#">0165 08 08</a> | 6.4  | 32.5 | 15 | 4         | 0.006 |
| 8   | 8   | <a href="#">0165 08 10</a> | 8.4  | 32.5 | 15 | 6         | 0.006 |
|     | 10  | <a href="#">0165 08 12</a> | 10.7 | 37.5 | 20 | 8         | 0.009 |
|     | 8   | <a href="#">0165 10 10</a> | 8.4  | 35.5 | 15 | 6         | 0.008 |
| 10  | 10  | <a href="#">0165 10 12</a> | 10.7 | 40.5 | 20 | 8         | 0.010 |
|     | 12  | <a href="#">0165 10 14</a> | 12.7 | 40.5 | 20 | 8         | 0.012 |
| 12  | 10  | <a href="#">0165 12 12</a> | 10.7 | 40.5 | 20 | 8         | 0.011 |
|     | 12  | <a href="#">0165 12 14</a> | 12.7 | 40.5 | 20 | 10        | 0.013 |
| 14  | 12  | <a href="#">0165 14 14</a> | 12.7 | 42.5 | 20 | 10        | 0.014 |
| 15  | 13  | <a href="#">0165 15 16</a> | 13.7 | 42.5 | 20 | 11        | 0.016 |
| 16  | 13  | <a href="#">0165 16 16</a> | 13.7 | 44   | 20 | 11        | 0.018 |

### Assembly: Barb Connectors

Our barb connectors 0122 and 0165 are designed to be used with different types of hose. They are secured using the nut and olive provided with the fitting.

