


Nickel-Plated Brass Adaptors

0191 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

ØD	ØD1	C		E	F	K	L	kg
4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
7	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
	9	G1/2	0191 07 21	11	27	7	29.5	0.065
10	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
	12.2	G1/2	0191 10 21	11	27	7	29.5	0.061
13	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
	15.2	G1/2	0191 13 21	11	27	7	29.5	0.058
16	18.5	G1/2	0191 16 21	11	27	7	36.5	0.067

Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging
Robotics
Textile
Pneumatics
Automotive Process
Food Process

Applications

Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C