




Brass Plugs

0201 Hex Head Plug with Collar, Male BSPP and Metric Thread

	Brass 	<div>  </div>						kg
		C	E	F	G	H1	H2	
		M16x1.5	0201 75 00	10	17	22	6.5	5
		M18x1.5	0201 78 00	10	17	24	7	5
		M20x1.5	0201 80 00	10	17	26	7.5	5
		M22x1.5	0201 82 00	10	22	30	7.5	5
		M24x1.5	0201 83 00	10	22	32	7.5	5
		M24x2	0201 92 00	10	22	32	7.5	5
		M30x2	0201 88 00	11	27	38	8.5	6
		G3/8	0201 17 00	10	17	21.7	6.5	4.5
		G1/2	0201 21 00	10	22	26.7	7.5	5
		G3/4	0201 27 00	11	22	31.7	8.5	6
		G1	0201 34 00	11	27	39.7	8.5	6
		G1¼	0201 42 00	12	30	49.7	10	7

Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging
Robotics
Textile
Pneumatics
Automotive Process
Food Process

Applications

Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C