




Brass Plugs

0202

Internal Hexagon Head Plug with Collar, Male Metric Thread

	<p>Brass</p> 	C		E	F	G	H	H1	kg
		M12x1	0202 65 00	9	6	17	11	8	0.009
		M12x1.25	0202 66 00	9	6	17	11	8	0.009
		M14x1.5	0202 71 00	10	6	19	13	10	0.015
		M16x1.5	0202 75 00	10	8	22	13	10	0.020
		M18x1.5	0202 78 00	10	10	24	13	10	0.022
		M20x1.5	0202 80 00	10	12	26	13	10	0.025
		M22x1.5	0202 82 00	10	12	30	13	10	0.034
		M27x2	0202 86 00	11	17	35	15	11	0.053
		M30x2	0202 88 00	11	19	38	15	11	0.062
		Parallel metric threads, ISO standard NFE 03-054							

Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging
Robotics
Textile
Pneumatics
Automotive Process
Food Process

Applications

Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C