




Brass Plugs

0209 Square Head Plug, Male BSPT Thread

	<p>Brass</p> 	C		E1	E2 min	E2 max	G	H	J	kg
		R1/8	0209 10 00	6	3.1	4.9	9.7	16	6	0.007
		R1/4	0209 13 00	8	4.7	7.3	13.2	18	8	0.014
		R3/8	0209 17 00	10	5.1	7.7	16.7	20	10	0.025
		R1/2	0209 21 00	11	6.4	10	21	22	13	0.047
		R3/4	0209 27 00	15	7.7	11.3	26.4	28	17	0.097
		R1	0209 34 00	18	8.1	12.7	33.2	32	19	0.170
		Conforms to DIN 906 Thread: EN 10226-1								

Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging
Robotics
Textile
Pneumatics
Automotive Process
Food Process

Applications

Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C