


# Steel Plugs

## 0210 Hex Head Plug, Male BSPP and Metric Thread



Steel



C		E	F	G	H	kg
M8x1.25	<a href="#">0210 57 00</a>	8	14	12	15	0.010
M10x1	<a href="#">0210 60 00</a>	8	14	14	15	0.013
M12x1.25	<a href="#">0210 66 00</a>	11	17	17	18	0.021
G1/8	<a href="#">0210 10 00</a>	8	14	14	15	0.012
M14x1.25	<a href="#">0210 70 00</a>	11	19	19	20	0.032
G1/4	<a href="#">0210 13 00</a>	12	19	18	21	0.031
G3/8	<a href="#">0210 17 00</a>	12	22	22	21	0.046
G1/2	<a href="#">0210 21 00</a>	14	27	26	24	0.078
G3/4	<a href="#">0210 27 00</a>	16	32	32	27	0.134
G1	<a href="#">0210 34 00</a>	18	41	39	33	0.269
G1¼	<a href="#">0210 42 00</a>	20	50	49	35	0.441

Profile of head undercut conforms to DIN 3852-1; form D/E  
 BSPP threads, ISO 228-1  
 Parallel metric threads, NFE 03-054

# Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

## Product Advantages

### Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

### Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging  
Robotics  
Textile  
Pneumatics  
Automotive Process  
Food Process

Applications

## Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer  -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C