







# Steel Plugs

## 0216 Hex Head Plug, Male BSPT Thread

	<p>Steel</p> 	<b>C</b>		<b>F</b>	<b>H</b>	<b>kg</b>
		R1/8	<a href="#">0216 10 00</a>	13	16	0.012
		R1/4	<a href="#">0216 13 00</a>	17	19	0.023
		R3/8	<a href="#">0216 17 00</a>	19	21	0.038
		R1/2	<a href="#">0216 21 00</a>	22	23	0.060
BSPT thread conforms to EN 10226-1						

## 0216 Hex Head Plug, Male NPT Thread

	<p>Steel</p> 	<b>C</b>		<b>F</b>	<b>H</b>	<b>kg</b>
		NPT1/8	<a href="#">0216 11 00</a>	13	16	0.012
		NPT1/4	<a href="#">0216 14 00</a>	17	19	0.024
		NPT3/8	<a href="#">0216 18 00</a>	19	21	0.038
		NPT1/2	<a href="#">0216 22 00</a>	22	23	0.060

# Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

## Product Advantages

### Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution  
 Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium  
 Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium  
 Stainless steel for corrosive environments  
 BSPP, BSPT, NPT and metric threads

### Performance

Robust design  
 Suitable for low to high pressure, depending on configuration and material  
 Forged shapes for mechanical strength



Packaging  
 Robotics  
 Textile  
 Pneumatics  
 Automotive Process  
 Food Process

Applications

## Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer  -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C