




Nickel-Plated Brass Adaptors

0906

Increaser, Male BSPP and Metric/Female BSPP Thread

	Nickel-plated brass	C1	C2		E1	E2	F	L	kg
		M5x0.8	G1/8	0906 10 19	4	8	14	10	0.009
			G1/8	0906 00 10	6	8	14	10	0.011
		G1/8	G1/4	0906 10 13	6	11	17	14	0.016
			G3/8	0906 10 17	6	11.5	22	14.5	0.029
		G1/4	G1/4	0906 00 13	8	11	17	14	0.020
			G3/8	0906 13 17	8	11.5	22	14.5	0.032
		G1/2	G1/2	0906 13 21	8	15	27	18	0.037
			G3/8	0906 00 17	9	11.5	22	14.5	0.034
		G3/8	G1/2	0906 17 21	9	14	27	18	0.038
			G1/2	0906 00 21	10	14	27	18	0.054

Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution
 Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium
 Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium
 Stainless steel for corrosive environments
 BSPP, BSPT, NPT and metric threads

Performance

Robust design
 Suitable for low to high pressure, depending on configuration and material
 Forged shapes for mechanical strength



Packaging
 Robotics
 Textile
 Pneumatics
 Automotive Process
 Food Process

Applications

Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C