




# Nickel-Plated Brass Adaptors

## 0908 Equal Cross, Female BSPP Thread

|  | Nickel-plated brass |   |  |    |      |    |       |  |
|---|---------------------|---|---|----|------|----|-------|--|
|   | C                   |  | E   | G  | H    | J  | kg    |  |
|   | G1/8                | 0908 00 10  | 8   | 13 | 21   | 10 | 0.038 |  |
|   | G1/4                | 0908 00 13  | 11  | 17 | 25.5 | 13 | 0.073 |  |
|   | G3/8                | 0908 00 17  | 11.5  | 21 | 28   | 17 | 0.107 |  |
|   | G1/2                | 0908 00 21  | 14  | 26 | 33.5 | 21 | 0.189 |  |

# Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

## Product Advantages

### Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility:  
brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance:  
nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

### Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging  
Robotics  
Textile  
Pneumatics  
Automotive Process  
Food Process

Applications

## Technical Characteristics

| Products            | Adaptors and Plugs   |                     |  |  | Manifolds          |
|---------------------|--|---------------------|--|--|--------------------|
| Component Materials | Brass  | Nickel-plated brass | Stainless steel 316L   | Steel  | Anodised aluminium |
| Working Pressure    | 1/8" to 1/2": 200 bar<br>3/4" and 1": 150 bar<br>1 1/4" to 2": 100 bar, without sealing washer | 60 bar              | 1/8" to 1/2": 200 bar<br>3/4" and 1": 150 bar<br>1 1/4" to 2": 100 bar, without sealing washer | 1/8" to 1/2": 200 bar<br>3/4" and 1": 150 bar<br>1 1/4" to 2": 100 bar, without sealing washer | 20 bar             |
| Working Temperature | -40°C to +150°C without sealing washer<br>-20°C to +80°C with sealing washer                   | -10°C to +80°C      | -20°C to +180°C  | -10°C to +80°C   | -10°C to +80°C     |