


# Stud Fittings

## 3101 Stud Fitting, Male BSPP and Metric Thread



Nickel-plated brass, NBR



	ØD	C		E	F1	F2	H	kg
3	M3x0.5	<b>3101 03 09*</b>		2.5	8	-	12.5	0.003
	M5x0.8	<b>3101 03 19</b>		3.5	8	2.5	12.5	0.004
4	M3x0.5	<b>3101 04 09*</b>		2.5	8	-	14.5	0.003
	M5x0.8	<b>3101 04 19</b>		3	9	2.5	14	0.003
4	M7x1	<b>3101 04 55</b>		5	10	2.5	14	0.004
	G1/8	<b>3101 04 10</b>		5	13	3	11.5	0.007
4	G1/4	<b>3101 04 13</b>		5.5	16	3	10.5	0.011
	M5x0.8	<b>3101 06 19</b>		3	11	2.5	16	0.005
4	M7x1	<b>3101 06 55</b>		5	10	3	16	0.006
	M10x1	<b>3101 06 60</b>		5	13	4	13	0.007
6	M12x1.5	<b>3101 06 67</b>		5.5	15	4	13	0.009
	G1/8	<b>3101 06 10</b>		5	13	4	13	0.007
6	G1/4	<b>3101 06 13</b>		5.5	16	4	12.5	0.011
	G3/8	<b>3101 06 17</b>		5.5	20	4	13	0.020
6	G1/2	<b>3101 06 21</b>		7.5	24	4	20	0.040
	M10x1	<b>3101 08 60</b>		5	13	5	21	0.011
6	M12x1.5	<b>3101 08 67</b>		5.5	15	5	21	0.015
	G1/8	<b>3101 08 10</b>		4.5	13	5	20.5	0.011
8	G1/4	<b>3101 08 13</b>		5.5	16	6	19.5	0.016
	G3/8	<b>3101 08 17</b>		5.5	20	6	18	0.022
8	G1/2	<b>3101 08 21</b>		7.5	24	6	16.5	0.039
	G1/4	<b>3101 10 13</b>		5.5	16	7	23	0.018
10	G3/8	<b>3101 10 17</b>		5.5	20	8	19.5	0.021
	G1/2	<b>3101 10 21</b>		7.5	24	8	18.5	0.033
10	G1/4	<b>3101 12 13</b>		5.5	19	7	27.5	0.027
	G3/8	<b>3101 12 17</b>		5.5	20	9	27	0.029
12	G1/2	<b>3101 12 21</b>		7	24	11	22.5	0.035
	G3/8	<b>3101 14 17</b>		5.5	22	9	29.5	0.041
14	G1/2	<b>3101 14 21</b>		7	24	11	28	0.047
	G3/8	<b>3101 16 17</b>		7.5	27	9	32.5	0.061
16	G1/2	<b>3101 16 21</b>		9	27	12	32.5	0.066

\* Bi-material O ring seal