


Stud Fittings

3103 Stud Run Tee, BSPT Thread



Technical polymer, nickel-plated brass, NBR



	ØD	C		F	G	H	H1	L	kg
4	R1/8	3103 04 10		10	8.5	23.5	9	14.5	0.006
	R1/4	3103 04 13		14	8.5	24	9.5	14.5	0.015
6	R1/8	3103 06 10		10	10.5	27.5	10	17.5	0.007
	R1/4	3103 06 13		14	10.5	28	10.5	17.5	0.016
8	R1/8	3103 08 10		10	13.5	35	12	23	0.009
	R1/4	3103 08 13		14	13.5	34	11	23	0.015
	R3/8	3103 08 17		17	13.5	34	11	23	0.020
10	R1/4	3103 10 13		15	16	40.5	14	26.5	0.017
	R3/8	3103 10 17		17	16	40.5	14	26.5	0.022
	R1/2	3103 10 21		21	16	40.5	14	26.5	0.033
12	R1/4	3103 12 13		15	19	46.5	15.5	31	0.028
	R3/8	3103 12 17		17	19	46.5	15.5	31	0.026
14	R1/2	3103 12 21		21	19	46.5	15.5	31	0.037
	R3/8	3103 14 17		20	22	55	19.5	35.5	0.037
	R1/2	3103 14 21		24	22	52.5	17.5	35.5	0.048
16	R3/8	3103 16 17		27	27	78	27	38.5	0.126
	R1/2	3103 16 21		27	27	78	27	38.5	0.124

Pre-coated thread
The body swivels for positioning purposes.