


Stud Fittings

3129 Extended Stud Elbow, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



	ØD	C		F	G	H	L	kg
4	R1/8	3129 04 10		10	8.5	23	19	0.008
	R1/4	3129 04 13		14	8.5	23.5	19	0.018
6	R1/8	3129 06 10		10	10.5	27	22.5	0.010
	R1/4	3129 06 13		14	10.5	27.5	22.5	0.020
8	R1/8	3129 08 10		13	13.5	34.5	29.5	0.018
	R1/4	3129 08 13		14	13.5	32.5	29.5	0.022
	R3/8	3129 08 17		17	13.5	33	29.5	0.032
10	R1/4	3129 10 13		15	16	39.5	34.5	0.031
	R3/8	3129 10 17		17	16	39.5	34.5	0.041
	R1/2	3129 10 21		21	16	39.5	34.5	0.060
12	R1/4	3129 12 13		19	19	45.5	40.5	0.035
	R3/8	3129 12 17		19	19	45.5	40.5	0.051
	R1/2	3129 12 21		21	19	45.5	40.5	0.065
14	R3/8	3129 14 17		21	22	51.5	46.5	0.064
	R1/2	3129 14 21		21	22	51.5	46.5	0.070

Pre-coated thread
The body swivels for positioning purposes.

Parker Legris offers the solution to enable many types of configuration options.

