


# Stud Fittings

## 3133 45° Elbow, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR



	ØD	C		E	F	G	H	L	kg
4	M5x0.8	<a href="#">3133 04 19</a>		3.5	8	9	23	13	0.003
	G1/8	<a href="#">3133 04 10</a>		4.5	13	9	20.5	13	0.006
6	M5x0.8	<a href="#">3133 06 19</a>		3.5	8	11	28	14.5	0.003
	G1/8	<a href="#">3133 06 10</a>		4.5	13	11	24	14.5	0.006
8	G1/4	<a href="#">3133 06 13</a>		5.5	16	11	24	14.5	0.011
	G1/8	<a href="#">3133 08 10</a>		4.5	13	13.5	31	19.5	0.011
8	G1/4	<a href="#">3133 08 13</a>		5.5	16	13.5	29	19.5	0.012
	G3/8	<a href="#">3133 08 17</a>		5.5	20	13.5	29	19.5	0.020
10	G1/4	<a href="#">3133 10 13</a>		5.5	16	16	35	23	0.014
	G3/8	<a href="#">3133 10 17</a>		5.5	20	16	33.5	23	0.017
12	G1/2	<a href="#">3133 10 21</a>		7	24	16	33.5	23	0.026
	G1/4	<a href="#">3133 12 13</a>		5.5	16	19	40.5	26	0.016
12	G3/8	<a href="#">3133 12 17</a>		5.5	20	19	39	26	0.019
	G1/2	<a href="#">3133 12 21</a>		7	24	19	39	26	0.028

The body swivels for positioning purposes.  
This model prevents distortion of the tube.