

Stud Fittings

LF 3000®

Push-In Fittings

3169

Extended Stud Elbow, Male BSPP and Metric Thread

Technical polymer, nickel-plated
brass, NBR

Technical drawing of the fitting showing dimensions: L (length), H (height), E (height of the base), ØG (outer diameter of the fitting), ØD (outer diameter of the base), OF (offset), and C (thread length).

	ØD	C		E	F	G	H	L	kg
4	M5x0.8	3169 04 19		3.5	8	8.5	23	19	0.005
	M7x1	3169 04 55		4.5	10	8.5	22.5	19	0.008
	G1/8	3169 04 10		5	13	8.5	22.5	19	0.009
	G1/4	3169 04 13		5.5	16	8.5	22.5	19	0.014
6	M5x0.8	3169 06 19		3.5	10	10.5	27.5	23	0.008
	M7x1	3169 06 55		4.5	10	10.5	26	23	0.012
	G1/8	3169 06 10		5	13	10.5	27	23	0.011
	G1/4	3169 06 13		5.5	16	10.5	27	23	0.016
8	G1/8	3169 08 10		5	13	13.5	36	29.5	0.018
	G1/4	3169 08 13		5.5	16	13.5	33	29.5	0.020
	G3/8	3169 08 17		5.5	20	13.5	33	29.5	0.028
	G1/4	3169 10 13		5.5	16	16	40.5	34.5	0.029
10	G3/8	3169 10 17		5.5	20	16	40.5	34.5	0.037
	G1/2	3169 10 21		7.5	24	16	40.5	34.5	0.042
	G1/4	3169 12 13		5.5	19	19	44.5	40.5	0.049
12	G3/8	3169 12 17		5.5	20	19	42	40.5	0.040
	G1/2	3169 12 21		7.5	24	19	42	40.5	0.049
	G3/8	3169 14 17		5.5	22	22	51	46.5	0.059
14	G1/2	3169 14 21		7.5	24	22	48.5	46.5	0.063
	G3/8	3169 16 17		7.5	27	27	82.5	52	0.220
16	G1/2	3169 16 21		9	27	27	82.5	52	0.206

The body swivels for positioning purposes.

The body swivels for positioning purposes.