

Stud Fittings

3175 Stud Fitting, Male BSPT Thread

Nickel-plated brass, NBR		ØD	C		F1	F2	H	kg
4			R1/8	3175 04 10	10	3	9.5	0.005
			R1/4	3175 04 13	14	3	6.5	0.012
			R3/8	3175 04 17	17	3	8	0.024
6			R1/8	3175 06 10	10	4	11.5	0.005
			R1/4	3175 06 13	14	4	8.5	0.011
			R3/8	3175 06 17	17	4	8.5	0.022
8			R1/2	3175 06 21	21	4	9	0.043
			R1/8	3175 08 10	13	5	20	0.011
			R1/4	3175 08 13	14	6	17	0.014
10			R3/8	3175 08 17	17	6	13	0.021
			R1/2	3175 08 21	21	6	12	0.040
			R1/8	3175 10 10	16	5	22.5	0.017
12			R1/4	3175 10 13	16	7	20	0.017
			R3/8	3175 10 17	17	8	16.5	0.019
			R1/2	3175 10 21	21	8	14	0.037
14			R1/4	3175 12 13	19	7	26.5	0.029
			R3/8	3175 12 17	19	9	24	0.028
			R1/2	3175 12 21	21	10	19.5	0.036
16			R3/8	3175 14 17	22	9	28.5	0.043
			R1/2	3175 14 21	24	10	23.5	0.047
			R3/8	3175 16 17	27	9	32.5	0.068
			R1/2	3175 16 21	27	12	32.5	0.079

Pre-coated thread

3175 Stud Fitting, Male NPT Thread

Nickel-plated brass, NBR		ØD	C		F1	F2	H	kg
6			NPT1/8	3175 06 11	11	4	11.5	0.006
			NPT1/4	3175 06 14	14	4	8.5	0.012
10			NPT1/4	3175 10 14	16	7	20	0.018
			NPT3/8	3175 10 18	18	8	16.5	0.023
12			NPT1/2	3175 10 22	22	8	14	0.037
			NPT3/8	3175 12 18	19	9	24	0.030
			NPT1/2	3175 12 22	22	10	19.5	0.037

Pre-coated thread

3175 Stud Fitting, Male NPT Thread

Inch

Nickel-plated brass, NBR		ØD	C		F1	F2	H	kg
1/8			NPT1/8	3175 53 11	11	2	7.2	0.006
			NPT1/4	3175 53 14	14	2	8	0.016
1/4			NPT1/8	3175 56 11	11	4	11.9	0.006
			NPT1/4	3175 56 14	14	4	9.4	0.013
			NPT3/8	3175 56 18	18	5	7.6	0.024
3/8			NPT1/8	3175 60 11	16	4	22.7	0.019
			NPT1/4	3175 60 14	16	7	20.5	0.019
			NPT3/8	3175 60 18	18	7	17.5	0.026
1/2			NPT3/8	3175 62 18	22	9.5	25.9	0.047
			NPT1/2	3175 62 22	24	9.5	22.1	0.064

Pre-coated thread

Other products are available upon request; please do not hesitate to consult us.


Stud Fittings

3175 Stud Fitting, Male BSPT Thread

Inch



Nickel-plated brass, NBR



ØD	C		F1	F2	H	kg
1/8	R1/8	3175 53 10	11	3	8.5	0.005
3/16	R1/8	3175 55 10	11.1	3.2	15.5	0.009
	R1/4	3175 55 13	14.3	4	15	0.020
1/4	R1/8	3175 56 10	11	4	12	0.006
	R1/4	3175 56 13	14	4	9.5	0.021
3/8	R1/4	3175 60 13	18	5	7.5	0.017
	R3/8	3175 60 17	13	5	20	0.019
1/2	R1/2	3175 60 21	14	6	16.8	0.061
	R1/4	3175 62 13	22	6	26.9	0.044
1/2	R3/8	3175 62 17	22	7	25.9	0.048
	R1/2	3175 62 21	24	7	20.5	0.049

Pre-coated thread