


# Stud Fittings

LF 3000®  
Push-In Fittings

## 3193 Stud Run Tee, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR



	ØD	C		E	F	G	H	H1	L	kg
4		M5x0.8	<a href="#">3193 04 19</a>	3.5	8	8.5	26	11.5	14.5	0.003
		G1/8	<a href="#">3193 04 10</a>	5	13	8.5	23	8.5	14.5	0.006
		G1/4	<a href="#">3193 04 13</a>	5.5	16	8.5	23	8.5	14.5	0.011
	6		M5x0.8	<a href="#">3193 06 19</a>	3.5	8	10.5	29.5	12.5	17.5
		G1/8	<a href="#">3193 06 10</a>	5	13	10.5	27	10	17.5	0.007
		G1/4	<a href="#">3193 06 13</a>	5.5	16	10.5	27	10	17.5	0.012
	8		G1/8	<a href="#">3193 08 10</a>	4.5	13	13.5	36.5	14	23
		G1/4	<a href="#">3193 08 13</a>	5.5	16	13.5	34.5	12	23	0.014
		G3/8	<a href="#">3193 08 17</a>	5.5	20	13.5	34.5	12	23	0.019
	10		G1/4	<a href="#">3193 10 13</a>	5.5	16	16	42	15.5	26.5
		G3/8	<a href="#">3193 10 17</a>	5.5	20	16	40.5	14	26.5	0.020
		G1/2	<a href="#">3193 10 21</a>	7.5	24	16	40.5	14	26.5	0.029
	12		G1/4	<a href="#">3193 12 13</a>	5.5	16	19	48	17	31
		G3/8	<a href="#">3193 12 17</a>	5.5	20	19	46.5	15.5	31	0.024
		G1/2	<a href="#">3193 12 21</a>	7	24	19	46.5	15.5	31	0.038
	14		G3/8	<a href="#">3193 14 17</a>	5.5	20	22	56.5	21.5	35.5
		G1/2	<a href="#">3193 14 21</a>	7	24	22	51	16	35.5	0.120
		G3/8	<a href="#">3193 16 17</a>	7.5	27	27	79.5	41	38.5	0.121
	16		G1/2	<a href="#">3193 16 21</a>	9	27	27	79.5	41	38.5

The body swivels for positioning purposes.