


# Anodised Aluminium Manifolds


**3311**

Manifold, Female BSPP and Metric Thread



Treated aluminium



C1	C2		Number of Outlets	H	H1	H2	K	L	L1	N	ØT	kg
G1/8	M5x0.8	<a href="#">3311 19 10 07</a>	7	3.5	20	8.5	15	95	80	11	4.4	0.067
	G1/8	<a href="#">3311 10 13 02</a>	2	4.5	30	15	20	61	50	30	5	0.079
	G1/8	<a href="#">3311 10 13 03</a>	3	4.5	30	15	20	91	30	30	5	0.121
G1/4	G1/8	<a href="#">3311 10 13 04</a>	4	4.5	30	15	20	121	60	30	5	0.165
	G1/8	<a href="#">3311 10 13 05</a>	5	4.5	30	15	20	151	90	30	5	0.209
	G1/8	<a href="#">3311 10 13 06</a>	6	4.5	30	15	20	181	120	30	5	0.244
G1/4	G1/4	<a href="#">3311 13 17 02</a>	2	5.5	30	11	20	74	61	36	6.5	0.076
	G1/4	<a href="#">3311 13 17 03</a>	3	6	30	11	20	110	36	36	6.5	0.121
	G1/4	<a href="#">3311 13 17 04</a>	4	6	30	11	20	146	72	36	6.5	0.144
G3/8	G1/4	<a href="#">3311 13 17 05</a>	5	6	30	11	20	182	108	36	6.5	0.212
	G1/4	<a href="#">3311 13 17 06</a>	6	6	30	11	20	218	144	36	6.5	0.265

# Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

## Product Advantages

### Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

### Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging  
Robotics  
Textile  
Pneumatics  
Automotive Process  
Food Process

Applications

## Technical Characteristics

Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C