



# Self-Sealing and Oscillating Fittings

LF 3000®

Push-In Fittings

## 3391 Self-Sealing Stud Fitting, Male BSPP Thread

|  | Nickel-plated brass, NBR                                                          |                                                                                   |  |    |      |            |     |    |      |     |    |     |       |  |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----|------|------------|-----|----|------|-----|----|-----|-------|--|
|                                                                                   |  |  |                                                                                   | ØD | C    | E          | F   | H  | H1   | H2  | ØT | kg  |       |  |
|                                                                                   |                                                                                   |                                                                                   |                                                                                   | 4  | G1/8 | 3391 04 10 | 5   | 13 | 18   | 7.5 | 6  | 5   | 0.017 |  |
|                                                                                   |                                                                                   |                                                                                   |                                                                                   | 6  | G1/8 | 3391 06 10 | 5   | 14 | 19.5 | 9   | 6  | 7.5 | 0.019 |  |
|                                                                                   |                                                                                   |                                                                                   |                                                                                   | 8  | G1/8 | 3391 08 10 | 5   | 14 | 29.5 | 10  | 6  | 7.5 | 0.025 |  |
|                                                                                   |                                                                                   |                                                                                   |                                                                                   |    | G1/4 | 3391 08 13 | 5.5 | 16 | 25.5 | 11  | 8  | 9   | 0.032 |  |
|                                                                                   |                                                                                   |                                                                                   |                                                                                   | 10 | G3/8 | 3391 10 17 | 5.5 | 20 | 27.5 | 13  | 11 | 10  | 0.055 |  |
| Maximum working pressure: 10 bar                                                  |                                                                                   |                                                                                   |                                                                                   |    |      |            |     |    |      |     |    |     |       |  |