


Stud Fittings

3601 Stud Fitting, Male BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM	ØD	C		E	F1	F2	H	kg
4	M5x0.8	3601 04 19			3.5	10	2.5	15.5	0.006
	M6x1	3601 04 52			4.5	10	3	16	0.006
	M8x1	3601 04 56			5	11	3	14.5	0.007
	G1/8	3601 04 10			5.5	13	3	14.5	0.009
6	G1/4	3601 04 13			6.5	16	3	14.5	0.015
	M5x0.8	3601 06 19			3.5	13	2.5	19	0.010
	M10x1	3601 06 60			5.5	13	4	17.5	0.011
	G1/8	3601 06 10			5.5	13	4	17.5	0.011
8	G1/4	3601 06 13			6.5	16	4	17	0.015
	G1/8	3601 08 10			5.5	16	5	20	0.014
	G1/4	3601 08 13			6.5	16	6	18	0.016
	G3/8	3601 08 17			7.5	20	6	19	0.028
10	G1/4	3601 10 13			6.5	18	7	25	0.025
	G3/8	3601 10 17			7.5	20	8	22.5	0.028
	G1/2	3601 10 21			9	24	8	22.5	0.043
	G1/4	3601 12 13			6.5	20	7	26.5	0.030
12	G3/8	3601 12 17			7.5	20	9	26	0.034
	G1/2	3601 12 21			9	24	10	23.5	0.042
14	G3/8	3601 14 17			7.5	22	9	28	0.038
	G1/2	3601 14 21			9	24	11	26.5	0.045



LF 3600

Related Products

- Polyurethane Tubing
- Polyamide Tubing
- Polyethylene Tubing
- Fluoropolymer Tubing
- Anti-Spark Tubing
- Fireproof PA Tubing
- Brass Flow Control Regulators