




# Stud Fittings

## 3693 Stud Run Tee, Male BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM			<b>ØD</b>	<b>C</b>		<b>E</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>H1</b>	<b>J</b>	<b>L</b>	<b>kg</b>
	4	M5x0.8 G1/8		3693 04 19 3693 04 10	3.5 5.5	10 13	10 10	22.5 20.5	18 18	7 7	23 23	0.019 0.021		
	6	G1/8 G1/4	3693 06 10 3693 06 13	5.5 6.5	13 16	12 12	25 24.5	21.5 21.5	8 8	28 28	0.031 0.035			
	8	G1/8 G1/4	3693 08 10 3693 08 13	5.5 6.5	14 16	15 15	26.5 26.5	23.5 23.5	10 10	31 31	0.041 0.044			
	10	G1/4	3693 10 13	6.5	18	17.5	33	29	12	37.5	0.066			
	12	G3/8	3693 12 17	7.5	20	19.5	36.5	31	15	40.5	0.090			
	14	G1/2	3693 14 21	9	24	21.5	38.5	34	16	45	0.112			

The body swivels for positioning purposes.

LF 3600

Each model has been designed to meet specific requirements: compactness due to small overall dimensions, with inter-connectability for customised configurations.

