


# Stud Fittings

## 3800/3900

### Cartridge



Stainless steel 316L, FKM



| ØD |                            |                            | L    | G  | G1   | H    | H1   | H2   | kg    |
|----|----------------------------|----------------------------|------|----|------|------|------|------|-------|
| 4  | <a href="#">3800 04 00</a> | <a href="#">3900 04 00</a> | 9.8  | 8  | 17   | 8.5  | 8.5  | 11   | 0.006 |
| 6  | <a href="#">3800 06 00</a> | <a href="#">3900 06 00</a> | 12.1 | 10 | 19   | 10.5 | 8.5  | 13.5 | 0.008 |
| 8  | <a href="#">3800 08 00</a> | <a href="#">3900 08 00</a> | 14.8 | 13 | 21   | 12.5 | 8.5  | 16   | 0.012 |
| 10 | <a href="#">3800 10 00</a> | <a href="#">3900 10 00</a> | 17.5 | 15 | 24.5 | 14   | 10.5 | 20   | 0.019 |
| 12 | <a href="#">3800 12 00</a> | <a href="#">3900 12 00</a> | 20   | 17 | 25   | 14.5 | 10.5 | 22.5 | 0.023 |

Cavity dimensions are available in Chapter 2.

3800: collet in stainless steel 303

3900: collet in stainless steel 316L

LF 3800/LF 3900

Stud standpipe 3821, 3921, 3831, 3931 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required

