

Stud Fittings

3803/3903

Stud Run Tee, Male BSPT Thread


Stainless steel 316L, FKM

ØD	C			F	G	H	H1	L	kg
4	R1/8	3803 04 10	3903 04 10	10	10	19	17	22	0.020
	R1/8	3803 06 10	3903 06 10	13	12	22	20	26.5	0.038
6	R1/4	3803 06 13	3903 06 13	14	15	22	20	27	0.035
	R1/8	3803 08 10	3903 08 10	14	15	24	23	31	0.050
8	R1/4	3803 08 13	3903 08 13	14	15	24	23	31	0.055
	R1/4	3803 10 13	3903 10 13	19	17.5	30	29	38	0.070
10	R3/8	3803 10 17	3903 10 17	19	17.5	30	29	38	0.084

The body swivels for positioning purposes.

3803

Stud Run Tee, Male NPT Thread

Stainless steel 316L, FKM



ØD	C		F	G	H	H1	L	kg
4	NPT1/8	3803 04 11	11	10	21	19	25	0.020
6	NPT1/8	3803 06 11	13	12	24	21	27	0.031
	NPT1/4	3803 06 14	14	12	24	21	27.5	0.037
8	NPT1/8	3803 08 11	14	15	26.5	24	30.5	0.050
	NPT1/4	3803 08 14	14	15	26.5	24	30.5	0.048
10	NPT1/4	3803 10 14	19	17.5	31	29.5	37.5	0.084

The body swivels for positioning purposes.

These models enable compact connection for elbow outlets, thus allowing space saving.