


Stud Fittings

3808/3908
Stud Branch Tee, Male BSPT Thread

ØD	C			F	G	H	L/2	kg
								
4	R1/8	3808 04 10	3908 04 10	10	10	23.5	19	0.020
6	R1/8	3808 06 10	3908 06 10	13	12	27.5	24	0.038
	R1/4	3808 06 13	3908 06 13	14	12	27.5	24	0.043
8	R1/8	3808 08 10	3908 08 10	14	15	32	25	0.049
	R1/4	3808 08 13	3908 08 13	14	15	32	25	0.048
10	R3/8	3808 08 17	3908 08 17	19	15	33	25	0.068
	R1/4	3808 10 13	3908 10 13	19	17.5	37.5	31	0.081
	R3/8	3808 10 17	3908 10 17	19	17.5	37.5	31	0.070

The body swivels for positioning purposes.



Stainless steel 316L, FKM


LF 3800/LF 3900

These models enable compact connection for elbow outlets, thus allowing space saving.

Stud Fittings

3808

Stud Branch Tee, Male NPT Thread

	Stainless steel 316L, FKM								
	ØD	C		F	G	H	L/2	kg	
	4	NPT1/8	3808 04 11	11	10	22	19	0.021	
	6	NPT1/8	3808 06 11	13	12.5	30	24	0.031	
		NPT1/4	3808 06 14	14	12.5	30	24	0.044	
	8	NPT1/8	3808 08 11	14	15	34	25	0.042	
		NPT1/4	3808 08 14	14	15	34	25	0.048	
	10	NPT1/4	3808 10 14	19	17.5	40	31	0.069	
		NPT3/8	3808 10 18	19	17.5	40	31	0.084	

The body swivels for positioning purposes.

LF 3800 : full 316L stainless steel (body) with 303 stainless steel collet, FKM seals
LF 3900 : full 316L, FKM seals