

Stud Fittings

3809/3909

Stud Elbow, Male BSPT Thread

	Stainless steel 316L, FKM									
	ØD	C				F	G	H	L	kg
4	R1/8	3809 04 10				10	10	23.5	16.5	0.020
	R1/8	3809 06 10				13	12	27.5	20	0.031
6	R1/4	3809 06 13				14	12	27.5	25	0.036
	R1/8	3809 08 10				14	15	32	25	0.041
8	R1/4	3809 08 13				14	14.5	34	25	0.046
	R1/4	3809 10 13				19	17.5	37.5	27.5	0.068
10	R3/8	3809 10 17				19	17.5	37.5	27.5	0.069

The body swivels for positioning purposes.

3809

Stud Elbow, Male NPT Thread

	Stainless steel 316L, FKM									
	ØD	C				F	G	H	L	kg
4	NPT1/8	3809 04 11				11	10	25.5	18.5	0.021
	NPT1/8	3809 06 11				13	12.5	29	22.5	0.025
6	NPT1/4	3809 06 14				14	12.5	29	22.5	0.030
	NPT1/8	3809 08 11				14	15	34	24	0.041
8	NPT1/4	3809 08 14				14	15	34	24	0.046
	NPT1/4	3809 10 14				19	17.5	39.5	30	0.057
10	NPT3/8	3809 10 18				19	17.5	39.5	30	0.071

The body swivels for positioning purposes.

LF 3800/LF 3900

Stud standpipe 3821, 3921, 3831, 3931 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required

